

Q1

sizeof(var) is 12

sizeof(var.a) is 4

sizeof(var.b) is 1

sizeof(var.c) is 4

value of var.a is 10.

value of var.b is b

value of var.c is 15.55

value of var.a is 10

value of var.b is b

value of var.c is 15.55

Q2

sizeof(var) is 4

sizeof(var.a) is 4

sizeof(var.b) is 1

value of var.a is 10

value of var.b is b

value of var.c is 15.55

Q3 #include <stdio.h>

#include <stdlib.h>

typedef struct Employee {

int eno;

char name[50];

float sal;

} e;

int main()

{ int n, i, hSI = 0;

printf("Enter number of employee");

scanf("%d", &n);

e empl[n];

for(i = 0; i < n; i++) {

printf("Enter the details");

scanf("%d %s %f", &empl[i].eno, empl[i].ename, &empl[i].sal);

}

for(int i = 0; i < n; i++) {

if (empl[i].sal > empl[hSI].sal) {

hSI = i;

}

}

printf("highest salary = %d", &hSI);

return 0;

}

Q4 include <stdio.h>

typedef union Data {

typedef Struct stu {

char nam[50];

int rol;

float percent;

} st;

} D;

int main()

{

D st da;

printf("Enter the details");

& scanf("%s.%d.%f", &da.st.nam, &da.st.rol, &da.st.percent);

printf("Student details");

printf("%s\n %d\n %.2f\n", da.st.nam, da.st.rol, da.st.percent);

return 0;

}

Q5 typedy struct telephone
char na[50];
int num;
} st;

int main() {

st tel;

printf("Enter details");
scanf("%s %d", tel.na, &tel.num);

printf("Telephone entry");
printf("%s\n %d\n", tel.na, tel.num);

return 0;

}