

TUTORIAL - 9

Q1)

a) The parameters which are passed in the function during the function call are called actual parameters and the parameters

The parameters which receive the values in the function definition are called formal parameters.

Q2)

```
#include <stdio.h>
```

```
int fact (int);
```

```
void main()
```

```
{
```

```
    int sum;
```

```
    sum = fact(1)/1 + fact(2)/2 + fact(3)/3 + fact(4)/4 + fact(5)/5;
```

```
    printf("Function : find sum of 1!/1 + 2!/2 + 3!/3 + 4!/4 + 5!/5");
```

```
    printf("The sum of series is: %d\n", sum);
```

```
}
```

```
int fact(int n)
```

```
int num = 0, f = 1
```

```
while (num <= n-1)
```

```
{
```

```
    f = f * num;
```

```

num++;
}
return f;
}

```

Q3)

```

#include <stdio.h>
void modify (int n) {
    n = n + 10;
    printf("Value of 'n' inside function = %d \n", n);
}
int main() {
    int x = 15;
    modify(x);
    printf("Modified value of x = %d \n", x);
    return 0;
}

```

Q4)

```

#include <stdio.h>
int harrising (int N)
{
    return 1;
}
else {
    return N * harrising(N-1);
}
int main()
{
    int N = 50;
}

```

```

printf ("Arrangement of %d Hair Pins is %d\n",
N, hairpins(N));
return 0;
}

```

Q5)

```

#include <stdio.h>
long toBin(int);
int main ()
{
    long bno;
    int dno;

```

```

printf ("Function : convert decimal to binary");
printf ("Input any decimal number:");
scanf ("%d", &dno);
bno = toBin(dno);

```

```

printf ("The Binary value is : %d\n\n", bno);
return 0;
}

```

```

long toBin (int dno)
{

```

```

    long bno = 0, remainder f = 1;
    bno = bno + remainder * f;

```

```

    f = f * 10;
    dno = dno / 2;

```

```

}
return bno;
}

```