7	Parul® University	NAAC OH	

Pg. No.: Date :....

Practical 6
Machial Description
10
vite a program. Lo create a es console and webapp
ets consolo and webapp
and the state
ute a Node ?s Project
1000 S 100 S 100 V 103 V
2 our npm init in normal termina
on who will affile a
n imit -y
will initialize a package json tile
an amazer a package Journ
The state of the s
out correspondent the
He to C: Indis package json:
4 (Completion of Completion) of E
ogene 1: mdic"

Parul® University	NAAC ()++
-------------------	-----------

Pg. N	0.:
_	te:

2.	Worte the Node is Console Application
tio	11 appis at another than
	console. 100 ("Welcome to my Mode. is
TOTAL	console log ("Welcome to my Node is
3	Run the Application
1 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1	Execute the script using Node is:
*	C. 100 100 0
	c. m.djs > console log ("Welcome to my Node js console app!");
	my Node js comsule app.);
,	'Console log' is mot recognized as an
	'Console log' is not recognized as an internal or external command,
14 1	operable program or batch file.
17.1	
	C: Indis > copy com firstis
-	console log ("Welcome to my Node is
	Com sole appins
	AZ Joujan oj show a skulpition s
1	6 0015
. /	1 étile copied.
117 9	c:\ndjs>node first.js
	Welcome to my Node 3s console app!
	I was and the same and and the same and the

	Parul® NAACOH+ Date:
11011	Second-95
	console log ("Welcome to my Node js console app!")
	process. stdout. wonte ("Enter your nome process. stdin. on ("data", (data) => }
	constiname = data to String (), toim() console log ('Hello, & Ename 3!").
01-	processiexité)
	Rum a Node is web application
1.	Create a Project Folder
	Flos mkdir my-node-app.
2	Tritialize a Node je Project
3.	Coeate a JavaScropt File for the Server
	touch Server js (for a macos) ech o> server js (for windows)

1	
4.	Write the Node is HTTP Server Code
· ·	var http = require ("http");
	var server = http. createServer (function Creq, res) &
	ves_content_type": "text/plain"});
	res. conte ("Hello, this is a simple Node is coeb server!"). res. end c);
	5.);
	server. listen (3000, function () &
	console. log ("Server is running at http://localhost:3000").
	2). at http://localhost:3000"),
5	Run the Server
. '	node semer. js
6.	Open in Browser
	Oro to http://localhost: 8000/ in browser
	You see?
	Size this week of a big to a district of the control of the contro
	Hello, this is a simple. Node js web
	server 1