

# Oodle Ads Analytics API Reference & Usage Guide

---

This document serves as the integration and usage guide for the internal Ads Analytics APIs hosted on `a`  
`pi.oodle.social`. These APIs consolidate installations, purchase details, country distribution, and demographic breakdowns from the backend databases (bypassing Meta/Firebase/SDK dependencies).

---

## Base Configuration

---

- **Base URL:** `https://api.oodle.social`
  - **Port / Protocol:** HTTPS / Standard SSL (default port 443)
  - **Authentication:** These endpoints are protected using a custom API Key Guard. Every request must include the `x-api-key` header containing the valid marketing analytics key configured on the server.
- 

## Core Business Rules & Data Source Definitions

---

Before consuming the endpoints, review the business logic governing the metrics:

### 1. User Installs (User IDs)

An "install" represents the successful creation of a brand-new user account in the primary database.

- **Excluded Profiles:** Dummy profiles and AI/bot user profiles are filtered out.
- **Platform Categorization:**
  - A user is categorized as **iOS** if an `appleAuthCode` is present OR if they have a matching record in the `user_attribution` table (where only the iOS app registers attribution).
  - Otherwise, they are categorized as **Android**.

### 2. Demographic Definitions

- **Gender Splits:** Resolved from user profile attributes:
  - `0`: Male
  - `1`: Female
  - `2` or other: Other
- **Country Resolution:** Mapped in order of preference:
  1. Mapped country name from `global-countries` table via `countryGid`.
  2. Fallback to the country code listed in the `user_attribution` table.
  3. Fallback to the user's phone `countryCode` (stripping dial prefixes).
  4. Defaults to `Unknown` if no indicators are present.

### 3. Revenue & Currency Conversion

Purchases are consolidated from three separate payment ledger tables:

- **Subscriptions** ( `user-global-subscription` )
- **Sparks Packs** ( `spark-purchases` )
- **Boost Packs** ( `boost-purchases` )

Only purchases with successful/completed transaction statuses are counted.

- **Dynamic Conversion to INR:** Every sale remains stored in its original currency (e.g., USD, AED, EUR, INR). Upon request, the system fetches the exchange rates for that transaction day from `publ i c.currency_rates` to dynamically convert the amount into **INR**.
- **Price Regularization:** The system automatically sanitizes currency symbols, handles comma-decimals, and normalizes platform-specific integer scaling (micro/milli-units returned from Apple App Store and Google Play billing APIs).

### 4. Estimated Net Proceeds

- **Formula:** `Estimated Net Proceeds (INR) = Gross Sales (INR) * 0.80`
- **Deduction:** The 20% hardcoded deduction accounts for app store commissions (Apple/Google), payment processing fees, and conversion/transfer losses.

## Transaction Status Code Filtering

To ensure the analytics dashboard reflects actual business revenue, the APIs filter out inactive, paused, canceled, or pending purchases.

| Product Type  | Allowed Status Codes (Included in API)                                                                                                        | Excluded Status Codes (Filtered Out)                                                                                                                                                                                 |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Subscriptions | <code>1</code> (Recovered), <code>2</code> (Renewed), <code>4</code> (Purchased), <code>7</code> (Restored), <code>8</code> (Price Confirmed) | <code>3</code> (Canceled), <code>5</code> (Account Hold), <code>6</code> (Grace Period), <code>10</code> (Paused), <code>12</code> (Revoked/Refunded), <code>13</code> (Expired), <code>20</code> (Canceled Pending) |
| Sparks        | <code>1</code> (Active/Success), <code>4</code> (Purchased)                                                                                   | All other status codes                                                                                                                                                                                               |
| Boosts        | <code>1</code> (Active/Success), <code>2</code> (Renewed), <code>4</code> (Purchased)                                                         | All other status codes                                                                                                                                                                                               |

[!NOTE] If your raw database counts are higher than the values returned by the API, check the transaction status codes. For example, a customer with a **paused** ( `status: 10` ) or **canceled** ( `status: 3` ) subscription will not be included in the order or revenue counts.

# Country Parameter Names & Formatting

When filtering orders or reports by country, you must pass the exact name string as stored in the database. The country filter is case-insensitive, but must match the full spelling (spaces must be URL-encoded as `%20`).

## Popular Countries in Oodle

Below is the list of popular countries in the application and their exact parameter values:

| Country                    | Parameter Value          | URL-Encoded Example                    |
|----------------------------|--------------------------|----------------------------------------|
| United Arab Emirates (UAE) | United Arab Emirates     | country=United%20Arab%20Emirates       |
| India                      | India                    | country=India                          |
| United States              | United States of America | country=United%20States%20of%20America |
| United Kingdom             | United Kingdom           | country=United%20Kingdom               |
| Philippines                | Philippines              | country=Philippines                    |
| Nigeria                    | Nigeria                  | country=Nigeria                        |
| Saudi Arabia               | Saudi Arabia             | country=Saudi%20Arabia                 |
| Qatar                      | Qatar                    | country=Qatar                          |
| Malaysia                   | Malaysia                 | country=Malaysia                       |
| Indonesia                  | Indonesia                | country=Indonesia                      |
| Pakistan                   | Pakistan                 | country=Pakistan                       |
| Kenya                      | Kenya                    | country=Kenya                          |
| Ghana                      | Ghana                    | country=Ghana                          |

# Endpoint Details & Curl Commands

## 1. Daily Dashboard

Provides a quick summary overview of a single day's performance.

- **HTTP Method:** `GET`
- **Path:** `/analytics/daily`
- **Headers:**
  - `x-api-key` (Required, String): Configure with your analytics API Key.
- **Query Parameters:**

- `date` (Optional, String): Target date formatted as `YYYY-MM-DD`. Defaults to yesterday if not supplied.

### Curl Command (Defaults to Yesterday)

```
curl -X GET "https://api.oodle.social/analytics/daily" \  
  -H "x-api-key: your_api_key_here" \  
  -H "Accept: application/json"
```

### Curl Command (Specific Date)

```
curl -X GET "https://api.oodle.social/analytics/daily?date=2026-07-13" \  
  -H "x-api-key: your_api_key_here" \  
  -H "Accept: application/json"
```

### Example Response

```
{  
  "date": "2026-07-13",  
  "new_users_total": 325,  
  "new_users_ios": 164,  
  "new_users_android": 161,  
  "new_men": 248,  
  "new_women": 73,  
  "gross_sales_inr": 11943.38,  
  "net_proceeds_inr": 9554.71,  
  "total_orders": 11,  
  "ios_orders": 8,  
  "android_orders": 3  
}
```

---

## 2. Country Breakdown

Aggregates sales metrics broken down by country, sorted by highest gross revenue first.

- **HTTP Method:** `GET`
- **Path:** `/analytics/countries`
- **Headers:**
  - `x-api-key` (Required, String): Configure with your analytics API Key.
- **Query Parameters:**
  - `startDate` (Optional, String): Start date formatted as `YYYY-MM-DD`. Defaults to 30 days ago.

- `endDate` (Optional, String): End date formatted as `YYYY-MM-DD`. Defaults to today.

### Curl Command (Defaults to Last 30 Days)

```
curl -X GET "https://api.oodle.social/analytics/countries" \  
  -H "x-api-key: your_api_key_here" \  
  -H "Accept: application/json"
```

### Curl Command (Specific Range)

```
curl -X GET "https://api.oodle.social/analytics/countries?startDate=2026-07-12&endDate=2026-07-13" \  
  -H "x-api-key: your_api_key_here" \  
  -H "Accept: application/json"
```

### Example Response

```
[  
  {  
    "country": "United Arab Emirates",  
    "orders": 15,  
    "gross_sales_inr": 12997.16,  
    "net_proceeds_inr": 10397.73  
  },  
  {  
    "country": "United States of America",  
    "orders": 2,  
    "gross_sales_inr": 6682.59,  
    "net_proceeds_inr": 5346.07  
  }  
]
```

---

## 3. Individual Orders

Audit trail mapping every individual sale transaction. Includes platform, country, original pricing, and calculated INR conversions.

- **HTTP Method:** `GET`
- **Path:** `/analytics/orders`
- **Headers:**
  - `x-api-key` (Required, String): Configure with your analytics API Key.

- **Query Parameters:**

- `page` (Optional, Integer): Page number for pagination. Defaults to `1`.
- `limit` (Optional, Integer): Number of items per page. Defaults to `50`.
- `startDate` (Optional, String): Start date formatted as `YYYY-MM-DD`. Defaults to 30 days ago.
- `endDate` (Optional, String): End date formatted as `YYYY-MM-DD`. Defaults to today.
- `platform` (Optional, String): Filter by platform: `ios` or `android`.
- `country` (Optional, String): Filter by country name (case-insensitive, e.g., `United Arab Emirates`).

## Curl Command (All Filters & Specific Range)

```
curl -X GET "https://api.oodle.social/analytics/orders?page=1&limit=10&platform=ios&country=United%20Arab%20Emirates&startDate=2026-07-12&endDate=2026-07-13" \  
  -H "x-api-key: your_api_key_here" \  
  -H "Accept: application/json"
```

## Curl Command (All-Time iOS Orders from India)

```
curl -X GET "https://api.oodle.social/analytics/orders?platform=ios&country=India&startDate=2020-01-01" \  
  -H "x-api-key: your_api_key_here" \  
  -H "Accept: application/json"
```

## Example Response

```
{
  "total": 106,
  "page": 1,
  "limit": 10,
  "orders": [
    {
      "order_id": "200003475879302",
      "platform": "ios",
      "country": "India",
      "currency": "INR",
      "original_amount": 599,
      "exchange_rate": 1,
      "inr_amount": 599,
      "estimated_net_inr": 479.2,
      "product": "one_week_subscription",
      "purchase_time": "2026-07-12T01:22:09.886Z"
    }
  ]
}
```

## 4. User Acquisition

Provides gender-split metrics separated by platform for user installs within a given range.

- **HTTP Method:** `GET`
- **Path:** `/analytics/users`
- **Headers:**
  - `x-api-key` (*Required, String*): Configure with your analytics API Key.
- **Query Parameters:**
  - `startDate` (*Optional, String*): Start date formatted as `YYYY-MM-DD`. Defaults to 30 days ago.
  - `endDate` (*Optional, String*): End date formatted as `YYYY-MM-DD`. Defaults to today.

### Curl Command (Defaults to Last 30 Days)

```
curl -X GET "https://api.oodle.social/analytics/users" \  
  -H "x-api-key: your_api_key_here" \  
  -H "Accept: application/json"
```

## Curl Command (Specific Range)

```
curl -X GET "https://api.oodle.social/analytics/users?startDate=2026-07-12&endDate=2026-07-13" \
  -H "x-api-key: your_api_key_here" \
  -H "Accept: application/json"
```

## Example Response

```
{
  "ios": {
    "male": 45,
    "female": 30,
    "other": 5
  },
  "android": {
    "male": 60,
    "female": 40,
    "other": 5
  }
}
```