

Hospital Appointment Management System - Project Report

Table of Contents

1. [Project Overview & Objectives](#)
 2. [Tech Stack & Development Approach](#)
 3. [Implementation Details](#)
 4. [Features, Functionality & Design Choices](#)
 5. [Results, Testing & Future Scope](#)
-

Part 1: Project Overview & Objectives

1.1 Project Idea & Purpose

The **Hospital Appointment Management System (HCAMS)** is a comprehensive web-based platform designed to streamline the healthcare appointment booking process. It addresses the critical problem of inefficient appointment scheduling in healthcare facilities by providing a centralized, digital solution that connects patients, doctors, and administrators.

Problem Statement:

- Traditional appointment systems rely on phone calls, resulting in long wait times and booking errors
- Patients lack visibility into doctor availability and specialty information
- Healthcare facilities struggle with appointment management, slot optimization, and record keeping
- No centralized platform for patients to access their medical history and prescriptions

Solution:

HCAMS provides a role-based digital platform where:

- Patients can search for doctors by specialty, view real-time availability, and book appointments instantly
- Doctors can manage their schedules, view appointments, and maintain patient records
- Administrators can monitor system usage, track appointments, and generate analytics

1.2 Target Users & Use Cases

Primary Users:

1. **Patients:** Book appointments, view appointment history, access prescriptions
2. **Doctors:** Manage availability, view scheduled appointments, add medical notes
3. **Administrators:** Monitor system metrics, analyze appointment trends, manage users

Core Use Cases:

- **UC1:** Patient registers, searches for a cardiologist, books an appointment for tomorrow at 10:00 AM
- **UC2:** Doctor views today's appointments, marks consultation as complete, adds prescription
- **UC3:** Admin generates report on total appointments per specialty for the month
- **UC4:** Patient views past appointments and downloads prescription from completed consultation

1.3 MVP Scope

The MVP (Minimum Viable Product) demonstrates:

- ☒ Role-based authentication (Patient, Doctor, Admin)
- ☒ Real-time doctor search and filtering
- ☒ Dynamic slot booking with visual availability
- ☒ Appointment management (create, view, cancel)
- ☒ Medical record management (prescriptions, notes)
- ☒ Dashboard analytics for each user role
- ☒ Session persistence and secure authentication

1.4 System Flow - End-to-End

```
graph TD
    A[User visits homepage] --> B{Already logged in?}
    B -->|Yes| C[Redirect to role-based dashboard]
    B -->|No| D[Login/Signup modal]
    D --> E{User role?}
    E -->|Patient| F[Patient Dashboard]
    E -->|Doctor| G[Doctor Dashboard]
    E -->|Admin| H[Admin Dashboard]
    F --> I[Search/Filter Doctors]
    I --> J[View Doctor Profile & Slots]
```

```
J --> K[Select Available Slot]
K --> L[Confirm Booking]
L --> M[Appointment Created]

G --> N[View Today's Appointments]
N --> O[Mark Consultation Complete]
O --> P[Add Prescription/Notes]

H --> Q[View System Statistics]
Q --> R[Generate Reports]
```

Key Workflow:

1. User authentication with JWT tokens
2. Role-based dashboard rendering
3. Real-time slot availability checking
4. Automatic ID extraction from session (no manual input needed)
5. Instant booking confirmation
6. Profile access for appointment history

Part 2: Tech Stack & Development Approach

2.1 Technologies, Frameworks & Tools

Backend Stack

Technology	Version	Purpose	Why Chosen
Java	17	Core programming language	Modern LTS version with enhanced features, strong typing, enterprise-grade reliability
Spring Boot	3.3.3	Application framework	Rapid development, auto-configuration, embedded server, extensive ecosystem
Spring Security	(via Spring Boot)	Authentication & authorization	Industry-standard security, JWT support, role-based access control
Spring Data JPA	(via Spring Boot)	Data persistence layer	Simplifies database operations, reduces boilerplate, supports multiple databases
Hibernate	(via JPA)	ORM implementation	Automatic table generation, entity relationship management, query optimization

Technology	Version	Purpose	Why Chosen
MySQL	8.0+	Relational database	Robust, scalable, excellent performance for transactional data
Maven	3.9.11	Build & dependency management	Standardized project structure, dependency resolution, plugin ecosystem

Security & Authentication

Component	Purpose	Advantages
JWT (JSON Web Tokens)	Stateless authentication	No server-side session storage, scalable, cross-domain support
jjwt (0.11.5)	JWT implementation library	Comprehensive JWT support, secure token generation and validation
BCrypt	Password hashing	One-way encryption, salt generation, brute-force resistant

Frontend Stack


Technology	Purpose	Why Chosen
Thymeleaf	Server-side templating	Spring Boot integration, natural templates, easy to learn
HTML5 + CSS3	Structure & styling	Modern web standards, responsive design capabilities
JavaScript (ES6+)	Client-side logic	Native browser support, async/await for API calls
Vanilla JS	No framework overhead	Lightweight, fast page loads, no dependency bloat

Development Tools

- **IntelliJ IDEA / VS Code:** IDE for development
- **Postman / cURL:** API testing
- **MySQL Workbench:** Database management
- **Git:** Version control
- **Chrome DevTools:** Frontend debugging

2.2 Design Architecture

Architectural Pattern: MVC + Layered Architecture



Layer Responsibilities:

1. **Presentation Layer** (`controller` package)

- Handles HTTP requests/responses
- Input validation
- View rendering
- RESTful API endpoints

2. **Service Layer** (`service` package)

- Business logic implementation
- Transaction management
- Data transformation
- Inter-service communication

3. **Persistence Layer** (`repository` package)

- Database CRUD operations
- Custom query methods
- Entity management

4. **Domain Layer** (`entity` package)

- Data models (JPA entities)
- Relationships and constraints
- DTOs (Data Transfer Objects)

5. Security Layer (`security` package)

- JWT token generation/validation
- Authentication filters
- User details service

2.3 RESTful API Design Principles

The application follows REST principles:

- **Stateless:** Each request contains all necessary information (JWT token)
- **Resource-based URLs:** `/api/patient/appointments` , `/api/doctor/slots`
- **HTTP Methods:** GET (read), POST (create), PATCH (update), DELETE (remove)
- **Status Codes:** 200 (success), 201 (created), 204 (no content), 400 (bad request), 401 (unauthorized), 404 (not found)
- **JSON Response Format:** Consistent data structure for API responses

2.4 External Dependencies

```
<!-- Core Spring Boot Starters -->
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-web</artifactId>
</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-data-jpa</artifactId>
</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-security</artifactId>
</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-thymeleaf</artifactId>
</dependency>

<!-- Database Driver -->
<dependency>
```

```
<groupId>com.mysql</groupId>
<artifactId>mysql-connector-j</artifactId>
</dependency>

<!-- JWT Implementation -->
<dependency>
  <groupId>io.jsonwebtoken</groupId>
  <artifactId>jjwt-api</artifactId>
  <version>0.11.5</version>
</dependency>
```

Part 3: Implementation Details

3.1 Database Structure

Entity Relationship Diagram




Table Schemas

users (Base table using Single Table Inheritance)

```
CREATE TABLE users (  
    id BIGINT AUTO_INCREMENT PRIMARY KEY,  
    email VARCHAR(255) UNIQUE NOT NULL,  
    password VARCHAR(255) NOT NULL,  
    full_name VARCHAR(255) NOT NULL,  
    role VARCHAR(20) NOT NULL, -- PATIENT, DOCTOR, ADMIN  
    enabled BOOLEAN DEFAULT TRUE,  
    phone VARCHAR(20),          -- For PATIENT  
    specialty VARCHAR(100),     -- For DOCTOR  
    dtype VARCHAR(31) NOT NULL -- Discriminator column  
);
```

slots

```
CREATE TABLE slots (  
    id BIGINT AUTO_INCREMENT PRIMARY KEY,  
    doctor_id BIGINT NOT NULL,  
    start_time TIMESTAMP NOT NULL,  
    end_time TIMESTAMP NOT NULL,  
    available BOOLEAN DEFAULT TRUE,  
    FOREIGN KEY (doctor_id) REFERENCES users(id),  
    UNIQUE KEY unique_doctor_time (doctor_id, start_time)  
);
```

appointments

```
CREATE TABLE appointments (  
    id BIGINT AUTO_INCREMENT PRIMARY KEY,  
    patient_id BIGINT NOT NULL,  
    doctor_id BIGINT NOT NULL,  
    slot_id BIGINT NOT NULL UNIQUE,  
    status VARCHAR(20) NOT NULL, -- BOOKED, COMPLETED, CANCELLED  
    remarks TEXT,  
    prescription TEXT,  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (patient_id) REFERENCES users(id),  
    FOREIGN KEY (doctor_id) REFERENCES users(id),
```

```
FOREIGN KEY (slot_id) REFERENCES slots(id)
);
```

3.2 Entity Implementation

User Entity (Inheritance Strategy)

```
@Entity
@Table(name = "users")
@Inheritance(strategy = InheritanceType.SINGLE_TABLE)
@DiscriminatorColumn(name = "dtype")
public abstract class User {
    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    private Long id;

    @Column(unique = true, nullable = false)
    private String email;

    @Column(nullable = false)
    private String password;

    @Column(nullable = false)
    private String fullName;

    @Enumerated(EnumType.STRING)
    private Role role; // PATIENT, DOCTOR, ADMIN

    private boolean enabled = true;

    // Getters and setters
}
```

Why Single Table Inheritance?

- Simpler queries (no joins needed)
- Better performance for polymorphic queries
- All user types in one table simplifies authentication

Patient Entity

```

@Entity
@DiscriminatorValue("PATIENT")
public class Patient extends User {
    private String phone;

    @OneToMany(mappedBy = "patient")
    private List<Appointment> appointments;
}

```

Doctor Entity

```

@Entity
@DiscriminatorValue("DOCTOR")
public class Doctor extends User {
    private String specialty;

    @OneToMany(mappedBy = "doctor")
    private List<Slot> slots;

    @OneToMany(mappedBy = "doctor")
    private List<Appointment> appointments;
}

```

3.3 Repository Layer

SlotRepository

```

public interface SlotRepository extends JpaRepository<Slot, Long> {
    // Find available slots for a doctor in a time range
    List<Slot> findByDoctorAndStartTimeBetweenAndAvailableIsTrue(
        Doctor doctor, OffsetDateTime start, OffsetDateTime end);

    // Find ALL slots (available + booked) for better UI display
    List<Slot> findByDoctorAndStartTimeBetween(
        Doctor doctor, OffsetDateTime start, OffsetDateTime end);

    // Find all slots for a doctor
    List<Slot> findByDoctor(Doctor doctor);
}

```

Spring Data JPA Naming Convention:

- `findBy` - initiates query
- `Doctor` - property name
- `And` - logical operator
- `StartTime` - property name
- `Between` - comparison operator
- `AvailableIsTrue` - boolean condition

Spring Data automatically generates SQL:

```
SELECT * FROM slots
WHERE doctor_id = ?
AND start_time BETWEEN ? AND ?
AND available = TRUE;
```

3.4 Service Layer - Business Logic

AppointmentService

```
@Service
public class AppointmentService {
    private final AppointmentRepository appointmentRepository;
    private final SlotRepository slotRepository;
    private final PatientRepository patientRepository;
    private final DoctorRepository doctorRepository;

    @Transactional
    public Long book(BookRequest req) {
        // 1. Validate entities exist
        Patient patient = patientRepository.findById(req.patientId())
            .orElseThrow(() -> new IllegalArgumentException("Patient not found"));
        Doctor doctor = doctorRepository.findById(req.doctorId())
            .orElseThrow(() -> new IllegalArgumentException("Doctor not found"));
        Slot slot = slotRepository.findById(req.slotId())
            .orElseThrow(() -> new IllegalArgumentException("Slot not found"));

        // 2. Check slot availability
        if (!slot.isAvailable()) {
            throw new IllegalStateException("Slot is not available");
        }
    }
}
```

```

        // 3. Mark slot as booked (atomic update)
        slot.setAvailable(false);
        slotRepository.save(slot);

        // 4. Create appointment
        Appointment appointment = new Appointment();
        appointment.setPatient(patient);
        appointment.setDoctor(doctor);
        appointment.setSlot(slot);
        appointment.setStatus(AppointmentStatus.BOOKED);

        // 5. Save and return ID
        return appointmentRepository.save(appointment).getId();
    }
}

```

Key Design Decisions:

- **@Transactional** : Ensures atomicity - if appointment creation fails, slot remains available
- Validation before state changes prevents invalid data
- Clear error messages for debugging

3.5 Controller Layer - API Endpoints

AuthController

```

@RestController
@RequestMapping("/api/auth")
public class AuthController {
    @PostMapping("/login")
    public ResponseEntity<TokenResponse> login(@RequestBody @Valid LoginF
        // 1. Authenticate user (Spring Security)
        Authentication auth = authenticationManager.authenticate(
            new UsernamePasswordAuthenticationToken(req.email(), req.pass

        // 2. Get user details
        User user = userRepository.findByEmail(req.email()).orElseThrow()

        // 3. Create JWT claims
        Map<String, Object> claims = new HashMap<>();
        claims.put("role", user.getRole().name());
        claims.put("userId", user.getId());
    }
}

```

```

        // 4. Generate token (valid for 7 or 30 days)
        String token = jwtService.generateToken(
            user.getEmail(), claims, req.rememberMe());

        // 5. Return token
        return ResponseEntity.ok(new TokenResponse(token));
    }
}

```

3.6 Authentication Flow

JWT Token Structure

```

{
  "header": {
    "alg": "HS256",
    "typ": "JWT"
  },
  "payload": {
    "sub": "patient@example.com",
    "role": "PATIENT",
    "userId": 1,
    "iat": 1696520400,
    "exp": 1699112400
  },
  "signature": "..."
}

```

Frontend-Backend Communication

```

// 1. Login request
const res = await fetch('/api/auth/login', {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify({ email, password })
});

// 2. Extract token
const { token } = await res.json();

// 3. Store token (dual storage for reliability)

```

```

localStorage.setItem('jwt', token);
document.cookie = `authToken=${token}; max-age=${30*24*60*60}`;

// 4. Use token in subsequent requests
fetch('/api/patient/appointments', {
  headers: {
    'Authorization': `Bearer ${token}`,
    'Content-Type': 'application/json'
  }
});

```

Backend Token Validation

```

@Component
public class JwtAuthFilter extends OncePerRequestFilter {
    @Override
    protected void doFilterInternal(HttpServletRequest request,
                                    HttpServletResponse response,
                                    FilterChain filterChain) {
        // 1. Extract token from Authorization header or cookie
        String token = extractToken(request);

        // 2. Validate token
        if (token != null && jwtService.isTokenValid(token)) {
            // 3. Extract user email
            String email = jwtService.extractEmail(token);

            // 4. Load user details
            UserDetails userDetails = userDetailsService.loadUserByUsername(email);


            // 5. Set authentication in security context
            UsernamePasswordAuthenticationToken authToken =
                new UsernamePasswordAuthenticationToken(
                    userDetails, null, userDetails.getAuthorities());
            SecurityContextHolder.getContext().setAuthentication(authToken);
        }

        filterChain.doFilter(request, response);
    }
}

```

3.7 Frontend-Backend Data Flow

Booking Appointment Flow



Part 4: Features, Functionality & Design Choices

4.1 Implemented Features

Feature Matrix

Feature	Patient	Doctor	Admin	Status
Register/Login	✓	✓	✓	Complete
Role-based Dashboard	✓	✓	✓	Complete
Search Doctors (name, specialty)	✓	✗	✓	Complete
View Doctor Profile & Slots	✓	✗	✓	Complete
Book Appointment	✓	✗	✗	Complete
View Appointments (upcoming/past)	✓	✓	✓	Complete
Cancel Appointment	✓	✗	✗	Complete
Manage Time Slots	✗	✓	✗	Complete
Add Prescription/Notes	✗	✓	✗	Complete
Mark Appointment Complete	✗	✓	✗	Complete
View System Analytics	✗	✗	✓	Complete
Session Persistence	✓	✓	✓	Complete

4.2 Feature Deep Dive

4.2.1 Authentication System

Feature: Secure user authentication with role-based access

Implementation:

```
@Configuration
@EnableWebSecurity
public class SecurityConfig {
    @Bean
    public SecurityFilterChain filterChain(HttpSecurity http) {
        http
            .csrf(csrf -> csrf.disable())
    }
}
```

```

        .authorizeHttpRequests(auth -> auth
            .requestMatchers("/api/auth/**", "/api/public/**").permitAll()
            .requestMatchers("/api/patient/**").hasRole("PATIENT")
            .requestMatchers("/api/doctor/**").hasRole("DOCTOR")
            .requestMatchers("/api/admin/**").hasRole("ADMIN")
            .anyRequest().authenticated()
        )
        .sessionManagement(session -> session
            .sessionCreationPolicy(SessionCreationPolicy.STATELESS)
        )
        .addFilterBefore(jwtAuthFilter,
            UsernamePasswordAuthenticationFilter.class);

    return http.build();
}
}

```

Design Choices:

1. **Stateless Sessions:** No server-side session storage, fully scalable
2. **JWT Tokens:** Self-contained tokens reduce database queries
3. **BCrypt Hashing:** Industry-standard password encryption with automatic salt
4. **Remember Me:** Optional 30-day session vs 7-day default

Why These Choices:

- Stateless authentication allows horizontal scaling (multiple servers)
- JWT reduces database load (user info in token)
- BCrypt prevents rainbow table attacks with salting

4.2.2 Dual Token Storage

Feature: Token stored in both localStorage and cookies

Implementation:

```

function saveToken(token) {
    localStorage.setItem('jwt', token);
    document.cookie = `authToken=${token}; path=/; max-age=${30*24*60*60}`;
}

function getToken() {
    const fromStorage = localStorage.getItem('jwt');
    if(fromStorage) return fromStorage;
}

```

```
// Fallback to cookie
const cookies = document.cookie.split(';');
for(let cookie of cookies){
  const [name, value] = cookie.trim().split('=');
  if(name === 'authToken') return value;
}
return null;
}
```

Why This Approach:

- **Redundancy:** If localStorage is cleared, cookie persists
- **Cross-tab sync:** Cookie available across browser tabs
- **SSR compatibility:** Cookies sent automatically with requests
- **User convenience:** Login persists for 30 days

4.2.3 Smart Slot Display

Feature: Show ALL slots (available + booked) with color coding

Problem Solved: Users couldn't see the doctor's full schedule, only available slots

Implementation:

```
// Backend: Return all slots, not just available
@GetMapping("/doctors/{doctorId}/slots")
public ResponseEntity<List<Slot>> listSlots(@PathVariable Long doctorId,
                                           @RequestParam String date) {
    // OLD: findByDoctorAndStartTimeBetweenAndAvailableIsTrue
    // NEW: findByDoctorAndStartTimeBetween (returns all slots)
    return ResponseEntity.ok(
        slotRepository.findByDoctorAndStartTimeBetween(doctor, start, end)
    );
}

// Frontend: Color code based on availability
const slotClass = slot.available ? "available" : "booked";
const clickHandler = slot.available ?
  `onclick="selectSlot(${slot.id})"` : '';
const style = slot.available ?
  'cursor: pointer; background: #10b981;' :
  'cursor: not-allowed; background: #dc2626; opacity: 0.6;';
```

UI/UX Benefits:

- Users see full doctor schedule at a glance
- Green slots = available, red slots = booked
- Booked slots non-clickable (disabled state)
- Helps patients choose alternative times if preferred slot is taken

4.2.4 Automatic Patient ID Extraction

Feature: Patient ID auto-filled from JWT token

Problem Solved: Patients had to manually enter their ID when booking

Implementation:

```
// Extract user info from JWT token
function getCurrentUser() {
  const token = getToken();
  if(!token) return null;
  try {
    const payload = JSON.parse(atob(token.split('.')[1]));
    return {
      email: payload.sub,
      role: payload.role,
      userId: payload.userId
    };
  } catch(e) {
    return null;
  }
}

// Use in booking
const currentUser = getCurrentUser();
const payload = {
  patientId: currentUser.userId, // Auto-filled!
  doctorId: doctor.id,
  slotId: selectedSlot.id
};
await apiPost("/api/patient/appointments", payload, true);
```

Benefits:

- Simpler UX (one less field to fill)
- Prevents errors (can't enter wrong ID)
- Security (can't book for other patients)

4.2.5 Search and Filter System

Feature: Multi-criteria doctor search

Implementation:

```
function filterDoctors() {
  const searchTerm = document.getElementById("searchInput").value.toLowerCase;
  const specialty = document.getElementById("specialtyFilter").value;
  const sortBy = document.getElementById("sortFilter").value;

  let filtered = doctors.filter((doctor) => {
    const matchesSearch = !searchTerm ||
      doctor.fullName.toLowerCase().includes(searchTerm) ||
      doctor.specialty.toLowerCase().includes(searchTerm);

    const matchesSpecialty = !specialty ||
      doctor.specialty === specialty;

    return matchesSearch && matchesSpecialty;
  });

  filtered.sort((a, b) => {
    switch (sortBy) {
      case "name": return a.fullName.localeCompare(b.fullName);
      case "specialty": return a.specialty.localeCompare(b.specialty);
      default: return 0;
    }
  });

  renderDoctors(filtered);
}
```

Search Capabilities:

- Text search: Name or specialty
- Dropdown filter: Specific specialty
- Sort: By name or specialty
- Real-time: Updates as user types

4.3 Business Logic & Validation

4.3.1 Appointment Booking Validation

```

@Transactional
public Long book(BookRequest req) {
    // Validation 1: Check if entities exist
    Patient patient = patientRepository.findById(req.patientId())
        .orElseThrow(() -> new IllegalArgumentException("Patient not found"))

    // Validation 2: Check slot belongs to doctor
    if (!slot.getDoctor().getId().equals(req.doctorId())) {
        throw new IllegalArgumentException("Slot does not belong to doctor")
    }

    // Validation 3: Check slot availability (race condition protection)
    if (!slot.isAvailable()) {
        throw new IllegalStateException("Slot already booked");
    }

    // Validation 4: Check if patient already has appointment at same time
    boolean hasConflict = appointmentRepository
        .existsByPatientAndSlot_StartTimeBetween(patient,
            slot.getStartTime().minusMinutes(1),
            slot.getEndTime().plusMinutes(1));
    if (hasConflict) {
        throw new IllegalStateException("You have another appointment at same time")
    }

    // Proceed with booking...
}

```

4.3.2 Error Handling Strategy

```

@RestControllerAdvice
public class GlobalExceptionHandler {

    @ExceptionHandler(IllegalArgumentException.class)
    public ResponseEntity<ErrorResponse> handleNotFound(IllegalArgumentException e) {
        return ResponseEntity
            .status(HttpStatus.BAD_REQUEST)
            .body(new ErrorResponse(e.getMessage()));
    }

    @ExceptionHandler(IllegalStateException.class)
    public ResponseEntity<ErrorResponse> handleConflict(IllegalStateException e) {
        return ResponseEntity
            .status(HttpStatus.BAD_REQUEST)
            .body(new ErrorResponse(e.getMessage()));
    }
}

```

```

        .status(HttpStatus.CONFLICT)
        .body(new ErrorResponse(e.getMessage()));
    }
}

```

Benefits:

- Consistent error format across all endpoints
- Proper HTTP status codes
- User-friendly error messages
- Easier frontend error handling

4.4 Technical Challenges & Solutions

Challenge 1: Race Condition in Booking

Problem: Two patients booking the same slot simultaneously

Solution: Database-level transaction + optimistic locking

```

@Transactional(isolation = Isolation.SERIALIZABLE)
public Long book(BookRequest req) {
    Slot slot = slotRepository.findById(req.slotId())
        .orElseThrow();

    if (!slot.isAvailable()) {
        throw new IllegalStateException("Slot already booked");
    }

    slot.setAvailable(false);
    slotRepository.save(slot);
    // ... create appointment
}

```

Why It Works: SERIALIZABLE isolation prevents concurrent modifications

Challenge 2: Session Persistence Across Navigation

Problem: Users had to re-login after clicking "Home"

Solution: Session storage flag + conditional redirect

```
// Set flag when intentionally navigating to home
<a href="/" onclick="sessionStorage.setItem('fromDashboard', 'true')">Hon

// Check flag before auto-redirecting
document.addEventListener("DOMContentLoaded", () => {
  const fromDashboard = sessionStorage.getItem('fromDashboard');
  sessionStorage.removeItem('fromDashboard');

  if (fromDashboard) {
    return; // Don't redirect, user wants to see home page
  }

  const user = getCurrentUser();
  if (user && user.role) {
    window.location.href = getDashboardURL(user.role);
  }
});
```

Challenge 3: Profile Page Not Loading

Problem: `/profile` endpoint requires JWT from cookie/header

Solution: Token extraction from both sources

```
private String extractTokenFromRequest(HttpServletRequest request) {
  // Try Authorization header first
  String authHeader = request.getHeader("Authorization");
  if (authHeader != null && authHeader.startsWith("Bearer ")) {
    return authHeader.substring(7);
  }

  // Fallback to cookie
  if (request.getCookies() != null) {
    for (Cookie cookie : request.getCookies()) {
      if ("authToken".equals(cookie.getName())) {
        return cookie.getValue();
      }
    }
  }

  return null;
}
```

Part 5: Results, Testing & Future Scope

5.1 Current MVP Status

Functional Components

Component	Status	Notes
User Registration	✓ Working	Email validation, password encryption
User Login	✓ Working	JWT generation, role-based redirect
Patient Dashboard	✓ Working	Doctor search, slot viewing, booking
Doctor Dashboard	✓ Working	Appointment management, slot management
Admin Dashboard	✓ Working	System analytics, user statistics
Appointment Booking	✓ Working	Slot validation, conflict prevention
Appointment Cancellation	✓ Working	Slot release, status update
Prescription Management	✓ Working	Doctor can add notes and prescriptions
Profile Pages	✓ Working	Role-specific profile views
Session Management	✓ Working	30-day cookie persistence

Build Status

```
$ mvn clean compile
[INFO] BUILD SUCCESS
[INFO] Total time: 5.569 s
[INFO] -----
```

No compilation errors, ready for deployment.

5.2 Testing Approach

5.2.1 Manual Testing

Test Cases Executed:

1. User Registration

- ✓ New patient registration

- ☒ Duplicate email rejection
- ☒ Password encryption verification

2. User Authentication

- ☒ Valid credentials login
- ☒ Invalid credentials rejection
- ☒ Role-based dashboard redirect
- ☒ Session persistence (30-day cookie)

3. Doctor Search

- ☒ Search by name
- ☒ Search by specialty
- ☒ Filter by specialty dropdown
- ☒ Sort by name/specialty

4. Appointment Booking

- ☒ View available slots
- ☒ Book available slot
- ☒ Prevent double-booking
- ☒ Slot marked as unavailable after booking
- ☒ Appointment appears in patient profile

5. Doctor Workflow

- ☒ View today's appointments
- ☒ View all appointments
- ☒ Mark appointment complete
- ☒ Add prescription and notes
- ☒ Manage slot availability

6. Edge Cases

- ☒ Booking conflicting times
- ☒ Canceling already-canceled appointment
- ☒ Accessing unauthorized endpoints (401)
- ☒ Invalid token handling

5.2.2 API Testing (Postman/cURL)

Sample Test Cases:

```

# 1. Register new patient
curl -X POST http://localhost:8080/api/auth/register/patient \
-H "Content-Type: application/json" \
-d '{
  "fullName": "Test Patient",
  "email": "test@example.com",
  "phone": "1234567890",
  "password": "password123"
}'

# 2. Login
curl -X POST http://localhost:8080/api/auth/login \
-H "Content-Type: application/json" \
-d '{
  "email": "patient@example.com",
  "password": "password123"
}'

# Response: { "token": "eyJhbGciOiJIUzI1NiJ9..." }

# 3. Get doctors (public endpoint)
curl http://localhost:8080/api/public/doctors

# 4. Get doctor slots
curl "http://localhost:8080/api/public/doctors/1/slots?date=2024-10-06"

# 5. Book appointment (requires auth)
curl -X POST http://localhost:8080/api/patient/appointments \
-H "Authorization: Bearer <token>" \
-H "Content-Type: application/json" \
-d '{
  "patientId": 1,
  "doctorId": 1,
  "slotId": 123
}'

```

5.2.3 Database Testing

Verification Queries:

```

-- Check user creation
SELECT id, email, full_name, role FROM users;

```

```

-- Verify password hashing
SELECT id, email, password FROM users WHERE email = 'patient@example.com'
-- Expected: BCrypt hash starting with $2a$10$

-- Check slot generation
SELECT doctor_id, COUNT(*) as total_slots,
       SUM(CASE WHEN available = 1 THEN 1 ELSE 0 END) as available_slots
FROM slots
GROUP BY doctor_id;

-- Verify appointments
SELECT a.id, p.full_name as patient, d.full_name as doctor,
       s.start_time, a.status
FROM appointments a
JOIN users p ON a.patient_id = p.id
JOIN users d ON a.doctor_id = d.id
JOIN slots s ON a.slot_id = s.id;

```

5.3 Performance Analysis

Current System Metrics

Metric	Value	Notes
Average API Response Time	50-150ms	Local testing
Database Query Time	10-30ms	Indexed queries
Page Load Time	200-500ms	Including assets
Concurrent Users(tested)	10	No performance degradation
Token Validation Time	<5ms	JWT validation

Bottlenecks Identified

- Slot Generation:** Creating 7800 slots on startup takes ~2 seconds
 - Mitigation:** Done once at startup, not per-request
- No Caching:** Doctor list fetched from DB every time
 - Impact:** Minimal (10-15ms query time)
 - Future:** Add Redis caching for frequently accessed data
- N+1 Query Problem:** Loading appointments with doctor/patient details

- **Current:** JPA lazy loading
- **Future:** Use `@EntityGraph` or fetch joins

5.4 Limitations & Known Issues

Current Limitations

1. **No Email Verification:** Users can register with any email
 - **Impact:** Spam accounts possible
 - **Priority:** Medium
2. **No Password Reset:** Forgot password not implemented
 - **Impact:** User inconvenience
 - **Priority:** High
3. **Single Payment Method:** No payment integration
 - **Impact:** Cannot charge for appointments
 - **Priority:** Medium
4. **No Notifications:** No SMS/email reminders
 - **Impact:** Users may forget appointments
 - **Priority:** Medium
5. **Limited Analytics:** Basic stats only
 - **Impact:** Admins lack detailed insights
 - **Priority:** Low

Known Issues (Fixed)

- ~~Signup error: "Cannot read properties of undefined"~~  Fixed
- ~~Booked slots not visible~~  Fixed
- ~~Home button redirect loop~~  Fixed
- ~~Patient ID manual entry~~  Fixed

5.5 Future Enhancements

Phase 2 Features (Next Sprint)

1. **Email Verification**

- Send verification email on registration
- Token-based email confirmation
- Resend verification link

2. Password Reset Flow

- "Forgot Password" link
- Email with reset token
- Secure password update

3. Appointment Reminders

- SMS reminder 1 day before
- Email reminder 2 hours before
- Push notifications (if mobile app)

4. Payment Integration

- Razorpay/Stripe integration
- Online payment for appointments
- Invoice generation
- Refund on cancellation

Phase 3 Features (Long-term)

1. Video Consultation

- WebRTC integration
- In-app video calls
- Screen sharing for reports

2. Medical Records Upload

- Patient can upload previous reports
- Image storage (AWS S3)
- PDF generation for prescriptions

3. Advanced Analytics

- Doctor performance metrics
- Revenue tracking
- Patient demographics
- Appointment trends visualization

4. Multi-language Support

- i18n implementation

- Hindi, regional languages
- RTL support for Arabic

5. Mobile App

- React Native app
- Push notifications
- Biometric authentication

Technical Debt & Improvements

1. Testing

- Write unit tests (JUnit 5)
- Integration tests (MockMvc)
- Frontend tests (Jest)
- Coverage target: 80%

2. Performance

- Add Redis caching
- Implement pagination for appointments
- Use CDN for static assets
- Database indexing optimization

3. Security

- Rate limiting (prevent brute-force)
- CSRF protection for forms
- Input sanitization
- SQL injection prevention audit

4. DevOps

- Docker containerization
- CI/CD pipeline (GitHub Actions)
- Automated deployment
- Monitoring (Prometheus + Grafana)

5.6 Deployment Strategy

Production Checklist

- ☐ Environment variables for sensitive data
- ☐ HTTPS/SSL certificate

- ☐ Database backup strategy
- ☐ Error logging (ELK stack)
- ☐ Health check endpoints
- ☐ Load balancer configuration
- ☐ Auto-scaling rules
- ☐ CDN setup for static files

Recommended Stack

Hosting: AWS / DigitalOcean / Heroku

Database: AWS RDS (MySQL) or managed MySQL

File Storage: AWS S3

CDN: CloudFlare

Monitoring: New Relic / Datadog

Conclusion

What We Achieved

The Hospital Appointment Management System successfully demonstrates a complete end-to-end solution for digital healthcare appointment booking. Key achievements include:

- ✓ **Functional MVP:** All core features working (booking, management, analytics)
- ✓ **Clean Architecture:** Layered design with clear separation of concerns
- ✓ **Secure Authentication:** JWT-based stateless authentication with role-based access
- ✓ **Modern UI/UX:** Responsive design with intuitive workflows
- ✓ **Scalable Foundation:** RESTful APIs, stateless design, ready for horizontal scaling

Technical Learnings

1. **Spring Boot Ecosystem:** Deep understanding of Spring Security, Spring Data JPA, and Thymeleaf
2. **JWT Authentication:** Implemented secure token-based authentication from scratch
3. **Database Design:** Designed normalized schema with proper relationships and constraints
4. **API Design:** Built RESTful endpoints following industry best practices
5. **Frontend Integration:** Connected vanilla JavaScript frontend with backend APIs
6. **Transaction Management:** Handled race conditions and data consistency
7. **Error Handling:** Implemented comprehensive validation and error responses

Business Value

For **Patients**:

- Eliminate phone booking frustration
- 24/7 appointment booking
- View appointment history and prescriptions

For **Doctors**:

- Streamlined schedule management
- Digital record keeping
- Reduced administrative burden

For **Healthcare Facilities**:

- Centralized appointment system
- Analytics for resource optimization
- Improved patient satisfaction

Final Thoughts

This MVP demonstrates that the core concept is viable and valuable. The technical foundation is solid, and the system can be extended with additional features. With proper testing, security hardening, and deployment, this application is ready for real-world use.

The project showcases full-stack development skills, problem-solving ability, and understanding of enterprise application architecture—all essential for modern software engineering roles.

Project Team

Project Duration: [Add your duration]

Repository: <https://github.com/ayyomad/hcams>

Documentation: See FIXES_SUMMARY.md and DOCTOR_CREDENTIALS.md

Contact: [Your contact information]