# Deciding What to Try Next Revisited

Evaluating a Learning Algorithm

Advice for Applying Machine Learning:

#### Debugging a learning algorithm:

Suppose you have implemented regularized linear regression to predict housing prices. However, when you test your hypothesis in a new set of houses, you find that it makes unacceptably large errors in its prediction. What should you try next?

Windows'u Etkinleştir Windows'u etkinleştirmek için Ayarlar'a gidin.

#### Debugging a learning algorithm:

Suppose you have implemented regularized linear regression to predict housing prices. However, when you test your hypothesis in a new set of houses, you find that it makes unacceptably large errors in its prediction. What should you try next?

- Get more training examples
- Try smaller sets of features
- Try getting additional features .
- Try adding polynomial features  $(x_1^2, x_2^2, x_1x_2, \text{etc})$
- Try decreasing  $\lambda$
- Try increasing  $\lambda$

Windows'u Etkinleştir Windows'u etkinleştirmek için Ayarlar'a gidin.

- Some actions
  - Get more training examples
  - Try smaller set of features (a small set of features)
  - Try getting additional features (just the opposite)
  - Try adding polynomical features
  - Try decreasing lambda
  - Try increasing lambda

- Some actions
  - Get more training examples (fixes high variance)
  - Try smaller set of features (a small set of features)
  - Try getting additional features (just the opposite)
  - Try adding polynomical features
  - Try decreasing lambda
  - Try increasing lambda

- Some actions
  - Get more training examples (fixes high variance)
  - Try smaller set of features (a small set of features) (fixes high variance)
  - Try getting additional features (just the opposite)
  - Try adding polynomical features
  - Try decreasing lambda
  - Try increasing lambda

- Some actions
  - Get more training examples (fixes high variance)
  - Try smaller set of features (a small set of features) (fixes high variance)
  - Try getting additional features (just the opposite) (fixes high bias)
  - Try adding polynomical features
  - Try decreasing lambda
  - Try increasing lambda


- Some actions
  - Get more training examples (fixes high variance)
  - Try smaller set of features (a small set of features) (fixes high variance)
  - Try getting additional features (just the opposite) (fixes high bias)
  - Try adding polynomical features (fixes high bias)
  - Try decreasing lambda
  - Try increasing lambda

- Some actions
  - Get more training examples (fixes high variance)
  - Try smaller set of features (a small set of features) (fixes high variance)
  - Try getting additional features (just the opposite) (fixes high bias)
  - Try adding polynomical features (fixes high bias)
  - Try decreasing lambda (fixes high bias)
  - Try increasing lambda

- Some actions
  - Get more training examples (fixes high variance)
  - Try smaller set of features (a small set of features) (fixes high variance)
  - Try getting additional features (just the opposite) (fixes high bias)
  - Try adding polynomical features (fixes high bias)
  - Try decreasing lambda (fixes high bias)
  - Try increasing lambda (fixes high variance)


#### Neural networks and overfitting

"Small" neural network (fewer parameters; more prone to underfitting)



Computationally cheaper

"Large" neural network (more parameters; more prone to overfitting)



Computationally more expensive.

Use regularization ( $\lambda$ ) to address overfitting.

Windows'u etkinleştirmek için Ayarlar'a gidin.

#### Exercise

- Suppose you fit a neural network with one hidden layer to a training set. You find that the cross validation error  $J_{CV}(\theta)$  is much larger than the training error  $J_{train}(\theta)$ . Is increasing the number of hidden units likely to help?
- Yes, because this increases the number of parameters and lets the network represent more complex functions.
- Yes, because it is currently suffering from high bias.
- No, because it is currently suffering from high bias, so adding hidden units is unlikely to help.
- No, because it is currently suffering from high variance, so adding hidden units is unlikely to help.