

# Multiclass Classification: One vs All

Multiclass Classification

*Logistic Regression*

## **Multiclass classification**

Email foldering/tagging: Work, Friends, Family, Hobby

## Multiclass classification

Email foldering/tagging: Work, Friends, Family, Hobby

$y=1$  ↑

$y=2$  ↑

$y=3$  ↑

$y=4$  ↑

## Multiclass classification

Email foldering/tagging: Work, Friends, Family, Hobby

$y=1$     $y=2$     $y=3$     $y=4$

Medical diagrams: Not ill, Cold, Flu

$y=1$    2   3

## Multiclass classification

Email foldering/tagging: Work, Friends, Family, Hobby

$y=1$        $y=2$        $y=3$        $y=4$


Medical diagrams: Not ill, Cold, Flu

$y=1$       2      3


Weather: Sunny, Cloudy, Rain, Snow

$y=1$       2      3      4


Binary classification:




Binary classification:




Multi-class classification:



Binary classification:






Multi-class classification:









## One-vs-all (one-vs-rest):










Class 1:  


Class 2:  

Class 3:  


## One-vs-all (one-vs-rest):










- Class 1:  
- Class 2:  
- Class 3:  




## One-vs-all (one-vs-rest):




- Class 1:  
- Class 2:  
- Class 3:  




## One-vs-all (one-vs-rest):







Class 1:  $\triangle$   $\leftarrow$   
Class 2:  $\square$   $\leftarrow$   
Class 3:  $\times$   $\leftarrow$





## One-vs-all (one-vs-rest):




Class 1:  

Class 2:  


Class 3:  

$$\underline{h_{\theta}^{(i)}(x)} = P(y = i | x; \theta) \quad (i = 1, 2, 3)$$





## One-vs-all (one-vs-rest):




Class 1:  $\triangle$   $\leftarrow$

Class 2:  $\square$   $\leftarrow$

Class 3:  $\times$   $\leftarrow$

$$h_{\theta}^{(i)}(x) = P(y = i | x; \theta) \quad (i = 1, 2, 3)$$



## One-vs-all

Train a logistic regression classifier  $h_{\theta}^{(i)}(x)$  for each class  $i$  to predict the probability that  $y = i$ .

On a new input  $x$ , to make a prediction, pick the class  $i$  that maximizes

$$\max_i \underline{h_{\theta}^{(i)}(x)}$$

# Exercise

- Suppose you have a multi-class classification problem with  $k$  classes  $y \in \{1, 2, \dots, k\}$ . Using the 1-vs.-all method, how many different logistic regression classifiers will you end up training?
  - $K-1$
  - $K$
  - $K+1$
  - Approximately  $\log_2(k)$