

# Trading off Precision and Recall

*Handling Skewed Data*

Advice for Applying Machine Learning:

## Trading off precision and recall

Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$

Predict 0 if  $h_{\theta}(x) < 0.5$

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$

Predict 0 if  $h_{\theta}(x) < 0.5$

Suppose we want to predict  $y = 1$  (cancer)  
only if very confident.

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq \cancel{0.5} \text{ } 0.7$

Predict 0 if  $h_{\theta}(x) < \cancel{0.5} \text{ } 0.7$

Suppose we want to predict  $y = 1$  (cancer)  
only if very confident.

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq \cancel{0.5} \text{ } 0.7$

Predict 0 if  $h_{\theta}(x) < \cancel{0.5} \text{ } 0.7$

Suppose we want to predict  $y = 1$  (cancer)  
only if very confident.

→ Higher precision,

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq \cancel{0.5} \text{ } 0.7$

Predict 0 if  $h_{\theta}(x) < \cancel{0.5} \text{ } 0.7$

Suppose we want to predict  $y = 1$  (cancer) only if very confident.

→ Higher precision, lower recall.

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$  ~~0.5~~ 0.7 0.9

Predict 0 if  $h_{\theta}(x) < 0.5$  ~~0.5~~ 0.7 0.9

Suppose we want to predict  $y = 1$  (cancer)  
only if very confident.

→ Higher precision, lower recall.

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$



## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$  ~~0.5~~ ~~0.7~~ 0.9

Predict 0 if  $h_{\theta}(x) < 0.5$  ~~0.5~~ ~~0.7~~ 0.9

Suppose we want to predict  $y = 1$  (cancer) only if very confident.

→ Higher precision, lower recall.

Suppose we want to avoid missing too many cases of cancer (avoid false negatives).

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$



## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$  ~~0.5~~ ~~0.7~~ ~~0.9~~ 0.3

Predict 0 if  $h_{\theta}(x) < 0.5$  ~~0.5~~ ~~0.7~~ ~~0.9~~ 0.3

Suppose we want to predict  $y = 1$  (cancer) only if very confident.

→ Higher precision, lower recall.

Suppose we want to avoid missing too many cases of cancer (avoid false negatives).

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$  ~~0.5~~ ~~0.7~~ ~~0.9~~ 0.3

Predict 0 if  $h_{\theta}(x) < 0.5$  ~~0.5~~ ~~0.7~~ ~~0.9~~ 0.3

Suppose we want to predict  $y = 1$  (cancer) only if very confident.

→ Higher precision, lower recall.

Suppose we want to avoid missing too many cases of cancer (avoid false negatives).

→ Higher recall, lower precision.

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$  ~~0.7~~ ~~0.9~~ 0.3

Predict 0 if  $h_{\theta}(x) < 0.5$  ~~0.7~~ ~~0.9~~ 0.3

→ Suppose we want to predict  $y = 1$  (cancer) only if very confident.

→ Higher precision, lower recall.

→ Suppose we want to avoid missing too many cases of cancer (avoid false negatives).

→ Higher recall, lower precision.

$$\rightarrow \text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$

$$\rightarrow \text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$

More generally: Predict 1 if  $h_{\theta}(x) \geq \text{threshold}$ .

## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$  ~~0.7~~ ~~0.9~~ 0.3 ←

Predict 0 if  $h_{\theta}(x) < 0.5$  ~~0.7~~ ~~0.9~~ 0.3

→ Suppose we want to predict  $y = 1$  (cancer) only if very confident.

→ Higher precision, lower recall.


→ Suppose we want to avoid missing too many cases of cancer (avoid false negatives).

→ Higher recall, lower precision.

More generally: Predict 1 if  $h_{\theta}(x) \geq \text{threshold}$ .

→ precision =  $\frac{\text{true positives}}{\text{no. of predicted positive}}$

→ recall =  $\frac{\text{true positives}}{\text{no. of actual positive}}$



Windows'u etkinleştirin  
Windows'u etkinleştirmek için Ayarlar'a gidin.



## Trading off precision and recall

→ Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$  ~~0.7~~ ~~0.9~~ 0.3 ←

Predict 0 if  $h_{\theta}(x) < 0.5$  ~~0.7~~ ~~0.9~~ 0.3

→ Suppose we want to predict  $y = 1$  (cancer) only if very confident.

→ Higher precision, lower recall.


→ Suppose we want to avoid missing too many cases of cancer (avoid false negatives).

→ Higher recall, lower precision.

More generally: Predict 1 if  $h_{\theta}(x) \geq \text{threshold}$ .

→ precision =  $\frac{\text{true positives}}{\text{no. of predicted positive}}$

→ recall =  $\frac{\text{true positives}}{\text{no. of actual positive}}$



Windows'u etkinleştirin  
Windows'u etkinleştirmek için Ayarlar'a gidin.

## **F<sub>1</sub> Score (F score)**

How to compare precision/recall numbers?

	Precision(P)	Recall (R)
Algorithm 1	0.5	0.4
Algorithm 2	0.7	0.1
Algorithm 3	0.02	1.0

Windows'u Etkinleştir  
Windows'u etkinleştirmek için Ayarlar'a gidin.

## F<sub>1</sub> Score (F score)

How to compare precision/recall numbers?

	Precision(P)	Recall (R)	Average
→ Algorithm 1	<u>0.5</u>	<u>0.4</u>	0.45
→ Algorithm 2	<u>0.7</u>	<u>0.1</u>	0.4
Algorithm 3	0.02	1.0	0.51

$$\text{Average: } \frac{P+R}{2}$$

Windows'u Etkinleştir  
Windows'u etkinleştirmek için Ayarlar'a gidin.



## F<sub>1</sub> Score (F score)

How to compare precision/recall numbers?

	Precision(P)	Recall (R)	Average
→ Algorithm 1	<u>0.5</u>	<u>0.4</u>	0.45
→ Algorithm 2	<u>0.7</u>	<u>0.1</u>	0.4
Algorithm 3	0.02	1.0	0.51

Average:  $\frac{P+R}{2}$

← Predict  $y=1$  all the time

## F<sub>1</sub> Score (F score)

How to compare precision/recall numbers?

	Precision(P)	Recall (R)	<del>Average</del>
→ Algorithm 1	<u>0.5</u>	<u>0.4</u>	<del>0.45</del>
→ Algorithm 2	<u>0.7</u>	<u>0.1</u>	<del>0.4</del>
Algorithm 3	<u>0.02</u>	1.0	<u>0.51</u>

Average:  ~~$\frac{P+R}{2}$~~

← Predict y=1 all the time

## F<sub>1</sub> Score (F score)

How to compare precision/recall numbers?

	Precision(P)	Recall (R)	<del>Average</del>	F <sub>1</sub> Score
→ Algorithm 1	<u>0.5</u>	<u>0.4</u>	<del>0.45</del>	0.444 ←
→ Algorithm 2	<u>0.7</u>	<u>0.1</u>	<del>0.4</del>	0.175 ←
Algorithm 3	<u>0.02</u>	1.0	<del>0.51</del>	0.0392 ←

Average:  ~~$\frac{P+R}{2}$~~

F<sub>1</sub> Score:  $2 \frac{PR}{P+R}$

Predict y=1 all the time