#### **CTIS**359

**Principles of Software Engineering** 

**Software Project Estimation Basics** 


# "In preparing for battle I have always found that plans are useless, but planning is indispensable."

Dwight D. Eisenhower

### Today

- What is software project estimation?
- What is Cone of Uncertainty?
- What are the factors to be considered for software estimation?
- Is estimation the basis for credible project management?

- Let us travel from Ankara to XYZ Camping Place?
- What estimations do we need?
  - What is the distance?
  - What is the means of the transportation?
  - What is the (average) speed of the travel?



- Let us travel from Ankara to XYZ Camping Place?
- What estimations do we need?
  - What is the distance?
  - What is the means of the transportation?



• What is the (average) speed of the travel?
















- Let us travel from Ankara to XYZ Camping Place?
- What estimations do we need?
  - What is the distance?
  - What is the means of the transportation?
  - What is the (average) speed of the travel?







- Thereby, we can estimate the time of travel.
- Also, based on the means of the travel, we can estimate the cost of the travel.
- Of course, the schedule can be planned based on the travel requirements.
- If we know history of such (similar) travels, then we can also predict some impediments which can cause some risks which can manifest some defects.



• Thereby, we can estimate the time of travel.



- Also, based on the means of the travel, we can estimate the cost of the travel.
- Of course, the schedule can be planned based on the travel requirements.
- If we know history of such (similar) travels, then we can also predict some impediments which can cause some risks which can manifest some defects.



Thereby, we can estimate the time of travel.



 Also, based on the means of the travel, we can estimate the cost of the travel.



- Of course, the schedule can be planned based on the travel requirements.
- If we know history of such (similar) travels, then we can also predict some impediments which can cause some risks which can manifest some defects.



• Thereby, we can estimate the time of travel.



 Also, based on the means of the travel, we can estimate the cost of the travel.



 Of course, the schedule can be planned based on the travel requirements.



• If we know history of such (similar) travels, then we can also predict some impediments which can cause some risks which can manifest some defects.



- What is the size of the project?
  - Will it be a new development project or an enhancement project?
- Once we know the size and applicable productivity factor, then we can convert this to effort estimation.



- Most of the time, People Cost ≈ Project Cost.
  - Hardware Cost
  - Travel Cost
  - Networking and Infrastructure Cost
  - etc.
- Once we know the effort (PM) estimation AND we have fixed team size (P), then we can estimate time/duration/schedule.

**Source:** https://www.youtube.com/watch?v=uTECToTO9Ec

- Most of the time, People Cost ≈ Project Cost.
  - Hardware Cost
  - Travel Cost
  - Networking and Infrastructure Cost
  - etc.
- Once we know the effort (PM) estimation AND we have fixed duration(M), then we can estimate team size (# of people required).


- Most of the time, People Cost ≈ Project Cost.
  - Hardware Cost
  - Travel Cost
  - Networking and Infrastructure Cost
  - etc.
- If we know the defect density of the previous (similar) project team, we can predict the # of defects that can occur in the project.

 Most Ha These estimates are project Tra specific... Ne etd • If we project team, we can predict the # of defects that can occur in the project.


• **Q:** What is the right time to make the project estimation?

- **Q:** What is the right time to make the project estimation?
- A: After the requirements are reasonably evolved and high level designs are to some extent frozen.

### Cone of Uncertainty



### Cone of Uncertainty



**Source:** https://www.youtube.com/watch?v=uTECToTO9Ec

- Estimated Effort = Size X Applicable Productivity
- Ex: Assume that we have a project to be developed.
  - Size to be delivered = 700 units
  - Applicable Productivity = 20 units/PM or 0,05 PMs/unit
  - Estimated Effort = 700 X 0,05 PMs/unit
  - Estimated Effort = 35 PMs
- Duration = Estimated Effort / Team Size
- Further, assume that we know the team size.
  - # of full-time SWEs = 7
  - Duration = 35 PMs / 7
  - Duration = 5 CMs (Calendar Months)
- Team Size = Estimated Effort / Duration
- If we are given a schedule constraints of 10 CMs
  - Team Size = 35 PMs / 10 CMs
  - Team Size = 3.5

- Defect Level Estimation
- Ex: If the applicable defect density history is 2,3 Defects/100 Units, what is the expected defect density?
- Estimated Defect Density = Total Units X defect density
- Estimated Defect Density = 700 X (2,3/100) = 16 Defects (expected)

- Size is the basis or foundation of the estimation.
  - The main normalization factor for many critical software

<b>Estimated Parameter</b>		Input
Size	<b>←</b>	Requirements
Effort	<b>←</b>	Size, Productivity
Schedule or Team Size	<b>←</b>	Effort, Team Size or Calendar Months
Number of Defects	<del>&lt;</del>	Size, Defect Density

**Source:** https://www.youtube.com/watch?v=uTECToTO9Ec

- Other Factors → Effort (Productivity, ...) → Productivity (....these factors)
  - Team Experience
  - Cohesion of the Project Team
  - Team familiarity with Technology, Domain, Customer
  - Tools used
  - Project Methodology
  - Reuse
  - Nature of Development
  - Phase scope of the project

**Source:** https://www.youtube.com/watch?v=uTECToTO9Ec

- PM is all about
  - Planning
  - Monitoring
  - Controlling

- PM is all about
  - Planning (You make estimations about the project)
  - Monitoring
  - Controlling

- PM is all about
  - Planning (You make estimations about the project)
  - Monitoring (You check the actual progress with the estimations)
  - Controlling

- Ex: A project
  - Total effort = 300 PMs
  - # of SWEs = 10
  - Duration = 30 CMs
    - @ Delivery Milestone 1 (Monitoring Checkpoint)
      - EV = 90 30 (AE PE) = +200%
      - Or
      - EV = 15 30 (AE PE) = -50%


EV = Effort Variance
AE = Actual Effort
PE = Planned Effort

# Software Domain vs. Other Domains

- Software domain is Unique with respect to estimations.
- Absence of physical dimensions
  - No way to weigh, see, touch, and feel the measured software
- Reusing and duplication is possible
  - Reuse already written code and/or already developed components
    - But, we cannot reuse a medicine.
  - We can duplicate the applications
    - But, we cannot copy+paste a wall of a building or a t-shirt.

### Why do we use FPs, OPs, UCPs as the Unit of measurement for Software?

- Weight → kg, pound
  - Length → inch, cm



 Volume → cm³, liters











Products and their size

### Why do we use FPs, OPs, UCPs as the Unit of measurement for Software?



### Why do we use FPs, OPs, UCPs as the Unit of measurement for Software?

- # of service requests handled in a specific period of time.
  - # of customer requests processed / week
- # of tickets resolved / secs





Un

• #

Software is a combination of products and services.

the

CUSTOLLE

# of tick secs

services products

ed /



Services and their size

Source: https://www.youtube.co

# What aspect of software shall we measure to assign a size?

 FPs, OPs, UCPs → benefit provided to the users in terms of tasks and services performed by the software for satisfying the business information processing needs of the users.

### Why not LOC?

• Why we do not use LOC as a unit of measuring the size of a software as these software are built in LOCs?

#### Late availability

- they are only available when the application is built
- Not make sense when it comes to estimation.

#### Vague definition of a LOC

- Logical lines, Physical lines
  - 1 LOC → with many logical functions
  - 1 LOC → with separated logical functions
  - What about looping?

#### LOC is very much programmer/PL dependent

• Efficient programmer might write less number of codes than an inefficient programmer to build the same functionality

### Why not LOC?

- Why we do not use LOC as a unit of measuring the size of a software as these software are built in LOCs?
- Late
- LOC is of not much use when it comes to estimation

- LOC very much programmer/PL dependent
  - Excient programmer might write less number of codes than an inefficient programmer to build the same functionality