

Hypothesis Representation

Classification and Representation

Logistic Regression

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = \theta^T x$$

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = g(\theta^T x)$$

.

Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = g(\theta^T x)$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

Logistic Regression Model


Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = g(\theta^T x)$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

Sigmoid function

Logistic function



Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.


Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = g(\theta^T x)$$

$$\rightarrow g(z) = \frac{1}{1 + e^{-z}}$$

$$h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$



→ Sigmoid function
→ Logistic function

Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$


$$h_{\theta}(x) = g(\theta^T x)$$

$$\rightarrow g(z) = \frac{1}{1 + e^{-z}}$$

$\theta^T x$

$$h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$

Sigmoid function
Logistic function



Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Logistic Regression Model


Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = g(\theta^T x)$$

$$\rightarrow g(z) = \frac{1}{1 + e^{-z}}$$

$\theta^T x$

$$h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$



Sigmoid function
Logistic function

Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.


Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = g(\theta^T x)$$

$$\rightarrow g(z) = \frac{1}{1 + e^{-z}}$$

$$h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$



Sigmoid function

Logistic function

Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Interpretation of Hypothesis Output

$h_{\theta}(x)$ = estimated probability that $y = 1$ on input x

Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Interpretation of Hypothesis Output

$h_{\theta}(x)$

$h_{\theta}(x)$ = estimated probability that $y = 1$ on input x \leftarrow

Example: If $x = \begin{bmatrix} x_0 \\ x_1 \end{bmatrix} = \begin{bmatrix} 1 \\ \text{tumorSize} \end{bmatrix}$

$$h_{\theta}(x) = 0.7$$

Interpretation of Hypothesis Output

$h_{\theta}(x)$

$h_{\theta}(x)$ = estimated probability that $y = 1$ on input x ←

Example: If $x = \begin{bmatrix} x_0 \\ x_1 \end{bmatrix} = \begin{bmatrix} 1 \\ \text{tumorSize} \end{bmatrix}$

$$h_{\theta}(x) = 0.7$$

Tell patient that 70% chance of tumor being malignant

Windows'u Etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Interpretation of Hypothesis Output

$h_{\theta}(x)$

$h_{\theta}(x)$ = estimated probability that $y = 1$ on input x \leftarrow

Example: If x = $\begin{bmatrix} x_0 \\ x_1 \end{bmatrix}$ = $\begin{bmatrix} 1 \leftarrow \\ \text{tumorSize} \leftarrow \end{bmatrix}$

$$\text{↑} \quad \text{y=1} \\ \underline{h_{\theta}(x)} = \underline{0.7}$$

Tell patient that 70% chance of tumor being malignant

$$h_{\theta}(x) = \underline{P(y=1|x;\theta)}$$

“probability that $y = 1$, given x ,
parameterized by θ ”

Exercise

- Suppose we want to predict, from data x about a tumor, whether it is malignant ($y=1$) or benign ($y=0$). Our logistic regression classifier outputs, for a specific tumor, $h_{\theta}(x) = P(y = 1|x; \theta) = 0.7$, so we estimate that there is a 70% chance of this tumor being malignant. What should be our estimate for the probability the tumor is benign?
- 0.7^2
- $0.7-0.3$
- $0.7-0.5$
- 0.3

Interpretation of Hypothesis Output

$h_{\theta}(x)$

$h_{\theta}(x)$ = estimated probability that $y = 1$ on input x \leftarrow

Example: If $\underline{x} = \begin{bmatrix} x_0 \\ x_1 \end{bmatrix} = \begin{bmatrix} 1 \leftarrow \\ \underline{\text{tumorSize}} \leftarrow \end{bmatrix}$

$$\underline{h_{\theta}(x)} = \underline{0.7}$$

$y = 1$

Tell patient that 70% chance of tumor being malignant

$$\underline{h_{\theta}(x)} = \underline{P(y=1|x;\theta)}$$

$y = 0 \text{ or } 1$

“probability that $y = 1$, given x ,
parameterized by θ ”

$$\rightarrow P(y=0|x;\theta) + P(y=1|x;\theta) = 1$$
$$P(y=0|x;\theta) = 1 - P(y=1|x;\theta)$$

Windows'u etkinleştir
Windows'u etkinleştirmek için Ayarlar'a gidin.

Interpretation of Hypothesis Output

$h_{\theta}(x)$

$h_{\theta}(x)$ = estimated probability that $y = 1$ on input x \leftarrow

Example: If $\underline{x} = \begin{bmatrix} x_0 \\ x_1 \end{bmatrix} = \begin{bmatrix} 1 \leftarrow \\ \text{tumorSize} \leftarrow \end{bmatrix}$

$$\underline{h_{\theta}(x)} = \underline{0.7}$$

$y = 1$

Tell patient that 70% chance of tumor being malignant

$$\underline{h_{\theta}(x)} = \underline{P(y=1|x;\theta)}$$

$$\underline{y = 0 \text{ or } 1}$$

“probability that $y = 1$, given x ,
parameterized by θ ”

$$\rightarrow P(y=0|\underline{x};\theta) + P(y=1|\underline{x};\theta) = 1$$
$$P(y=0|x;\theta) = 1 - P(y=1|x;\theta)$$