HIS to VERITA Data Mapping and Dashboard Filters

Nov 4, 2026 · @Mujassir Nasir

Catalogue mapping

The catalogue pack fills 13 VERITA tables from HIS. All queries filter on `SetupID` and `ProjectID`, except where noted.

Hospital

- **HIS tables:** `STP_Project`, `STP_City`, `STP_Currency`
- **Rows picked:** the one project matching the given SetupID and ProjectID. Not applied on a HIS import.

Facility

- **HIS table:** `INP_Building`
- **Rows picked:** active buildings

ServiceLine

- **HIS table:** `HIS_ClinicGroup`
- **Rows picked:** active groups
- **Verita Seed:** `SL-UNMAPPED`
- **Why `SL-UNMAPPED` is needed:** not everything in HIS belongs to a clinic group, so these rows need a service line to point to:
  - Clinics with no `GroupID`
  - Wards, theatres and lab divisions, which have no group in HIS
  - All procedures, because the extract does not assign them a service line
  - Encounters whose clinic is not found in `HIS_Clinic`
- **Effect:** those rows still load, and their cost and revenue appear under an "Unmapped" row on the Service line tab, so the tab still adds up to the run total. A large "Unmapped" row means clinics need a group in HIS.

Department

- **HIS tables:** `HIS_Clinic`, `INP_NursingStation`, `INP_OTMain`, `LAB_Division`
- **Rows picked:** all clinics, active wards, theatres and lab divisions

- **Verita Seed:** `UNMAPPED`, named "Unmapped", of type `ADMIN`, under service line `SL-UNMAPPED`
- **Why `UNMAPPED` is needed:** several tables must have a department, and HIS does not always give one. Without this row, those rows would be rejected on import:
  - Encounters with no clinic
  - Procedures with no lab division and no mapped clinic
  - All cost centres, because HIS gives no reliable link to a department
  - Doctors with no default clinic
  - Encounter or doctor rows in a HIS pack whose department code is not found, which import falls back to `UNMAPPED`
- **Effect:** those encounters still load, and their cost and revenue appear under an "Unmapped" row on the Department tab, so the tab still adds up to the run total. A large "Unmapped" row means clinic data needs fixing in HIS.

They're columns on the VERITA Department table. Each one gets its value from HIS as follows:

HIS table	`serviceLineCode`	`catalogCode`	`deptType`
`HIS_Clinic`	`GroupID`, as `SL-{GroupID}`, which links to `HIS_ClinicGroup`. `SL-UNMAPPED` if empty.	`MappingCode`, otherwise `CLN-{ClinicID}`	Fixed: `CLINICAL`
`INP_NursingStation` (wards)	Always `SL-UNMAPPED`	`MappingCode`, otherwise `NS-{NursingStationID}`	Fixed: `CLINICAL`
`INP_OTMain` (theatres)	Always `SL-UNMAPPED`	Always `OT-{OTID}`	Fixed: `CLINICAL`
`LAB_Division` (labs)	Always `SL-UNMAPPED`	Always `LAB-{DivisionID}`	Fixed: `ANCILLARY`

CostCenter

- **HIS tables:** `HIS_CostCenterSetup`, `HIS_InvoiceDetail`
- **Rows picked:** all for the `SetupID`, plus codes seen on invoices, plus `CC-UNMAPPED`
- **`departmentCode`:** always `UNMAPPED`, because HIS gives no reliable link

Resource

- **HIS tables:** none read directly, because HIS has no resource table. The roles are a fixed list in the extract tool. They link to HIS only through doctors: the doctor's default clinic in HIS_DoctorClinic picks the role.
- **Rows picked:** physician roles only, such as `RES-MD-CARD`

Provider

- **HIS tables:** `HIS_Doctor`, `HIS_DoctorClinic`, `HIS_DoctorSpeciality`
- **Rows picked:** active, non-dummy doctors
- **`departmentCode`:** the doctor's default clinic in `HIS_DoctorClinic`
- **`resourceCode`:** role chosen from that clinic number by a fixed list in `PhysicianRoles`, otherwise `OTHER`
- **`specialty`** and **`grade`:** `SPEC-{SpecialityID}` and `ET-{EmploymentType}`

Procedure

- **HIS tables:** `HIS_Procedure`, `HIS_ProcedureCategory`, `HIS_ProcedureClinicMapping`, `LAB_TestMain`
- **Rows picked:** all except medicines
- **`departmentCode`:** lab division if it is a lab test, otherwise the first mapped clinic, otherwise `UNMAPPED`
- **`serviceLineCode`:** always `SL-UNMAPPED`
- **`catalogCode`:** `OracleItemCode`, otherwise the procedure ID
- **`procType`:** surgery flag, lab test, then keywords in the category and name, such as `IMAGING` or `CONSULT`
- **`complexity`:** `SurgerySeverity` if between 1 and 5, otherwise 3

ProcedureRate

- **HIS table:** `HIS_Procedure`
- **Rows picked:** all except medicines
- **`listPrice`:** `PublishedPrice`, otherwise `Price`
- **`effectiveFrom`:** always 2000-01-01

Package

- **HIS table:** `HIS_Procedure`
- **Rows picked:** `IsPackage = 1`, except medicines

- **`price`:** `PublishedPrice`, otherwise `Price`
- **`coveredLOS`:** `LOS`
- **Also a procedure:** the procedure query excludes only medicines, so invoice lines can point to a package as a billable service

PackageComponent

- **HIS tables:** `HIS_ProcedurePackageDetail`, `HIS_Procedure`
- **Rows picked:** active lines, child not a medicine
- **`quantity`:** number of lines for that child, because HIS repeats a procedure once per unit

Payer/Insurer

- **HIS table:** `HIS_Company`
- **Rows picked:** all companies, plus `PAY-SELF`
- **`payerType`:** keywords in the name first (`CASH`, `MOH`, `GOSI`), then `CompanyType`
- **`contractRate`:** always 1 from HIS
- **Insurer and administrator:** worked out by VERITA from the payer name after import

Facts mapping

The facts pack holds one month. A row belongs to the pack if its visit or its invoice falls in that month, so an old admission billed this month is included.

Patient

- **HIS table:** `HIS_Patient`
- **Rows picked:** patients with a visit or uncancelled invoice in the month. A missing patient becomes an "Unknown patient" stub.
- **`mrn`:** HIS `PatientID`
- **`segment`:** `MATERNITY` if `IsPregnant`, otherwise by age, taken as the pack's end-date year minus birth year: under 18 `PEDIATRIC`, 65 or over `GERIATRIC`, else `ADULT`
- **`fullName`** and **`nationalIdMasked`:** name fields, and `PatientIdentificationNo` masked by the tool

Encounter

- **HIS tables:**

  - IP: `INP_Admission`, `INP_DischargeSummary`, `INP_OTReservation`, `INP_AdmissionDRGList`, `HIS_InvoiceMain`
  - ER: `INP_ERAssessment`, `HIS_Appointment`, `HIS_InvoiceMain`
  - OP: `HIS_Appointment`, `HIS_InvoiceMain`
- **Rows picked:**
  - IP: admitted in the month, or invoiced in the month
  - ER: assessed in the month, or invoiced in the month
  - OP: appointment in the month, or invoiced in the month, unless already written as ER
- **`encounterNo`:** `AdmissionNo`, `AppointmentNo` or `AssessmentNo`. An ER visit linked to an appointment uses the appointment number.
- **`encType`:** `IP`, `ER` or `OP`, from which HIS table the row came
- **`departmentCode`:** IP: `AdmittingClinicID`, otherwise `ClinicID`. OP and ER: `ClinicID`.
- **`serviceLineCode`:** the `GroupID` of that clinic in `HIS_Clinic`, otherwise `SL-UNMAPPED`
- **`providerCode`:** IP: `AdmittingDoctorID`, otherwise `DoctorID`. OP and ER: `DoctorID`.
- **`payerCode`:** IP: `CompanyId`. OP: `CompanyID`. ER: the appointment's company, otherwise the invoice's. `PAY-SELF` when empty.
- **`drgCode`:** HIS DRG sources by admission or appointment
- **`packageCode`:** always blank
- **`acuity`:** always `ROUTINE`

EncounterService

- **HIS tables:** `HIS_InvoiceDetail`, `HIS_InvoiceMain`, `HIS_Procedure`
- **Rows picked:** uncancelled invoice lines that have an encounter, except medicines
- **`costCentreCode`:** `ORA-{CostCenterID}`, otherwise `CC-UNMAPPED`
- **`providerCode`:** `PrimaryDoctorID` on the line
- **`quantity`:** `Quantity`, at least 1
- **`performedAt`:** `PerformDate`, otherwise the invoice date
- **`sourceRef`:** `INV-{TransactionType}-{InvoiceNo}-{LineItemNo}`

RevenueTransaction

- **HIS tables:** `HIS_InvoiceDetail`, `HIS_InvoiceMain`, `HIS_Procedure`

- **Rows picked:** the same lines as EncounterService, medicines included, with no procedure on medicine lines
- **`grossAmount`:** `Price` × `Quantity`
- **`discount`:** `DiscountAmount` + `WaivedAmount`
- **`netAmount`:** `PatientShare` + `CompanyShare`. If that is 0: gross − discount.
- **`sourceRef`:** `REV-{TransactionType}-{InvoiceNo}-{LineItemNo}`, which pairs the line with its service
- **Reference fields:** the raw shares, waiver, tax, claim, settlement and package fields, stored but not used by any calculation

RefundTransaction

- **HIS tables:** `HIS_RefundMain`, `HIS_RefundDetail`, `HIS_InvoiceMain`
- **Rows picked:** all refunds dated in the month, cancelled ones included

InvoicePackageItem

- **HIS tables:** `HIS_InvoicePackageItem`, `HIS_InvoiceMain`
- **Rows picked:** components on uncancelled invoices in the month

ActivityTransaction

- **Rows picked:** measured HIS clocks and quantities, from these sources:
  - OP visit minutes: `HIS_Appointment`, `HIS_Clinic`. `sourceRef` starts `APPT-`.
  - ER stay minutes: `INP_ERAssessment`. `sourceRef` starts `ER-`.
  - Surgery and anaesthesia minutes: `INP_OTReservation`, `INP_Admission`. `sourceRef` starts `OR-`.
  - Bed and ward nursing minutes: `INP_Transfer`, or `INP_Admission` and `INP_DischargeSummary` when no transfer. `sourceRef` starts `BED-`.
  - Floor consumption quantity: `HIS_FloorConsumption`. `sourceRef` starts `FLR-`.
  - Inpatient consumed items: `INP_PatientConsumedItem`. `sourceRef` starts `CON-`.
  - OP dispensed medicines: `HIS_ProgNoteMedicine`. `sourceRef` starts `MED-`.
- **Catalogue dependency:** these rows name activities and resources such as `ER-ASSESS` and `RN-ER`, but the catalogue pack only creates physician roles. With seeding retired, a row is rejected unless its activity and resource already exist in VERITA.

Dashboard tab filters

The tabs do not remove any encounters: each one regroups the same run by a different attribute. Only the Resources tab can place one encounter in more than one row.

What every tab shares

1. **Hospital and period pick the run.** The dashboard reads one calculation run for that pair, preferring a published run, then the newest. Simulation runs are never used.
2. **The run fixes the encounters.** A run covers encounters of that hospital whose `AdmitAt` falls in the period. Revenue follows the encounter, whatever date it was posted.
3. **Figures are read, not filtered live.** Costs and revenue are saved when the run executes. A later import changes nothing until the run is executed again.
4. **Sorting:** highest operating margin first, or highest total cost if revenue is masked.
5. **Access:** the tabs need `profitability.view`. Without `revenue.view`, revenue and margin are hidden. A run in a hospital outside your scope is refused. Department scope does not apply to these tabs.

Each row shows Encounters, Direct, Indirect, Overhead and Total cost, plus Revenue, Operating margin and Margin % for users who can see revenue.

What each tab groups by

Tab	Groups by, and where it comes from in HIS	Shows "Not assigned" when
Service line	The encounter's service line: the `GroupID` of its clinic in `HIS_Clinic`, from `HIS_ClinicGroup`	Never in HIS data: an unmatched clinic goes to the "Unmapped" row
Department	The encounter's department. IP: `AdmittingClinicID`, otherwise `ClinicID`. OP and ER: `ClinicID`.	Never: an unmatched clinic goes to the "Unmapped" row
Resources	Each service line's doctor, `HIS_InvoiceDetail.PrimaryDoctorID`, then that doctor's role resource	The line has no doctor, or the doctor has no resource
Physician	The encounter's doctor. IP: `AdmittingDoctorID`, otherwise `DoctorID`. OP and ER: `DoctorID`.	The encounter has no doctor

Tab	Groups by, and where it comes from in HIS	Shows "Not assigned" when
Payer	The encounter's payer. IP: `INP_Admission.CompanyId`. OP: `HIS_Appointment.CompanyID`. ER: appointment's company, otherwise the invoice's.	Never: an empty company becomes "Self pay / cash"
Encounter type	Which HIS table created the encounter: `IP`, `ER` or `OP`	Never
Patient segment	The patient's segment, from `HIS_Patient.IsPregnant` and `DateofBirth`	Never: a stub patient counts as `ADULT`