



The University of the West Indies, St. Augustine
COMP 2603 Object Oriented Programming I
Assignment 1 Grade Sheet
2020/2021 Semester 2

Govinda Ramcharan (816003108)

27.67%

F3

Criteria	Mark
VirtualMeetingSystem	26.0
VirtualRoom	24.0
BreakoutRoom	21.0
Participant	8.0
Bonuses	+5.0
Deductions	-60.2
Total (out of 86.0)	23.8

Grade Changes

Observe any deductions or bonuses that you have incurred or earned.

Bonuses	
Question Bonus: allocateParticipants(String)	+5.0

Deductions	
Plagiarism Detected: "Repeated Infraction of Academic Dishonesty" from cluster with 3 other persons (-70%)	-60.2

VirtualMeetingSystem Class

Passed 8/10; Partially passed 1/10; Failed 1/10.

Method	createVirtualRoom(String)	2.0 / 2.0
Method	allocateParticipants(String)	10.0 / 10.0
Method	addParticipant(String, int)	2.0 / 2.0
Method	listParticipants(int)	3.0 / 3.0
Method	openBreakoutRoom(int)	2.0 / 2.0
Method	closeBreakoutRoom(int)	2.0 / 2.0
Method	listAllBreakoutRooms()	2.0 / 2.0
Method	findParticipantBreakoutRoom(String)	2.0 / 2.0
Method	listParticipantsInAllBreakoutRooms()	0.0 / 2.0
Returns some values but not all. We expect your method to return a set of values, but instead yours returns only some.		
Check VirtualMeetingSystem() constructor exists and is accessible		✓
Check createVirtualRoom(String) method exists and is accessible		✓

Check <code>openBreakoutRoom(int)</code> method exists and is accessible	✓
Check <code>addParticipant(String, int)</code> method exists and is accessible	✓
Check <code>public String listParticipantsInAllBreakoutRooms()</code> method exists and defined properly	✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓
Check <code>createVirtualRoom(String)</code> method runs with args (<code>"VirtualRoom"</code>)	✓
Check <code>openBreakoutRoom(int)</code> method runs with args (<code>1</code>)	✓
Check <code>addParticipant(String, int)</code> method runs with args (<code>"12345678", 1</code>)	✓
Check <code>listParticipantsInAllBreakoutRooms()</code> method returns a string containing <code>"12345678"</code>	✗

Method	<code>loadParticipantData(String)</code>	1.0 / 5.0
Does not alter the <code>arrayID</code> attribute as it should. We expect your method to change the values of a particular set of instance attributes, but yours doesn't, or it does it in an unanticipated way.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible	✓	
Check <code>public void loadParticipantData(String)</code> method exists and defined properly	✓	
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓	
Check <code>loadParticipantData(String)</code> method runs with args (<code>"src/al/test/resources/participant.dat"</code>)	✓	
Check first attribute with type <code>String[]</code> equals an array with size 50	✓	
Check <code>arrayID</code> attribute equals an array with size 50 +1.0	✓	
Check first attribute with type <code>String[]</code> equals not an array containing null +1.0	✓	
Check <code>arrayID</code> attribute equals not an array containing null	✗	

VirtualRoom Class

Passed 14/14.

Attribute	<code>breakoutRooms</code>	1.0 / 1.0
-----------	----------------------------	-----------

Attribute	breakoutRoomLimit	1.0 / 1.0
Attribute	name	1.0 / 1.0
Constructor	VirtualRoom(String, int)	2.0 / 2.0
Constructor	VirtualRoom(String)	2.0 / 2.0
Method	listBreakoutRooms()	2.0 / 2.0
Method	findBreakoutRoom(int)	2.0 / 2.0
Method	createBreakoutRooms()	2.0 / 2.0
Method	openBreakoutRoom(int)	2.0 / 2.0
Method	closeBreakoutRoom(int)	2.0 / 2.0
Method	findParticipantBreakoutRoom(String)	2.0 / 2.0
Method	getNumberOfBreakoutRooms()	1.0 / 1.0
Method	listParticipantsInBreakoutRoom(int)	2.0 / 2.0
Method	addParticipantToBreakoutRoom(String, int)	2.0 / 2.0

BreakoutRoom Class

Passed 15/16; Partially passed 1/16.

Attribute	breakoutRoomID	1.0 / 1.0
Attribute	breakoutRoomSize	1.0 / 1.0
Attribute	participants	1.0 / 1.0
Attribute	numberOfParticipants	1.0 / 1.0
Attribute	open	1.0 / 1.0

Attribute	<code>breakoutRoomNumberCounter</code>	1.0 / 1.0
Constructor	<code>BreakoutRoom(String)</code>	3.0 / 3.0
Method	<code>findParticipant(String)</code>	2.0 / 2.0
Method	<code>toString()</code>	2.0 / 2.0
Method	<code>getBreakoutRoomID()</code>	1.0 / 1.0
Method	<code>getOpen()</code>	1.0 / 1.0
Method	<code>addParticipant(String)</code>	2.0 / 2.0
Method	<code>openBreakoutRoom()</code>	1.0 / 1.0
Method	<code>closeBreakoutRoom()</code>	1.0 / 1.0
Method	<code>getNumberOfParticipants()</code>	1.0 / 1.0
Method	<code>listParticipants()</code>	1.0 / 2.0
Returns correct information in an incorrect format. We expect your method to return a particular value in a given format, but instead yours returns the value in another format.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓
Check <code>addParticipant(String)</code> method exists and is accessible		✓
Check <code>openBreakoutRoom()</code> method exists and is accessible		✓
Check <code>breakoutRoomID</code> attribute exists		✓
Check <code>public String listParticipants()</code> method exists and defined properly		✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args (<code>"Room1"</code>)		✓
Check <code>openBreakoutRoom()</code> method runs		✓
Check <code>addParticipant(String)</code> method runs with args (<code>"10000000"</code>)		✓
Check <code>listParticipants()</code> method returns string containing attribute <code>breakoutRoomID</code> +1.0		✓
Check <code>listParticipants()</code> method returns string containing attribute <code>participants</code> in format <code>"participant_1.toString() \n participant_2.toString() \n ... participant_</code>		✗

```
n.toString() "
```

Participant Class

Passed 5/5.

Attribute	<code>participantID</code>	1.0 / 1.0
Constructor	<code>Participant(String)</code>	2.0 / 2.0
Method	<code>toString()</code>	2.0 / 2.0
Method	<code>verifyID(String)</code>	2.0 / 2.0
Method	<code>getParticipantID()</code>	1.0 / 1.0