



The University of the West Indies, St. Augustine
COMP 2603 Object Oriented Programming I
Assignment 1 Grade Sheet
2020/2021 Semester 2

Tamia Tuitt (816021561)

78.49%

A-

Criteria	Mark
VirtualMeetingSystem	15.0
VirtualRoom	22.5
BreakoutRoom	22.0
Participant	8.0
Total (out of 86.0)	67.5

VirtualMeetingSystem Class

Passed 7/10; Failed 3/10.

Method	<code>createVirtualRoom(String)</code>	2.0 / 2.0
Method	<code>listParticipants(int)</code>	3.0 / 3.0
Method	<code>openBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>closeBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>listAllBreakoutRooms()</code>	2.0 / 2.0
Method	<code>findParticipantBreakoutRoom(String)</code>	2.0 / 2.0
Method	<code>listParticipantsInAllBreakoutRooms()</code>	2.0 / 2.0
Method	<code>loadParticipantData(String)</code>	0.0 / 5.0
<p>Does not work as anticipated: produced java.io.FileNotFoundException: src/a1/test/resources/participant.dat (No such file or directory). We expect your method to run without problems, but instead yours contains bad code that creates problems.</p> <p>Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible ✓</p> <p>Check <code>public void loadParticipantData(String)</code> method exists and defined properly ✓</p> <p>Check <code>VirtualMeetingSystem()</code> constructor creates instances ✓</p> <p>Check <code>loadParticipantData(String)</code> method runs with args ("src/a1/test/resources/participant.dat") ✗</p>		
Method	<code>allocateParticipants(String)</code>	0.0 / 10.0
<p>Cannot be further tested because testing relies on the <code>loadParticipantData</code> method that does not work as anticipated: produced java.io.FileNotFoundException: src/a1/test/resources/participant.dat (No such file or directory). We expect your method to run without problems, but instead yours contains bad code that creates problems.</p> <p>Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible ✓</p> <p>Check <code>loadParticipantData(String)</code> method exists and is accessible ✓</p>		

Check <code>createVirtualRoom(String)</code> method exists and is accessible	✓
Check <code>public void allocateParticipants(String)</code> method exists and defined properly	✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓
Check <code>loadParticipantData(String)</code> method runs with args ("src/a1/test/resources/participant.dat")	✗

Method	<code>addParticipant(String, int)</code>	0.0 / 2.0
Cannot be further tested because testing relies on the <code>loadParticipantData</code> method that does not work as anticipated: produced <code>java.io.FileNotFoundException: src/a1/test/resources/participant.dat</code> (No such file or directory). We expect your method to run without problems, but instead yours contains bad code that creates problems.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible		✓
Check <code>loadParticipantData(String)</code> method exists and is accessible		✓
Check <code>createVirtualRoom(String)</code> method exists and is accessible		✓
Check <code>openBreakoutRoom(int)</code> method exists and is accessible		✓
Check <code>public boolean addParticipant(String, int)</code> method exists and defined properly		✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances		✓
Check <code>loadParticipantData(String)</code> method runs with args ("src/a1/test/resources/participant.dat")		✗

VirtualRoom Class

Passed 12/14; Partially passed 1/14; Failed 1/14.

Attribute	<code>breakoutRooms</code>	1.0 / 1.0
Attribute	<code>breakoutRoomLimit</code>	1.0 / 1.0
Attribute	<code>name</code>	1.0 / 1.0
Constructor	<code>VirtualRoom(String)</code>	2.0 / 2.0

Method	<code>listBreakoutRooms()</code>	2.0 / 2.0
Method	<code>findBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>createBreakoutRooms()</code>	2.0 / 2.0
Method	<code>openBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>closeBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>findParticipantBreakoutRoom(String)</code>	2.0 / 2.0
Method	<code>listParticipantsInBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>addParticipantToBreakoutRoom(String, int)</code>	2.0 / 2.0
Constructor	<code>VirtualRoom(String, int)</code>	1.5 / 2.0
<p>Does not initialize the breakoutRooms attribute. We expect your constructor to initialize a particular set of instance attributes, but yours doesn't.</p> <p>Check <code>public VirtualRoom(String, int)</code> constructor exists and defined properly ✓</p> <p>Check <code>VirtualRoom(String, int)</code> constructor creates instances with args ("VirtualRoom", 10) +0.5 ✓</p> <p>Check name attribute equals "VirtualRoom" +0.5 ✓</p> <p>Check breakoutRoomLimit attribute equals 10 +0.5 ✓</p> <p>Check breakoutRooms attribute equals an array with size 10 ✗</p>		
Method	<code>getNumberOfBreakoutRooms()</code>	0.0 / 1.0
<p>Does not work as anticipated: produced java.lang.NullPointerException: Cannot invoke "out.Tamia__Ashley_Tuitt_657761_assignsubmission_file_.BreakoutRoom.getBreakoutRoomNumberCounter()" because "this.breakoutRooms[i]" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.</p> <p>Check <code>VirtualRoom(String)</code> constructor exists and is accessible ✓</p> <p>Check breakoutRoomLimit attribute exists ✓</p> <p>Check <code>public int getNumberOfBreakoutRooms()</code> method exists and defined properly ✓</p>		

Check `VirtualRoom(String)` constructor creates instances with args ("VirtualRoom")



Check `getNumberOfBreakoutRooms()` method returns value equal to attribute `breakoutRoomLimit`



BreakoutRoom Class

Passed 16/16.

Attribute	<code>breakoutRoomID</code>	1.0 / 1.0
Attribute	<code>breakoutRoomSize</code>	1.0 / 1.0
Attribute	<code>participants</code>	1.0 / 1.0
Attribute	<code>numberOfParticipants</code>	1.0 / 1.0
Attribute	<code>open</code>	1.0 / 1.0
Attribute	<code>breakoutRoomNumberCounter</code>	1.0 / 1.0
Constructor	<code>BreakoutRoom(String)</code>	3.0 / 3.0
Method	<code>findParticipant(String)</code>	2.0 / 2.0
Method	<code>toString()</code>	2.0 / 2.0
Method	<code>getBreakoutRoomID()</code>	1.0 / 1.0
Method	<code>getOpen()</code>	1.0 / 1.0
Method	<code>addParticipant(String)</code>	2.0 / 2.0
Method	<code>listParticipants()</code>	2.0 / 2.0
Method	<code>openBreakoutRoom()</code>	1.0 / 1.0
Method	<code>closeBreakoutRoom()</code>	1.0 / 1.0

Method	<code>getNumberOfParticipants()</code>	1.0 / 1.0
--------	--	-----------

Participant Class

Passed 5/5.

Attribute	<code>participantID</code>	1.0 / 1.0
Constructor	<code>Participant(String)</code>	2.0 / 2.0
Method	<code>toString()</code>	2.0 / 2.0
Method	<code>verifyID(String)</code>	2.0 / 2.0
Method	<code>getParticipantID()</code>	1.0 / 1.0