



The University of the West Indies, St. Augustine
COMP 2603 Object Oriented Programming I
Assignment 1 Grade Sheet
2020/2021 Semester 2

Aleksi Olivier (816023287)

91.86%

A+

Criteria	Mark
VirtualMeetingSystem	18.0
VirtualRoom	22.5
BreakoutRoom	20.5
Participant	8.0
Bonuses	+10.0
Total (out of 86.0)	79.0

Grade Changes

Observe any deductions or bonuses that you have incurred or earned.

Bonuses	
Merit Bonus: Early submission	+5.0
Question Bonus: allocateParticipants(String)	+5.0

VirtualMeetingSystem Class

Passed 8/10; Partially passed 1/10; Failed 1/10.

Method	<code>createVirtualRoom(String)</code>	2.0 / 2.0
Method	<code>addParticipant(String, int)</code>	2.0 / 2.0
Method	<code>listParticipants(int)</code>	3.0 / 3.0
Method	<code>openBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>closeBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>listAllBreakoutRooms()</code>	2.0 / 2.0
Method	<code>findParticipantBreakoutRoom(String)</code>	2.0 / 2.0
Method	<code>listParticipantsInAllBreakoutRooms()</code>	2.0 / 2.0
Method	<code>allocateParticipants(String)</code>	0.0 / 10.0
Does not work as anticipated: produced java.lang.NullPointerException: Cannot invoke "String.length()" because "participantID" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible		✓
Check <code>loadParticipantData(String)</code> method exists and is accessible		✓
Check <code>createVirtualRoom(String)</code> method exists and is accessible		✓

Check <code>public void allocateParticipants(String)</code> method exists and defined properly	✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓
Check <code>loadParticipantData(String)</code> method runs with args (<code>"src/al/test/resources/participant.dat"</code>)	✓
Check <code>createVirtualRoom(String)</code> method runs with args (<code>"VirtualRoom"</code>)	✓
Check <code>allocateParticipants(String)</code> method runs with args (<code>"RR"</code>)	✓

Method	<code>loadParticipantData(String)</code>	1.0 / 5.0
Does not alter the data attribute as it should. We expect your method to change the values of a particular set of instance attributes, but yours doesn't, or it does it in an unanticipated way.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible		✓
Check <code>public void loadParticipantData(String)</code> method exists and defined properly		✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances		✓
Check <code>loadParticipantData(String)</code> method runs with args (<code>"src/al/test/resources/participant.dat"</code>)		✓
Check first attribute with type <code>String[]</code> equals an array with size 50		✓
Check data attribute equals an array with size 50 +1.0		✓
Check first attribute with type <code>String[]</code> equals not an array containing null +1.0		✓
Check data attribute equals not an array containing null		✗

VirtualRoom Class

Passed 12/14; Partially passed 2/14.

Attribute	<code>breakoutRooms</code>	1.0 / 1.0
-----------	----------------------------	-----------

Attribute	<code>breakoutRoomLimit</code>	1.0 / 1.0
-----------	--------------------------------	-----------

Attribute	<code>name</code>	1.0 / 1.0
-----------	-------------------	-----------

Constructor	<code>VirtualRoom(String)</code>	2.0 / 2.0
-------------	----------------------------------	-----------

Method	<code>findBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>createBreakoutRooms()</code>	2.0 / 2.0
Method	<code>openBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>closeBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>findParticipantBreakoutRoom(String)</code>	2.0 / 2.0
Method	<code>getNumberOfBreakoutRooms()</code>	1.0 / 1.0
Method	<code>listParticipantsInBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>addParticipantToBreakoutRoom(String, int)</code>	2.0 / 2.0
Constructor	<code>VirtualRoom(String, int)</code>	1.0 / 2.0
Does not initialize the <code>breakoutRoomLimit</code> attribute. We expect your constructor to initialize a particular set of instance attributes, but yours doesn't.		
Check <code>public VirtualRoom(String, int)</code> constructor exists and defined properly		✓
Check <code>VirtualRoom(String, int)</code> constructor creates instances with args (<code>"VirtualRoom"</code> , <code>10</code>) +0.5		✓
Check <code>name</code> attribute equals <code>"VirtualRoom"</code> +0.5		✓
Check <code>breakoutRoomLimit</code> attribute equals <code>10</code>		✗
Method	<code>listBreakoutRooms()</code>	1.5 / 2.0
Returns correct information in an incorrect format. We expect your method to return a particular value in a given format, but instead yours returns the value in another format.		
Check <code>VirtualRoom(String)</code> constructor exists and is accessible		✓
Check <code>createBreakoutRooms()</code> method exists and is accessible		✓
Check <code>public String listBreakoutRooms()</code> method exists and defined properly		✓
Check <code>VirtualRoom(String)</code> constructor creates instances with args (<code>"VirtualRoom"</code>)		✓
Check <code>createBreakoutRooms()</code> method runs		✓

Check `listBreakoutRooms()` method returns string containing attribute `name` +1.5



Check `listBreakoutRooms()` method returns string containing attribute `breakoutRooms` in format `"breakoutRoom_1.toString() \n breakoutRoom_2.toString() \n ... breakoutRoom_n.toString() "`



BreakoutRoom Class

Passed 14/16; Partially passed 2/16.

Attribute	<code>breakoutRoomID</code>	1.0 / 1.0
Attribute	<code>breakoutRoomSize</code>	1.0 / 1.0
Attribute	<code>participants</code>	1.0 / 1.0
Attribute	<code>numberOfParticipants</code>	1.0 / 1.0
Attribute	<code>open</code>	1.0 / 1.0
Attribute	<code>breakoutRoomNumberCounter</code>	1.0 / 1.0
Constructor	<code>BreakoutRoom(String)</code>	3.0 / 3.0
Method	<code>findParticipant(String)</code>	2.0 / 2.0
Method	<code>getBreakoutRoomID()</code>	1.0 / 1.0
Method	<code>getOpen()</code>	1.0 / 1.0
Method	<code>addParticipant(String)</code>	2.0 / 2.0
Method	<code>openBreakoutRoom()</code>	1.0 / 1.0
Method	<code>closeBreakoutRoom()</code>	1.0 / 1.0
Method	<code>getNumberOfParticipants()</code>	1.0 / 1.0
Method	<code>listParticipants()</code>	1.0 / 2.0

Returns correct information in an incorrect format. We expect your method to return a particular value in a given format, but instead yours returns the value in another format.

Check <code>BreakoutRoom(String)</code> constructor exists and is accessible	✓
Check <code>addParticipant(String)</code> method exists and is accessible	✓
Check <code>openBreakoutRoom()</code> method exists and is accessible	✓
Check <code>breakoutRoomID</code> attribute exists	✓
Check <code>public String listParticipants()</code> method exists and defined properly	✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args ("Room1")	✓
Check <code>openBreakoutRoom()</code> method runs	✓
Check <code>addParticipant(String)</code> method runs with args ("10000000")	✓
Check <code>listParticipants()</code> method returns string containing attribute <code>breakoutRoomID +1.0</code>	✓
Check <code>listParticipants()</code> method returns string containing attribute <code>participants</code> in format "participant_1.toString() \n participant_2.toString() \n ... participant_ n.toString() "	✗

Method	<code>toString()</code>	1.5 / 2.0
Returns correct information in an incorrect format. We expect your method to return a particular value in a given format, but instead yours returns the value in another format.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓
Check <code>breakoutRoomID</code> attribute exists		✓
Check <code>numberOfParticipants</code> attribute exists		✓
Check <code>public String toString()</code> method exists and defined properly		✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args ("Room1")		✓
Check <code>openBreakoutRoom()</code> method runs		✓
Check <code>toString()</code> method returns string containing attribute <code>breakoutRoomID +0.5</code>		✓
Check <code>toString()</code> method returns string containing attribute <code>numberOfParticipants +0.5</code>		✓
Check <code>toString()</code> method returns string containing attribute <code>breakoutRoomID</code> in format <code>breakoutRoomID OPEN +0.5</code>		✓

Check toString() method returns string containing attribute numberOfParticipants in format
OPEN numberOfParticipants



Participant Class

Passed 5/5.

Attribute	participantID	1.0 / 1.0
Constructor	Participant(String)	2.0 / 2.0
Method	toString()	2.0 / 2.0
Method	verifyID(String)	2.0 / 2.0
Method	getParticipantID()	1.0 / 1.0