



The University of the West Indies, St. Augustine
COMP 2603 Object Oriented Programming I
Assignment 1 Grade Sheet
2020/2021 Semester 2

Cameron Sugden (816014699)

52.56%

C

Criteria	Mark
VirtualMeetingSystem	26.0
VirtualRoom	21.0
BreakoutRoom	17.0
Participant	8.0
Deductions	-26.8
Total (out of 86.0)	45.2

Grade Changes

Observe any deductions or bonuses that you have incurred or earned.

Deductions	
Formatting Error: Incorrect zip name format	-1
Plagiarism Detected: "Cheater - First Infraction" from cluster with 5 other persons (-30%)	-25.8

VirtualMeetingSystem Class

Passed 8/10; Partially passed 1/10; Failed 1/10.

Method	<code>createVirtualRoom(String)</code>	2.0 / 2.0
Method	<code>allocateParticipants(String)</code>	10.0 / 10.0
Method	<code>addParticipant(String, int)</code>	2.0 / 2.0
Method	<code>listParticipants(int)</code>	3.0 / 3.0
Method	<code>openBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>closeBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>listAllBreakoutRooms()</code>	2.0 / 2.0
Method	<code>listParticipantsInAllBreakoutRooms()</code>	2.0 / 2.0
Method	<code>findParticipantBreakoutRoom(String)</code>	0.0 / 2.0
Does not work as anticipated for valid inputs. We expect your method to work in a particular way (and possibly return an anticipated value) when given valid inputs, but yours doesn't.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible		✓
Check <code>createVirtualRoom(String)</code> method exists and is accessible		✓
Check <code>openBreakoutRoom(int)</code> method exists and is accessible		✓

Check <code>addParticipant(String, int)</code> method exists and is accessible	✓
Check <code>public String findParticipantBreakoutRoom(String)</code> method exists and defined properly	✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓
Check <code>createVirtualRoom(String)</code> method runs with args <code>("VirtualRoom")</code>	✓
Check <code>openBreakoutRoom(int)</code> method runs with args <code>(1)</code>	✓
Check <code>addParticipant(String, int)</code> method runs with args <code>("12345678", 1)</code>	✓
Check <code>findParticipantBreakoutRoom(String)</code> method returns not null with args <code>("12345678")</code>	✗

Method	<code>loadParticipantData(String)</code>	1.0 / 5.0
Does not alter the data attribute as it should. We expect your method to change the values of a particular set of instance attributes, but yours doesn't, or it does it in an unanticipated way.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible		✓
Check <code>public void loadParticipantData(String)</code> method exists and defined properly		✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances		✓
Check <code>loadParticipantData(String)</code> method runs with args <code>("src/al/test/resources/participant.dat")</code>		✓
Check first attribute with type <code>String[]</code> equals an array with size 50		✓
Check data attribute equals an array with size 50 +1.0		✓
Check first attribute with type <code>String[]</code> equals not an array containing null +1.0		✓
Check data attribute equals not an array containing null		✗

VirtualRoom Class

Passed 12/14; Failed 2/14.

Attribute	<code>breakoutRooms</code>	1.0 / 1.0
-----------	----------------------------	-----------

Attribute	<code>name</code>	1.0 / 1.0
-----------	-------------------	-----------

Constructor	<code>VirtualRoom(String, int)</code>	2.0 / 2.0
Constructor	<code>VirtualRoom(String)</code>	2.0 / 2.0
Method	<code>listBreakoutRooms()</code>	2.0 / 2.0
Method	<code>findBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>createBreakoutRooms()</code>	2.0 / 2.0
Method	<code>openBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>closeBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>getNumberOfBreakoutRooms()</code>	1.0 / 1.0
Method	<code>listParticipantsInBreakoutRoom(int)</code>	2.0 / 2.0
Method	<code>addParticipantToBreakoutRoom(String, int)</code>	2.0 / 2.0
Attribute	<code>breakoutRoomLimit</code>	0.0 / 1.0
<p>Does not have final modifier. We expect your attribute or method to have the final keyword indicating that it is a constant attribute or an un-overridable method, but yours doesn't.</p> <p>Check <code>private final int breakoutRoomLimit</code> attribute exists and defined properly</p>		
Method	<code>findParticipantBreakoutRoom(String)</code>	0.0 / 2.0
<p>Does not work as anticipated for valid inputs. We expect your method to work in a particular way (and possibly return an anticipated value) when given valid inputs, but yours doesn't.</p> <p>Check <code>VirtualRoom(String)</code> constructor exists and is accessible</p> <p>Check <code>createBreakoutRooms()</code> method exists and is accessible</p> <p>Check <code>listParticipantsInBreakoutRoom(int)</code> method exists and is accessible</p> <p>Check <code>addParticipantToBreakoutRoom(String, int)</code> method exists and is accessible</p> <p>Check <code>public String findParticipantBreakoutRoom(String)</code> method exists and defined properly</p> <p>Check <code>VirtualRoom(String)</code> constructor creates instances with args (<code>"VirtualRoom"</code>)</p>		

Check <code>createBreakoutRooms()</code> method runs	✓
Check <code>openBreakoutRoom(int)</code> method runs with args (1)	✓
Check <code>addParticipantToBreakoutRoom(String, int)</code> method runs with args ("12345678", 1)	✓
Check <code>findParticipantBreakoutRoom(String)</code> method returns not null with args ("12345678")	✗

BreakoutRoom Class

Passed 13/16; Failed 3/16.

Attribute	<code>breakoutRoomID</code>	1.0 / 1.0
Attribute	<code>breakoutRoomSize</code>	1.0 / 1.0
Attribute	<code>participants</code>	1.0 / 1.0
Attribute	<code>numberOfParticipants</code>	1.0 / 1.0
Attribute	<code>open</code>	1.0 / 1.0
Attribute	<code>breakoutRoomNumberCounter</code>	1.0 / 1.0
Constructor	<code>BreakoutRoom(String)</code>	3.0 / 3.0
Method	<code>getBreakoutRoomID()</code>	1.0 / 1.0
Method	<code>getOpen()</code>	1.0 / 1.0
Method	<code>addParticipant(String)</code>	2.0 / 2.0
Method	<code>listParticipants()</code>	2.0 / 2.0
Method	<code>openBreakoutRoom()</code>	1.0 / 1.0
Method	<code>closeBreakoutRoom()</code>	1.0 / 1.0

Method	<code>findParticipant(String)</code>	0.0 / 2.0
Does not work as anticipated for valid inputs. We expect your method to work in a particular way (and possibly return an anticipated value) when given valid inputs, but yours doesn't.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓
Check <code>addParticipant(String)</code> method exists and is accessible		✓
Check <code>openBreakoutRoom()</code> method exists and is accessible		✓
Check <code>public Participant findParticipant(String)</code> method exists and defined properly		✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args (<code>"Room1"</code>)		✓
Check <code>openBreakoutRoom()</code> method runs		✓
Check <code>addParticipant(String)</code> method runs with args (<code>"10000000"</code>)		✓
Check <code>findParticipant(String)</code> method returns <code>not null</code> with args (<code>"10000000"</code>)		✗

Method	<code>toString()</code>	0.0 / 2.0
Returns some values but not all. We expect your method to return a set of values, but instead yours returns only some.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓
Check <code>breakoutRoomID</code> attribute exists		✓
Check <code>numberOfParticipants</code> attribute exists		✓
Check <code>public String toString()</code> method exists and defined properly		✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args (<code>"Room1"</code>)		✓
Check <code>openBreakoutRoom()</code> method runs		✓
Check <code>toString()</code> method returns string containing attribute <code>breakoutRoomID</code>		✗

Method	<code>getNumberOfParticipants()</code>	0.0 / 1.0
Is not defined. We expect your attribute, method or constructor to be defined in a particular way, but yours isn't or not defined at all.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓

Check numberOfParticipants attribute exists



Check public int getNumberOfParticipants() method exists and defined properly



Participant Class

Passed 5/5.

Attribute	participantID	1.0 / 1.0
Constructor	Participant(String)	2.0 / 2.0
Method	toString()	2.0 / 2.0
Method	verifyID(String)	2.0 / 2.0
Method	getParticipantID()	1.0 / 1.0