



The University of the West Indies, St. Augustine
COMP 2603 Object Oriented Programming I
Assignment 1 Grade Sheet
2020/2021 Semester 2

Aaron Payne (816009846)

35.47%

F3

Criteria	Mark
VirtualMeetingSystem	10.0
VirtualRoom	4.0
BreakoutRoom	7.5
Participant	4.0
Bonuses	+5.0
Total (out of 86.0)	30.5

Grade Changes

Observe any deductions or bonuses that you have incurred or earned.

Bonuses	
Question Bonus: allocateParticipants(String)	+5.0

VirtualMeetingSystem Class

Passed 1/10; Failed 9/10.

Method	allocateParticipants(String)	10.0 / 10.0
--------	------------------------------	-------------

Method	loadParticipantData(String)	0.0 / 5.0
--------	-----------------------------	-----------

Does not have anticipated type. We expect your attribute to be defined with a particular type, but yours isn't.

Check VirtualMeetingSystem() constructor exists and is accessible ✓

Check public void loadParticipantData(String) method exists and defined properly ✓

Check VirtualMeetingSystem() constructor creates instances ✓

Check loadParticipantData(String) method runs with args
("src/al/test/resources/participant.dat") ✓

Check first attribute with type String[] equals an array with size 50 ✗

Method	createVirtualRoom(String)	0.0 / 2.0
--------	---------------------------	-----------

Does not alter the virtualRoom attribute as it should. We expect your method to change the values of a particular set of instance attributes, but yours doesn't, or it does it in an unanticipated way.

Check VirtualMeetingSystem() constructor exists and is accessible ✓

Check public void createVirtualRoom(String) method exists and defined properly ✓

Check VirtualMeetingSystem() constructor creates instances ✓

Check createVirtualRoom(String) method runs with args ("VirtualRoom") ✓

Check first attribute with type VirtualRoom equals not null ✓

Check virtualRoom attribute equals not null

✗

Method

addParticipant(String, int)

0.0 / 2.0

Cannot be further tested because testing relies on the openBreakoutRoom method that does not work as anticipated: produced java.lang.NullPointerException: Cannot invoke "out.Aaron_Payne_657799_assignsubmission_file_.VirtualRoom.openBreakoutRoom(int)" because "this.virtualRoom" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check VirtualMeetingSystem() constructor exists and is accessible

✓

Check loadParticipantData(String) method exists and is accessible

✓

Check createVirtualRoom(String) method exists and is accessible

✓

Check openBreakoutRoom(int) method exists and is accessible

✓

Check public boolean addParticipant(String, int) method exists and defined properly

✓

Check VirtualMeetingSystem() constructor creates instances

✓

Check loadParticipantData(String) method runs with args
("src/al/test/resources/participant.dat")

✓

Check createVirtualRoom(String) method runs with args ("VirtualRoom")

✓

Check openBreakoutRoom(int) method runs with args (1)

✗

Method

listParticipants(int)

0.0 / 3.0

Cannot be further tested because testing relies on the openBreakoutRoom method that does not work as anticipated: produced java.lang.NullPointerException: Cannot invoke "out.Aaron_Payne_657799_assignsubmission_file_.VirtualRoom.openBreakoutRoom(int)" because "this.virtualRoom" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check VirtualMeetingSystem() constructor exists and is accessible

✓

Check createVirtualRoom(String) method exists and is accessible

✓

Check openBreakoutRoom(int) method exists and is accessible

✓

Check addParticipant(String, int) method exists and is accessible

✓

Check public String listParticipants(int) method exists and defined properly

✓

Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓
Check <code>createVirtualRoom(String)</code> method runs with args (<code>"VirtualRoom"</code>)	✓
Check <code>openBreakoutRoom(int)</code> method runs with args (<code>1</code>)	✗

Method	<code>openBreakoutRoom(int)</code>	0.0 / 2.0
Does not work as anticipated: produced <code>java.lang.NullPointerException: Cannot invoke "out.Aaron_Payne_657799_assignsubmission_file_.VirtualRoom.openBreakoutRoom(int)"</code> because <code>"this.virtualRoom"</code> is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible	✓	
Check <code>createVirtualRoom(String)</code> method exists and is accessible	✓	
Check <code>public boolean openBreakoutRoom(int)</code> method exists and defined properly	✓	
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓	
Check <code>createVirtualRoom(String)</code> method runs with args (<code>"VirtualRoom"</code>)	✓	
Check <code>openBreakoutRoom(int)</code> method runs with args (<code>1</code>)	✗	

Method	<code>closeBreakoutRoom(int)</code>	0.0 / 2.0
Does not work as anticipated: produced <code>java.lang.NullPointerException: Cannot invoke "out.Aaron_Payne_657799_assignsubmission_file_.VirtualRoom.closeBreakoutRoom(int)"</code> because <code>"this.virtualRoom"</code> is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.		
Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible	✓	
Check <code>createVirtualRoom(String)</code> method exists and is accessible	✓	
Check <code>public boolean closeBreakoutRoom(int)</code> method exists and defined properly	✓	
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓	
Check <code>createVirtualRoom(String)</code> method runs with args (<code>"VirtualRoom"</code>)	✓	
Check <code>closeBreakoutRoom(int)</code> method runs with args (<code>1</code>)	✗	

Method	<code>listAllBreakoutRooms()</code>	0.0 / 2.0
--------	-------------------------------------	-----------

Does not work as anticipated: produced java.lang.NullPointerException: Cannot invoke "out.Aaron_Payne_657799_assignsubmission_file_.VirtualRoom.listBreakoutRooms()" because "this.virtualRoom" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.

- Check `VirtualMeetingSystem()` constructor exists and is accessible ✓
- Check `createVirtualRoom(String)` method exists and is accessible ✓
- Check `public String listAllBreakoutRooms()` method exists and defined properly ✓
- Check `VirtualMeetingSystem()` constructor creates instances ✓
- Check `createVirtualRoom(String)` method runs with args ("VirtualRoom") ✓
- Check `listAllBreakoutRooms()` method returns a string containing "VirtualRoom" ✗

Method	<code>findParticipantBreakoutRoom(String)</code>	0.0 / 2.0
--------	--	-----------

Cannot be further tested because testing relies on the `openBreakoutRoom` method that does not work as anticipated: produced java.lang.NullPointerException: Cannot invoke "out.Aaron_Payne_657799_assignsubmission_file_.VirtualRoom.openBreakoutRoom(int)" because "this.virtualRoom" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.

- Check `VirtualMeetingSystem()` constructor exists and is accessible ✓
- Check `createVirtualRoom(String)` method exists and is accessible ✓
- Check `openBreakoutRoom(int)` method exists and is accessible ✓
- Check `addParticipant(String, int)` method exists and is accessible ✓
- Check `public String findParticipantBreakoutRoom(String)` method exists and defined properly ✓
- Check `VirtualMeetingSystem()` constructor creates instances ✓
- Check `createVirtualRoom(String)` method runs with args ("VirtualRoom") ✓
- Check `openBreakoutRoom(int)` method runs with args (1) ✗

Method	<code>listParticipantsInAllBreakoutRooms()</code>	0.0 / 2.0
--------	---	-----------

Cannot be further tested because testing relies on the `openBreakoutRoom` method that does not work as anticipated: produced java.lang.NullPointerException: Cannot invoke

"out.Aaron_Payne_657799_assignsubmission_file_.VirtualRoom.openBreakoutRoom(int)" because "this.virtualRoom" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check <code>VirtualMeetingSystem()</code> constructor exists and is accessible	✓
Check <code>createVirtualRoom(String)</code> method exists and is accessible	✓
Check <code>openBreakoutRoom(int)</code> method exists and is accessible	✓
Check <code>addParticipant(String, int)</code> method exists and is accessible	✓
Check <code>public String listParticipantsInAllBreakoutRooms()</code> method exists and defined properly	✓
Check <code>VirtualMeetingSystem()</code> constructor creates instances	✓
Check <code>createVirtualRoom(String)</code> method runs with args ("VirtualRoom")	✓
Check <code>openBreakoutRoom(int)</code> method runs with args (1)	✗

VirtualRoom Class

Passed 2/14; Partially passed 2/14; Failed 10/14.

Attribute	<code>name</code>	1.0 / 1.0
-----------	-------------------	-----------

Method	<code>createBreakoutRooms()</code>	2.0 / 2.0
--------	------------------------------------	-----------

Attribute	<code>breakoutRooms</code>	0.0 / 1.0
-----------	----------------------------	-----------

Does not have private access. We expect your attribute, method or constructor to have the private keyword indicating that it has private access, but yours doesn't.

Check `private BreakoutRoom[] breakoutRooms` attribute exists and defined properly ✗

Attribute	<code>breakoutRoomLimit</code>	0.0 / 1.0
-----------	--------------------------------	-----------

Does not have private access. We expect your attribute, method or constructor to have the private keyword indicating that it has private access, but yours doesn't.

Check `private final int breakoutRoomLimit` attribute exists and defined properly ✗

Constructor	VirtualRoom(String, int)	0.5 / 2.0
Does not initialize the name attribute. We expect your constructor to initialize a particular set of instance attributes, but yours doesn't.		
Check public VirtualRoom(String, int) constructor exists and defined properly		✓
Check VirtualRoom(String, int) constructor creates instances with args ("VirtualRoom", 10) +0.5		✓
Check name attribute equals "VirtualRoom"		✗

Constructor	VirtualRoom(String)	0.5 / 2.0
Does not initialize the name attribute. We expect your constructor to initialize a particular set of instance attributes, but yours doesn't.		
Check public VirtualRoom(String) constructor exists and defined properly		✓
Check VirtualRoom(String) constructor creates instances with args ("VirtualRoom") +0.5		✓
Check name attribute equals "VirtualRoom"		✗

Method	listBreakoutRooms()	0.0 / 2.0
Does not work as anticipated: produced java.lang.NullPointerException: Cannot load from object array because "this.breakoutRooms" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.		
Check VirtualRoom(String) constructor exists and is accessible		✓
Check createBreakoutRooms() method exists and is accessible		✓
Check public String listBreakoutRooms() method exists and defined properly		✓
Check VirtualRoom(String) constructor creates instances with args ("VirtualRoom")		✓
Check createBreakoutRooms() method runs		✓
Check listBreakoutRooms() method returns string containing attribute name		✗

Method	findBreakoutRoom(int)	0.0 / 2.0
Does not work as anticipated: produced java.lang.NullPointerException: Cannot load from object array because "this.breakoutRooms" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.		

Check <code>VirtualRoom(String)</code> constructor exists and is accessible	✓
Check <code>createBreakoutRooms()</code> method exists and is accessible	✓
Check <code>public BreakoutRoom findBreakoutRoom(int)</code> method exists and defined properly	✓
Check <code>VirtualRoom(String)</code> constructor creates instances with args (<code>"VirtualRoom"</code>)	✓
Check <code>createBreakoutRooms()</code> method runs	✓
Check <code>findBreakoutRoom(int)</code> method returns <code>not null</code> with args (<code>1</code>)	✗

Method	<code>openBreakoutRoom(int)</code>	0.0 / 2.0
Cannot be further tested because testing relies on the <code>closeBreakoutRoom</code> method that does not work as anticipated: produced <code>java.lang.NullPointerException: Cannot load from object array because "this.breakoutRooms" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.</code>		
Check <code>VirtualRoom(String)</code> constructor exists and is accessible	✓	
Check <code>createBreakoutRooms()</code> method exists and is accessible	✓	
Check <code>closeBreakoutRoom(int)</code> method exists and is accessible	✓	
Check <code>breakoutRooms</code> attribute exists	✓	
Check <code>public boolean openBreakoutRoom(int)</code> method exists and defined properly	✓	
Check <code>VirtualRoom(String)</code> constructor creates instances with args (<code>"VirtualRoom"</code>)	✓	
Check <code>createBreakoutRooms()</code> method runs	✓	
Check <code>closeBreakoutRoom(int)</code> method runs with args (<code>1</code>)	✗	

Method	<code>closeBreakoutRoom(int)</code>	0.0 / 2.0
Does not work as anticipated: produced <code>java.lang.NullPointerException: Cannot load from object array because "this.breakoutRooms" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.</code>		
Check <code>VirtualRoom(String)</code> constructor exists and is accessible	✓	
Check <code>createBreakoutRooms()</code> method exists and is accessible	✓	
Check <code>breakoutRooms</code> attribute exists	✓	

Check <code>public boolean closeBreakoutRoom(int)</code> method exists and defined properly	✓
Check <code>VirtualRoom(String)</code> constructor creates instances with args ("VirtualRoom")	✓
Check <code>createBreakoutRooms()</code> method runs	✓
Check <code>closeBreakoutRoom(int)</code> method runs with args (1)	✗

Method	<code>findParticipantBreakoutRoom(String)</code>	0.0 / 2.0
--------	--	-----------

Cannot be further tested because testing relies on the `openBreakoutRoom` method that does not work as anticipated: produced `java.lang.NullPointerException: Cannot load from object array because "this.breakoutRooms" is null`. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check <code>VirtualRoom(String)</code> constructor exists and is accessible	✓
Check <code>createBreakoutRooms()</code> method exists and is accessible	✓
Check <code>listParticipantsInBreakoutRoom(int)</code> method exists and is accessible	✓
Check <code>addParticipantToBreakoutRoom(String, int)</code> method exists and is accessible	✓
Check <code>public String findParticipantBreakoutRoom(String)</code> method exists and defined properly	✓
Check <code>VirtualRoom(String)</code> constructor creates instances with args ("VirtualRoom")	✓
Check <code>createBreakoutRooms()</code> method runs	✓
Check <code>openBreakoutRoom(int)</code> method runs with args (1)	✗

Method	<code>getNumberOfBreakoutRooms()</code>	0.0 / 1.0
--------	---	-----------

Is not defined. We expect your attribute, method or constructor to be defined in a particular way, but yours isn't or not defined at all.

Check <code>VirtualRoom(String)</code> constructor exists and is accessible	✓
Check <code>breakoutRoomLimit</code> attribute exists	✓
Check <code>public int getNumberOfBreakoutRooms()</code> method exists and defined properly	✗

Method	<code>listParticipantsInBreakoutRoom(int)</code>	0.0 / 2.0
--------	--	-----------

Does not work as anticipated: produced `java.lang.NullPointerException: Cannot load from object array`

because "this.breakoutRooms" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check <code>VirtualRoom(String)</code> constructor exists and is accessible	✓
Check <code>createBreakoutRooms()</code> method exists and is accessible	✓
Check <code>addParticipantToBreakoutRoom(String, int)</code> method exists and is accessible	✓
Check <code>public String listParticipantsInBreakoutRoom(int)</code> method exists and defined properly	✓
Check <code>VirtualRoom(String)</code> constructor creates instances with args (<code>"VirtualRoom"</code>)	✓
Check <code>createBreakoutRooms()</code> method runs	✓
Check <code>listParticipantsInBreakoutRoom(int)</code> method returns not null with args (1)	✗

Method	<code>addParticipantToBreakoutRoom(String, int)</code>	0.0 / 2.0
--------	--	-----------

Cannot be further tested because testing relies on the `openBreakoutRoom` method that does not work as anticipated: produced `java.lang.NullPointerException: Cannot load from object array because "this.breakoutRooms" is null`. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check <code>VirtualRoom(String)</code> constructor exists and is accessible	✓
Check <code>createBreakoutRooms()</code> method exists and is accessible	✓
Check <code>listParticipantsInBreakoutRoom(int)</code> method exists and is accessible	✓
Check <code>public boolean addParticipantToBreakoutRoom(String, int)</code> method exists and defined properly	✓
Check <code>VirtualRoom(String)</code> constructor creates instances with args (<code>"VirtualRoom"</code>)	✓
Check <code>createBreakoutRooms()</code> method runs	✓
Check <code>openBreakoutRoom(int)</code> method runs with args (1)	✗

BreakoutRoom Class

Passed 5/16; Partially passed 1/16; Failed 10/16.

Attribute	<code>participants</code>	1.0 / 1.0
Attribute	<code>numberOfParticipants</code>	1.0 / 1.0
Attribute	<code>open</code>	1.0 / 1.0
Method	<code>toString()</code>	2.0 / 2.0
Method	<code>openBreakoutRoom()</code>	1.0 / 1.0
Attribute	<code>breakoutRoomID</code>	0.0 / 1.0
Does not have private access. We expect your attribute, method or constructor to have the private keyword indicating that it has private access, but yours doesn't.		
Check <code>private String breakoutRoomID</code> attribute exists and defined properly		✗
Attribute	<code>breakoutRoomSize</code>	0.0 / 1.0
Does not have final modifier. We expect your attribute or method to have the final keyword indicating that it is a constant attribute or an un-overridable method, but yours doesn't.		
Check <code>private final int breakoutRoomSize</code> attribute exists and defined properly		✗
Attribute	<code>breakoutRoomNumberCounter</code>	0.0 / 1.0
Does not have private access. We expect your attribute, method or constructor to have the private keyword indicating that it has private access, but yours doesn't.		
Check <code>private static int breakoutRoomNumberCounter</code> attribute exists and defined properly		✗
Constructor	<code>BreakoutRoom(String)</code>	1.5 / 3.0
Does not initialize the breakoutRoomSize attribute. We expect your constructor to initialize a particular set of instance attributes, but yours doesn't.		
Check <code>public BreakoutRoom(String)</code> constructor exists and defined properly		✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args ("Room1") +1.0		✓
Check <code>breakoutRoomID</code> attribute equals <code>not null</code> +0.5		✓
Check <code>breakoutRoomSize</code> attribute equals 10		✗

Method	<code>findParticipant(String)</code>	0.0 / 2.0
Cannot be further tested because testing relies on the <code>addParticipant</code> method that does not work as anticipated: produced <code>java.lang.NullPointerException: Cannot store to object array because "this.participants" is null</code> . We expect your method to run without problems, but instead yours contains bad code that creates problems.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓
Check <code>addParticipant(String)</code> method exists and is accessible		✓
Check <code>openBreakoutRoom()</code> method exists and is accessible		✓
Check <code>public Participant findParticipant(String)</code> method exists and defined properly		✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args ("Room1")		✓
Check <code>openBreakoutRoom()</code> method runs		✓
Check <code>addParticipant(String)</code> method runs with args ("10000000")		✗

Method	<code>getBreakoutRoomID()</code>	0.0 / 1.0
Is not defined. We expect your attribute, method or constructor to be defined in a particular way, but yours isn't or not defined at all.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓
Check <code>breakoutRoomID</code> attribute exists		✓
Check <code>public String getBreakoutRoomID()</code> method exists and defined properly		✗

Method	<code>getOpen()</code>	0.0 / 1.0
Is not defined. We expect your attribute, method or constructor to be defined in a particular way, but yours isn't or not defined at all.		
Check <code>BreakoutRoom(String)</code> constructor exists and is accessible		✓
Check <code>open</code> attribute exists		✓
Check <code>public boolean getOpen()</code> method exists and defined properly		✗

Method	<code>addParticipant(String)</code>	0.0 / 2.0
Does not work as anticipated: produced <code>java.lang.NullPointerException: Cannot store to object array</code>		

because "this.participants" is null. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check <code>BreakoutRoom(String)</code> constructor exists and is accessible	✓
Check <code>openBreakoutRoom()</code> method exists and is accessible	✓
Check <code>public boolean addParticipant(String)</code> method exists and defined properly	✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args ("Room1")	✓
Check <code>openBreakoutRoom()</code> method runs	✓
Check <code>addParticipant(String)</code> method returns <code>true</code> with args ("10000000")	✗

Method	<code>listParticipants()</code>	0.0 / 2.0
--------	---------------------------------	-----------

Cannot be further tested because testing relies on the `addParticipant` method that does not work as anticipated: produced `java.lang.NullPointerException: Cannot store to object array because "this.participants" is null`. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check <code>BreakoutRoom(String)</code> constructor exists and is accessible	✓
Check <code>addParticipant(String)</code> method exists and is accessible	✓
Check <code>openBreakoutRoom()</code> method exists and is accessible	✓
Check <code>breakoutRoomID</code> attribute exists	✓
Check <code>public String listParticipants()</code> method exists and defined properly	✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args ("Room1")	✓
Check <code>openBreakoutRoom()</code> method runs	✓
Check <code>addParticipant(String)</code> method runs with args ("10000000")	✗

Method	<code>closeBreakoutRoom()</code>	0.0 / 1.0
--------	----------------------------------	-----------

Does not work as anticipated: produced `java.lang.NullPointerException: Cannot read the array length because "a" is null`. We expect your method to run without problems, but instead yours contains bad code that creates problems.

Check <code>BreakoutRoom(String)</code> constructor exists and is accessible	✓
Check <code>open</code> attribute exists	✓

Check <code>numberOfParticipants</code> attribute exists	✓
Check <code>public void closeBreakoutRoom()</code> method exists and defined properly	✓
Check <code>BreakoutRoom(String)</code> constructor creates instances with args ("Room1")	✓
Check <code>closeBreakoutRoom()</code> method runs	✗

Method	<code>getNumberOfParticipants()</code>	0.0 / 1.0
--------	--	-----------

Is not defined. We expect your attribute, method or constructor to be defined in a particular way, but yours isn't or not defined at all.

Check <code>BreakoutRoom(String)</code> constructor exists and is accessible	✓
Check <code>numberOfParticipants</code> attribute exists	✓
Check <code>public int getNumberOfParticipants()</code> method exists and defined properly	✗

Participant Class

Passed 2/5; Partially passed 1/5; Failed 2/5.

Method	<code>toString()</code>	2.0 / 2.0
--------	-------------------------	-----------

Method	<code>getParticipantID()</code>	1.0 / 1.0
--------	---------------------------------	-----------

Attribute	<code>participantID</code>	0.0 / 1.0
-----------	----------------------------	-----------

Does not have private access. We expect your attribute, method or constructor to have the private keyword indicating that it has private access, but yours doesn't.

Check <code>private String participantID</code> attribute exists and defined properly	✗
---	---

Constructor	<code>Participant(String)</code>	1.0 / 2.0
-------------	----------------------------------	-----------

Does not initialize the `participantID` attribute. We expect your constructor to initialize a particular set of instance attributes, but yours doesn't.

Check <code>public Participant(String)</code> constructor exists and defined properly	✓
Check <code>Participant(String)</code> constructor creates instances with args ("12345678") +1.0	✓

Check `participantID` attribute equals `equalToIgnoringWhiteSpace("12345678")`



Method

`verifyID(String)`

0.0 / 2.0

Is not a class method. We expect your method to be defined with the `static` keyword indicating that it is an class method, but yours isn't.

Check `public static boolean verifyID(String)` method exists and defined properly

