



UNIVERSITEIT VAN PRETORIA  
UNIVERSITY OF PRETORIA  
YUNIBESITHI YA PRETORIA

---

DEPARTMENT OF COMPUTER SCIENCE

COS 301

MAIN PROJECT

---

## Unit Test Plan and Report

---

### TEAM CODEX

Andreas du Preez	12207871
Azhar Mohungoo	12239799
Gift Sefako	12231097

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Purpose . . . . .	3
1.2	Scope . . . . .	3
1.3	Test Environment . . . . .	3
1.3.1	Programming Languages: . . . . .	3
1.3.2	Testing Framework: . . . . .	3
1.3.3	Coding Environment: . . . . .	4
1.3.4	Operating Systems: . . . . .	4
1.3.5	Internet Browsers: . . . . .	4
1.4	Assumptions and Dependencies . . . . .	4
<b>2</b>	<b>Functional Features to be Tested</b>	<b>5</b>
<b>3</b>	<b>Test Cases</b>	<b>6</b>
3.1	Blockchain Module . . . . .	6
3.1.1	Test Case 1: ConfigurationAndConnection . . . . .	6
3.1.1.1	Condition 1: InvalidIPandPort . . . . .	6
3.1.1.1.1	Objective: . . . . .	6
3.1.1.1.2	Input: . . . . .	6
3.1.1.1.3	Outcome: . . . . .	6
3.1.1.2	Condition 2: InvalidRPCCredentials . . . . .	7
3.1.1.2.1	Objective: . . . . .	7
3.1.1.2.2	Input: . . . . .	7
3.1.1.2.3	Outcome: . . . . .	7
3.1.2	Test Case 2: sendVote . . . . .	7
3.1.2.1	Condition 1: InvalidToAddress . . . . .	7
3.1.2.1.1	Objective: . . . . .	7
3.1.2.1.2	Input: . . . . .	7
3.1.2.1.3	Outcome: . . . . .	8
3.1.2.2	Condition 2: InvalidVotesLeft . . . . .	8
3.1.2.2.1	Objective: . . . . .	8
3.1.2.2.2	Input: . . . . .	8

3.1.2.2.3	Outcome: . . . . .	8
3.1.2.3	Condition 3: SendVoteFromAdminToNode . . . . .	8
3.1.2.3.1	Objective: . . . . .	8
3.1.2.3.2	Input: . . . . .	9
3.1.2.3.3	Outcome: . . . . .	9
3.1.2.4	Condition 4: SendVoteFromNodeToAdmin . . . . .	9
3.1.2.4.1	Objective: . . . . .	9
3.1.2.4.2	Input: . . . . .	9
3.1.2.4.3	Outcome: . . . . .	9
3.1.3	Test Case 3: GetBalance . . . . .	10
3.1.3.1	Condition 1: GetAdminBalance . . . . .	10
3.1.3.1.1	Objective: . . . . .	10
3.1.3.1.2	Input: . . . . .	10
3.1.3.1.3	Outcome: . . . . .	10
3.1.3.2	Condition 2: GetNodeBalance . . . . .	10
3.1.3.2.1	Objective: . . . . .	10
3.1.3.2.2	Input: . . . . .	10
3.1.3.2.3	Outcome: . . . . .	10
<b>4</b>	<b>Item Pass/Fail Criteria</b>	<b>11</b>
<b>5</b>	<b>Test Deliverables</b>	<b>11</b>
<b>6</b>	<b>Detailed Test Results</b>	<b>12</b>
6.1	Overview of Test Results . . . . .	12
6.2	Functional Requirements Test Results . . . . .	12
<b>7</b>	<b>Other</b>	<b>13</b>
<b>8</b>	<b>Conclusions and Recommendations</b>	<b>13</b>

# 1 Introduction

Software testing is performed to verify that the completed software package functions according to the expectations defined by our requirements/specifications.

EVoting consists of different components, each designed to do a specific separate task. It is important to test each component individually to insure that they do what is expected from them before building the project as a whole and executing it. Tests are therefore essential to our system to prevent bugs, compile time and run time errors.

## 1.1 Purpose

EVoting is an electronic voting system, designed specifically for government elections, but it can also be used in other scenarios where reliable electronic voting is needed. Since it is crucial that the voting process cannot be tampered with in any way, both reliability and security is of main importance. It is therefore extremely important to test the crucial parts of the system to ensure the system executes as expected and eliminate unexpected security and reliability threats.

## 1.2 Scope

The scope of this document is structured as follows:

In this document, we elaborate on the purpose as well as the specific details to why we are testing certain functionality. The functionality that are considered for testing are listed in section 2. Tests that have been identified from the requirements are discussed in detail in section TODO Furthermore, this document outlines the test environment and the risks involved in the testing approaches that will be followed. Assumptions and dependencies of this test plan will also be mentioned. Section 6 outlines, discusses and concludes on the results of the tests.

## 1.3 Test Environment

Our testing environment is as follows:

### 1.3.1 Programming Languages:

Java version 1.8+

### 1.3.2 Testing Framework:

JUnit Testing framework.

Maven - Testing phase.

### **1.3.3 Coding Environment:**

IntelliJ Ultimate Edition 2016.1

### **1.3.4 Operating Systems:**

Windows 10

Mac OS

Android version 4.4+

### **1.3.5 Internet Browsers:**

HTML5 supported web browsers.

Firefox

Chrome

Safari

## **1.4 Assumptions and Dependencies**

Assumptions:

- Server-side, client-side and the Blockchain are running on the same network.
- Each OS doesn't have a firewall blocking any of the incoming and outgoing messages as well as ports used by the system.
- The Blockchain is running (at least 1 Admin Node).

Dependencies:

- The Blockchain is reachable by the system.
- Network IP range and mask: 192.168.1.0/255.255.255.0.
- Each Blockchain node and the webservice all have static IP addresses.

# Unit Test Plan

## 2 Functional Features to be Tested

The aspects that will be tested and evaluated in these tests are described in the following sections. The items that are tested is the crutial fundamental use cases that are required of the system to function at a core level. These use cases are specified in the section below.

The following is a list of features to be tested:

- Blockchain Module:
  - Connection to the blockchain and general module configuration.
  - Be able to send a vote from and to different Nodes.
  - Be able to get the vote balance of a Node.

2. TODO-Andreas: Provide references to the Requirements and/or Design specications of the features to be tested. Explain briefly and provide a table to introduce the different test cases

Table 1: Test Cases Descriptions

Feature ID	Source	Summary	Test Case ID
TODO	Blockchain	Test the general configuration. These test won't stop the system from building. But if these fail then some configuration might need to get checked.	1
TODO	Blockchain	Test the sendVote functionality to ensure voters' vote won't get lost during run time.	1
TODO	Blockchain	Test the getBalance functionality to see if parties can retrieve their total votes.	1
1	test	test	1

### 3 Test Cases

#### 3.1 Blockchain Module

##### 3.1.1 Test Case 1: ConfigurationAndConnection

###### 3.1.1.1 Condition 1: InvalidIPandPort

**3.1.1.1.1 Objective:** The purpose of this test is to see if the system can detect if the specified Node IP address and port are invalid or empty.

**3.1.1.1.2 Input:** Parameters:

- An incorrect IP address string and/or
- An incorrect port address string.
- A correct RPC username string.
- A correct RPC password string.
- A correct Node address (to address).
- A positive interger amount.

**3.1.1.1.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "false".

- Also a key-value pair of "result":<BlockchainErrorMessages.InvalidIP> or "result":<BlockchainErrorMessages.InvalidRPCCredentials> respectively where the values in brackets are strings defined in the BlockchainErrorMessages enumerate.

### 3.1.1.2 Condition 2: InvalidRPCCredentials

**3.1.1.2.1 Objective:** The purpose of this test is to see if the system can detect if the specified RPC username and/or password are incorrect.

**3.1.1.2.2 Input:** Parameters:

- A correct IP address string.
- A correct port address string.
- An incorrect RPC username string and/or
- An incorrect RPC password string.
- A correct Node address (to address).
- A positive interger amount.

**3.1.1.2.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "false".
- Also a key-value pair of "result":<BlockchainErrorMessages.InvalidRPCCredentials> where the value in brackets is a string defined in the BlockchainErrorMessages enumerate.

## 3.1.2 Test Case 2: sendVote

### 3.1.2.1 Condition 1: InvalidToAddress

**3.1.2.1.1 Objective:** The purpose of this test is to see if the system can detect wether votes are trying to be sent to an invalid Node address (i.e. an address that doesn't exist in the Blockchain).

**3.1.2.1.2 Input:** Parameters:

- A correct IP address string.
- A correct port address string.
- A correct RPC username string and/or



- A correct RPC password string.
- An incorrect Node address (to address).
- A positive interger amount.

#### **3.1.2.1.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "false".
- Also a key-value pair of "result": <BlockchainErrorMessages.InvalidToAddress> where the value in brackets is a string defined in the BlockchainErrorMessages enumerate.

### **3.1.2.2 Condition 2: InvalidVotesLeft**

**3.1.2.2.1 Objective:** The purpose of this test is to see if the system can detect wether a voting Node is trying to send a vote when its vote balance is 0.

#### **3.1.2.2.2 Input:** Parameters:

- A correct IP address string.
- A correct port address string.
- A correct RPC username string and/or
- A correct RPC password string.
- A correct Node address (to address).
- A positive interger amount.

Existing Entity: The voting Node's vote balance is 0.

#### **3.1.2.2.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "false".
- Also a key-value pair of "result": <BlockchainErrorMessages.InvalidVotesLeft> where the value in brackets is a string defined in the BlockchainErrorMessages enumerate.

### **3.1.2.3 Condition 3: SendVoteFromAdminToNode**

**3.1.2.3.1 Objective:** The purpose of this test is to see if the system can successfully send 1 vote from the Admin Node to any other Node.

**3.1.2.3.2 Input:** Parameters:

- A correct IP address string.
- A correct port address string.
- A correct RPC username string and/or
- A correct RPC password string.
- A correct Node address (to address).
- A positive interger amount.

**3.1.2.3.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "true".
- Also a key-value pair of "result": <TransactionHash> where the value in brackets is a hash value to identify the transaction.

**3.1.2.4 Condition 4: SendVoteFromNodeToAdmin**

**3.1.2.4.1 Objective:** The purpose of this test is to see if the system can successfully send 1 vote from a Node other than the Admin to the Admin Node.

**3.1.2.4.2 Input:** Parameters:

- A correct IP address string.
- A correct port address string.
- A correct RPC username string and/or
- A correct RPC password string.
- A correct Node address (to address).
- A positive interger amount.

**3.1.2.4.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "true".
- Also a key-value pair of "result": <TransactionHash> where the value in brackets is a hash value to identify the transaction.

### 3.1.3 Test Case 3: GetBalance

#### 3.1.3.1 Condition 1: GetAdminBalance

**3.1.3.1.1 Objective:** The purpose of this test is to see if the system can successfully retrieve the vote balance of the Admin Node.

**3.1.3.1.2 Input:** Parameters:

- A correct IP address string.
- A correct port address string.
- A correct RPC username string and/or
- A correct RPC password string.

**3.1.3.1.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "false".
- Also a key-value pair of "result": <Balance> where the value in brackets is an interger of the balance.

#### 3.1.3.2 Condition 2: GetNodeBalance

**3.1.3.2.1 Objective:** The purpose of this test is to see if the system can successfully retrieve the vote balance of any other Node other than the Admin Node.

**3.1.3.2.2 Input:** Parameters:

- A correct IP address string.
- A correct port address string.
- A correct RPC username string and/or
- A correct RPC password string.

**3.1.3.2.3 Outcome:**

- JSON Object returned with a key-value pair of "success": "false".
- Also a key-value pair of "result": <Balance> where the value in brackets is an interger of the balance.

## 4 Item Pass/Fail Criteria

- All of the post conditions has to be met.
- TODO-Andreas

If any of the above criteria are not met, the item will be considered failed.

## 5 Test Deliverables

- Test Report located at:
- The link to Test Code:

# Unit Test Report

## 6 Detailed Test Results

### 6.1 Overview of Test Results

### 6.2 Functional Requirements Test Results

**7 Other**

**8 Conclusions and Recommendations**