

IUTFood-Project-client
-codes/IUTFoodClient/src
/UI/restaurantownermenu.h

```
graph BT; A["IUTFood-Project-client<br>-codes/IUTFoodClient/build<br>/Desktop_Qt_6_8_2_MinGW_64<br>-bit-Debug/debug/moc_restaurantownermenu.cpp"] --> C["IUTFood-Project-client<br>-codes/IUTFoodClient/src<br>/UI/restaurantownermenu.h"]; B["IUTFood-Project-client<br>-codes/IUTFoodClient/src<br>/UI/restaurantownermenu.cpp"] --> C;
```

The diagram illustrates a dependency relationship in a Qt project. At the top, a grey box represents the header file `restaurantownermenu.h`. Below it, two white boxes represent source files. The left box is the moc-generated file `moc_restaurantownermenu.cpp`, which is located in a build directory. The right box is the original source file `restaurantownermenu.cpp`. Blue arrows point from both source files up to the header file, indicating that both files depend on the header.

IUTFood-Project-client
-codes/IUTFoodClient/build
/Desktop_Qt_6_8_2_MinGW_64
_bit-Debug/debug/moc_restaurantownermenu.cpp

IUTFood-Project-client
-codes/IUTFoodClient/src
/UI/restaurantownermenu.cpp