

1. `FILTER(Sales, Sales[Amount] > 1000)` in DAX returns:
 - A **table** (not a single value).
 - That table contains **all the rows from Sales** where the condition `Sales[Amount] > 1000` is true.
 - It **does not aggregate** or calculate anything — it just reduces the rows.
-

Example:

Suppose Sales table is:

SaleID Amount

1	500
2	1200
3	2000

Then:

`FILTER(Sales, Sales[Amount] > 1000) →`

SaleID Amount

2	1200
3	2000

⚠ Important: Since `FILTER()` returns a **table**, you cannot display it directly in a measure. You normally pass it into another function like `CALCULATE`, `SUMX`, `COUNTROWS`, etc.

👉 Example usage:

High Sales =

```
CALCULATE (
    SUM ( Sales[Amount] ),
    FILTER ( Sales, Sales[Amount] > 1000 )
)
```

This would return the **total of sales greater than 1000**.

3. 1. `ALL(Sales)`

- Removes **all filters** from the Sales table.
- It's like looking at the entire Sales table without any slicers or filters applied.

👉 Example:

If you have filters on **Region** and **Category**, ALL(Sales) ignores both of them.

2. ALLEXCEPT(Sales, Sales[Region])

- Removes **all filters except the ones you specify**.
- In this case, it **keeps the Region filter**, but ignores all other filters (like Category, Product, Date, etc.).

👉 Example:

If you're filtering on **Region = "USA"** and **Category = "Electronics"**:

- ALL(Sales) → sees the full Sales table (no filters).
 - ALLEXCEPT(Sales, Sales[Region]) → keeps only Region = "USA", but removes the Category filter.
-

🔑 **Key difference:**

- **ALL(Sales):** "Forget ALL filters."
 - **ALLEXCEPT(Sales, Sales[Region]):** "Forget everything EXCEPT Region."
-

👉 In practice, ALLEXCEPT is often used when you want to calculate things like *% of total by Region*.

Example measure:

% of Region Sales =

```
DIVIDE (
    SUM(Sales[Amount]),
    CALCULATE(SUM(Sales[Amount]), ALLEXCEPT(Sales, Sales[Region]))
)
```

This gives each row's share of its **Region total**, instead of the **Grand total**.

5. In **DAX**, the function **ALLSELECTED()** is used to **remove filters but still respect user selections (from slicers, filters, etc.)**.

Purpose of ALLSELECTED

- It **ignores filters applied inside the visual itself** (like rows/columns in a table or matrix).
- But it **keeps slicer and report/page-level filters**.
- Most often, it's used to calculate **percentages (%) of totals** within the user's current selection.

Example 1: % of Selected Total Sales

% of Selected Sales =

```
DIVIDE(  
    SUM(Sales[Amount]),  
    CALCULATE(SUM(Sales[Amount]), ALLSELECTED(Sales))  
)
```

 Here:

- SUM(Sales[Amount]) → current row's sales
- ALLSELECTED(Sales) → sales total for **only what the user selected** in slicers
- Result → each row shows % of its selection total

Example 2: Difference Between ALL vs ALLSELECTED

- ALL(Sales) → removes *all* filters (ignores slicers too).
- ALLSELECTED(Sales) → removes only *visual filters*, but still respects slicers.

For example:

- If a slicer selects **Year = 2023**,
 - ALL(Sales) → calculates across **all years**
 - ALLSELECTED(Sales) → calculates only within **2023**

In short:

ALLSELECTED is very useful when you want calculations that are relative to **what the user has chosen**, not the entire dataset.

9. ♦ What ALLSELECTED does

- ALLSELECTED clears filters **but only within the current user selection (slicer, filter, or pivot table selection)**.
- This means it "remembers" what the user selected, unlike ALL which clears everything.

♦ Why it can behave unexpectedly in a pivot table

1. Depends on visible selection

If the pivot table only shows a subset of categories, ALLSELECTED uses only those visible categories as the denominator. This can give results that look inconsistent if you expected the total across all categories.

2. Nested levels in pivot table

In a pivot with hierarchies (e.g., Region → Country), ALLSELECTED can return different totals depending on which level is expanded. At Region level, it includes all selected Regions; at Country level, only those Countries under visible Regions.

3. Interaction with slicers

If a slicer is applied (e.g., Year = 2024), ALLSELECTED respects that. So results may change unexpectedly when slicer values are changed or multiple slicers interact.

4. Misunderstood denominator

Often ALLSELECTED is used in % of Total measures. If the pivot table shows only part of the selection, the percentage may not be against the *true* grand total but only the currently visible selection.

✅ In short:

ALLSELECTED is context-sensitive. In a pivot table, the “total” it returns is based on whatever rows/columns the user has chosen or expanded. That’s why it sometimes looks “unexpected” if you assume it behaves like ALL.



13. Power BI’da ALLSELECTED ikki xil usulda ishlatiladi:

- **ALLSELECTED(Table[Column])** → faqat shu column bo’yicha slicer/selectionlarni hurmat qiladi.
- **ALLSELECTED()** (parametrsiz) → butun model bo’yicha slicerlarni hurmat qiladi, **lekin visual-level filterlarni e’tiborga olmaydi.**

♦ Misol

Sales Respecting Slicers =
CALCULATE (
SUM (Sales[Amount]),
ALLSELECTED()
)

◆ Qanday ishlaydi?

1. Agar siz slicer qo'ysangiz (masalan, faqat **2024 yilni tanlasangiz**) → bu measure **faqat 2024 yil savdosini** ko'rsatadi. 
 2. Lekin agar siz bar chart ustida filtrlasangiz (masalan, faqat **Electronics** kategoriyani tanlab qolsangiz) → bu measure **hamma kategoriyani** hisoblaydi, chunki u **visual-level filterlarni e'tiborga olmaydi**. 
-

◆ Foydali joyi

- % of Total Sales kabi hisoblarda ishlatiladi → slicer tanlovi saqlanadi, lekin visualdagi boshqa filterlar e'tiborga olinmaydi.

14. This usually isn't a SWITCH bug—it's **context**. When you add fields to a matrix, the filter context changes; things like SELECTEDVALUE() may start returning **Blank** (because there are multiple values), grand totals lose row context, and branches inside SWITCH can flip unexpectedly.

Here's a tight checklist + a robust pattern:

Why it goes wrong

1. **SELECTEDVALUE() = Blank (or different)**
 - Adding rows/columns means more than one value is in scope → SELECTEDVALUE() returns Blank → SWITCH hits the wrong/else branch.
 - Fix: give SELECTEDVALUE() a **default** and source it from a **disconnected selector** table (not from fields used in the matrix).
2. **Totals vs detail (row context disappears at totals)**
 - At totals, AVERAGE, COUNT, etc. can mean something else than per-row logic.
 - Fix: branch with ISINSCOPE() to handle totals differently.

3. Mixed return types

- Every SWITCH branch must return the **same type** (all numbers). If one returns text/blank mishandled, results look wrong.

4. Overriding filters in branches

- If some branches use ALL/ALLEXCEPT/ALLSELECTED, they can ignore slicers/visual filters; others don't → inconsistent results.

Robust SWITCH pattern

Use a disconnected selector and guard for totals:

Dynamic Measure :=

VAR Choice =

SELECTEDVALUE('Measure Selector'[OptionName], "Sum") -- default!

VAR AtProductLevel =

ISINSCOPE(Products[ProductName]) -- adjust to your hierarchy

RETURN

SWITCH (

TRUE(),

Choice = "Sum",

[Total Sales], -- e.g. SUM(Sales[Amount])

Choice = "Average",

IF (

AtProductLevel,

AVERAGE (Sales[Amount]), -- per-row level

AVERAGEX (VALUES (Products[ProductName]), [Total Sales]) -- total
logic

),

Choice = "Count",

COUNTROWS (VALUES (Sales[SaleID])), -- stable counting
pattern

BLANK()

)

Tips

- **Disconnected table** for the selector (Home → Enter Data): “Sum”, “Average”, “Count”. Use it in a slicer.
- Always give SELECTEDVALUE(..., "fallback").
- Use ISINSCOPE() to make totals/grand totals do what you expect.
- Keep all branches numeric and avoid ALL* unless you truly want to ignore filters.