

carland_auth API changes — Flutter

Old → New mapping. Base path unchanged: /api/v1/users and /api/v1/otp

1. Endpoints

OLD: POST /api/v1/users/register

NEW: POST /api/v1/users/authentication

OLD: PUT /api/v1/users/setPassword

NEW: PUT /api/v1/users/set/pin

OLD: PUT /api/v1/users/updatePassword

NEW: PUT /api/v1/users/update/pin

OLD: POST /api/v1/users/login (path same)

NEW: POST /api/v1/users/login (body field changed)

OLD: POST /api/v1/otp/* (path same)

NEW: POST /api/v1/otp/* (token name in response chain changed)

2. Request body fields

OLD: { "phoneNumber", "password", "name", "surname" }

NEW: { "phoneNumber", "pin", "name", "surname" }

OLD: InviteRequest.password

NEW: InviteRequest.pin

OLD: pin format: free text password

NEW: pin: exactly 4 digits, not all same (e.g. 5555 invalid)

3. Response fields

OLD: RegisterResponse.registerToken

NEW: AuthenticationResponse.authenticationToken

OLD: UserResponse (no password field) — unchanged shape

NEW: UserResponse — unchanged; login uses pin in request only

4. Auth header usage (flow)

OLD: Authorization: Bearer <registerToken>

NEW: Authorization: Bearer <authenticationToken>

Used on:

POST /api/v1/otp/createAndSend

POST /api/v1/otp/verify

PUT /api/v1/users/set/pin

5. Example — authenticate

OLD:

POST /api/v1/users/register?role=USER

{ "phoneNumber": "+994...", "name": "...", "surname": "..." }

→ { "registerToken": "...", "message": "..." }

NEW:

POST /api/v1/users/authentication?role=USER

{ "phoneNumber": "+994...", "name": "...", "surname": "..." }

→ { "authenticationToken": "...", "message": "..." }

6. Example — login

OLD:

POST /api/v1/users/login

{ "phoneNumber": "+994...", "password": "..." }

NEW:

POST /api/v1/users/login

```
{ "phoneNumber": "+994...", "pin": "1234" }
```

7. Example — set pin

OLD:

PUT /api/v1/users/setPassword

Authorization: Bearer <registerToken>

```
{ "password": "..." }
```

NEW:

PUT /api/v1/users/set/pin

Authorization: Bearer <authenticationToken>

```
{ "pin": "1234" }
```

8. Example — update pin (start OTP flow)

OLD:

PUT /api/v1/users/updatePassword

```
{ "phoneNumber": "+994..." }
```

→ { "registerToken": "..." }

NEW:

PUT /api/v1/users/update/pin

```
{ "phoneNumber": "+994..." }
```

→ { "authenticationToken": "..." }

9. Errors (PIN)

OLD: N/A (old password rules)

NEW: WeakPinException → HTTP 400, message az/en/ru (weak PIN)

OLD: Wrong password message

NEW: Wrong PIN message (same exception type, new text)

10. Token TTL (config)

OLD: refresh.token.expiration = 2592000 (1 month)

NEW: refresh.token.expiration = 31536000 (1 year)

OLD: register.token.*

NEW: authentication.token.* (same secret/TTL values)

11. DB (backend only — Flutter ignore)

OLD: users.password

NEW: users.pin (still BCrypt hash)

Regenerate: python docs/generate_auth_api_changes_flutter_pdf.py