Payment Gateway

Merchant Integration Document

Version 2.1

Document Control

Version	Date	Personal	Changes
1.0	Juli 22, 2024	Bastomy	Add QRIS integration
2.1	Maret 11, 2024	Sada	Update Redirect Payment Page

Table of Contents

Document Control 2

1. Redirect Payment Page 4

1.1. General 4

1.2. Security Signature 4

1.3. Request format 6

1.4. Check Status 9

2. Response List 11

1. Redirect Payment Page

Redirect Payment Page (RPP), redirect from consumer website to payment page.

1.1. General

You can use this type of integration within one step:

1. **Submit form to end point Payment Page**

   After submit form will redirect to payment page with following information:

   - payment_id
   - merchant_key

   example:

   https://merchant-dev.pvpg.co.id:7977/v2/payment?id=63713648-13bb-4f61-b287-cf1ea24a2403&merchant_key=MDE5NWEzMTgtZjFlYS03ODlkLWI3NDYtMDE4NDkyM2YxYmYw

2. **URL**

   URL : https://merchant-dev.pvpg.co.id:7977

1.2. Security Signature

Signature is used to verify data requested from client not modified during transmission.

The signature calculation involve data such as:

1. **Expires in**

   expire payment page in minutes.

2. **Order id**

   Unique order id from merchant must be ***unique***.

3. **User id**

   User id from client.

4. **Merchant Name**

   Merchant name for display on payment page.

5. **Payment Method**

   Fill in if you want to specify payment method or leave with empty string if want to display all payment method.

6. **Total amount**

   Total amount transaction.

7. **Customer name**
   Customer name.
8. **Currency**
   Currency payment.
9. **Push URL**
   Webhook if payment has been paid.
10. **Callback URL**

    If payment is done, will be redirected to that url.

11. **Client Key**

    Given client key

12. **Secret Key**

    Given secret key to HMAC-SHA256 the signature data

13. **Timestamp**

    Timestamp generated as ISO8601, zero UTC offset

    e.g. 2020-01-02T13:14:15.678Z

Example of signature calculation:

Given payload data component:

- Expires in → 120
- order id → 1742540113776AX
- User id → 1
- Merchant name → SAMPLE MERCHANT NAME
- Payment method→
- Total amount → 10000
- Customer name → Jhon
- Currency → IDR
- Push url → https://merchanturl.com/payment/pg-get-notif
- Callback url → https://merchanturl.com/payment/success
- Timestamp → 2025-03-21T06:50:02.358Z
- Client Key → 0195a318-f1ea-789d-b746-0184923f1bf0

Payload = [expires in]:[order id]:[User id]:[Merchant name]:[Payment method]:[Total amount]:[Customer name]:[Currency]:[Push url]:[Callback url]

Payload = lower case([SHA256(Payload)]): [Client Key]:[Timestamp]

Then Signature = encode BASE64 (HMAC-SHA256(Payload, Secret Key))

Finally convert Signature to BASE64 string.

1.3. Request format

The merchant must request for redirect URL to Prima Vista PG's backend system by sending several parameters included in the POST HTTP request.

Note:

- Each parameter must be named precisely as indicated in these notes, as matching is case-sensitive.
- If the required parameter is not present, the transaction may yield an exception
- The length of characters / numeric given are the maximum length that Prima Vista PG database will store. Anything longer will be truncated.

Path

Path	**api/v2.1/payment/create**

Parameter

Method	**POST**

Name	Type	Requirement	Description
expires_in	String(100)	M	Time in minutes
order_id	String(100)	M	Order id transaction from merchant (must be unique)
user_id	Integer	M	
merchant_name	String(50)	M	
merchant_id	Integer	O	
payment_method	String(30)	M	Payment method name (card, QRIS), leave the blank for all payment method
total_amount	Integer	M	Total amount transaction
customer_name	String(30)	M	
currency	String(30)	M	
items	Array Object	O	

items.name	String(20)	C	
items.quantity	Integer	C	
Items.amount	Integer	C	
product_type	String(50)	C	
shipping_address	Array Object	O	
shipping_address.first_name	String(50)	C	
shipping_address.last_name	String(50)	C	
shipping_address.address	String(100)	C	
shipping_address.city	String(50)	C	
shipping_address.region	String(20)	C	
shipping_address.postal_code	String(10)	C	
shipping_address.email	String(50)	C	
shipping_address.phone_number	String(20)	C	
shipping_address.country_name	String(30)	C	
push_url	String(200)	M	Link for receive status payment
callback_url	String(200)	M	Link redirect after payment finish
courier_agent	String(30)	O	
x-timestamp	String(100)	M	Timestamp generated as ISO8601, zero UTC offset
x-client-id	String(100)	M	encode BASE64 Client Key

Example:


```
{
  "expires_in": "120",
  "order_id": "1742540113776AX",
  "user_id": "1",
  "merchant_name": "SAMPLE MERCHANT NAME",
  "payment_method": "",
```

```
  "total_amount": 10000,
  "customer_name": "Jhon",
  "currency": "IDR",
  "push_url": "https://merchanturl.com/payment/pg-get-notif ",
  "callback_url": "https:// merchanturl.com /payment/success",
  "courier_agent": "",
  "items": [
    {
      "name": "PRODUCT01",
      "quantity": 1,
      "amount": 10000,
      "product_type": "Electronic"
    }
  ],
  "shipping_address": {
    "first_name": "Jhon",
    "last_name": "Handsome",
    "address": "MT. Haryono kav. 15",
    "city": "Bandung",
    "region": "Jawa Barata",
    "postal_code": "11110",
    "email": "edob@gmai.com",
    "phone_number": "+6281224711261",
    "country_name": "Indonesia"
  },
  "x-timestamp": "2025-03-21T06:50:02.358Z",
  "x-client-id": "MDE5NWEzMTgtZjFlYS03ODlkLWI3NDYtMDE4NDkyM2YxYmYw",
  "x-signature": "LuzcCxvaZ+2hx/+TvXZkYwi0t5rerC8PfY6PCxJBMUI="
}
```


Response

Example:

Response is redirect as html
Example URL response :

https://merchant-dev.pvpg.co.id:7977/v2/payment?id=63713648-13bb-4f61-b287-cf1ea24a2403&merchant_key=MDE5NWEzMTgtZjFlYS03ODlkLWI3NDYtMDE4NDkyM2YxYmYw

1.4. Check Status

Path

Path	api/v2/general-check-payment

Parameter

Method	POST

Name	Type	Requirement	Description
payment_id	String(100)	M	Order id from merchant (Order id when generate QR)
merchant_key	String(100)	M	encode BASE64 Client Key

Example :


```
{
  "payment_id":"1742540113776AX ",
  "merchant_key":"MDE5NWEzMTgtZjFlYS03ODlkLWI3NDYtMDE4NDkyM2YxYmYw"
}
```


Response

Example:


```
{
  "transaction_id": "216c837e-af18-4259-93f8-9bec72153e69",
  "payment_method": "",
  "transaction_time": "20250321141506523",
  "transaction_status": "SUCCESS",
  "payment_id": "",
  "order_id": "1742540113776AX",
```

"amount": 0,
"payment_status": "NOT PAID",
"payment_time": "",
"account_number": "",
"issuer_name": ""
}

1.5. Push Notif

Push notifications are made from the Primavista API to the Push Notification URL listed in the payment creation body.

Path

Path	**“push notif url from merchant in body”**

Parameter

Method	**POST**

Example Format Massege:

{
"payment_method": "CARD",
"transaction_id": "216c837e-af18-4259-93f8-9bec72153e69",
"transaction_time": "20250321141711513",
"transaction_status": "SUCCESS",
"payment_id": "5797b03d-10df-4206-b740-211d64afdf72",
"order_id": "1742540113776AX",
"amount": 10000,
"payment_status": "PAID",
"payment_time": "20250321141611513",
"account_number": "******0075",
"issuer_name": "OTHER"
}

2. Response List

Message	To Do
"[FAILED] Duplicate order ID"	Please make sure order id uniqe
"[FAILED] Invalid signature"	Please make sure the signature calculation is correct
500 Internal Server Error	Please check mandatory parameter data is correct
"[FAILED] Merchant data not found"	x-client-id is incorrect, make sure x-client-id value is encode BASE64 Client Key