HYGROSCOPE P

Calcium Oxide

HYGROSCOPE P is a powder of 95 % calcium oxide to delay reactivity and is used as a desiccant in PE Masterbatch, PP Masterbatch, Rubber Compounds and PVC Plastisol which are cured pressurless (Micro wave system, LCM, Hot air or Fluid bed)
Moisture which presents in all Plastic, PE, PP, Rubber and PVC chemicals, especially fillers, will be absorbed and the calcium oxide will change to calcium hydroxide after reaction with the moisture.

HYGROSCOPE P should be used in order to prevent blisters and porosity in the following Plastic and rubber processes;

- PE Masterbatches, PP, Masterbatches, PVC Plastisol....
- Pressurless continuous curing systems like Micro wave, LCM, Hot air, Fluid beds,
- Low pressure curing in the cable industry,
- In cases where the influence of humidity in rubber compounds should be suppressed.
- Industrial application.

HYGROSCOPE P can be supplied in sachets containing any weight between 0.5 kg and 25 kg to suit customers requirements.

PROPERTIES

Chemical Characteristics	:	Calcium oxide
Appearance	:	Of white, powder
CaO %	:	95 ±2
SiO_2 (%)	:	0.02 Max.
MgO (%)	:	0.8 Max.
Al_2O_3 (%)	:	0.20 Max.
Fe_2O_3 (%)	:	0.02 Max
Particle size	:	x10= 0.63 µm x50= 1.30 µm x90= 11.36 µm
Storage Stability	:	1 year under cool and dry storage conditions originally packing
Packing	:	in PE or EVA bag and cardboard boxes containing 25 kg or 1000kg Big bag

Tepe Kimya (M) SDN. BHD.
Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848
Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.
Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla Istanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.
63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435
Email: info@tepekimya.com