Tepelub H110 (PE-Wax)

Tepelub H110 (PE-Wax):

- Very effective External Lubricant.
- Compatible for PVC and all PVC additives.
- Compatible for all Plastics especially for Master Batch sector.
- Regulates the melt flow and prevents melt stickiness.
- Excellent suitable for transparent articles.
- Imparts very smooth and shiny/glossy finish to the product.
- Very excellent dispersion for color master batch.

PROPERTIES

Appearance	:	White Flake
Melting point	:	110 ºC ± 5
Density	:	0.89 ºC ± 0.03
Viscosity (at 23 C)	:	200-500
Moisture	:	1% max.
Flash Point	:	300 ºC ± 5
Molecular Weight	:	2,500~3000
Storage Stability	:	2 years under cool and dry storage conditions in originally Packing
Packing	:	25-Kgs Paper, PP or PE Bags.
Dosage	:	0.5 – 2phr.

Tepe Kimya (M) SDN. BHD.
Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848
Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.
Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla Istanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.
63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435
Email: ramay@tepekimya.com