# Anti-tack TP 131

## ***Batch off Soap/Lubricant***

ANTI-TACK TP 131 is used for the treatment of unvulcanised rubber compounds in the form of sheet or strip to prevent surface sticking.

ANTI-TACK TP 131 is liquid type Antitack agent. It is non foaming and some industry can use like as a Lubricant.

## PROPERTIES

| | | |
|---|---|---|
| Chemical Characteristics | : | Mixture of anti adhesive |
| Appearance | : | Yellowish liquid |
| PH | : | 10± 0,5 |
| Dilution ratio | : | 1:10 (Anti-tack TP 131: $H_2O$) |
| Storage Stability | : | 1 years under cool and dry storage conditions in orginally packing |
| Packing | : | Plastic drums containing 60 kg net |

**Tepe Kimya (M) SDN. BHD.**
Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848
**Web:** www.tepekimya.com

**Tepe Kimya San. ve Tic.Ltd.Şti.**
Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla Istanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

**Tepe Trade Intl. Chem Pte. Ltd.**
63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435
**Email:** info@tepekimya.com