Anti-tack TP 133-MG

Batch off Soap

ANTI-TACK TP 133-MG is used for the treatment of unvulcanised rubber compounds in the form of sheet or strip to prevent surface sticking.

ANTI-TACK TP 133-MG is paste type Antitack agent. It is non-foaming

PROPERTIES

Chemical Characteristics	:	Mixture of anti adhesive and stearates
Appearance	:	White paste of medium viscosity
PH	:	7± 0,5
Dilution ratio	:	1:10 (Anti-tack TP 133: H_2O)
Storage Stability	:	1 years under cool and dry storage conditions in orginally packing
Packing	:	Plastic drums containing 60 or 100 kg net

Tepe Kimya (M) SDN. BHD.
Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848
Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.
Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla Istanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.
63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435
Email: info@tepekimya.com