HYGROSCOPE GR

Calcium Oxide

HYGROSCOPE GR is a soft granule of 80 % calcium oxide coated with special dispersing agents to delay reactivity and is used as a desiccant in rubber compounds which are cured pressurless (Micro wavesystem, LCM, Hot air or Fluid bed)
Moisture which presents in all rubber chemicals, especially fillers, will be absorbed and the calcium oxide will change to calcium hydroxide after reaction with the moisture.
HYGROSCOPE GR should be used in order to prevent blisters and porosity in the following rubber processes;
Pressurless continuous curing systems like Micro wave, LCM, Hot air, Fluid beds,
Low pressure curing in the cable industry,
In cases where the influence of humidity in rubber compounds should be suppressed.

HYGROSCOPE GR can be supplied in sachets containing any weight between 0.5 kg and 20 kg to suit customers requirements at no extra cost.

PROPERTIES

Chemical Characteristics	: Calcium oxide coated by special dispersing agents
Appearance	: Light gray, soft granules
CaO content	: 80 % ±2
Density	: approx.2.35 g/cm^3
Storage Stability	: 1 year under cool and dry storage conditions originally packing
Packing	: cardboard boxes containing 15, 20 or 25 kg net

Tepe Kimya (M) SDN. BHD.
Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848
Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.
Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla Istanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.
63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435
Email: info@tepekimya.com