

# Multinomial regression of spouse characteristics for the ChitwanABM

**Author:** Alex Zvoleff

**Email:** [azvoleff@mail.sdsu.edu](mailto:azvoleff@mail.sdsu.edu)

**Date:** July, 2012

Analyzes the relationship grid data from the CVFS to build a multinomial regression predict the probability of marrying a spouse within each of a set of age groups, together with the probability of marrying someone of a different ethnicity.

The results of this analysis are used to inform the marriage process in the ChitwanABM. Once the determination has been made that a woman is marrying (based on the probability derived from event history analysis), the multinomial regression developed here is used to assign a probability of marriage to each possible spouse, based on the age of that person, so that the age differential between spouses is realistic.

## Load the data and setup R

```
library(ggplot2)
library(mlogit)
```

```
## Loading required package: Formula
```

```
## Loading required package: statmod
```

```
## Loading required package: lmtest
```

```
## Loading required package: zoo
```

```
## Attaching package: 'zoo'
```

```
## The following object(s) are masked from 'package:base':
##
## as.Date, as.Date.numeric
```

```
## Loading required package: maxLik
```

```
## Loading required package: miscTools
```

```
## Loading required package: MASS
```

```
library(arm)
```

```
## Loading required package: Matrix
```

```
## Loading required package: lattice
```

```
## Loading required package: lme4
```

```
## Attaching package: 'lme4'
```

```
## The following object(s) are masked from 'package:stats':  
##  
## AIC, BIC
```

```
## Loading required package: R2WinBUGS
```

```
## Loading required package: coda
```

```
## Attaching package: 'coda'
```

```
## The following object(s) are masked from 'package:lme4':  
##  
## HPDinterval
```

```
## Loading required package: abind
```

```
## Loading required package: foreign
```

```
## arm (Version 1.5-05, built: 2012-6-6)
```

```
## Working directory is C:/Users/azvoleff/Code/R/Chitwan_R_files/Event_History_Analysis
```

```
## Attaching package: 'arm'
```

```
## The following object(s) are masked from 'package:coda':  
##  
## traceplot
```

```
library(rms) # Note 'Design' package was renamed to 'rms'
```

```
## Loading required package: Hmisc
```

```
## Loading required package: survival
```

```
## Loading required package: splines
```

```
## Hmisc library by Frank E Harrell Jr
##
## Type library(help='Hmisc'), ?Overview, or ?Hmisc.Overview') to see overall documentation.
##
## NOTE:Hmisc no longer redefines [.factor to drop unused levels when subsetting. To get the old
## behavior of Hmisc type dropUnusedLevels().
```

```
## Attaching package: 'Hmisc'
```

```
## The following object(s) are masked from 'package:survival':
##
## untangle.specials
```

```
## The following object(s) are masked from 'package:base':
##
## format.pval, round.POSIXt, trunc.POSIXt, units
```

```
## Attaching package: 'rms'
```

```
## The following object(s) are masked from 'package:survival':
##
## Surv
```

```
## The following object(s) are masked from 'package:lmtest':
##
## lrtest
```

```
theme_update(theme_bw(base_size = 10))
```

```
load("V:/Nepal/CVFS_R_format/hhrel_with_respIDs.Rdata")
hhrel <- hhrel_with_respIDs

# Drop 'other' ethnicity for consistency with existing work
hhrel <- hhrel[!(hhrel$ethnic == "Other"), ]
hhrel$ethnic <- factor(hhrel$ethnic)
hhrel$CENGENDR <- factor(hhrel$CENGENDR)

hhrel$age_cat <- cut(hhrel$CENAGE, breaks = c(0, 15, 20, 30, 40, 50, 60, 999), ordered_result = TRUE)
```

## Basic statistics

First look at some basic statistics on who is married, and on how many spouses they have, by gender.

```
hhrel$HASSPOUSE1 <- !is.na(hhrel$SPOUSE1)
hhrel$HASSPOUSE2 <- !is.na(hhrel$SPOUSE2)
hhrel$HASSPOUSE3 <- !is.na(hhrel$SPOUSE3)
xtabs(~CENGENDR + HASSPOUSE1, data = hhrel)
```

```
##           HASSPOUSE1
## CENGENDR FALSE TRUE
##   female   2218 1892
##   male     2293 1849
```

```
xtabs(~CENGENDR + HASSPOUSE2, data = hhrel)
```

```
##           HASSPOUSE2
## CENGENDR FALSE TRUE
##   female  4110    0
##   male    4109   33
```

```
xtabs(~CENGENDR + HASSPOUSE3, data = hhrel)
```

```
##           HASSPOUSE3
## CENGENDR FALSE TRUE
##   female  4110    0
##   male    4140    2
```

Now look at who has more than one spouse (only males do) by age group:

```
xtabs(~age_cat + HASSPOUSE2, data = hhrel)
```

```
##           HASSPOUSE2
## age_cat  FALSE TRUE
## (0,15]    3228    0
## (15,20]   989    0
## (20,30]   1393    1
## (30,40]   970    7
## (40,50]   711    7
## (50,60]   470   10
## (60,999]  458    8
```

```
xtabs(~age_cat + HASSPOUSE3, data = hhrel)
```

```
##           HASSPOUSE3
## age_cat  FALSE TRUE
## (0,15]    3228    0
## (15,20]   989    0
## (20,30]   1394    0
## (30,40]   977    0
## (40,50]   718    0
## (50,60]   479    1
## (60,999]  465    1
```

Having multiple wives is mostly confined to older men. Now look into the difference in spouse age, by gender.


```
spouse1_row <- match(hhrel$SPOUSE1, hhrel$RESPID)
hhrel$sp_age <- hhrel$CENAGE[spouse1_row]
hhrel$sp_age_cat <- hhrel$age_cat[spouse1_row]
hhrel$sp_age_diff <- hhrel$CENAGE - hhrel$sp_age
xtabs(~age_cat + sp_age_cat, data = hhrel)
```

```
##           sp_age_cat
## age_cat  (0,15] (15,20] (20,30] (30,40] (40,50] (50,60] (60,999]
## (0,15]      0      1      2      0      0      0      0
## (15,20]     1     88    160      8      0      1      0
## (20,30]     2    160    689    271     27      6      1
## (30,40]     0      7    265    425    194     31      8
## (40,50]     0      0     26    189    268    146     41
## (50,60]     0      1      4     28    142    133     85
## (60,999]    0      0      1      7     38     83    188
```

```
qplot(sp_age_diff, facets = CENGENDR ~ ., xlab = "Age difference in years (self - spouse)",
      data = hhrel)
```

```
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
```

```
## stat_bin: binwidth defaulted to range/30. Use 'binwidth = x' to adjust this.
```



*Comparison of spouse age difference by gender*

Setup some age categories for the difference in spouse age.

```
hhrel$sp_age_diff_cat <- cut(hhrel$sp_age_diff, breaks = c(-999, -15, -10, -5, -2, -1,
  0, 1, 2, 5, 10, 15, 999), ordered_result = TRUE)
xtabs(~sp_age_diff_cat + age_cat + CENGENDR, data = hhrel)
```

```
## , , CENGENDR = female
##
##           age_cat
## sp_age_diff_cat (0,15] (15,20] (20,30] (30,40] (40,50] (50,60] (60,999]
## (-999,-15]      0      4      29      34      41      14      2
## (-15,-10]       1     17     64     68     59     30     12
## (-10,-5]        1     79    242    146     95     51     30
## (-5,-2]         1     78    219    122     77     23     23
## (-2,-1]         0     25     48     24     14     12      7
## (-1,0]          0      4     27     30     16     11      8
```

```
##      (0,1]      0      3      8      8      5      6      3
##      (1,2]      0      0      5      6      5      2      3
##      (2,5]      0      1      3      5      8      3      5
##      (5,10]     0      0      1      0      4      1      2
##      (10,15]    0      0      0      0      1      0      2
##      (15,999]   0      0      0      0      1      0      0
##
## , , CENGENDR = male
##
##           age_cat
## sp_age_diff_cat (0,15] (15,20] (20,30] (30,40] (40,50] (50,60] (60,999]
##      (-999,-15]    0      0      1      0      0      0      0
##      (-15,-10]     0      0      1      2      0      0      3
##      (-10,-5]      0      0      1      3      6      1      3
##      (-5,-2]       0      2      9      9     10      4      4
##      (-2,-1]       0      3      9      8      4      6      3
##      (-1,0]        0      6     27     30     14     12      8
##      (0,1]         0     17     54     25     13     14      7
##      (1,2]         0      8     81     42     36     13     14
##      (2,5]         0     11    212    162    100     45     28
##      (5,10]        0      0    106    165     99     75     60
##      (10,15]       0      0      9     33     49     50     37
##      (15,999]      0      0      0      8     13     20     53
##
```

Do people marry outside of their ethnic group?

```
spouse1_row <- match(hhrel$SPOUSE1, hhrel$RESPID)
hhrel$spouse_ethnicity <- hhrel$ethnic[spouse1_row]
xtabs(~ethnic + spouse_ethnicity, data = hhrel)
```


```
##           spouse_ethnicity
## ethnic      UpHindu HillTibeto LowHindu Newar TeraiTibeto
## UpHindu      1733         2         0         0         0
## HillTibeto    2         633         0         0         2
## LowHindu      0         0        413         0         0
## Newar         0         0         0        244         0
## TeraiTibeto   0         2         0         0        696
```

Marriages outside of your ethnic group are VERY uncommon. There are only 4 in the data. So we will disallow these marriages in the model - there are not enough of them to develop any kind of predictive model of when they might occur.

Make a few final summary plots: the mean of spouse\_age\_diff versus gender, and a histogram of spouse\_age\_diff by gender.


```
qplot(CENGENDR, sp_age_diff, geom = "boxplot", xlab = "Gender", ylab = "Spouse age difference in years (self - spouse)",
      data = hhrel)
```

```
## Warning: Removed 4525 rows containing non-finite values (stat_boxplot).
```



*plot of chunk mean-sp-age-diff-versus-age*

```
ggplot(sp_age_diff_cat, facets = CENGENDR ~ ., geom = "histogram", xlab = "Gender", ylab = "Spouse age difference in years (self - spouse)",
  data = hhrel[hhrel$HASSPOUSE1, ])
```



*Histogram of marriages by spouse age categories and gender*

## Multinomial logistic regression predicting spouse age difference based on gender

```
hhrel_mlogit_data <- mlogit.data(hhrel, varying = NULL, choice = "sp_age_diff_cat", shape = "wide")
mlogit_spouseage <- mlogit(sp_age_diff_cat ~ 1 | CENGENDR, data = hhrel_mlogit_data)
summary(mlogit_spouseage)
```

```
##
## Call:
## mlogit(formula = sp_age_diff_cat ~ 1 | CENGENDR, data = hhrel_mlogit_data,
## method = "nr", print.level = 0)
```

```
##
## Frequencies of alternatives:
##      (-1,0]   (-10,-5]   (-15,-10]   (-2,-1]   (-5,-2]   (-999,-15]   (0,1]   (1,2]
##      0.0518   0.1765   0.0690   0.0437   0.1559   0.0335   0.0437   0.0577
##      (10,15]   (15,999]   (2,5]   (5,10]
##      0.0486   0.0255   0.1564   0.1376
##
## nr method
## 8 iterations, 0h:0m:2s
## g'(-H)^-1g = 3.65E-06
## successive fonction values within tolerance limits
##
## Coefficients :
##              Estimate Std. Error t-value Pr(>|t|)
## (-10,-5]:(intercept)    1.903     0.109   17.40 < 2e-16 ***
## (-15,-10]:(intercept)    0.961     0.120    8.01 1.1e-15 ***
## (-2,-1]:(intercept)     0.303     0.135    2.25 0.024 *
## (-5,-2]:(intercept)     1.733     0.111   15.65 < 2e-16 ***
## (-999,-15]:(intercept)   0.256     0.136    1.88 0.060 .
## (0,1]:(intercept)       -1.068     0.202   -5.29 1.2e-07 ***
## (1,2]:(intercept)       -1.520     0.241   -6.31 2.8e-10 ***
## (10,15]:(intercept)     -3.466     0.586   -5.91 3.4e-09 ***
## (15,999]:(intercept)    -4.564     1.005   -4.54 5.6e-06 ***
## (2,5]:(intercept)       -1.345     0.225   -5.99 2.1e-09 ***
## (5,10]:(intercept)      -2.485     0.368   -6.75 1.5e-11 ***
## (-10,-5]:CENGENDRmale   -3.839     0.306  -12.54 < 2e-16 ***
## (-15,-10]:CENGENDRmale  -3.744     0.437   -8.56 < 2e-16 ***
## (-2,-1]:CENGENDRmale   -1.381     0.242   -5.70 1.2e-08 ***
## (-5,-2]:CENGENDRmale   -2.670     0.221  -12.08 < 2e-16 ***
## (-999,-15]:CENGENDRmale -4.831     1.014   -4.76 1.9e-06 ***
## (0,1]:CENGENDRmale      1.361     0.242    5.62 2.0e-08 ***
## (1,2]:CENGENDRmale      2.213     0.271    8.16 2.2e-16 ***
## (10,15]:CENGENDRmale     4.073     0.600    6.79 1.1e-11 ***
## (15,999]:CENGENDRmale     4.533     1.016    4.46 8.1e-06 ***
## (2,5]:CENGENDRmale      3.095     0.250   12.38 < 2e-16 ***
## (5,10]:CENGENDRmale     4.135     0.384   10.76 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Log-Likelihood: -6720
## McFadden R^2: 0.212
## Likelihood ratio test : chisq = 3620 (p.value = <2e-16)
```

```
mlogit_spouseage_odds <- cbind(odds_ratio = exp(coef(mlogit_spouseage)), exp(confint.default(mlogit_spouseage)))
(mlogit_spouseage_odds <- round(mlogit_spouseage_odds, 4))
```

```
##              odds_ratio    2.5 %    97.5 %
## (-10,-5]:(intercept)    6.7083  5.4136  8.3127
## (-15,-10]:(intercept)    2.6146  2.0666  3.3079
## (-2,-1]:(intercept)     1.3542  1.0402  1.7629
## (-5,-2]:(intercept)     5.6562  4.5529  7.0270
## (-999,-15]:(intercept)   1.2917  0.9895  1.6860
## (0,1]:(intercept)        0.3437  0.2315  0.5105
## (1,2]:(intercept)        0.2187  0.1364  0.3508
## (10,15]:(intercept)      0.0312  0.0099  0.0986
## (15,999]:(intercept)     0.0104  0.0015  0.0747
## (2,5]:(intercept)        0.2604  0.1677  0.4044
## (5,10]:(intercept)       0.0833  0.0405  0.1714
## (-10,-5]:CENGENDRmale    0.0215  0.0118  0.0392
## (-15,-10]:CENGENDRmale    0.0237  0.0100  0.0558
## (-2,-1]:CENGENDRmale     0.2512  0.1562  0.4040
## (-5,-2]:CENGENDRmale     0.0693  0.0449  0.1068
```



## (-999,-15]:CENGENDRmale	0.0080	0.0011	0.0583
## (0,1]:CENGENDRmale	3.8988	2.4247	6.2690
## (1,2]:CENGENDRmale	9.1429	5.3742	15.5543
## (10,15]:CENGENDRmale	58.7216	18.1262	190.2349
## (15,999]:CENGENDRmale	93.0309	12.7110	680.8861
## (2,5]:CENGENDRmale	22.0899	13.5320	36.0599
## (5,10]:CENGENDRmale	62.4742	29.4146	132.6904

```
write.csv(coef(mlogit_spouseage), file = "mlogit_spouseage_coefs.csv")  
write.csv(mlogit_spouseage_odds, file = "mlogit_spouseage_odds.csv")
```