**Technische Universität Berlin**
Faculty IV: Electrical Engineering and Computer Science
**Freie Universität Berlin**
Department of Mathematics and Computer Science
Algorithmic Bioinformatics

welche uni angeben, welche reihenfolge..?

# Automatic Optimization of Level Parameters for RSHash

**(RSHash is a minimizer based fast, compressed hash table for storing DNA k-mers. It was recently introduced by the Reinert Group.)**

**Bjarne David Jehn**

Thesis submitted in fulfillment of the requirements for the degree "Bachelor of Science"(B. Sc.) in the field of Computer Science

| | |
|---|---|
| First Reviewer: | Prof. Dr. Knut Reinert |
| Second Reviewer: | Prof. Dr. Stephan Kreutzer |
| Supervisor: | Jonas Schulte-Mattler |

# Declaration of Authorship

I hereby declare that the thesis submitted is my own, unaided work, completed without any external help. Only the sources and resources listed were used. All passages taken from the sources and aids used, either unchanged or paraphrased, have been marked as such.

Where generative AI tools were used, I have indicated the product name, manufacturer, the software version used, as well as the respective purpose (e.g. checking and improving language in the texts, systematic research). I am fully responsible for the selection, adoption, and all results of the AI-generated output I use.

I have taken note of the Principles for Ensuring Good Research Practice at TU Berlin dated 15 February 2023. https://www.static.tu.berlin/fileadmin/www/10002457/K3-AMBl/Amtsblatt_2023/Amtliches_Mitteilungsblatt_Nr._16_vom_30.05.2023.pdf

I further declare that I have not submitted the thesis in the same or similar form to any other examination authority.

Berlin, _____ _____

Date Signature

## Abstract

in English

## Zusammenfassung

auf Deutsch

# Contents


**1 Notation** **5**

**2 Introduction** **6**
2.1 RSHash Explanation . . . . . 6
2.2 Problem Definition . . . . . 6

**3 Sequence Statistics** **8**
3.1 Minimizer Distribution . . . . . 8
3.2 Average Frequencies . . . . . 9
3.3 Times for Operations on Datastructure . . . . . 10

**4 MINLP Modeling** **11**
4.1 Model Input . . . . . 11
4.2 Model for One Level . . . . . 11
4.2.1 Lookup Time . . . . . 12
4.2.2 Space Consumption . . . . . 13
4.2.3 Optimization Goal . . . . . 16
4.3 Model for Several Levels . . . . . 18
4.3.1 Lookup Time . . . . . 19
4.3.2 Space Consumption . . . . . 20
4.4 Locate . . . . . 21

**5 Experiments** **22**
5.1 Solving the MINLP . . . . . 22
5.2 Limitations . . . . . 22

**6 Subsampling** **23**
6.1 Motivation . . . . . 23
6.2 Subsampling Method . . . . . 23
6.3 Time Complexity of Finding the Minimizer Distributions . . . . . 23
6.4 Time Complexity using Subsampling . . . . . 23
6.5 Error Analysis . . . . . 24
6.6 Choosing $l$ . . . . . 24
6.7 Choosing $n$ . . . . . 24

**Bibliography** **25**

# 1 Notation

Let $L \in \mathbb{N}^+$ be the number of levels specified. We refer to the set of used levels $\mathcal{L} := \{l \in \mathbb{N}^+ \mid l \leq L\}$. The minimizer length and threshold on a specified level $l \in \mathcal{L}$ are denoted $m^l$ and $t^l$. We use the tuple $p^l := (m^1, ..., m^l, t^1, ..., t^l) \in \mathcal{M}^l \times \mathcal{T}^l$ to denote the level parameters up to level $l$.
Let $q$ be a k-mer. The computation of its minimizer $min^l_{m^l}(q)$ depends both on the minimizer length $m^l$ on that level as well as directly on the level $l$ which determines the hashfunctions seed. We denote the minimizers frequency with $freq(min^l_{m^l}(q))$ which is equivalent to the number of occurrences of the minimizer in a given set of input sequences. We call a minimizer *infrequent* on level $l$ only if $1 \leq freq(min^l_{m^l}(q)) \leq t^l$ holds i.e. the minimizer occurs at least once but no more than the given threshold. Minimizers with frequencies larger than the threshold are effered to as being *frequent* .
We write $S_{p^l} := \{S^l_1, S^l_2, ..., S^l_n\}$ to denote the sequences on level $l$ in dependence of the level parameters on the previous levels i.e. the k-mers which have *infrequent* minimizers on all previous levels.

Hier würde ich gerne einmal besprechen, inwiefern die abhängigkeit von Instanzen von bestimmten parametern durch indezes gekennzeichnet werden soll oder lieber einfach einmal erklärt aber dann nicht jedes mal aufgeschrieben werden, um übersichtlichkeit zu gewaren - z.B. einfach $min(k)$ statt $min^l_{m^l}(k)l$

# 2 Introduction

## 2.1 RSHash Explanation

Wie detailiert soll ich RSHash beschreiben? Reicht eine grobe Beschreibung und ein Verweis auf [SMR26]?

RSHash is a minimizer based fast, compressed hash table for storing DNA k-mers that answers lookup and can be extended for supporting locate. It was recently introduced by Schulte-Mattler and Reinert [SMR26].
The data structure works with one, two or three levels and a hash table. For each level $l$ a pair of level parameters has to be specified: the minimizer length $m^l$ and a threshold $t^l$.

Each level $l$ is build in the following way:
For each k-mer $q$ in the input sequences the minimizer $min^l_{m^l}(q)$ of length $m^l$ is computed. A temporary hash table is used to count the number of occurrences of each appearing minimizer, also referred to as the minimizers frequency $freq(min^l_{m^l}(q))$.
A bit vector $R^l$ of lengths $4^{m^l}$ is used to mark all minimizers that appear at least once but no more than $t^l$ times. We call those minimizers *infrequent* .
The position of every occurrence of each infrequent minimizer in the text are stored in the offset vector $O^l$ in the order induced by $R^l$.
The boundaries of offsets in $O^l$ belonging to different minimizers are marked in the bit vector $S^l \in \{0,1\}^{|O|+1}$.
All k-mers with frequent minimizers on level $l$ make up the input sequences for the next higher level $l+1$ which works exactly like the previous apart from having its own level parameters. Those k-mers with frequent minimizers on all specified levels end up being stored in a hash table $H$.

## 2.2 Problem Definition

Choosing the minimizer length $m$ is an inherent problem of minimizer based k-mer indexing methods. Zheng, Kingsford, and Marçais [ZKM20] show that a minimizer is expected to be valid for an average of $(k-m+2)/2$ k-mers. Using a small $m << k$ thus leads to a relatively small number of super-k-mers meaning a better compression. Picking a small $m$ however also means that minimizers will be more frequent which leads to high query times because each minimizer offset has to be evaluated for an actual match with the queried k-mer. This means a constant trade off between space consumption and query times. Existing methods use a number of approaches to deal with this problem

beispiele und quellen angeben

The leveled approach used by RSHash exploits the skewed distribution of minimizers. It allows to achieve high compression by using relatively short minimizers on the lower levels whilst also mitigating the burden of very frequent minimizers by using thresholds to move them to higher levels.

So far the level parameters have to be specified when building the data structure which requires manual testing and extensive understanding of the RSHash algorithm.

With this thesis we attempt to expand the understanding of how exactly the level parameters influence the time and space consumption of RSHash and make the algorithm more accessible to use by automating the optimization of level parameters for a given genome and optimization goal.

Problems:

- work towards a better understanding of minimizer distribution across several levels
- analyze how level parameters influence time and space consumption of RSHash
- automize finding optimal level parameters

# 3 Sequence Statistics

## 3.1 Minimizer Distribution

The skewness of minimizer distributions has been observed by several previous works [Chi+14; Jai+20; Pib22; SMR26].
The approach of using consequent levels with respective thresholds as introduced by Schulte-Mattler and Reinert [SMR26] makes use of this property by handling k-mers with *infrequent* minimizers on a level directly and "moving" those k-mers with *frequent* minimizers to the next higher level on which a different hash function is used in hopes of further reducing the amount of k-mers with *frequent* minimizers.
The distribution of k-mers on the first level is ...., the distribution for higher levels however doesn't compare to .q.-r.-

zu vage?

well known?

hier will ich eigentlich etwas schreiben im Sinne von: Für das erste Level gelten die Beobachtung vorheriger Arbeiten, für weitere Level allerding gelten diese nicht mehr? oder doch?, da.... - deswegen wollen wir das verhalten der minimizer untersuchen

We decribe the minimizer distribution on a level $l$ in dependence of the level parameters $p^l \in \mathcal{M}^l \times \mathcal{T}^l$ on all levels up to and including the level $l$.
For each level $l$ we will define the set of input sequences $S_{p^l}$ on level $l$, the set of distinct k-mers $\mathcal{K}_{p^l}$ in these sequences and the set of distinct minimizers $\mathcal{M}_{p^l}$ of these k-mers. Even though some of these instances are only dependent on the level parameters $p^{l-1}$ on the previous levels, we always use the index $p^l$ in order to avoid confusion about the level and achieve better readability.
With $S_{p^l}$ being the input sequences on level $l$ let $\mathcal{K}_{p^l}$ be the set of distinct k-mers in $S_{p^l}$.[1]:

properly define $S_{p^l}$?

$$\mathcal{K}_{p^l} := \{x \in \{0, 1, ..., 4^k\} \mid \exists S' \in S_{p^l}\ \exists (1 \leq i \leq |S'| - k)\ S'[i : i + k] = x\} \tag{3.1}$$

define k-mers, indices, sequences, minimizers

Let $\mathcal{M}_{p^l}$[2] be the set of distinct minimizers of lengths $m^l$ of the k-mers in $\mathcal{K}_{p^l}$:

$$\mathcal{M}_{p^l} := \{x \in \{0, 1, ..., 4^{m^l}\} \mid \exists k \in \mathcal{K}_{p^l}\ min^l_{m^l}(k) = x\} \tag{3.2}$$

[1] Both $S_{p^l}$ and $\mathcal{K}_{p^l}$ are technically only dependent of the level parameters $p^{l-1}$ on all previous levels but not of the minimizer length $m^l$ and threshold $t^l$ on level $l$ (Section 2.1).
[2] $\mathcal{M}_{p^l}$ is technically only dependent of the level parameters $p^{l-1}$ on all previous levels as well as the minimizer length $m^l$ on level $l$ but not of the threshold $t^l$ on level $l$.

Let $M_{p^l}$ be a discrete random variable that describes the frequency of these minimizers:

$$M_{p^l} : \mathcal{M}_{p^l} \to \mathbb{N} \tag{3.3}$$
$$M_{p^l}(x) = freq(x) \tag{3.4}$$

We define its probability distribution $p_{M_{p^l}}$ and its cumulative distribution function $F_{M_{p^l}}$[3]:

$$p_{M_{p^l}} : \mathbb{N} \to [0, 1] \tag{3.5}$$
$$p_{M_{p^l}}(f) = \mathbb{P}(M_{p^l} = f) := \frac{|\{x \in \mathcal{M}_{p^l} \mid M_{p^l}(x) = f\}|}{|\mathcal{M}_{p^l}|} \tag{3.6}$$
$$F_{M_{p^l}} : \mathbb{N} \to [0, 1] \tag{3.7}$$
$$F_{M_{p^l}}(f) = \mathbb{P}(M_{p^l} \leq f) := \sum_{i=1}^{f} p_{M_{p^l}}(i) \tag{3.8}$$

The discrete random variable $M_{p^l}$ and its distribution can be used to model certain values related to a random (appearing) minimizer.
RSHash however is used to lookup k-mers, not minimizers. Therefore we introduce the discrete random variable $K_{p^l}$ to describe the frequency of a random (appearing) k-mers minimizer of length $m^l$:

$$K_{p^l} : \mathcal{K}_{p^l} \to \mathbb{N} \tag{3.9}$$
$$K_{p^l}(q) = freq(min^l_{m^l}(q)) \tag{3.10}$$

Its probability distribution $p_{K_{p^l}}$ and its cumulative distribution function $F_{K_{p^l}}$ are:

$$p_{K_{p^l}} : \mathbb{N} \to [0, 1] \tag{3.11}$$
$$p_{K_{p^l}}(f) = \mathbb{P}(K_{p^l} = f) := \frac{|\{q \in \mathcal{K}_{p^l} \mid K_{p^l}(q) = f\}|}{|\mathcal{K}_{p^l}|} \tag{3.12}$$
$$F_{K_{p^l}} : \mathbb{N} \to [0, 1] \tag{3.13}$$
$$F_{K_{p^l}}(f) = \mathbb{P}(K_{p^l} \leq f) := \sum_{i=1}^{f} p_{K_{p^l}}(i) \tag{3.14}$$

Explain how and why distribution on the first level affects the distributions on higher levels.

## 3.2 Average Frequencies

The average frequency of minimizers on a level $l \in \mathcal{L}$ given the level parameters $p^l$ and the sequences $S_{p^l}$ is given by the expected value of the probability distribution of the

[3]This notation differs slightly from that used by Schulte-Mattler and Reinert [SMR26] who do not introduce the probability distributions but instead use $p_M$ and $p_K$ to denote the cumulative distribution functions which we denote with $F_M$ and $F_K$

random variable $M_{p^l}$:

$$\mathbb{E}[M_{p^l}] = \sum_{f \in M_{p^l}(\mathcal{M}_{p^l})} p_{M_{p^l}}(f) * f \tag{3.15}$$

wertebereich $\mathcal{M}_{p^l}$) definieren

This value always exists, as the set $\mathcal{M}_{p^l}$ of distinct minimizers of length $m$ in a given set of (finite) sequences is always finite.

More relevant for the optimization of level parameters however is the average frequency of *infrequent* minimizers i.e. the average frequency of minimizers whose frequency do not exceed the threshold $t^l$. We denote this value with $f_{avg}(p^l)$ and can derive it from $p_{M_{p^l}}$ by computing a weighted sum over all frequencies up until the threshold $t^l$ and then norming the result by dividing through the percentage of *infrequent* minimizers:

$$f_{avg}(p^l) = \frac{1}{F_{M_{p^l}}(t^l)} \cdot \sum_{f=1}^{t^l} p_{M_{p^l}}(f) \cdot f \tag{3.16}$$

## 3.3 Times for Operations on Datastructure

We denote the time needed to perform an operation *op* on a data structure *struct* with $T_{op_{struct}}$ e.g. the time for a rank query on the bit vector $R$ is $T_{rank_R}$.

incomplete. measure or model?

**Vector Access** Accessing an element of a Vector can be done in constant time, we use the following values based on measurements:

$$T_{acc_R} = ...$$
$$T_{acc_O} = ...$$

**Hash Table Access** Accessing an element of a Hash Table can be done in constant time, we use the following values based on measurements:

$$T_{check_H} = ...$$

**Bit Vector Rank Query** A bitvector of length $U$ with $n$ $1s$ can be encoded with $n\lceil log_2 U/n \rceil + 3n$ many bits supporting rank in $O(log_2(U/n)$ time (Okanohara and Sadakane, 2007).

does that help here? Doesn't the model require actual time instead of O notation - maybe measurements would be more suited

**Bit Vector Select Query** ???

**Comparison with Text** ???

# 4 MINLP Modeling

We model the optimization problem as a Mixed Integer Non Linear Programming (MINLP). In Section 4.2 we model the runtime and space needed by RSHash on one level in dependence of the level parameters and minimizers distribution. We then extend this to the case of several levels in Section 4.3.
In Chapter 5 we describe how to find the optimal level parameters for a given sequence using the MINLP.

## 4.1 Model Input

The set of levels $\mathcal{L}$, the sets of minimizer lengths $\mathcal{M} \subset \mathbb{N}$ and thresholds $\mathcal{T} \subset \mathbb{N}$ to consider have to be specified explicitly.
The computed minimizer statistics $F_{M_{p^l}}(p^l)$, $F_{K_{p^l}}(p^l)$ and $f_{avg}(p^l)$ for all possible combinations $p^l$ of the level parameters on each level $l \in \mathcal{L}$ also have to be passed as input to the MINLP.
Lastly, a measure of the times $T_{acc_R}$, $T_{rank_R}$, $T_{sel_S}$, $T_{acc_O}$, $T_{comp_T}$, $T_{check_H}$ needed for the access of bit vector $R$, the rank and select queries on bit vectors $R$ and $S$, comparison with the text $T$ and checking whether a key exists in the hash set $H$. The computation of the minimizer distribution as well as the times needed to perform these actions on the specified data structures is outlined in Chapter 5.

## 4.2 Model for One Level

Aiming to improve readability, we omit the superscript index indicating an instances belonging to a specific level as only one level is considered in this section e.g. a tuple of level parameters is simply referred to as $p$ instead of $p^1$.
In order to determine $\mathbf{m}$ and $\mathbf{t}$ we use binary indicator variables $\mu_m$ and $\tau_t$ for each possible $m \in \mathcal{M}$ and $t \in \mathcal{T}$:

$$\mu_m \in \{0,1\} \mid \forall m \in \mathcal{M} \tag{4.1}$$
$$\tau_t \in \{0,1\} \mid \forall t \in \mathcal{T} \tag{4.2}$$

The indicator variables for each minimizer length should be mutually exclusive as $\mathbf{m}$ can only take one distinct value. The same holds for the indicator variables for each

threshold:

$$\sum_{m \in \mathcal{M}} \mu_m = 1 \tag{4.3}$$

$$\sum_{t \in \mathcal{T}} \tau_t = 1 \tag{4.4}$$

The variables $\mathbf{m} \in \mathcal{M}$ and $\mathbf{t} \in \mathcal{T}$ are introduced to describe the optimal minimizer length and threshold.
There values can be modeled through a sum over the indicator variables multiplied with there corresponding values:

$$\mathbf{m} \in \mathcal{M} \tag{4.5}$$

$$\mathbf{t} \in \mathcal{T} \tag{4.6}$$

$$\mathbf{m} = \sum_{m \in \mathcal{M}} \mu_m \cdot m \tag{4.7}$$

$$\mathbf{t} = \sum_{t \in \mathcal{T}} \tau_t \cdot t \tag{4.8}$$

We introduce the variable $\mathbf{F}_M \in [0, 1]$ to take the value of $F_{M_{(\mathbf{m},\mathbf{t})}}(\mathbf{t})$ (Section 3.1).
It is not possible to directly evaluate this value as both $\mathbf{m}$ and $\mathbf{t}$ are variables of the model. Instead we use the indicator variables to model a constraint forcing $\mathbf{F}_M$ to take the value of the only $F_{M_{(m,t)}}(t)$ for which $\mu_m = 1$ and $\tau_t = 1$:

$$\mathbf{F}_M \in [0, 1] \tag{4.9}$$

$$\mathbf{F}_M = \sum_{m \in \mathcal{M}} \mu_m \cdot \sum_{t \in \mathcal{T}} \tau_t \cdot F_{M_{(m,t)}}(t) \tag{4.10}$$

Analogously we introduce $\mathbf{F}_K \in [0, 1]$ to represent $F_{K_{(\mathbf{m},\mathbf{t})}}(\mathbf{t})$ and $\mathbf{f_{avg}} \in \mathbb{R}_0^+$ to represent $f_{avg}((\mathbf{m}, \mathbf{t}))$ (Section 3.2):

$$\mathbf{F}_K \in [0, 1] \tag{4.11}$$

$$\mathbf{f_{avg}} \in \mathbb{R}_0^+ \tag{4.12}$$

$$\mathbf{F}_K = \sum_{m \in \mathcal{M}} \mu_m \cdot \sum_{t \in \mathcal{T}} \tau_t \cdot F_{K_{(m,t)}}(t) \tag{4.13}$$

$$\mathbf{f_{avg}} = \sum_{m \in \mathcal{M}} \mu_m \cdot \sum_{t \in \mathcal{T}} \tau_t \cdot f_{avg}((m, t)) \tag{4.14}$$

### 4.2.1 Lookup Time

note that this is the average lookup time for k-mers that appear in the sequence! k-mers that do not appear in the sequence will simply have a lookup time of a check in R on every level and then a check in H

In order to model the time needed for a lookup using RSHash, we closely follow the lookup procedure as described by Schulte-Mattler and Reinert [SMR26]:
A k-mer $q$ is looked up by first computing its minimizer $min_m(q)$ and checking whether the bit $R[min_m(q)]$ is set, taking $T_{acc_R}$ time (part of the model input Section 4.1).
For the percentage $\mathbf{F}_K$ (Equation (4.13)) of the k-mers this bit is set and the lookup is completed by searching for $q$ on the level. We introduce the variable $T_{level} \in \mathbb{R}_0^+$ to describe the time needed for this.
If the bit $R[min_m(q)]$ is not set, the lookup is completed through a lookup in the hash table $H$ taking $T_{check_H}$ time (part of the model input Section 4.1). The variable $T_{lookup_{RSHash}} \in \mathbb{R}_0^+$ describing the lookup time can thus be modeled as:

$$T_{level} \in \mathbb{R}_0^+ \tag{4.15}$$

$$T_{lookup_{RSHash}} \in \mathbb{R}_0^+ \tag{4.16}$$

$$\begin{aligned} T_{lookup_{RSHash}} = T_{acc_R} &+ \mathbf{F}_K \cdot T_{level} \\ &+ (1 - \mathbf{F}_K) \cdot T_{check_H} \end{aligned} \tag{4.17}$$

The search for those k-mers $q$ for which the bit $R[min_m(q)]$ is set continues on the level by first computing the minimizer's rank $r = rank_R(min_m(q))$ taking $T_{rank_R}$ time. This rank is then used in the select queries $first = sel_S(r)$ and $last = sel_S(r+1) - 1$ which tell the indices in Offsets $O$ where the minimizer's first and last offset in the text $T$ are stored. These two queries take $2T_{sel_S}$ time.
Finally the presence of $q$ in $T$ is checked at every minimizer offset in the interval $O[first : last]$ until $q$ is either found or the end of the interval is reached. The average frequency $\mathbf{f_{avg}}$ of *infrequent* minimizers is exactly the average length of this interval. In the lookup case, the comparison is terminated as soon as $q$ is found for the first time, which is on average the case after $(\mathbf{f_{avg}} + 1)/2$ comparisons (+1 is necessary because the first index always has to be checked) with each comparison taking $T_{comp_T}$ time.
The following constraint models the complete time $T_{level}$ needed to search for a k-mers presence on the level:

$$T_{level} = T_{rank_R} + 2T_{sel_S} + (\mathbf{f_{avg}} + 1)/2 \cdot (T_{acc_O} + T_{comp_T}) \tag{4.18}$$

Without further constraints, solving the described MINLP for minimal $T_{lookup_{RSHash}}$ results in a solution where the $\mu_m$, $\tau_t$ corresponding to the smallest $m \in \mathcal{M}$, $t \in \mathcal{T}$ will be set to one.
This is expected, as this leads to the smallest possible $\mathbf{F}_K$ which minimizes the k-mers having to be looked up in the text and maximizes the lookups in the (faster) hash table. This however results in maximal space consumption, as each entry in the hash table is significantly larger than an entry in $O$ as described in Section 2.2.
In order to account for that, we have to add constraints modeling the space consumption.

### 4.2.2 Space Consumption

Instead of modeling the total space used by RSHash we will focus on the bits per k-mer (bpk) used by the data structure as this metric allows to compare compression

independent of the sequence length.
The space consumption of RSHash can be decomposed into the space needed for the data structures components: the text $T$, the vectors $R$, $S$ and $O$ as well as the hash table $H$. We use one variable to describe the bits per k-mer needed by each of the components:

$$bpk_T \in \mathbb{R}_0^+ \tag{4.19}$$
$$bpk_R \in \mathbb{R}_0^+ \tag{4.20}$$
$$bpk_S \in \mathbb{R}_0^+ \tag{4.21}$$
$$bpk_O \in \mathbb{R}_0^+ \tag{4.22}$$
$$bpk_H \in \mathbb{R}_0^+ \tag{4.23}$$

**The text** $T$ is much longer than k. Because of this the bits per k-mer for storing the text $T$ can be set to a constant of 2 bits needed to store one base:

$$bpk_T = 2 \tag{4.24}$$

larger for unitigs!

**Bit vector** $R$ is a bit vector of length $4^{\mathbf{m}}$ in which each bit set to 1 marks the occurrence of one distinct *infrequent* minimizer in the sequences. We can compute the number $n_{DIM}$ of distinct *infrequent* minimizers by multiplying the percentage of *infrequent* minimizers with the total number of minimizers devided through the average frequency of each minimizer:

$$n_{DIM} \in \mathbb{R}_0^+ \tag{4.25}$$
$$n_{DIM} = \frac{\mathbf{F}_K \cdot n_{kmers}}{\mathbf{f_{avg}}} \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR} \tag{4.26}$$
$$= \frac{\mathbf{F}_M \cdot n_{minimizers}}{\mathbf{f_{avg}}} \tag{4.27}$$

decide what to use

add $n_{kmers}$ (only total?) and $n_{minimizers}$ (for every level in depence of level parameters) to the Model

figure out how to model the ratio between k-mers and minimizers for fractured input sequences OR use $n_{minimizers}$?

Using Elias-Fano-Encoding, a bit vector of size $U$ with $n$ bits set to one can be compressed to $n\lceil log_2(U/n)\rceil + 3n$ [OS07] . Compressing $R$ and dividing this by the total number $n_{kmers}$ of k-mers yields the constraint describing the bits per k-mer of $R$:

$$bpk_R = \frac{1}{n_{kmers}} \cdot \left( n_{DIM} \lceil log_2 \frac{4^{\mathbf{m}}}{n_{DIM}} \rceil + 3 n_{DIM} \right)$$
$$\Rightarrow bpk_R = \frac{n_{DIM}}{n_{kmers}} \cdot (\lceil 2\mathbf{m} - log_2 n_{DIM} \rceil + 3) \tag{4.28}$$

woher kommt diese formel, kann sie so im paper nicht finden

make $n_{kmers}$ part of model - either

argue in experiments section, that $n_{kmers}$ has only a small effect on the size of $R$ and can thus be disregarded as it is not needed for anything else

**Bit vector** $S$ has length $|O| + 1 \approx |O|$ where every bit corresponds to the offset of one minimizer encountered in the sequences and one extra bit marks the end of all offsets - this last bit can however be disregarded when modeling $bpk_S$ as its effect is insignificantly small.
Since $\mathbf{F}_K$ describes the percentage of k-mers with *infrequent* minimizers and every minimizer covers an average of $(k - \mathbf{m} + 2)/2$ consecutive k-mers, we can model the bits per k-mer in $S$ through:

$$bpk_S = \mathbf{F}_K \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR} \tag{4.29}$$

$$= \frac{\mathbf{F}_M * n_{minimizers}}{n_{kmers}} \tag{4.30}$$

figure out how to model the ratio between k-mers and minimizers for fractured input sequences OR use $n_{minimizers}$?

**The offset vector** $O$ contains one entry of size $log_2|T|$ for the offset of each *infrequent* minimizer.
Since $bpk_S$ already describes the number of offsets per k-mer, we can model the bits per k-mer in $O$ with:

$$bpk_O = bpk_S \cdot log_2|T| \tag{4.31}$$

**The hash set** $H$ contains an entry $(key : q)$ for each distinct k-mer $q$ with an infrequent minimizer, which are $1 - \mathbf{F}_K$ of all k-mers in $T$. Each entry has size $size(key) = 64$ bit. We introduce the load factor $\alpha$ to the model, in order to account for empty buckets in the hash table. The bits per k-mer required for the hash table can thus be modeled by:

$$bpk_H = (1 - \mathbf{F}_K) \cdot \frac{64}{\alpha} \tag{4.32}$$

überall hash table durch hash set ersetzten

in the used gtl::flat_hash_set there is one byte of metadata for each entry. because of this, it should be $bpk_H = (1 - \mathbf{F}_K) \cdot \frac{64+8}{\alpha}$ - should I add this here or in experiments?

This only models correctly for the unitigs. Figure out how to take into account that k-mers can appear many times in the Input but will only be added once to the hashtable

Locate benötigt eine Liste mit allen offsets: $bpk_H = (1 - \mathbf{F}_K) \cdot \frac{(64+(log_2|T| \cdot frequency))}{\alpha}$

reminder to include somewhere that we set $\alpha = 0.75$ in practice and explain why that is a reasonable value

**The total bits per k-mer** $bpk_{total} \in \mathbb{R}_0^+$ can be modeled by simply adding up the space requirements of each component:

$$bpk_{total} \in \mathbb{R}_0^+ \tag{4.33}$$

$$bpk_{total} = bpk_T + bpk_R + bpk_S + bpk_O + bpk_H \tag{4.34}$$

### 4.2.3 Optimization Goal

Having defined all constraints regarding the lookup time and space consumption of RSHash, we can now construct a MINLP in order to find optimal level parameters.
We introduce three more external parameters to the model: The optimization goal $OptGoal$ which specifies whether to minimize $T_{lookup_{RSHash}}$ or $bpk_{total}$ and upper bounds $Bound_{time}, Bound_{bpk}$ for the lookup time and space consumption.

$$\begin{aligned} OptGoal &\in \{T_{lookup_{RSHash}}, bpk_{total}\} \\ Bound_{time} &\in \mathbb{R}_0^+ \\ Bound_{bpk} &\in \mathbb{R}_0^+ \end{aligned}$$

When using the MINLP, the upper bound belonging to the optimization goal should be set to $\infty$. In addition to the already defined ones, the following two constraints are added to the MINLP to enforce these bounds:

$$T_{lookup_{RSHash}} \leq Bound_{time} \tag{4.35}$$
$$bpk_{total} \leq Bound_{bpk} \tag{4.36}$$

One could for example search for level parameters minimizing the lookup time whilst not exceeding eight bits per k-mer by setting $OptGoal \leftarrow T_{lookup_{RSHash}}, Bound_{time} \leftarrow \infty, Bound_{bpk} \leftarrow 8$. The constructed MINLP for this example is:

$$\begin{aligned} INPUT : & OptGoal = T_{lookup_{RSHash}}, Bound_{time} = \infty, Bound_{bpk} = 8, \\ & \mathcal{L} = \{1\}, \mathcal{M}, \mathcal{T}, \\ & F_K, f_{avg}(p)\ \forall p \in \mathcal{M} \times \mathcal{T}, \\ & T_{acc_R}, T_{rank_R}, T_{sel_S}, T_{acc_O}, T_{comp_T}, T_{check_H} \end{aligned}$$

MINIMIZE

$$OptGoal = T_{lookup_{RSHash}}$$

SUBJECT TO

$$\sum_{m \in \mathcal{M}} \mu_m = 1 \qquad \textit{Equation (4.3)}$$

$$\sum_{t \in \mathcal{T}} \tau_t = 1 \qquad \textit{Equation (4.4)}$$

$$\mathbf{m} = \sum_{m \in \mathcal{M}} \mu_m \cdot m \qquad \textit{Equation (4.7)}$$

$$\mathbf{t} = \sum_{t \in \mathcal{T}} \tau_t \cdot t \qquad \textit{Equation (4.8)}$$

$$n_{minimizers} = \mathbf{???}$$

$$n_{kmers} = \mathbf{???}$$

$$\mathbf{F}_M = \sum_{m \in \mathcal{M}} \mu_m \cdot \sum_{t \in \mathcal{T}} \tau_t \cdot F_{M_{(m,t)}}(t) \qquad \textit{Equation (4.10)}$$

$$\mathbf{F}_K = \sum_{m \in \mathcal{M}} \mu_m \cdot \sum_{t \in \mathcal{T}} \tau_t \cdot F_{K_{(m,t)}}(t) \qquad \textit{Equation (4.13)}$$

$$\mathbf{f_{avg}} = \sum_{m \in \mathcal{M}} \mu_m \cdot \sum_{t \in \mathcal{T}} \tau_t \cdot f_{avg}((m,t)) \qquad \textit{Equation (4.14)}$$

$$T_{level} = T_{rank_R} + 2T_{sel_S} + (\mathbf{f_{avg}} + 1)/2 \cdot (T_{acc_O} + T_{comp_T}) \qquad \textit{Equation (4.18)}$$

$$T_{lookup_{RSHash}} = T_{acc_R} + \mathbf{F}_K \cdot T_{level} + (1 - \mathbf{F}_K) \cdot T_{check_H} \qquad \textit{Equation (4.17)}$$

$$T_{lookup_{RSHash}} \leq Bound_{time} = \infty \qquad \textit{Equation (4.35)}$$

$$bpk_T = 2 \qquad \textit{Equation (4.24)}$$

$$n_{DIM} = \frac{\mathbf{F}_K \cdot n_{kmers}}{\mathbf{f_{avg}}} \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR}$$

$$= \frac{\mathbf{F}_M \cdot n_{minimizers}}{\mathbf{f_{avg}}} \qquad \textit{Equation (4.27)}$$

$$bpk_R = \frac{n_{DIM}}{n_{kmers}} \cdot (\lceil 2\mathbf{m} - log_2 n_{DIM} \rceil + 3) \qquad \textit{Equation (4.28)}$$

$$bpk_S = \mathbf{F}_K \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR}$$

$$= \frac{\mathbf{F}_M * n_{minimizers}}{n_{kmers}} \qquad \textit{Equation (4.30)}$$

$$bpk_O = bpk_S \cdot log_2 |T| \qquad \textit{Equation (4.31)}$$

$$bpk_H = (1 - \mathbf{F}_K) \cdot \frac{64}{\alpha} \qquad \textit{Equation (4.32)}$$

$$bpk_{total} = bpk_T + bpk_R + bpk_S + bpk_O + bpk_H \qquad \textit{Equation (4.34)}$$

$$bpk_{total} \leq Bound_{bpk} = 8 \qquad \textit{Equation (4.36)}$$

VARIABLES

| | |
|---|---|
| $\mu_m \in \{0,1\} \mid \forall m \in M$ | *Equation* (4.1) |
| $\tau_t \in \{0,1\} \mid \forall t \in T$ | *Equation* (4.2) |
| $\mathbf{m} \in \mathcal{M}$ | *Equation* (4.5) |
| $\mathbf{t} \in \mathcal{T}$ | *Equation* (4.6) |
| $n_{minimizers} \in$ ??? | |
| $n_{kmers} \in$ ??? | |
| $\mathbf{F}_M \in [0,1]$ | *Equation* (4.9) |
| $\mathbf{F}_K \in [0,1]$ | *Equation* (4.11) |
| $\mathbf{f_{avg}} \in \mathbb{R}_0^+$ | *Equation* (4.12) |
| $T_{level} \in \mathbb{R}_0^+$ | *Equation* (4.15) |
| $T_{lookup_{RSHash}} \in \mathbb{R}_0^+$ | *Equation* (4.16) |
| $bpk_T \in \mathbb{R}_0^+$ | *Equation* (4.19) |
| $bpk_R \in \mathbb{R}_0^+$ | *Equation* (4.20) |
| $bpk_S \in \mathbb{R}_0^+$ | *Equation* (4.21) |
| $bpk_O \in \mathbb{R}_0^+$ | *Equation* (4.22) |
| $bpk_H \in \mathbb{R}_0^+$ | *Equation* (4.23) |
| $n_{DIM} \in \mathbb{R}_0^+$ | *Equation* (4.25) |
| $bpk_{total} \in \mathbb{R}_0^+$ | *Equation* (4.33) |

## 4.3 Model for Several Levels

In the following, we adapt the constraints defined for using only one level in Section 4.2 to model the use of $L \in \mathbb{N}^+$ levels with $\mathcal{L} = \{l \in \mathbb{N}^+ \mid l \leq L\}$ being the set of levels used[1].

When modeling several levels, we add a superscript $l$ to variables in order to indicate there belonging to a level $l \in \mathcal{L}$ e.g. $\mathbf{m}^1, \mathbf{m}^2$ and $\mathbf{m}^3$ denote the optimal minimizer lengths on level $1, 2$ and $3$.

We still assume, that the times $T_{acc_{R^l}}, T_{rank_{R^l}}, T_{sel_{S^l}}, T_{acc_{O^l}}, T_{comp_T}, T_{check_H}$ are (practically) independent of the parameters $\mathbf{m}^l, \mathbf{t}^l$ and the level $l$.

reason in chap: experiments

Unique sets of binary indicator variables $\mu_m^l$ and $\tau^l$ are needed for the level parameters $\mathbf{m}^l$ and $\mathbf{t}^l$ of each level $l$. The constraints regarding these variables are analog to those

[1] We model the space consumption and lookup time for any positive natural number of levels even though RSHash currently only supports the use of one, two or three levels [SMR26].

when using only one level:

$$
\begin{aligned}
\mu_m^l &\in \{0,1\} && \mid \forall (l,m) \in (\mathcal{L} \times \mathcal{M}) \\
\tau_t^l &\in \{0,1\} && \mid \forall (l,t) \in (\mathcal{L} \times \mathcal{T}) \\
\sum_{m \in \mathcal{M}} \mu_m^l &= 1 && \mid \forall l \in \mathcal{L} \\
\sum_{t \in \mathcal{T}} \tau_t^l &= 1 && \mid \forall l \in \mathcal{L} \\
\mathbf{m}^l &\in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
\mathbf{t}^l &\in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
\mathbf{m}^l &= \sum_{m \in \mathcal{M}} \mu_m^l \cdot m^l && \mid \forall l \in \mathcal{L} \\
\mathbf{t}^l &= \sum_{t \in \mathcal{T}} \tau_t^l \cdot t^l && \mid \forall l \in \mathcal{L}
\end{aligned}
$$

For each level $l$ we can model $\mathbf{F}_M^l$, $\mathbf{F}_K^l$ and $\mathbf{f}_{\mathbf{avg}}^l$ analogously to using a single level, only summing over every possible combination of level parameters $p^l$ for each level up to and including $l$ instead of just those for one level:

$$
\begin{aligned}
&\mathbf{F}_M^l \in [0,1] && \mid \forall l \in \mathcal{L} \\
&\mathbf{F}_K^l \in [0,1] && \mid \forall l \in \mathcal{L} \\
&\mathbf{f}_{\mathbf{avg}}^l \in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
&\mathbf{F}_M^l = \sum_{p^l \in \mathcal{M}^l \times \mathcal{T}^l} F_{M_{p^l}}(t^l) \cdot \prod_{1 \le i \le l} \mu^i_{p^l[m^i]} \tau^i_{p^l[t^i]} && \mid \forall l \in \mathcal{L} \\
&\mathbf{F}_K^l = \sum_{p^l \in \mathcal{M}^l \times \mathcal{T}^l} F_{K_{p^l}}(t^l) \cdot \prod_{1 \le i \le l} \mu^i_{p^l[m^i]} \tau^i_{p^l[t^i]} && \mid \forall l \in \mathcal{L} \\
&\mathbf{f}_{\mathbf{avg}}^l = \sum_{p^l \in \mathcal{M}^l \times \mathcal{T}^l} f_{avg}(p^l) \cdot \prod_{1 \le i \le l} \mu^i_{p^l[m^i]} \tau^i_{p^l[t^i]} && \mid \forall l \in \mathcal{L}
\end{aligned}
$$

$\prod_{1 \le i \le l} \mu^i_{p^l[m^i]} \tau^i_{p^l[t^i]}$ besser formulieren oder notation $p^l[t^i]$ vorher einführen und dann den Ausdruck hier nochmal explizit erklären

### 4.3.1 Lookup Time

The search time on a level $l \in \mathcal{L}$ can be leveled analogously to that on one level:

$$
\begin{aligned}
&T_{level}^l \in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
&T_{level}^l = T_{rank_R} + 2T_{sel_S} + \frac{\mathbf{f}_{\mathbf{avg}}^l + 1}{2} \cdot (T_{acc_O} + T_{comp_T}) && \mid \forall l \in \mathcal{L}
\end{aligned}
$$

For $\mathbf{F}_K^l$ of the k-mers on a level $l \in \mathcal{L}$ the lookup is completed by a search through the offsets on that level whilst the remaining $(1 - \mathbf{F}_K^l)$ of queries result in a lookup on the next level.

We can thus model the lookup time recursively:

$$T^l_{lookup_{RSHash}} = \begin{cases} T_{acc_{R^l}} + \mathbf{F}^l_K \cdot T^l_{level} \\ \qquad + (1 - \mathbf{F}^l_K) \cdot T^{l+1}_{lookup_{RSHash}} & \mid l \in \mathcal{L} \\ T_{check_H} & \mid l \notin \mathcal{L} \end{cases}$$

Considering the set $\mathcal{L} = \{1, 2\}$ of two levels as an example, this results in the following total lookup time:

$$\begin{aligned} T^1_{lookup_{RSHash}} = T_{acc_{R^1}} &+ \mathbf{F}^1_K \cdot T^1_{level} \\ &+ (1 - \mathbf{F}^1_K) \cdot \Big( T_{acc_{R^2}} + \mathbf{F}^2_K \cdot T^2_{level} \\ &\qquad + (1 - \mathbf{F}^2_K) \cdot T_{check_H} \Big) \end{aligned}$$

Inserting $T^1_{level}$ and $T^2_{level}$ yields:

$$\begin{aligned} T^1_{lookup_{RSHash}} = T_{acc_R} &+ \mathbf{F}^1_K \cdot (T_{rank_R} + 2T_{sel_S} + \frac{\mathbf{f}^1_{\mathbf{avg}} + 1}{2} \cdot (T_{acc_O} + T_{comp_T})) \\ &+ (1 - \mathbf{F}^1_K) \cdot \Bigg( T_{acc_R} + \mathbf{F}^2_K \cdot (T_{rank_R} + 2T_{sel_S} + \frac{\mathbf{f}^2_{\mathbf{avg}} + 1}{2} \cdot (T_{acc_O} + T_{comp_T})) \\ &\qquad + (1 - \mathbf{F}^2_K) \cdot T_{check_H} \Bigg) \end{aligned}$$

insertion weglassen?

### 4.3.2 Space Consumption

**The text** $T$ is only being stored once, so the constant approximation $bpk_T \approx 2$ still holds.

**Bit vector** $R^l$ $n^l_{DIM}$ on each level $l$ and are modeled analogously to using only one level:

$$\begin{aligned} n_{DIM} &\in \mathbb{R}^+_0 && \mid \forall l \in \mathcal{L} \\ bpk_{R^l} &\in \mathbb{R}^+_0 && \mid \forall l \in \mathcal{L} \\ n_{DIM} &= \frac{\mathbf{F}^l_K \cdot n^l_{kmers}}{\mathbf{f}^l_{\mathbf{avg}}} \cdot \frac{2}{k - \mathbf{m}^l + 2} \mathbf{OR} \\ &= \frac{\mathbf{F}^l_M \cdot n^l_{minimizers}}{\mathbf{f}^l_{\mathbf{avg}}} && \mid \forall l \in \mathcal{L} \\ bpk^l_R &= \frac{n^l_{DIM}}{n_{kmers}} \cdot \left( \lceil 2\mathbf{m}^l - log_2 n^l_{DIM} \rceil + 3 \right) && \mid \forall l \in \mathcal{L} \end{aligned}$$

**Bit vector** $S^l$ on each level $l$ has length $|O^l| + 1 \approx |O^l|$. Only k-mers that have frequent minimizers on all previous levels but an *infrequent* minimizer on level $l$ lead to an offset in $O^l$ and thus to a bit in $S^l$:

$$bpk_{S^l} \in \mathbb{R}_0^+ \qquad | \; \forall l \in \mathcal{L}$$

$$bpk_{S^l} = \left( \prod_{i=1}^{l-1} 1 - \mathbf{F}_K^i \right) \cdot \mathbf{F}_K^l \cdot \frac{2}{(k - \mathbf{m}^l + 2)} \qquad | \; \forall l \in \mathcal{L}$$

**OR** analogously to on level

$$bpk_S^l = \frac{\mathbf{F}_M^l * n_{minimizers}^l}{n_{kmers}} \qquad | \; \forall l \in \mathcal{L}$$

adapt to whatever stays on one model

For levels $l > 1$ the input consist of the super-k-mers with frequent minimizers on the previous level. Because those fragments are fairly short (sometimes close to k bases), every minimizer NO LONGER covers an average of $(k - \mathbf{m} + 2)/2$ consecutive k-mers - Find a way to account for that and describe this observation somewhere! When optimizing for the unitigs, this is the case for every level including ther first.

**The offset vector** $O^l$ for every level $l$ is modeled analogously to using only one level:

$$bpk_{O^l} \in \mathbb{R}_0^+ \qquad | \; \forall l \in \mathcal{L}$$

$$bpk_{O^l} = bpk_{S^l} \cdot log_2|T| \qquad | \; \forall l \in \mathcal{L}$$

**The hash table** $H$ only contains an entry for k-mers $q$, which have frequent minimizers on all levels. The bits per k-mer for the hash table can thus be modeled as

$$bpk_H = \left( \prod_{l=1}^{L} 1 - \mathbf{F}_K^l \right) \cdot \frac{64}{\alpha}$$

**The total bits per k-mer** for $L$ levels only differ to those on one level, as there are now a vector $R, S$ and $O$ on each level:

$$bpk_{total} = bpk_T + \sum_{l=1}^{L} (bpk_{R^l} + bpk_{S^l} + bpk_{O^l}) + bpk_H$$

## 4.4 Locate

outline differences to lookup

- lookup time: check every offset instead of only an average of half of the offsets
- hashtable instead of hash set - contains one entry (key:k-mer, value:offset) for each appearance of every k-mer (no longer distinct) - for the unitigs, this shouldn't have an effect

# 5 Experiments

## 5.1 Solving the MINLP

In order to evaluate the accuracy of the proposed MINLP in Chapter 4, we first show how to compute the model input for a given set of sequences $S_p$ For a given sequence, we can compute the minimizer distributions $p_{M_{p^l}}$ and $p_{K_{p^l}}$ asoutlined in Chapter 3 and use a MINLP solver like SCIP [Ach+08; Ach09; Bes+23] to solve the MINLP defined in Chapter 4 and find those level parameters leading to the optimization goal:

## 5.2 Limitations

The MINLP approach for finding optimal level parameters has the advantage of finding the optimal level parameters for the specified optimization goal.

This approaches plausibility however, is heavily dependent on the time needed to compute the model input. Especially the runtime for the computation of the distributions $p_{M_{p^l}}$ and $p_{K_{p^l}}$ for every combination of the level parameters $p^l$ on every level $l$ grows exponentially with the number of levels when done in a trivial .

AHHHHH - Achtung das böse Wort!!!

We further outline this in Chapter 5.

For this reason, an approach yielding only an approximation of the optimal level parameters but taking less time to do so could be of interest.

We will further explore methods Chapter 6 the genome in order to reduce the computation of minimizer distribution.

TODO

In another approach we will try to approximate the distributions on higher levels based on that on the first level in order to get arround the exponential cost of computing those values.

TODO

# 6 Subsampling

## 6.1 Motivation

The time for processing a genome in order to find the minimizer distribution $\mathbf{F}_K(p^l)$ for possible minimizer lengths $m \in \mathcal{M}$ and thresholds $t \in \mathcal{T}$ is directly proportional to the size of the genome.
For large genomes, this processing can become the dominating factor when searching for optimal parameters using the Chapter 4 approach. In order to speed up the search for the empirical values, we introduce a subsampling method.

## 6.2 Subsampling Method

Instead of calculating the distribution over the full genome, we sample $n$ sequences of length $l \geq k$ at random positions in the genome.

how to handle overlapping samples

müsste die gezählte frequenz der minimizer mit eine Faktor mutipliziert werden, um auf die länge des ursprünglichen textes zu skalieren?? schließlich kommen minimizer ja in einem kürzeren text perse seltener vor als in einem längeren

## 6.3 Time Complexity of Finding the Minimizer Distributions

genaue zeitliche abhängigkeit 1. verstehen und 2. aufschreiben

## 6.4 Time Complexity using Subsampling

By applying the proposed subsampling strategy, the original genome $T$ of length $|T|$ is reduced to the subsampled text $T^S$ of length $|T^S| = n \cdot l$. This means a reduction in size by a factor of $\frac{|T|}{|T^S|}$.
Depending on the choice of $n$ and $l$ this results in a speedup of the processing time by a factor of or even a constant processing time when both parameters are chosen as a constand regardless of $|T|$ (this however should result in a growing error for larger genomes).

assuming no overlaps

factor

time

## 6.5 Error Analysis

## 6.6 Choosing $l$

The length $l$ has to be at least $k$.

wenn $l > k$ ist, überlappen sich mehrere kmere an den gesampleten stellen.
Frage: ich verstehe noch nicht, warum genau dass von vorteil ist.
Antwort: Weil roling hash - l ca 1000, dann quasi linear

## 6.7 Choosing $n$

Choosing a constant $n$ would result in a processing time that would no longer be dependent of the genomes length $|T|$, as the sampled text would have constant size $n \cdot l$. For large genomes, the percentage $\frac{|T^S|}{|T|}$ of the genome represented in the subsample can become arbitrarily small, resulting in growing error.
If instead $n$ is chosen relative to $|T|$, $\frac{|T^S|}{|T|}$ will have a constant value independent of the genomes size. Even though this means, that the time needed, in order to find the minimizer distributions would still be proportional to the genomes size, this should be the preferred option as it results in a bounded error of the approximation.
For a large enough $n$, the probability of choosing a bad representation becomes highly unlikely.

assuming no overlaps

zu vage, begründen

# Bibliography


[Ach+08] T. Achterberg, T. Berthold, T. Koch, and K. Wolter. *Constraint Integer Programming: a New Approach to Integrate CP and MIP*. eng. Tech. rep. 08-01. Takustr. 7, 14195 Berlin: ZIB, 2008 (cit. on p. 22).

[Ach09] T. Achterberg. "SCIP: solving constraint integer programs". In: *Mathematical Programming Computation* 1.1 (2009), pp. 1–41. URL: https://doi.org/10.1007/s12532-008-0001-1 (cit. on p. 22).

[Bes+23] K. Bestuzheva, A. Chmiela, B. MÃ¼ller, F. Serrano, S. Vigerske, and F. Wegscheider. *Global Optimization of Mixed-Integer Nonlinear Programs with SCIP 8*. Tech. rep. 2301.00587. arXiv, 2023 (cit. on p. 22).

[Chi+14] R. Chikhi, A. Limasset, S. Jackman, J. Simpson, and P. Medvedev. *On the representation of de Bruijn graphs*. en. arXiv:1401.5383 [q-bio.QM]. Oct. 2014. URL: http://arxiv.org/abs/1401.5383 (visited on 09/18/2026) (cit. on p. 8).

[Jai+20] C. Jain, A. Rhie, H. Zhang, C. Chu, B. P. Walenz, S. Koren, and A. M. Phillippy. "Weighted minimizer sampling improves long read mapping". en. In: *Bioinformatics* 36.Supplement_1 (July 2020), pp. i111–i118. URL: https://academic.oup.com/bioinformatics/article/36/Supplement_1/i111/5870473 (visited on 09/18/2026) (cit. on p. 8).

[OS07] D. Okanohara and K. Sadakane. "Practical entropy-compressed rank/select dictionary". In: *2007 Proceedings of the ninth workshop on algorithm engineering and experiments (ALENEX)*. SIAM. 2007, pp. 60–70 (cit. on p. 14).

[Pib22] G. E. Pibiri. "Sparse and skew hashing of K-mers". en. In: *Bioinformatics* 38.Supplement_1 (June 2022), pp. i185–i194. URL: https://academic.oup.com/bioinformatics/article/38/Supplement_1/i185/6617506 (visited on 07/06/2026) (cit. on p. 8).

[SMR26] J. Schulte-Mattler and K. Reinert. "RSHash: a fast and space-efficient hash table for $k$ -mers". en. In: *Bioinformatics* 42.Supplement_2 (Aug. 2026), btag440. URL: https://academic.oup.com/bioinformatics/article/doi/10.1093/bioinformatics/btag440/8767308 (visited on 09/15/2026) (cit. on pp. 6, 8, 9, 13, 18).

[ZKM20] H. Zheng, C. Kingsford, and G. Marçais. "Improved design and analysis of practical minimizers". en. In: *Bioinformatics* 36.Supplement_1 (July 2020), pp. i119–i127. URL: https://academic.oup.com/bioinformatics/article/36/Supplement_1/i119/5870484 (visited on 07/06/2026) (cit. on p. 6).