**Technische Universität Berlin**
Faculty IV: Electrical Engineering and Computer Science
**Freie Universität Berlin**
Department of Mathematics and Computer Science
Algorithmic Bioinformatics

welche uni angeben, welche reihenfolge..?

# Automatic Optimization of Level Parameters for RSHash

**(RSHash is a minimizer based fast, compressed hash table for storing DNA k-mers. It was recently introduced by the Reinert Group.)**

**Bjarne David Jehn**

Thesis submitted in fulfillment of the requirements for the degree "Bachelor of Science"(B. Sc.) in the field of Computer Science

| | |
|---|---|
| First Reviewer: | Prof. Dr. Knut Reinert |
| Second Reviewer: | Prof. Dr. Stephan Kreutzer |
| Supervisor: | Jonas Schulte-Mattler |

# Declaration of Authorship

I hereby declare that the thesis submitted is my own, unaided work, completed without any external help. Only the sources and resources listed were used. All passages taken from the sources and aids used, either unchanged or paraphrased, have been marked as such.

Where generative AI tools were used, I have indicated the product name, manufacturer, the software version used, as well as the respective purpose (e.g. checking and improving language in the texts, systematic research). I am fully responsible for the selection, adoption, and all results of the AI-generated output I use.

I have taken note of the Principles for Ensuring Good Research Practice at TU Berlin dated 15 February 2023. https://www.static.tu.berlin/fileadmin/www/10002457/K3-AMBl/Amtsblatt_2023/Amtliches_Mitteilungsblatt_Nr._16_vom_30.05.2023.pdf

I further declare that I have not submitted the thesis in the same or similar form to any other examination authority.

Berlin, _____ _____

Date Signature

## Abstract

in English

## Zusammenfassung

auf Deutsch

# Contents


**1 Introduction** **6**
- 1.1 RSHash Explanation . . . 8
- 1.2 The Problem of Choosing "Good" Level Parameters . . . 9

**2 Notation** **11**

**3 Sequence Statistics** **12**
- 3.1 Minimizer Distribution . . . 12
- 3.2 Average Frequencies . . . 14
- 3.3 Times for Operations on Data Structures . . . 14

**4 MINLP Modeling** **16**
- 4.1 Model Input . . . 16
- 4.2 Model for One Level . . . 16
  - 4.2.1 Lookup Time . . . 17
  - 4.2.2 Space Consumption . . . 19
  - 4.2.3 Optimization Goal . . . 21
- 4.3 Model for Several Levels . . . 24
  - 4.3.1 Lookup Time . . . 25
  - 4.3.2 Space Consumption . . . 26
- 4.4 Locate . . . 27

**5 Experiments** **28**
- 5.1 Datasets . . . 28
- 5.2 Computing the Model Input . . . 28
- 5.3 Model Accuracy . . . 30
  - 5.3.1 Lookup Time . . . 30
  - 5.3.2 Space Consumption . . . 30
- 5.4 Limitations . . . 30

**6 Outlook** **31**

**7 Subsampling** **32**
- 7.1 Motivation . . . 32
- 7.2 Subsampling Method . . . 32
- 7.3 Time Complexity of Finding the Minimizer Distributions . . . 32
- 7.4 Time Complexity using Subsampling . . . 32
- 7.5 Error Analysis . . . 33

7.6 Choosing $l$ . . . . . 33
7.7 Choosing $n$ . . . . . 33

**Bibliography** **34**

# 1 Introduction

**Genetic Sequences**
Genetic strands are chains of the nucleobases adenine (A), cytosine (C), guanine (G), thymine (T), and uracil (U). Adenine, cytosine and guanine are present in both DNA and RNA whilst thymine only appears in DNA and uracil is specific to RNA. A genetic sequence can thus be represented as a string over an alphabet of length four meaning a compact representation of two bits needed to store each base. Despite of this, genetic databases are often very large as sequences often consist of several billion bases e.g. approximately $3.1 \cdot 10^9$ bases for the human genomes sequences.

**K-mers**
The growth of available data due to better sequencing techniques has led to the need for efficient algorithms for processing genetic sequences. Many approaches are based on so called k-mers. The k-mers of a sequence are all its substrings of length $k$, meaning that a sequence $S$ with $|S| \geq k$ contains exactly $|S| - k + 1$ k-mers. The sequence $CGACAT$ for example consists of the 3-mers $CGA, GAC, ACA, CAT$. Uses for k-mers include k-mer counting, frequency analysis, sequence indexing, genome assembly, sequence comparison, taxonomic classification, phylogeny reconstruction, protein sequence searching and alignment as well the construction of k-mer databases [Moe+24].

**Lookup and Locate Queries**
One important task is the comparison of sequences against large genomic reference datasets by checking whether each k-mer in sequence of interest is present in the reference dataset, this is referred to as a lookup of the queried k-mers. A so called locate query on the other hand not only answers whether queried k-mers are present but also returns all positions of the queried k-mers in the sequences, also referred to as their offsets.

**Space/Time Trade-Off**
Designing a data structure to answer lookup or locate queries comes with an inherent trade of between the time needed for a lookup and the space consumption of the data structure. This can be demonstrated by considering the two extremes for data structures enabling a lookup or locate of a queried k-mer $q$ in a sequence $S$ with $|S| \gg k$ that doesn't contain any duplicate k-mers:
The most space efficient representation of all k-mers in $S$ is the sequence itself needing approximately two bits per k-mer (bpk). A locate query for $q$ would require scanning through the whole sequence and comparing every k-mer with $q$ and returning a list of all the offsets at which $q$ was encountered. A lookup on the other hand could return as soon as a match is either found or the end of the sequence is reached. Essentially both queries would need $O(|S|)$ time.
A very fast lookup (and locate) on the other hand could be achieved by storing the appearance of every k-mer in $S$ in a hash set (locate: hash table) enabling both queries

in $O(1)$ time. For this approach every k-mer would have to be stored in the hash set (table) leading to a space consumption of $2k$ bits per k-mer in the lookup case and $2k + log_2(|S|)$ bits per k-mer to enable locate queries which require the offsets to be stored as well.
Since both a lookup time in $O(|S|)$ as well as $2k$ bits per k-mer are not viable for large genomes, there has been much work on data structures enabling queries in much less than $O(|S|)$ whilst also maintaining a certain compression.

**Minimizers**

A common approach to achieve this is the use of so called minimizers. A minimizer of length $m$ is the smallest m-mer of a k-mer regarding a total order over all strings of length $m$. Using the lexicographical order for example to determine the minimizer of length 2 in the 6-mer $CGACAT$ results in $AC$ because that is the lexicographically smallest 2-mer in $CGACAT$.

Minimizers have several properties which render them highly interesting for this domain. Firstly they are considered to be sparse because consecutive k-mers are very likely to share the same minimizer. Zheng, Kingsford, and Marçais [ZKM20] show that in a random string each minimizer of length $m$ is expected to cover an average of $(k - m + 2)/2$ k-mers. These consecutive k-mers sharing the same minimizer are also referred to as super-k-mers. Even in a sequence only containing unique k-mers, several super-k-mers can have the same minimizer as $m < k$.
A second interesting property is the skewness of the distribution of minimizers in regards to their *frequencies* which is the number of super-k-mers which have a specific minimizer. In a given sequence only a few minimizers have high frequencies whilst most have small frequencies or do not appear at all. Some intuition for this property can be gained by considering an m-mer consisting only of $A$s versus one of $T$s. Using the lexicographical order the first will be the minimizer of every super-k-mer in which it appears whilst the second would only become the minimizer of a super-k-mer containing only $T$s.
Both the sparsity and skewness of minimizers have been observed by several previous works [Chi+14; Jai+20; Pib22; SMR26].

**SSHash**

Pibiri [Pib22] for example describes the SSHash (Sparse and Skew hashing of K-mers) algorithm which exploits these two properties by computing all minimizers appearing in a sequence and then use a minimal perfect hash function to store every super-k-mers offsets in an array *Offsets* in the order induced by their minimizers hashes. They use a second array *Sizes* in which the $n$th element stores the starting index in *Offsets* for the offsets belonging to the $n$th minimizer. The sparsity of minimizers mainly effects the data structures space consumption: By indexing super-k-mers, they can compress the data structures size by a factor of $(k - m + 2)/2$ compared to indexing individual k-mers. The skewness of minimizers on the other hand is of importance to the locate time: Querying a k-mer $q$ requires computing its minimizer and then searching for it in every super-k-mer with the same minimizer. For a sufficiently large minimizer length, minimizers of high frequency become increasingly unlikely.
The both space consumption and locate time of SSHash are highly dependent of the

minimizer length $m$: A smaller $m$ means a higher compression $(k - m + 2)/2$. The lookup/locate time on the other hand is largest for small $m$ because those result in minimizers of higher *frequencies*. This demonstrates the challenge that comes with choosing an optimal minimizer length.

## 1.1 RSHash Explanation

der Fokuss sollte hier sein, zu erklären was es bedeutet frequente minimizer abzuschneiden, wie davon der platz in der hashtabelle abhängt und wie mehrere level dabei helfen können.
Wird das erfüllt?

RSHash is a minimizer based fast, compressed hash table for storing DNA k-mers that answers lookup and can be extended for supporting locate. It was recently introduced by Schulte-Mattler and Reinert [SMR26]. It follows a minimizer based approach like SSHash; however, instead of using minimal perfect hashing, RSHash relies on bitvectors supporting rank and select queries. Its main difference to previous methods is the introduction of a layered multi-minimizer scheme aiming to reduce the cost of high *frequencies* whilst at also maintaining large compression.
The data structure works with one, two or three so called levels and a hash table. In order to build RSHash to answer lookup (or locate) queries one has to specify the number of levels as well as a pair of level parameters for each level $l$: the minimizer length $m^l$ and a threshold $t^l$.

When using only one level, that level is build by first computing each k-mers minimizer of length $m^1$ using a hash function $h_1$ and counting the number of times each minimizer occurs in the sequences. We call minimizers that appear at least once but no more than the threshold $t^1$ to be *infrequent* on the level.
A bitvector $R^1$ of lengths $4^{m^1}$ is used to mark the appearance of each distinct *infrequent* minimizers. For this, the minimizers are interpreted as binary numbers of $2m^1$ bits and serve directly as indices to the vector. If for example the minimizers length were chosen to be $m^1 = 2$ and $AA$ was an *infrequent* minimizer in the sequences, then $R^1[AA] = R^1[0]$ would be set to one.
The offsets each *infrequent* minimizers occurrences in the sequences are stored in the offset vector $O^1$ in the order induced by $R^1$. Let $f$ for example be the frequency of the smallest *infrequent* minimizer, that is the number of occurrences of the smallest minimizer for which the bit in $R^1$ is set. Then $O^1[0 : n[$ contains the offsets of that minimizer whilst the next offsets $O^1[n : ...[$ belong to the second smallest minimizer and so forth.
The boundaries of each minimizers offsets in $O^1$ are marked in the bitvector $S^1$ of length $|O^1| + 1$. Following up on the example above, the first bit $S^1[0]$ would be set to one, indicating the start of the offsets belonging to the smallest minimizer, this would be followed by zeros until the $n$th bit $S^1[n] = 1$ indicating the start of the offsets belonging to the second smallest minimizer and so forth. The last bit in $S$ is also set to one marking the end of the largest minimizers offsets.

further explain the use of the hash function

If a second level is specified, only those super-k-mers with *frequent* minimizers on the first level are handled on the second level which is build almost identically to the first level, creating the vectors $R^2, O^2$ and $S^2$ but using the hash function $h_2$ for the computation of minimizers. The use of a different hash function for the computation leads to a skewed distribution of minimizers, in which most k-mers having *frequent* minimizers on the first level, have *infrequent* ones on the second. This holds even when the specified minimizer length $m^2$ and threshold $t^2$ are equal to those on the first.
A third level would be build analogously, if specified.

Only the offsets of k-mers that have *frequent* minimizers on all specified levels are then directly stored in a fast hash table sacrificing some space in return for a fast lookup which is viable as those k-mers are only a small fraction of the whole input sequence for a good choice of the level parameters.

## 1.2 The Problem of Choosing "Good" Level Parameters

We already noted that using a small $m << k$ thus leads to a relatively small number of super-k-mers meaning a better compression, because each minimizer is expected to be valid for an average of $(k - m + 2)/2$ k-mers [ZKM20]. However, as described, a small $m$ also means that minimizers will be more *frequent* which can lead to high query times when each occurrence of a queried k-mers minimizer has to be evaluated for an actual match with the k-mer itself. This trade off between space consumption and query times both dependent of the chosen parameters is an inherent problem of minimizer based k-mer indexing methods. Existing methods use a number of approaches to deal with this problem like Pibiri [Pib22] who choose a relatively large minimizer length, accepting a smaller compression in order to maintain reasonable locate times.

The leveled approach introduced in the RSHash algorithm on the other hand aims to achieve high compression by using relatively short minimizers on the lower levels whilst at the same time mitigating the burden of very *frequent* minimizers by using thresholds to cut them off and guaranty fast queries on every level. The use of distinct hash function to compute minimizers on each level leads to different skewed distributions of the minimizers on each level. Because only a small percentage of the k-mers are frequent for each distribution, the number of k-mers reduces drastically with each level and only a small percentage of the sequences k-mers end up being stored in the spatially expensive hash table.

The RSHash approach thus allow significantly faster queries opposed to SSHash whilst remaining similarly compact. However, this is highly dependent on the chosen minimizer lengths which influence the sparsity and skewness of minimizer distributions on each level and the chosen thresholds, which affect both the lookup (or locate) time on each level as well as the percentage of k-mers having to be stored in the hash table. For example, choosing very short minimizers and small thresholds on every level would result in a very large hash table as almost no minimizer would be *infrequent* .

Choosing "good" level parameters to build the data structure for a given set of sequences requires manual testing and extensive understanding of the RSHash algorithm.

We will attempt to expand the understanding of how exactly the level parameters influence the time and space consumption of RSHash and make the algorithm more accessible to use by automating the optimization of level parameters for a given genome and optimization goal.

# 2 Notation

A sequence is a string over the DNA alphabet $\Sigma = \{A, C, G, T\}$. A k-mer is a string of length $k$ over $\Sigma$. Let $i, j \in \mathbb{N}$ with $i < j$ be zero based indices of a string $S$ of length $|S| > j$. We use $S[i : j)$ to denote the substring from the $i$th to the $(j-1)$th character of $S$.
Let $q \in \Sigma^k$ be a k-mer. The computation of its minimizer $min^{h_l}_{m^l}(q)$ on level $l$ depends both on the specified minimizer length $m^l$ as well as the hash function on that level, which is not dependent of the level parameters but different for every level. We denote the minimizers frequency with $freq(min^{h_l}_{m^l}(q))$ which represents the number of occurrences of the minimizer in a given set of input sequences.
We call a minimizer *infrequent* on level $l$ only if $1 \leq freq(min^{h_l}_{m^l}(q)) \leq t^l$ holds i.e. the minimizer occurs at least once but no more than the given threshold. Minimizers with frequencies larger than the threshold are referred to as being *frequent* .
Let $L \in \mathbb{N}^+$ be the number of levels specified. We refer to the set of used levels $\mathcal{L} := \{l \in \mathbb{N}^+ \mid l \leq L\}$. We use $\mathcal{M} \subset [1, k] \cap \mathbb{N}$ and $\mathcal{T} \subset \mathbb{N}^+$ to denote the sets of minimizer lengths and thresholds considered. We denote the Cartesian $n$th power of a set $X$ with $X^n$ e.g. $X^3 = X \times X \times X$. A chosen minimizer length and threshold on a specified level $l \in \mathcal{L}$ are denoted $m^l$ and $t^l$. We use the tuple $p^l := (m^1, ..., m^l, t^1, ..., t^l) \in \mathcal{M}^l \times \mathcal{T}^l$ to denote the level parameters up to level $l$.
We write $S_{p^{l-1}} := \{S^l_1, S^l_2, ..., S^l_n\}$ to denote the set of sequences on level $l$ in dependence of the level parameters $p^{l-1}$ on the previous levels i.e. the k-mers which have *infrequent* minimizers on all previous levels. The full set of input sequences when building RSHash are denoted with $S_{p^0}$ and do not depend on any parameters.

# 3 Sequence Statistics

As outlined in the Chapter 1, the space consumption and query time of RSHash are highly dependent on the choice of level parameters as those influence the distributions of minimizers on all levels. We define aspects of the minimizer distribution which will be needed for modeling the space consumption and query time in Chapter 4. Specifically relevant for this is the behavior of minimizer distributions across several levels, which is unique to the approach proposed by Schulte-Mattler and Reinert [SMR26] and therefor not considered in previous works.

## 3.1 Minimizer Distribution

Recall that we use $p^l \in \mathcal{M}^l \times \mathcal{T}^l$ to describe the level parameters on all levels up to and including the level $l$, that $S_{p^{l-1}}$ is the the set of input sequences on level $l$ which depends on the level parameters $p^{l-1}$ on all previous and that $S_{p^0}$ is the full set of input sequences on the first level, which is independent of any parameters.

Let $\mathcal{K}_{p^{l-1}}$ be the set of distinct k-mers in a set of sequences $S_{p^{l-1}}$. In other words, the set of distinct k-mers on a level $l$ contains every distinct substring of length $k$ in the input sequences which are affected by the level parameters on previous levels:

$$\mathcal{K}_{p^{l-1}} := \{x \in \{0, 1, ..., 4^k\} \mid \exists S' \in S_{p^{l-1}} \; \exists (1 \leq i \leq |S'| - k) \; S'[i : i + k] = x\} \tag{3.1}$$

Let $\mathcal{M}_{p^{l-1},m^l}$ be the set of distinct minimizers of lengths $m^l$ on level $l$ of the k-mers in $\mathcal{K}_{p^{l-1}}$. The set of distinct minimizers is not only affected by the choice of level parameters on previous levels but also depends on the minimizer length on the current level:

$$\mathcal{M}_{p^{l-1},m^l} := \{x \in \{0, 1, ..., 4^{m^l}\} \mid \exists q \in \mathcal{K}_{p^{l-1}} \; min^{h_l}_{m^l}(q) = x\} \tag{3.2}$$

Let $M[p^{l-1}, m]$ be a discrete random variable that describes the frequency of these minimizers:

$$M[p^{l-1}, m] : \mathcal{M}_{p^{l-1},m^l} \to \mathbb{N} \tag{3.3}$$

$$M[p^{l-1}, m](x) = freq(x) \tag{3.4}$$

wahrscheinlichkeits und verteilungsfunktion für K einmal etwas ausführlicher beschreiben aber für M mehr oder weniger so lassen

We define its probability distribution $p_{M[p^{l-1},m^l]}$, which tells the probability of a minimizer having an exact frequency $f \in \mathbb{N}$. The distribution of minimizers depends both on the level parameters $p^{l-1}$ on previous levels, which affect the remaining k-mers on level $l$ and the minimizer length $m^l$ on the current level, which directly affects the computation of minimizers. For these reasons, we index the distributions with those parameters:

$$p_{M[p^{l-1},m^l]} : \mathbb{N} \to [0,1] \tag{3.5}$$

$$p_{M[p^{l-1},m^l]}(f) = \mathbb{P}(M[p^{l-1},m^l] = f) = \frac{|\{x \in \mathcal{M}_{p^{l-1},m^l} \mid M[p^{l-1},m^l](x) = f\}|}{|\mathcal{M}_{p^{l-1},m^l}|} \tag{3.6}$$

Using the random variables probability function we can derive its cumulative distribution function $F_{M[p^{l-1},m]}$[1], which returns the probability of a minimizer having a frequency that does not exceed an upper bound $f$:

$$F_{M[p^{l-1},m^l]} : \mathbb{N} \to [0,1] \tag{3.7}$$

$$F_{M[p^{l-1},m^l]}(f) = \mathbb{P}(M[p^{l-1},m^l] \leq f) = \sum_{i=1}^{f} p_{M[p^{l-1},m^l]}(i) \tag{3.8}$$

Whilst $M[p^{l-1},m^l]$ and its distribution are useful for modeling values depending of a random (appearing) minimizer, RSHash is used to lookup k-mers, not minimizers. Therefore, we introduce the discrete random variable $K[p^{l-1},m^l]$ which is defined for every distinct (appearing) k-mer on the level and describes the frequency each k-mers minimizer dependent of the level parameters $p^{l-1}$ on all previous levels and the minimizer length $m^l$ on the current one:

$$K[p^{l-1},m^l] : \mathcal{K}_{p^{l-1}} \to \mathbb{N} \tag{3.9}$$

$$K[p^{l-1},m^l](q) = freq(min^{h_l}_{m^l}(q)) \tag{3.10}$$

Its probability distribution $p_{K[p^{l-1},m^l]}$ and its cumulative distribution function $F_{K[p^{l-1},m^l]}$ are:

$$p_{K[p^{l-1},m^l]} : \mathbb{N} \to [0,1] \tag{3.11}$$

$$p_{K[p^{l-1},m^l]}(f) = \mathbb{P}(K[p^{l-1},m^l] = f) = \frac{|\{q \in \mathcal{K}_{p^{l-1}} \mid K[p^{l-1},m^l](q) = f\}|}{|\mathcal{K}_{p^{l-1}}|} \tag{3.12}$$

$$F_{K[p^{l-1},m^l]} : \mathbb{N} \to [0,1] \tag{3.13}$$

$$F_{K[p^{l-1},m^l]}(f) = \mathbb{P}(K[p^{l-1},m^l] \leq f) = \sum_{i=1}^{f} p_{K[p^{l-1},m^l]}(i) \tag{3.14}$$

Let $p^l$ be a combination of level parameters on a level $l$. Recall that we use $p^l[m^l]$ to denote retrieving the minimizer length specified for level $l$ from the level parameters

[1] This notation differs slightly from that used by Schulte-Mattler and Reinert [SMR26] who do not introduce the probability distributions but instead use $p_M$ and $p_K$ to denote the cumulative distribution functions which we denote with $F_M$ and $F_K$

and analogously for $p^l[t^l]$. For better readability we introduce a more compact notation to denote the probability $F_{M[p^l]}$ of a minimizer being *infrequent* on level $l$ and $F_{K[p^l]}$ of a k-mer having an *infrequent* minimizer on that level, both in dependence of all level parameters:

$$F_{M[p^l]} = F_{M[p^{l-1},p^l[m^l]]}(p^l[t^l]) \tag{3.15}$$

$$F_{K[p^l]} = F_{K[p^{l-1},p^l[m^l]]}(p^l[t^l]) \tag{3.16}$$

Explain how and why distribution on the first level affects the distributions on higher levels. Aber nur kurz mit verweis -¿ Experiments

## 3.2 Average Frequencies

Let $\Omega_{M[p^{l-1},m^l]}$ be the sample space of the random variable $M[p^{l-1}, m^l]$ i.e. the set which contains all frequencies $f$ for which there is at least one minimizer $x$ on level $l$ which occurs exactly $f$ times:

$$\Omega_{M[p^{l-1},m^l]} = \{f \mid \exists x \in \mathcal{M}_{p^{l-1},m^l} freq(x) = f\} \tag{3.17}$$

The average frequency of minimizers on a level $l \in \mathcal{L}$ is given by the expected value of the probability distribution of the random variable $M[p^{l-1}, m]$:

$$\mathbb{E}[M[p^{l-1}, m^l]] = \sum_{f \in \Omega_{M[p^{l-1},m^l]}} p_{M[p^{l-1},m^l]}(f) * f \tag{3.18}$$

For a given set of finite sequences the set of distinct minimizers on each level and for each combination of level parameters is finite by definition. It follows that for a given sequence and set of level parameters, the average frequency $\mathbb{E}[M[p^{l-1}, m^l]]$ can always be computed, because the sample space $\Omega_{M[p^{l-1},m^l]}$ is then finite by definition.

More relevant to the optimization of level parameters is the average frequency of *infrequent* minimizers i.e. the average frequency of minimizers whose frequency do not exceed the threshold $t^l$. We denote this value with $f_{avg}(p^l)$ and can derive it from $p_{M[p^{l-1},m]}$ by computing a weighted sum over all frequencies up until the threshold $t^l$ and then norming the result by dividing through the percentage of *infrequent* minimizers:

$$f_{avg}(p^l) = \frac{1}{F_{M[p^l]}} \cdot \sum_{f=1}^{t^l} p_{M[p^{l-1},p^l[m^l]]}(f) \cdot f \tag{3.19}$$

## 3.3 Times for Operations on Data Structures

-¿ Experimente??

We denote the time needed to perform an operation *op* on a data structure *struct* with $T_{op_{struct}}$ e.g. the time for a select query on the bitvector $S$ is $T_{sel_S}$.

incomplete. measure or model?

**Vector Access** Accessing an element of a Vector can be done in constant time, we use the following values based on measurements:

$$T_{contains_R} = ...$$
$$T_{contains_O} = ...$$

**Hash Table Access** Accessing an element of a hash table can be done in constant time, we use the following values based on measurements:

$$T_{check_H} = ...$$

**Bit Vector Rank Query** A bitvector of length $U$ with $n$ $1s$ can be encoded with $n\lceil log_2 U/n \rceil + 3n$ many bits supporting rank in $O(log_2(U/n)$ time [OS07].

does that help here? Doesn't the model require actual time instead of O notation - maybe measurements would be more suited

**Bit Vector Select Query** ???

**Comparison with Text** ???

# 4 MINLP Modeling

We model the optimization problem as a Mixed Integer Non Linear Programming (MINLP). In Section 4.2 we model the runtime and space needed by RSHash on one level in dependence of the level parameters and minimizers distribution. We then extend this to the case of several levels in Section 4.3.
In Chapter 5 we describe how to find the optimal level parameters for a given sequence using the MINLP.

## 4.1 Model Input

The set of levels $\mathcal{L}$, the sets of minimizer lengths $\mathcal{M} \subset \mathbb{N}$ and thresholds $\mathcal{T} \subset \mathbb{N}$ to consider have to be specified explicitly.
From the computed minimizer statistics, the values $F_{M[p^{l-1},p^l[m^l]]}(t^l)$, $F_{K[p^{l-1},p^l[m^l]]}(t^l)$ and $f_{avg}(p^l)$ for all possible combinations $p^l$ of the level parameters on each level $l \in \mathcal{L}$ also have to be passed as input to the MINLP.
Lastly, a measure of the times $T_{contains_R}$, $T_{sel_S}$, $T_{contains_O}$, $T_{comp_T}$, $T_{check_H}$ needed for the contains query on bitvector $R$, the select queries on bitvector $S$, a comparison with the text $T$ at a random offset and checking whether a key exists in the hash set $H$. The computation of the minimizer distribution as well as the times needed to perform these actions on the specified data structures is outlined in Chapter 5.

## 4.2 Model for One Level

Aiming to improve readability, we omit the superscript index indicating an instances belonging to a specific level as only one level is considered in this section e.g. a tuple of level parameters is simply referred to as $p$ instead of $p^1$.
In order to determine $\mathbf{m}$ and $\mathbf{t}$ we use binary indicator variables $\mu_m$ and $\tau_t$ for each possible $m \in \mathcal{M}$ and $t \in \mathcal{T}$:

$$\mu_m \in \{0,1\} \mid \forall m \in \mathcal{M} \tag{4.1}$$
$$\tau_t \in \{0,1\} \mid \forall t \in \mathcal{T} \tag{4.2}$$

The indicator variables for each minimizer length should be mutually exclusive as $\mathbf{m}$ can only take one distinct value. The same holds for the indicator variables for each

threshold:

$$\sum_{m \in \mathcal{M}} \mu_m = 1 \tag{4.3}$$

$$\sum_{t \in \mathcal{T}} \tau_t = 1 \tag{4.4}$$

The variables $\mathbf{m} \in \mathcal{M}$ and $\mathbf{t} \in \mathcal{T}$ are introduced to describe the optimal minimizer length and threshold.
There values can be modeled through a sum over the indicator variables multiplied with there corresponding values:

$$\mathbf{m} \in \mathcal{M} \tag{4.5}$$

$$\mathbf{t} \in \mathcal{T} \tag{4.6}$$

$$\mathbf{m} = \sum_{m \in \mathcal{M}} \mu_m \cdot m \tag{4.7}$$

$$\mathbf{t} = \sum_{t \in \mathcal{T}} \tau_t \cdot t \tag{4.8}$$

We introduce the variable $\mathbf{F}_M \in [0, 1]$ to take the value of $F_{M[(\mathbf{m},\mathbf{t})]}$ i.e. the percentage of minimizers of length $\mathbf{m}$ in the input sequence, whose frequencies do not exceed $\mathbf{t}$ (Section 3.1).
It is not possible to directly evaluate this value as both $\mathbf{m}$ and $\mathbf{t}$ are variables of the model. Instead we use the indicator variables to model a constraint forcing $\mathbf{F}_M$ to take the value of $F_{M[(m,t)]}$ for which $\mu_m = 1$ and $\tau_t = 1$:

$$\mathbf{F}_M \in [0, 1] \tag{4.9}$$

$$\mathbf{F}_M = \sum_{(m,t) \in \mathcal{M} \times \mathcal{T}} F_{M[(m,t)]} \cdot \mu_m \tau_t \tag{4.10}$$

Analogously we introduce $\mathbf{F}_K \in [0, 1]$ to represent $F_{K[(\mathbf{m},\mathbf{t})]}$ and $\mathbf{f_{avg}} \in \mathbb{R}_0^+$ to represent $f_{avg}((\mathbf{m}, \mathbf{t}))$ (Section 3.2):

$$\mathbf{F}_K \in [0, 1] \tag{4.11}$$

$$\mathbf{f_{avg}} \in \mathbb{R}_0^+ \tag{4.12}$$

$$\mathbf{F}_K = \sum_{(m,t) \in \mathcal{M} \times \mathcal{T}} F_{K[(m,t)]} \cdot \mu_m \tau_t \tag{4.13}$$

$$\mathbf{f_{avg}} = \sum_{(m,t) \in \mathcal{M} \times \mathcal{T}} f_{avg}((m,t)) \cdot \mu_m \tau_t \tag{4.14}$$

### 4.2.1 Lookup Time

note that this is the average lookup time for k-mers that appear in the sequence! k-mers that do not appear in the sequence will simply have a lookup time of a check in R on every level and then a check in H

In order to model the time needed for a lookup using RSHash, we closely follow the lookup procedure as described by Schulte-Mattler and Reinert [SMR26]:
A k-mer $q$ is looked up by first computing its minimizer $min_m^h(q)$ and checking whether the bit $R[min_m^h(q)]$ is set whilst simultaneously computing its rank $r = rank_R(min_m^h(q))$, taking $T_{contains_R}$ time (part of the model input Section 4.1).
For the percentage $\mathbf{F}_K$ (Equation (4.13)) of the k-mers this bit is set and the lookup is completed by searching for $q$ on the level. We introduce the variable $T_{level} \in \mathbb{R}_0^+$ to describe the time needed for this.
If the bit $R[min_m^h(q)]$ is not set, the lookup is completed through a lookup in the hash table $H$ taking $T_{check_H}$ time (part of the model input Section 4.1). The variable $T_{lookup_{RSHash}} \in \mathbb{R}_0^+$ describing the lookup time can thus be modeled as:

$$T_{level} \in \mathbb{R}_0^+ \tag{4.15}$$

$$T_{lookup_{RSHash}} \in \mathbb{R}_0^+ \tag{4.16}$$

$$T_{lookup_{RSHash}} = T_{contains_R} + \mathbf{F}_K \cdot T_{level} + (1 - \mathbf{F}_K) \cdot T_{check_H} \tag{4.17}$$

The search for those k-mers $q$ for which the bit $R[min_m^h(q)]$ is set continues on the level by using the minimizers rank $r = rank_R(min_m^h(q))$ in the select queries $first = sel_S(r)$ and $last = sel_S(r+1) - 1$ which tell the indices in Offsets $O$ where the minimizer's first and last offset in the text $T$ are stored. These two queries take $2T_{sel_S}$ time.
explain select and rank
Finally the presence of $q$ in $T$ is checked at every minimizer offset in the interval $O[first : last]$ until $q$ is either found or the end of the interval is reached. The average frequency $\mathbf{f_{avg}}$ of *infrequent* minimizers is exactly the average length of this interval. In the lookup case, the comparison is terminated as soon as $q$ is found for the first time, which is on average the case after $(\mathbf{f_{avg}} + 1)/2$ comparisons ($+1$ is necessary because the first index always has to be checked) with each comparison taking $T_{comp_T}$ time.
The following constraint models the complete time $T_{level}$ needed to search for a k-mers presence on the level:

$$T_{level} = 2T_{sel_S} + (\mathbf{f_{avg}} + 1)/2 \cdot (T_{contains_O} + T_{comp_T}) \tag{4.18}$$

access and rank of R are computed simultaneously - combine $T_{R_{acc}}$ and $T_{R_{rank}}$ and move them out of $T_{level_{arg2}}$

Without further constraints, solving the described MINLP for minimal $T_{lookup_{RSHash}}$ results in a solution where the $\mu_m$, $\tau_t$ corresponding to the smallest $m \in \mathcal{M}$, $t \in \mathcal{T}$ will be set to one.
This is expected, as this leads to the smallest possible $\mathbf{F}_K$ which minimizes the k-mers having to be looked up in the text and maximizes the lookups in the (faster) hash table. However, this results in maximal space consumption, as each entry in the hash table is significantly larger than an entry in $O$ as described in Section 1.2.
In order to account for that, we have to add constraints modeling the space consumption.

### 4.2.2 Space Consumption

Instead of modeling the total space used by RSHash we will focus on the bits per k-mer (bpk) used by the data structure as this metric allows to compare compression independent of the sequence length.
The space consumption of RSHash can be decomposed into the space needed for the data structures components: the text $T$, the vectors $R$, $S$ and $O$ as well as the hash table $H$. We use one variable to describe the bits per k-mer needed by each of the components:

$$bpk_T \in \mathbb{R}_0^+ \tag{4.19}$$
$$bpk_R \in \mathbb{R}_0^+ \tag{4.20}$$
$$bpk_S \in \mathbb{R}_0^+ \tag{4.21}$$
$$bpk_O \in \mathbb{R}_0^+ \tag{4.22}$$
$$bpk_H \in \mathbb{R}_0^+ \tag{4.23}$$

**The text** $T$ is much longer than k. Because of this the bits per k-mer for storing the text $T$ can be set to a constant of 2 bits needed to store one base:

$$bpk_T = 2 \tag{4.24}$$

larger for unitigs!

**Bitvector** $R$ is a bitvector of length $4^{\mathbf{m}}$ in which each bit set to 1 marks the occurrence of one distinct *infrequent* minimizer in the sequences. We can compute the number $n_{DIM}$ of distinct *infrequent* minimizers by multiplying the percentage of *infrequent* minimizers with the total number of minimizers divided through the average frequency of each minimizer:

$$n_{DIM} \in \mathbb{R}_0^+ \tag{4.25}$$
$$n_{DIM} = \frac{\mathbf{F}_K \cdot n_{kmers}}{\mathbf{f_{avg}}} \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR} \tag{4.26}$$
$$= \frac{\mathbf{F}_M \cdot n_{minimizers}}{\mathbf{f_{avg}}} \tag{4.27}$$

decide what to use

add $n_{kmers}$ (only total?) and $n_{minimizers}$ (for every level in depence of level parameters) to the Model

figure out how to model the ratio between k-mers and minimizers for fractured input sequences OR use $n_{minimizers}$?

Using Elias-Fano-Encoding, a bitvector of size $U$ with $n$ bits set to one can be compressed to $n\lceil log_2(U/n)\rceil + 3n$ [OS07] . Compressing $R$ and dividing this by the total

woher kommt diese formel, kann sie so im paper nicht finden

number $n_{kmers}$ of k-mers yields the constraint describing the bits per k-mer of $R$:

$$bpk_R = \frac{1}{n_{kmers}} \cdot \left( n_{DIM} \lceil log_2 \frac{4^{\mathbf{m}}}{n_{DIM}} \rceil + 3n_{DIM} \right)$$
$$\Rightarrow bpk_R = \frac{n_{DIM}}{n_{kmers}} \cdot (\lceil 2\mathbf{m} - log_2 n_{DIM} \rceil + 3) \tag{4.28}$$

argue in experiments section, that $n_{kmers}$ has only a small effect on the size of $R$ and can thus be disregarded as it is not needed for anything else

start experimental

**Bit Vector Rank Query** A bitvector of length $U$ with $n$ $1s$ can be encoded with $n\lceil log_2 U/n \rceil + 3n$ many bits supporting rank in $O(log_2(U/n)$ time [OS07].

$$T_{contains_R} = log_2 \frac{4^{\mathbf{m}}}{n_{DIM}} = 2\mathbf{m} - log_2 n_{DIM}$$

end experimental

make $n_{kmers}$ part of model - either through sum of products or simply product of pKs times number of k-mers in the genome

**Bitvector** $S$ has length $|O|+1 \approx |O|$ where every bit corresponds to the offset of one minimizer encountered in the sequences and one extra bit marks the end of all offsets - this last bit can be disregarded when modeling $bpk_S$ as its effect is insignificantly small. Since $\mathbf{F}_K$ describes the percentage of k-mers with *infrequent* minimizers and every minimizer covers an average of $(k - \mathbf{m} + 2)/2$ consecutive k-mers, we can model the bits per k-mer in $S$ through:

$$bpk_S = \mathbf{F}_K \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR} \tag{4.29}$$
$$= \frac{\mathbf{F}_M \cdot n_{minimizers}}{n_{kmers}} \tag{4.30}$$

figure out how to model the ratio between k-mers and minimizers for fractured input sequences OR use $n_{minimizers}$?

start experimental

**Bit Vector Rank Query** A bitvector of length $U$ with $n$ $1s$ can be encoded with $n\lceil log_2 U/n \rceil + 3n$ many bits supporting rank in $O(log_2(U/n)$ time [OS07].

$$T_{sel_S} = log_2 \frac{\mathbf{F}_M \cdot n_{minimizers}}{n_{DIM}} = \mathbf{f_{avg}}$$

end experimental

**The offset vector** $O$ contains one entry of size $log_2|T|$ for the offset of each *infrequent* minimizer.

Since $bpk_S$ already describes the number of offsets per k-mer, we can model the bits per k-mer in $O$ with:

$$bpk_O = bpk_S \cdot log_2|T| \tag{4.31}$$

**The hash set** $H$ contains an entry $(key : q)$ for each distinct k-mer $q$ with an infrequent minimizer, which are $1-\mathbf{F}_K$ of all k-mers in $T$. Each entry has size $size(key) = 64$ bit. We introduce the load factor $\alpha$ to the model, in order to account for empty buckets in the hash table. The bits per k-mer required for the hash table can thus be modeled by:

$$bpk_H = (1 - \mathbf{F}_K) \cdot \frac{64}{\alpha} \tag{4.32}$$

überall hash table durch hash set ersetzten

reminder to include somewhere that we set $\alpha = 0.75$ in practice and explain why that is a reasonable value

in the used gtl::flat_hash_set there is one byte of metadata for each entry. because of this, it should be $bpk_H = (1 - \mathbf{F}_K) \cdot \frac{64+8}{\alpha}$ - should I add this here or in experiments?

This only models correctly for the unitigs. Figure out how to take into account that k-mers can appear many times in the Input but will only be added once to the hashtable

Locate benötigt eine Liste mit allen offsets: $bpk_H = (1 - \mathbf{F}_K) \cdot \frac{(64+(log_2|T| \cdot frequency))}{\alpha}$

**The total bits per k-mer** $bpk_{total} \in \mathbb{R}_0^+$ can be modeled by simply adding up the space requirements of each component:

$$bpk_{total} \in \mathbb{R}_0^+ \tag{4.33}$$
$$bpk_{total} = bpk_T + bpk_R + bpk_S + bpk_O + bpk_H \tag{4.34}$$

### 4.2.3 Optimization Goal

Having defined all constraints regarding the lookup time and space consumption of RSHash, we can now construct a MINLP in order to find optimal level parameters.
We introduce three more external parameters to the model: The optimization goal $OptGoal$ which specifies whether to minimize $T_{lookup_{RSHash}}$ or $bpk_{total}$ and upper bounds $Bound_{time}, Bound_{bpk}$ for the lookup time and space consumption.

$$OptGoal \in \{T_{lookup_{RSHash}}, bpk_{total}\}$$
$$Bound_{time} \in \mathbb{R}_0^+$$
$$Bound_{bpk} \in \mathbb{R}_0^+$$

When using the MINLP, the upper bound belonging to the optimization goal should be set to $\infty$. In addition to the already defined ones, the following two constraints are added to the MINLP to enforce these bounds:

$$T_{lookup_{RSHash}} \leq Bound_{time} \tag{4.35}$$
$$bpk_{total} \leq Bound_{bpk} \tag{4.36}$$

One could for example search for level parameters minimizing the lookup time whilst not exceeding eight bits per k-mer by setting $OptGoal \leftarrow T_{lookup_{RSHash}}, Bound_{time} \leftarrow \infty, Bound_{bpk} \leftarrow 8$. The constructed MINLP for this example is:

$$
\begin{aligned}
INPUT : \; & OptGoal = T_{lookup_{RSHash}}, Bound_{time} = \infty, Bound_{bpk} = 8, \\
& \mathcal{L} = \{1\}, \mathcal{M}, \mathcal{T}, \\
& F_{M[(m,t)]}, F_{K[(m,t)]}, f_{avg}((m,t)) \; \forall (m,t) \in \mathcal{M} \times \mathcal{T}, \\
& T_{contains_R}, T_{sel_S}, T_{contains_O}, T_{comp_T}, T_{check_H}
\end{aligned}
$$

include $n_{minimizers}$ and $n_{kmers}$!!! and make them dependent of the level

MINIMIZE

$$OptGoal = T_{lookup_{RSHash}}$$

SUBJECT TO

$$\sum_{m \in \mathcal{M}} \mu_m = 1 \qquad \textit{Equation (4.3)}$$

$$\sum_{t \in \mathcal{T}} \tau_t = 1 \qquad \textit{Equation (4.4)}$$

$$\mathbf{m} = \sum_{m \in \mathcal{M}} \mu_m \cdot m \qquad \textit{Equation (4.7)}$$

$$\mathbf{t} = \sum_{t \in \mathcal{T}} \tau_t \cdot t \qquad \textit{Equation (4.8)}$$

$$n_{minimizers} = \mathbf{???}$$

$$n_{kmers} = \mathbf{???}$$

$$\mathbf{F}_M = \sum_{(m,t) \in \mathcal{M} \times \mathcal{T}} F_{M[(m,t)]} \cdot \mu_m \tau_t \qquad \textit{Equation (4.10)}$$

$$\mathbf{F}_K = \sum_{(m,t) \in \mathcal{M} \times \mathcal{T}} F_{K[(m,t)]} \cdot \mu_m \tau_t \qquad \textit{Equation (4.13)}$$

$$\mathbf{f_{avg}} = \sum_{(m,t) \in \mathcal{M} \times \mathcal{T}} f_{avg}((m,t)) \cdot \mu_m \tau_t \qquad \textit{Equation (4.14)}$$

$$T_{level} = 2T_{sel_S} + (\mathbf{f_{avg}} + 1)/2 \cdot (T_{contains_O} + T_{comp_T}) \qquad \textit{Equation (4.18)}$$

$$T_{lookup_{RSHash}} = T_{contains_R} + \mathbf{F}_K \cdot T_{level} + (1 - \mathbf{F}_K) \cdot T_{check_H} \qquad \textit{Equation (4.17)}$$

$$T_{lookup_{RSHash}} \leq Bound_{time} = \infty \qquad \textit{Equation (4.35)}$$

$$bpk_T = 2 \qquad \textit{Equation (4.24)}$$

$$n_{DIM} = \frac{\mathbf{F}_K \cdot n_{kmers}}{\mathbf{f_{avg}}} \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR}$$

$$= \frac{\mathbf{F}_M \cdot n_{minimizers}}{\mathbf{f_{avg}}} \qquad \textit{Equation (4.27)}$$

$$bpk_R = \frac{n_{DIM}}{n_{kmers}} \cdot (\lceil 2\mathbf{m} - log_2 n_{DIM} \rceil + 3) \qquad \textit{Equation (4.28)}$$

$$bpk_S = \mathbf{F}_K \cdot \frac{2}{k - \mathbf{m} + 2} \mathbf{OR}$$

$$= \frac{\mathbf{F}_M \cdot n_{minimizers}}{n_{kmers}} \qquad \textit{Equation (4.30)}$$

$$bpk_O = bpk_S \cdot log_2 |T| \qquad \textit{Equation (4.31)}$$

$$bpk_H = (1 - \mathbf{F}_K) \cdot \frac{64}{\alpha} \qquad \textit{Equation (4.32)}$$

$$bpk_{total} = bpk_T + bpk_R + bpk_S + bpk_O + bpk_H \qquad \textit{Equation (4.34)}$$

$$bpk_{total} \leq Bound_{bpk} = 8 \qquad \textit{Equation (4.36)}$$

VARIABLES

| | |
|---|---|
| $\mu_m \in \{0,1\} \mid \forall m \in M$ | *Equation* (4.1) |
| $\tau_t \in \{0,1\} \mid \forall t \in T$ | *Equation* (4.2) |
| $\mathbf{m} \in \mathcal{M}$ | *Equation* (4.5) |
| $\mathbf{t} \in \mathcal{T}$ | *Equation* (4.6) |
| $n_{minimizers} \in$ ??? | |
| $n_{kmers} \in$ ??? | |
| $\mathbf{F}_M \in [0,1]$ | *Equation* (4.9) |
| $\mathbf{F}_K \in [0,1]$ | *Equation* (4.11) |
| $\mathbf{f_{avg}} \in \mathbb{R}_0^+$ | *Equation* (4.12) |
| $T_{level} \in \mathbb{R}_0^+$ | *Equation* (4.15) |
| $T_{lookup_{RSHash}} \in \mathbb{R}_0^+$ | *Equation* (4.16) |
| $bpk_T \in \mathbb{R}_0^+$ | *Equation* (4.19) |
| $bpk_R \in \mathbb{R}_0^+$ | *Equation* (4.20) |
| $bpk_S \in \mathbb{R}_0^+$ | *Equation* (4.21) |
| $bpk_O \in \mathbb{R}_0^+$ | *Equation* (4.22) |
| $bpk_H \in \mathbb{R}_0^+$ | *Equation* (4.23) |
| $n_{DIM} \in \mathbb{R}_0^+$ | *Equation* (4.25) |
| $bpk_{total} \in \mathbb{R}_0^+$ | *Equation* (4.33) |

## 4.3 Model for Several Levels

teils veraltet - one level finalisieren und dann dementsprechend für several levels anpassen

In the following, we adapt the constraints defined for using only one level in Section 4.2 to model the use of $L \in \mathbb{N}^+$ levels with $\mathcal{L} = \{l \in \mathbb{N}^+ \mid l \leq L\}$ being the set of levels used[1].
When modeling several levels, we add a superscript $l$ to variables in order to indicate there belonging to a level $l \in \mathcal{L}$ e.g. $\mathbf{m}^1, \mathbf{m}^2$ and $\mathbf{m}^3$ denote the optimal minimizer lengths on level $1, 2$ and $3$.
We still assume, that the times $T_{contains_{R^l}}, T_{sel_{S^l}}, T_{contains_{O^l}}, T_{comp_T}, T_{check_H}$ are (practically) independent of the parameters $\mathbf{m}^l, \mathbf{t}^l$ and the level $l$.

reason in chap: experiments

Unique sets of binary indicator variables $\mu_m^l$ and $\tau^l$ are needed for the level parameters $\mathbf{m}^l$ and $\mathbf{t}^l$ of each level $l$. The constraints regarding these variables are analog to those

[1] We model the space consumption and lookup time for any positive natural number of levels even though RSHash currently only supports the use of one, two or three levels [SMR26].

when using only one level:

$$
\begin{aligned}
\mu_m^l &\in \{0,1\} && \mid \forall (l,m) \in (\mathcal{L} \times \mathcal{M}) \\
\tau_t^l &\in \{0,1\} && \mid \forall (l,t) \in (\mathcal{L} \times \mathcal{T}) \\
\sum_{m \in \mathcal{M}} \mu_m^l &= 1 && \mid \forall l \in \mathcal{L} \\
\sum_{t \in \mathcal{T}} \tau_t^l &= 1 && \mid \forall l \in \mathcal{L} \\
\mathbf{m}^l &\in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
\mathbf{t}^l &\in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
\mathbf{m}^l &= \sum_{m \in \mathcal{M}} \mu_m^l \cdot m^l && \mid \forall l \in \mathcal{L} \\
\mathbf{t}^l &= \sum_{t \in \mathcal{T}} \tau_t^l \cdot t^l && \mid \forall l \in \mathcal{L}
\end{aligned}
$$

For each level $l$ we model $\mathbf{F}_M^l$, $\mathbf{F}_K^l$ and $\mathbf{f}_{\mathbf{avg}}^l$ analogously to using a single level; however, it is necessary to sum over every possible combination of level parameters $p^l$. The number of additions grows exponentially for an increasing number of levels. We will outline the resulting consequences for solving the MINLP in Chapter 5.

don't forget to do this

$$
\begin{aligned}
\mathbf{F}_M^l &\in [0,1] && \mid \forall l \in \mathcal{L} \\
\mathbf{F}_K^l &\in [0,1] && \mid \forall l \in \mathcal{L} \\
\mathbf{f}_{\mathbf{avg}}^l &\in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
\mathbf{F}_M^l &= \sum_{p^l \in \mathcal{M}^l \times \mathcal{T}^l} F_{M[p^l]} \cdot \prod_{1 \le i \le l} \mu_{p^l[m^i]}^i \tau_{p^l[t^i]}^i && \mid \forall l \in \mathcal{L} \\
\mathbf{F}_K^l &= \sum_{p^l \in \mathcal{M}^l \times \mathcal{T}^l} F_{K[p^l]} \cdot \prod_{1 \le i \le l} \mu_{p^l[m^i]}^i \tau_{p^l[t^i]}^i && \mid \forall l \in \mathcal{L} \\
\mathbf{f}_{\mathbf{avg}}^l &= \sum_{p^l \in \mathcal{M}^l \times \mathcal{T}^l} f_{avg}(p^l) \cdot \prod_{1 \le i \le l} \mu_{p^l[m^i]}^i \tau_{p^l[t^i]}^i && \mid \forall l \in \mathcal{L}
\end{aligned}
$$

$p^l[t^l]$ in Notation einführen

### 4.3.1 Lookup Time

The search time on a level $l \in \mathcal{L}$ can be leveled analogously to that on one level:

$$
\begin{aligned}
T_{level}^l &\in \mathbb{R}_0^+ && \mid \forall l \in \mathcal{L} \\
T_{level}^l &= 2T_{sel_{S^2}} + \frac{\mathbf{f}_{\mathbf{avg}}^l + 1}{2} \cdot (T_{contains_{O^2}} + T_{comp_T}) && \mid \forall l \in \mathcal{L}
\end{aligned}
$$

For $\mathbf{F}_K^l$ of the k-mers on a level $l \in \mathcal{L}$ the lookup is completed by a search through the offsets on that level whilst the remaining $(1 - \mathbf{F}_K^l)$ of queries result in a lookup on the next level.

We can thus model the lookup time recursively:

$$T^l_{lookup_{RSHash}} = \begin{cases} T_{contains_{R^l}} + \mathbf{F}^l_K \cdot T^l_{level} \\ \qquad + (1 - \mathbf{F}^l_K) \cdot T^{l+1}_{lookup_{RSHash}} & \mid l \in \mathcal{L} \\ T_{check_H} & \mid l \notin \mathcal{L} \end{cases}$$

Considering the set $\mathcal{L} = \{1, 2\}$ of two levels as an example, this results in the following total lookup time:

$$\begin{aligned} T^1_{lookup_{RSHash}} = T_{contains_{R^1}} &+ \mathbf{F}^1_K \cdot T^1_{level} \\ &+ (1 - \mathbf{F}^1_K) \cdot \Big( T_{contains_{R^2}} + \mathbf{F}^2_K \cdot T^2_{level} \\ &\qquad + (1 - \mathbf{F}^2_K) \cdot T_{check_H} \Big) \end{aligned}$$

Inserting $T^1_{level}$ and $T^2_{level}$ yields:

$$\begin{aligned} T^1_{lookup_{RSHash}} = T_{contains_{R^1}} &+ \mathbf{F}^1_K \cdot (2T_{sel_{S^1}} + \frac{\mathbf{f}^1_{\mathbf{avg}} + 1}{2} \cdot (T_{contains_{O^1}} + T_{comp_T})) \\ &+ (1 - \mathbf{F}^1_K) \cdot \Bigg( T_{contains_{R^2}} + \mathbf{F}^2_K \cdot (2T_{sel_{S^2}} + \frac{\mathbf{f}^2_{\mathbf{avg}} + 1}{2} \cdot (T_{contains_{O^2}} + T_{comp_T})) \\ &\qquad + (1 - \mathbf{F}^2_K) \cdot T_{check_H} \Bigg) \end{aligned}$$

insertion weglassen?

### 4.3.2 Space Consumption

**The text** $T$ is only being stored once, so the constant approximation $bpk_T \approx 2$ still holds.

**Bitvector** $R^l$ $n^l_{DIM}$ on each level $l$ and are modeled analogously to using only one level:

$$\begin{aligned} n_{DIM} &\in \mathbb{R}^+_0 && \mid \forall l \in \mathcal{L} \\ bpk_{R^l} &\in \mathbb{R}^+_0 && \mid \forall l \in \mathcal{L} \\ n_{DIM} &= \frac{\mathbf{F}^l_K \cdot n^l_{kmers}}{\mathbf{f}^l_{\mathbf{avg}}} \cdot \frac{2}{k - \mathbf{m}^l + 2} \mathbf{OR} \\ &= \frac{\mathbf{F}^l_M \cdot n^l_{minimizers}}{\mathbf{f}^l_{\mathbf{avg}}} && \mid \forall l \in \mathcal{L} \\ bpk^l_R &= \frac{n^l_{DIM}}{n_{kmers}} \cdot \left( \lceil 2\mathbf{m}^l - log_2 n^l_{DIM} \rceil + 3 \right) && \mid \forall l \in \mathcal{L} \end{aligned}$$

**Bitvector** $S^l$ on each level $l$ has length $|O^l| + 1 \approx |O^l|$. Only k-mers that have frequent minimizers on all previous levels but an *infrequent* minimizer on level $l$ lead to an offset in $O^l$ and thus to a bit in $S^l$:

$$bpk_{S^l} \in \mathbb{R}_0^+ \qquad | \forall l \in \mathcal{L}$$

$$bpk_{S^l} = \left( \prod_{i=1}^{l-1} 1 - \mathbf{F}_K^i \right) \cdot \mathbf{F}_K^l \cdot \frac{2}{(k - \mathbf{m}^l + 2)} \qquad | \forall l \in \mathcal{L}$$

**OR** analogously to on level

$$bpk_S^l = \frac{\mathbf{F}_M^l * n_{minimizers}^l}{n_{kmers}} \qquad | \forall l \in \mathcal{L}$$

adapt to whatever stays on one model

For levels $l > 1$ the input consist of the super-k-mers with frequent minimizers on the previous level. Because those fragments are fairly short (sometimes close to k bases), every minimizer NO LONGER covers an average of $(k - \mathbf{m} + 2)/2$ consecutive k-mers - Find a way to account for that and describe this observation somewhere! When optimizing for the unitigs, this is the case for every level including ther first.

**The offset vector** $O^l$ for every level $l$ is modeled analogously to using only one level:

$$bpk_{O^l} \in \mathbb{R}_0^+ \qquad | \forall l \in \mathcal{L}$$

$$bpk_{O^l} = bpk_{S^l} \cdot log_2|T| \qquad | \forall l \in \mathcal{L}$$

**The hash table** $H$ only contains an entry for k-mers $q$, which have frequent minimizers on all levels. The bits per k-mer for the hash table can thus be modeled as

$$bpk_H = \left( \prod_{l=1}^{L} 1 - \mathbf{F}_K^l \right) \cdot \frac{64}{\alpha}$$

**The total bits per k-mer** for $L$ levels only differ to those on one level, as there are now a vector $R, S$ and $O$ on each level:

$$bpk_{total} = bpk_T + \sum_{l=1}^{L} (bpk_{R^l} + bpk_{S^l} + bpk_{O^l}) + bpk_H$$

## 4.4 Locate

outline differences to lookup

- lookup time: check every offset instead of only an average of half of the offsets
- hash table instead of hash set - contains one entry (key:k-mer, value:offset) for each appearance of every k-mer (no longer distinct) - for the unitigs, this shouldn't have an effect

# 5 Experiments

We evaluate how suited the MINLP proposed in Chapter 4 is for finding optimal level parameters by analyzing how accurate the modeled lookup time and space consumption are compared to the actual lookup time measured and space needed when building RSHash. We then examine how well the model can be optimized using the SCIP solver [Ach+08; Ach09; Bes+23]. Whether the resulting parameters are actually optimal in practice is highly dependent on how accurate the model is in the first place.

## 5.1 Datasets

We use the same datasets as Pibiri [Pib22]. Those are the whole genomes of the atlantic cod (*Gadus morhua*), the common kestrel (*Falco tinnunculus*) and the whole GRCh38 human genome (*Homo sapiens*). This choice allows a direct comparison with Schulte-Mattler and Reinert [SMR26] who use the same datasets for benchmarking RSHash.

absatz kopiert von [SMR26] - ist das okay?

## 5.2 Computing the Model Input

In order to evaluate the accuracy of the proposed MINLP, we first show how to compute the model input for a given dataset which we refer to as the set of sequences $S_{p^0}$. The sets $\mathcal{M}$ and $\mathcal{T}$ of minimizer lengths and thresholds to be considered as well as the number of levels $L$ resulting in a set of levels $\mathcal{L} := \{l \in \mathbb{N}^+ \mid l \leq L\}$ are also hyper parameters that have to be specified explicitly.
The MINLP requires the cumulative distributions of minimizer frequencies $F_{M[p^{l-1},p^l[m^l]]}$ and $F_{K[p^{l-1},p^l[m^l]]}$ and the average frequencies $f_{avg}(p^l)$ for every combination of level parameters $p^l \in \mathcal{M}^l \times \mathcal{T}^l$ on every level $l \in \mathcal{L}$ as input.

A fairly straightforward way of computing these is to use a recursion over the levels. The input for each recursive call consist of the current level $l$, the number of levels $L$, the previous level parameters $p^{l-1}$ and the set of input sequences in dependence of those parameters.

zu umgangssprachlich?

Upon being called, the first minimizer $m \in \mathcal{M}$ is selected and used to compute the distribution stats for the input sequence on this level in dependence of $m$. The function then loops over each threshold $t \in \mathcal{T}$, removes all k-mers with *infrequent* minimizers when using $(m, t)$ from the input sequences and then calls the recursion for the next level, which receives the next level, the previous parameters extended by $(m, t)$ and the modified sequences as input. Only once this recursion is completed for every threshold $t \in \mathcal{T}$, the next minimizer is picked from $\mathcal{M}$. The described algorithm can be seen in Algorithm 1.

soll ich hier erklären, wie die Berechnung in der Praxis noch ein bisschen schneller geschieht? Oder ist das an dieser Stelle egal, wenn es am grundlegenden Problem der exponentiellen Laufzeit nichts ändert?

**Algorithm 1** Computation of Minimizer Distribution

**Input:** level $l$, max Level $L$, level parameters $p^{l-1}$, sequences $S_{p^{l-1}}$
  **function** RECURSIVEMINIMIZERDISTRIBUTION($l, L, p^{l-1}S_{p^{l-1}}$)
    **if** $l = L$ **then**
      **return**
    **end if**
    **for** $m \in \mathcal{M}$ **do**
      **for** $t \in \mathcal{T}$ **do**
        $p^l \leftarrow extend(p^{l-1}, m, t)$ ▷ $extend((m^1, t^1), m^2, t^2) = (m^1, m^2, t^1, t^2)$
        $S_{p^l} \leftarrow getFrequentKmers(l, S_{p^{l-1}}, m, t)$

        $n_{kmers}, n_{minimizers} \leftarrow getCounts(h_l, S_{p^{l-1}}, m)$
        $F_{M[p^l]}, F_{K[p^l]}, f_{avg}(p^l) \leftarrow distributionStats(h_l, S_{p^{l-1}}, m)$
        RECURSIVEMINIMIZERDISTRIBUTION($l + 1, L, p^l, S_{p^l}$)
      **end for**
    **end for**
  **end function**

add $n_{minimizers}, n_{kmers}$ to model and include dependence of level parameters

This approach is guaranteed to compute correct minimizer distributions for every set of level parameters on every level as it effectively performs the same steps as the RSHash algorithm only without building the data structure itself. This also means, that one could include the building of bitvectors $R, S$ and $O$ on every level as well as the hash set $H$ and simply measure the space consumption and lookup time for every combination, which would render the MINLP obsolete.
However, this approach is sufficient for computing the input needed for analyzing how well the MINLP models the lookup time and space consumption using only the minimizer distributions. Possibilities of speeding up the time needed are outlined in Chapter 6.

Explain results of minimizer distribution across several levels

- higher levels distributions are highly dependent on previous parameters (hypothesis: highly repetitive regions are more likely to have *infrequent* minimizers on every level regardless of the hash functions used)
- probability functions of minimizer distributions always follow a log normal / log logistic distribution?? Because there cumulative probability function has logarithmic growth, considering exponentially growing thresholds like $2, 4, 8, 16, 32, 64, 128$ is a viable choice (the change between 2 and 4 is proportional (equal?) to that between 64 and 128)

- outlook: it might be possible to only compute a selection of distributions and extrapolate the remaining ones

## 5.3 Model Accuracy

We assess the accuracy of the lookup time and space consumption modeled by the MINLP Chapter 4 by analyzing the differences between the values modeled by the MINLP and the values measured when building RSHash for a selection of possible level Parameters and the ge

### 5.3.1 Lookup Time

### 5.3.2 Space Consumption

## 5.4 Limitations

The MINLP approach for finding optimal level parameters has the advantage of finding the optimal level parameters for the specified optimization goal.

This approaches plausibility is heavily dependent on the time needed to compute the model input as outlined Section 5.2. Especially the runtime for the computation of the distributions $p_{M[p^{l-1},p^l[m^l]]}$ and $p_{K[p^{l-1},p^l[m^l]]}$ for every combination of the level parameters $p^l$ on every level $l$ grows exponentially with the number of levels when done in a trivial way.

AHHHHH - Achtung das böse Wort!!!

We further outline this in Chapter 5.

For this reason, an approach yielding only an approximation of the optimal level parameters but taking less time to do so could be of interest.

We will further explore methods Chapter 7 the genome in order to reduce the computation of minimizer distribution.

In another approach we will try to approximate the distributions on higher levels based on that on the first level in order to get around the exponential cost of computing those values.

TODO

TODO

# 6 Outlook

# 7 Subsampling

## 7.1 Motivation

The time for processing a genome in order to find the minimizer distribution $\mathbf{F}_K(p^l)$ for possible minimizer lengths $m \in \mathcal{M}$ and thresholds $t \in \mathcal{T}$ is directly proportional to the size of the genome.
For large genomes, this processing can become the dominating factor when searching for optimal parameters using the Chapter 4 approach. In order to speed up the search for the empirical values, we introduce a subsampling method.

## 7.2 Subsampling Method

Instead of calculating the distribution over the full genome, we sample $n$ sequences of length $l \geq k$ at random positions in the genome.

how to handle overlapping samples

müsste die gezählte frequenz der minimizer mit eine Faktor mutipliziert werden, um auf die länge des ursprünglichen textes zu skalieren?? schließlich kommen minimizer ja in einem kürzeren text perse seltener vor als in einem längeren

## 7.3 Time Complexity of Finding the Minimizer Distributions

genaue zeitliche abhängigkeit 1. verstehen und 2. aufschreiben

## 7.4 Time Complexity using Subsampling

By applying the proposed subsampling strategy, the original genome $T$ of length $|T|$ is reduced to the subsampled text $T^S$ of length $|T^S| = n \cdot l$. This means a reduction in size by a factor of $\frac{|T|}{|T^S|}$.
Depending on the choice of $n$ and $l$ this results in a speedup of the processing time by a factor of or even a constant processing time when both parameters are chosen as a constand regardless of $|T|$ (However, this should result in a growing error for larger genomes).

assuming no overlaps

factor

time

## 7.5 Error Analysis

## 7.6 Choosing $l$

The length $l$ has to be at least $k$.

wenn $l > k$ ist, überlappen sich mehrere kmere an den gesampleten stellen.
Frage: ich verstehe noch nicht, warum genau dass von vorteil ist.
Antwort: Weil roling hash - l ca 1000, dann quasi linear

## 7.7 Choosing $n$

Choosing a constant $n$ would result in a processing time that would no longer be dependent of the genomes length $|T|$, as the sampled text would have constant size $n \cdot l$. For large genomes, the percentage $\frac{|T^S|}{|T|}$ of the genome represented in the subsample can become arbitrarily small, resulting in growing error.
If instead $n$ is chosen relative to $|T|$, $\frac{|T^S|}{|T|}$ will have a constant value independent of the genomes size. Even though this means, that the time needed, in order to find the minimizer distributions would still be proportional to the genomes size, this should be the preferred option as it results in a bounded error of the approximation.
For a large enough $n$, the probability of choosing a bad representation becomes highly unlikely.

assuming no overlaps

zu vage, begründen

# Bibliography


[Ach+08] T. Achterberg, T. Berthold, T. Koch, and K. Wolter. *Constraint Integer Programming: a New Approach to Integrate CP and MIP*. eng. Tech. rep. 08-01. Takustr. 7, 14195 Berlin: ZIB, 2008 (cit. on p. 28).

[Ach09] T. Achterberg. "SCIP: solving constraint integer programs". In: *Mathematical Programming Computation* 1.1 (2009), pp. 1–41. URL: https://doi.org/10.1007/s12532-008-0001-1 (cit. on p. 28).

[Bes+23] K. Bestuzheva, A. Chmiela, B. MÃ¼ller, F. Serrano, S. Vigerske, and F. Wegscheider. *Global Optimization of Mixed-Integer Nonlinear Programs with SCIP 8*. Tech. rep. 2301.00587. arXiv, 2023 (cit. on p. 28).

[Chi+14] R. Chikhi, A. Limasset, S. Jackman, J. Simpson, and P. Medvedev. *On the representation of de Bruijn graphs*. en. arXiv:1401.5383 [q-bio.QM]. Oct. 2014. URL: http://arxiv.org/abs/1401.5383 (visited on 09/18/2026) (cit. on p. 7).

[Jai+20] C. Jain, A. Rhie, H. Zhang, C. Chu, B. P. Walenz, S. Koren, and A. M. Phillippy. "Weighted minimizer sampling improves long read mapping". en. In: *Bioinformatics* 36.Supplement_1 (July 2020), pp. i111–i118. URL: https://academic.oup.com/bioinformatics/article/36/Supplement_1/i111/5870473 (visited on 09/18/2026) (cit. on p. 7).

[Moe+24] C. Moeckel, M. Mareboina, M. A. Konnaris, C. S. Chan, I. Mouratidis, A. Montgomery, N. Chantzi, G. A. Pavlopoulos, and I. Georgakopoulos-Soares. "A survey of k-mer methods and applications in bioinformatics". en. In: *Computational and Structural Biotechnology Journal* 23 (Dec. 2024), pp. 2289–2303. URL: https://spj.science.org/doi/10.1016/j.csbj.2024.05.025 (visited on 11/02/2026) (cit. on p. 6).

[OS07] D. Okanohara and K. Sadakane. "Practical entropy-compressed rank/select dictionary". In: *2007 Proceedings of the ninth workshop on algorithm engineering and experiments (ALENEX)*. SIAM. 2007, pp. 60–70 (cit. on pp. 15, 19, 20).

[Pib22] G. E. Pibiri. "Sparse and skew hashing of K-mers". en. In: *Bioinformatics* 38.Supplement_1 (June 2022), pp. i185–i194. URL: https://academic.oup.com/bioinformatics/article/38/Supplement_1/i185/6617506 (visited on 07/06/2026) (cit. on pp. 7, 9, 28).

[SMR26] J. Schulte-Mattler and K. Reinert. "RSHash: a fast and space-efficient hash table for $k$ -mers". en. In: *Bioinformatics* 42.Supplement_2 (Aug. 2026), btag440. URL: https://academic.oup.com/bioinformatics/article/doi/10.1093/bioinformatics/btag440/8767308 (visited on 09/15/2026) (cit. on pp. 7, 8, 12, 13, 18, 24, 28).

[ZKM20] H. Zheng, C. Kingsford, and G. Marçais. "Improved design and analysis of practical minimizers". en. In: *Bioinformatics* 36.Supplement_1 (July 2020), pp. i119–i127. URL: https://academic.oup.com/bioinformatics/article/36/Supplement_1/i119/5870484 (visited on 07/06/2026) (cit. on pp. 7, 9).