Using AI to improve your code

Eris :3 (they/them)

October 23, 2026

I FUCKING HATE AI!!!

I FUCKING HATE AI!!!

Please imagine a video of Sam Altman being blown up by a missile.

I FUCKING HATE AI!!!

Please imagine a video of Sam Altman being blown up by a missile.
These are my thoughts on ai :)

I FUCKING HATE AI!!!

Please imagine a video of Sam Altman being blown up by a missile.
These are my thoughts on ai :) Artificial intelligence will not be mentioned again for the rest of this talk.

Using ~~AI~~ Abstract Interpretation to improve your code

Eris :3 (they/them)

October 23, 2026

How other people use Abstract Interpretation to improve your code when you run it


Eris :3 (they/them)

October 23, 2026

Optimising compilers



Optimising compilers



Fibonacci program

$F \leftarrow \underbrace{[0, \ldots, 0]}_{\text{100 of them}}$
$F[0] \leftarrow 0$
$F[1] \leftarrow 1$
$i \leftarrow 2$
while $i < 100$ **do**
    $F[i] \leftarrow F[i-1] + F[i-2]$
    $i \leftarrow i + 1$
end while
return F

Fibonacci program

$F \leftarrow \underbrace{[0, \ldots, 0]}_{\text{100 of them}}$
if $\neg(0 \leq 0 \leq 99 \wedge 0 \leq 1 \leq 99)$ **then**
    explode (out of bounds)
end if
$F[0] \leftarrow 0$
$F[1] \leftarrow 1$
$i \leftarrow 2$
while $i < 100$ **do**
    if $\neg(0 \leq i - 2 \leq 99 \wedge 0 \leq i - 1 \leq 99 \wedge 0 \leq i \leq 99)$ **then**
        explode (out of bounds)
    end if
    $F[i] \leftarrow F[i - 1] + F[i - 2]$
    $i \leftarrow i + 1$
end while
return F

Fibonacci program

$F \leftarrow \underbrace{[0, \ldots, 0]}_{\text{100 of them}}$
if $\neg(0 \leq 0 \leq 99 \wedge 0 \leq 1 \leq 99)$ **then**
    explode (out of bounds)
end if
$F[0] \leftarrow 0$
$F[1] \leftarrow 1$
$i \leftarrow 2$
while $i < 100$ **do**
    if $\neg(0 \leq i - 2 \leq 99 \wedge 0 \leq i - 1 \leq 99 \wedge 0 \leq i \leq 99)$ **then**
        explode (out of bounds)
    end if
    $F[i] \leftarrow F[i - 1] + F[i - 2]$
    $i \leftarrow i + 1$
end while
return F

The bounds check is redundant!

Syntax

Expressions, conditions and statements are defined inductively. Let n be numeric literals and v variables.

$$
\begin{array}{lcl}
e & := & n \mid v \mid e + e \mid e - e \mid e \times e \\
c & := & \mathrm{true} \mid \mathrm{false} \mid e \leq e \mid e = e \mid c \wedge c \mid c \vee c \mid \neg c \\
s & := & v \leftarrow e \mid s; s \mid \textbf{if } c \textbf{ then } s \textbf{ else } s \textbf{ end if} \\
 & & \mid \textbf{while } c \textbf{ do } s \textbf{ end while} \mid \textbf{explode} \mid \textbf{skip}
\end{array}
$$

Oh wait arrays

Let a be array variables. Then we can extend expressions and statements to include array syntax.

$$\begin{array}{rcl} e & := & \cdots \mid a[e] \\ s & := & \cdots \mid a[e] \leftarrow e \end{array}$$

Semantics

There is a set $\mathcal{E}$ of states (E for environment i think?) and (letting $\mathcal{D} = \mathcal{P}(\mathcal{E})$) an operator $\mathbb{S}[\![s]\!] : \mathcal{D} \to \mathcal{D}$ for each statement s. This operator describes "what the statements do".

Semantics

There is a set $\mathcal{E}$ of states (E for environment i think?) and (letting $\mathcal{D} = \mathcal{P}(\mathcal{E})$) an operator $\mathbb{S}[\![s]\!] : \mathcal{D} \to \mathcal{D}$ for each statement s. This operator describes "what the statements do".
Let's write it out! Let $\mathcal{E} = \mathbb{Z}^V \times A^W$ where V is the set of variables and W is the set of array variables.

Semantics

There is a set $\mathcal{E}$ of states (E for environment i think?) and (letting $\mathcal{D} = \mathcal{P}(\mathcal{E})$) an operator $\mathbb{S}[\![s]\!] : \mathcal{D} \to \mathcal{D}$ for each statement s. This operator describes "what the statements do".
Let's write it out! Let $\mathcal{E} = \mathbb{Z}^V \times A^W$ where V is the set of variables and W is the set of array variables. And A is the set of integer valued arrays... so that would be... umm

$$A = \bigcup_{n \in \mathbb{N}} \{n\} \times \mathbb{Z}^n$$

so like each array has a number telling us its length and then a whole bunch of integers...

Semantics

There is a set $\mathcal{E}$ of states (E for environment i think?) and (letting $\mathcal{D} = \mathcal{P}(\mathcal{E})$) an operator $\mathbb{S}[\![s]\!] : \mathcal{D} \to \mathcal{D}$ for each statement s. This operator describes "what the statements do".
Let's write it out! Let $\mathcal{E} = \mathbb{Z}^V \times A^W$ where V is the set of variables and W is the set of array variables. And A is the set of integer valued arrays... so that would be... umm

$$A = \bigcup_{n \in \mathbb{N}} \{n\} \times \mathbb{Z}^n$$

so like each array has a number telling us its length and then a whole bunch of integers... and then we can define the semantics operator..... that sounds SOOOO annoying!! these arrays are so ugly! i don't wanna

Order theory 1

Definition

A poset is a set P equipped with a partial order $\sqsubseteq$ (reflexive, antisymmetric and transitive).

(I really hope you've seen this before else this talk will go way too fast)

Order theory 1

Definition

A poset is a set P equipped with a partial order $\sqsubseteq$ (reflexive, antisymmetric and transitive).

(I really hope you've seen this before else this talk will go way too fast)

Example

For any set S, $(\mathcal{P}(S), \subseteq)$ is a poset.

Order theory 1

Insert hasse diagram here

Order theory 1

Definition

A map $f : P \to Q$ between posets is monotone if whenever $x \sqsubseteq_P y$, $f(x) \sqsubseteq_Q f(y)$.

Order theory 1

Definition

A map $f : P \to Q$ between posets is monotone if whenever $x \sqsubseteq_P y$, $f(x) \sqsubseteq_Q f(y)$.

Proposition

The identity map is monotone. Composites of monotone maps are monotone.

Proof.

If $x \sqsubseteq y$ then $x \sqsubseteq y$.
If $x \sqsubseteq y$ then $f(x) \sqsubseteq f(y)$ then $g(f(x)) \sqsubseteq g(f(y))$. □

Order theory 1

Definition

A map $f : P \to Q$ between posets is monotone if whenever $x \sqsubseteq_P y$, $f(x) \sqsubseteq_Q f(y)$.

Proposition

The identity map is monotone. Composites of monotone maps are monotone.

Proof.

If $x \sqsubseteq y$ then $x \sqsubseteq y$.
If $x \sqsubseteq y$ then $f(x) \sqsubseteq f(y)$ then $g(f(x)) \sqsubseteq g(f(y))$. □

Monotone maps are ordered pointwise, $f \sqsubseteq g$ iff $f(x) \sqsubseteq g(x)$ for all x in the domain.

Approximating semantics

Instead of defining the full semantics, define an approximation set of states $\hat{\mathcal{E}}$ and (letting $\hat{\mathcal{D}} = \mathcal{P}(\hat{\mathcal{E}})$) define an approximation operator $\hat{\mathbb{S}}[\![s]\!] : \hat{\mathcal{D}} \to \hat{\mathcal{D}}$ for each statement s.

Approximating semantics

Instead of defining the full semantics, define an approximation set of states $\hat{\mathcal{E}}$ and (letting $\hat{\mathcal{D}} = \mathcal{P}(\hat{\mathcal{E}})$) define an approximation operator $\hat{\mathbb{S}}[\![s]\!] : \hat{\mathcal{D}} \to \hat{\mathcal{D}}$ for each statement s.
Need a monotone map $\hat{\gamma} : \hat{\mathcal{D}} \to \mathcal{D}$ such that $\mathbb{S}[\![s]\!] \circ \gamma \sqsubseteq \gamma \circ \hat{\mathbb{S}}[\![s]\!]$.

$$\begin{array}{ccc} \hat{\mathcal{D}} & \xrightarrow{\hat{\mathbb{S}}[\![s]\!]} & \hat{\mathcal{D}} \\ {\scriptstyle\gamma}\downarrow & \swarrow\!\!\!\swarrow & \downarrow{\scriptstyle\gamma} \\ \mathcal{D} & \xrightarrow[\mathbb{S}[\![s]\!]]{} & \mathcal{D} \end{array}$$

Approximating semantics

Instead of defining the full semantics, define an approximation set of states $\hat{\mathcal{E}}$ and (letting $\hat{\mathcal{D}} = \mathcal{P}(\hat{\mathcal{E}})$) define an approximation operator $\hat{\mathbb{S}}[\![s]\!] : \hat{\mathcal{D}} \to \hat{\mathcal{D}}$ for each statement s.
Need a monotone map $\hat{\gamma} : \hat{\mathcal{D}} \to \mathcal{D}$ such that $\mathbb{S}[\![s]\!] \circ \gamma \sqsubseteq \gamma \circ \hat{\mathbb{S}}[\![s]\!]$.

$$\begin{array}{ccc} \hat{\mathcal{D}} & \xrightarrow{\hat{\mathbb{S}}[\![s]\!]} & \hat{\mathcal{D}} \\ {\scriptstyle\gamma}\downarrow & \swarrow & \downarrow{\scriptstyle\gamma} \\ \mathcal{D} & \xrightarrow[\mathbb{S}[\![s]\!]]{} & \mathcal{D} \end{array}$$

If you prefer, we need $\hat{\gamma}$ a lax natural transformation viewing semantics opeators as functors from the one object category of statements under sequential composition to the poset-enriched category of posets!

Approximating semantics

Define $\hat{\mathcal{E}} = \mathbb{Z}^V$ (no arrays!) and $\hat{\mathcal{D}} = \mathcal{P}(\hat{\mathcal{E}})$. Then $\gamma : \hat{\mathcal{D}} \to \mathcal{D}$ by $\gamma(S) = S \times A^W$, giving all possible assignments of array variables, is an approximation.
Then we'll define $\mathbb{E}[\![e]\!] : \hat{\mathcal{E}} \to \mathcal{P}(\mathbb{Z})$, $\mathbb{C}[\![c]\!] : \hat{\mathcal{D}} \to \hat{\mathcal{D}}$ and $\hat{\mathbb{S}}[\![s]\!] : \hat{\mathcal{D}} \to \hat{\mathcal{D}}$ inductively.

Approximating semantics

$$
\begin{aligned}
\mathbb{E}[\![n]\!](\sigma) &= \{n\} \\
\mathbb{E}[\![v]\!](\sigma) &= \{\sigma(v)\} \\
\mathbb{E}[\![e_1 + e_2]\!](\sigma) &= \{x + y \mid x \in \mathbb{E}[\![e_1]\!](\sigma), y \in \mathbb{E}[\![e_2]\!](\sigma)\} \\
\mathbb{E}[\![e_1 - e_2]\!](\sigma) &= \{x - y \mid x \in \mathbb{E}[\![e_1]\!](\sigma), y \in \mathbb{E}[\![e_2]\!](\sigma)\} \\
\mathbb{E}[\![e_1 \times e_2]\!](\sigma) &= \{x \times y \mid x \in \mathbb{E}[\![e_1]\!](\sigma), y \in \mathbb{E}[\![e_2]\!](\sigma)\} \\
\mathbb{E}[\![a[i]]\!](\sigma) &= \mathbb{Z}
\end{aligned}
$$

$$
\begin{aligned}
\mathbb{C}[\![\text{true}]\!](S) &= S \\
\mathbb{C}[\![\text{false}]\!](S) &= \emptyset \\
\mathbb{C}[\![e_1 \leq e_2]\!](S) &= \{\sigma \in S \mid \exists x \in \mathbb{E}[\![e_1]\!], y \in \mathbb{E}[\![e_2]\!] : x \leq y\} \\
\mathbb{C}[\![e_1 = e_2]\!](S) &= \{\sigma \in S \mid \exists x \in \mathbb{E}[\![e_1]\!], y \in \mathbb{E}[\![e_2]\!] : x = y\} \\
\mathbb{C}[\![c_1 \wedge c_2]\!](S) &= \mathbb{C}[\![c_1]\!](S) \cap \mathbb{C}[\![c_2]\!](S) \\
\mathbb{C}[\![c_1 \vee c_2]\!](S) &= \mathbb{C}[\![c_1]\!](S) \cup \mathbb{C}[\![c_2]\!](S) \\
\mathbb{C}[\![\neg c]\!](S) &= \hat{\mathcal{D}} - \mathbb{C}[\![c]\!](S)
\end{aligned}
$$

Approximating semantics

$$\hat{\mathbb{S}}[\![s_1; s_2]\!](S) = \hat{\mathbb{S}}[\![s_2]\!](\hat{\mathbb{S}}[\![s_1]\!](S))$$
$$\hat{\mathbb{S}}[\![v \leftarrow e]\!](S) = \{\sigma[v \mapsto \mathbb{E}[\![e]\!](\sigma)] \mid \sigma \in S\}$$
$$\hat{\mathbb{S}}[\![a[i] \leftarrow e]\!](S) = S$$
$$\hat{\mathbb{S}}[\![\textbf{if } c \textbf{ then } s_1 \textbf{ else } s_2 \textbf{ end if}]\!](S) = \hat{\mathbb{S}}[\![s_1]\!](\mathbb{C}[\![c]\!](S)) \cup \hat{\mathbb{S}}[\![s_1]\!](\mathbb{C}[\![\neg c]\!](S))$$

Approximating semantics

$$\hat{\mathbb{S}}[\![s_1; s_2]\!](S) = \hat{\mathbb{S}}[\![s_2]\!](\hat{\mathbb{S}}[\![s_1]\!](S))$$

$$\hat{\mathbb{S}}[\![v \leftarrow e]\!](S) = \{\sigma[v \mapsto \mathbb{E}[\![e]\!](\sigma)] \mid \sigma \in S\}$$

$$\hat{\mathbb{S}}[\![a[i] \leftarrow e]\!](S) = S$$

$$\hat{\mathbb{S}}[\![\textbf{if } c \textbf{ then } s_1 \textbf{ else } s_2 \textbf{ end if}]\!](S) = \hat{\mathbb{S}}[\![s_1]\!](\mathbb{C}[\![c]\!](S)) \cup \hat{\mathbb{S}}[\![s_1]\!](\mathbb{C}[\![\neg c]\!](S))$$

$$\hat{\mathbb{S}}[\![\textbf{while } c \textbf{ do } s \textbf{ end while}]\!](S) = \text{wait what}$$

Approximating semantics

$$\hat{\mathbb{S}}[\![s_1; s_2]\!](S) = \hat{\mathbb{S}}[\![s_2]\!](\hat{\mathbb{S}}[\![s_1]\!](S))$$
$$\hat{\mathbb{S}}[\![v \leftarrow e]\!](S) = \{\sigma[v \mapsto \mathbb{E}[\![e]\!](\sigma)] \mid \sigma \in S\}$$
$$\hat{\mathbb{S}}[\![a[i] \leftarrow e]\!](S) = S$$
$$\hat{\mathbb{S}}[\![\textbf{if } c \textbf{ then } s_1 \textbf{ else } s_2 \textbf{ end if}]\!](S) = \hat{\mathbb{S}}[\![s_1]\!](\mathbb{C}[\![c]\!](S)) \cup \hat{\mathbb{S}}[\![s_1]\!](\mathbb{C}[\![\neg c]\!](S))$$
$$\hat{\mathbb{S}}[\![\textbf{while } c \textbf{ do } s \textbf{ end while}]\!](S) = \text{wait what}$$

We need some sort of limit of repeatedly applying s! Alternatively, we could find some minimal X such that $X = X \cup \hat{\mathbb{S}}[\![s]\!](\mathbb{C}[\![c]\!](X))$.

Order theory 2

Definition

There is a poset $\omega = \mathbb{N}$ under the standard ordering.

Order theory 2

Definition

There is a poset $\omega = \mathbb{N}$ under the standard ordering.

Definition

An ω-chain in a poset $(P, \sqsubseteq)$ is the image of a monotone map $f : \omega \to P$. Equivalently, it is a sequence $(x_i)_{i \in \omega}$ such that if $i \sqsubseteq j$ then $x_i \sqsubseteq x_j$.

Order theory 2

Definition

There is a poset $\omega = \mathbb{N}$ under the standard ordering.

Definition

An ω-chain in a poset $(P, \sqsubseteq)$ is the image of a monotone map $f : \omega \to P$. Equivalently, it is a sequence $(x_i)_{i \in \omega}$ such that if $i \sqsubseteq j$ then $x_i \sqsubseteq x_j$.

Definition

An ω complete partial order, or ω-CPO is a poset $(C, \sqsubseteq)$ such that all ω-chains (x_i) admit a least upper bound $\bigsqcup_i x_i$ (so $x_j \sqsubseteq \bigsqcup_i x_i$ for all j and is minimal among such). We may call these least upper bounds *joins*. An ω-CPO is *pointed* if it has a least element $\bot$.

Order theory 2

Insert hasse diagram here

Order theory 2

Example

For any set X, the poset $(\mathcal{P}(X), \subseteq)$ is an ω-cpo! Joins are given by unions of sets, $\bigsqcup_i X_i = \bigcup_i X_i$. Moreover, it is pointed by $\emptyset$!

We can think of joins as generalisations of unions, but we will only see instances of non-union joins later.

Order theory 2

Definition

A monotone map $f : C \to D$ of ω-cpos is ω-continuous if for any ω-chain $(x_i)_{i \in \omega}$ in C, $f(\bigsqcup_i x_i) = \bigsqcup_i f(x_i)$.

Theorem (Kleene fixed-point theorem for ω-cpos)

If C is a pointed ω-cpo and $f : C \to C$ is an ω-continuous map, then a fixed point of f exists, and the least fixed point is

$$\mathrm{lfp}(f) = \bigsqcup_i f^i(\bot).$$

Order theory 2

Proof.

Notice that f^i is monotone since it is a composite of monotone maps. Applied to $\bot \sqsubseteq f(\bot)$, we get $f^i(\bot) \sqsubseteq f^{i+1}(\bot)$, so $f^i(\bot)$ does form an ω-chain!



Order theory 2

Proof.

Notice that f^i is monotone since it is a composite of monotone maps. Applied to $\bot \sqsubseteq f(\bot)$, we get $f^i(\bot) \sqsubseteq f^{i+1}(\bot)$, so $f^i(\bot)$ does form an ω-chain!

Next, our computation does give a fixed point, since

$$f\left(\bigsqcup_i f^i(\bot)\right) = \bigsqcup_i f^{i+1}(\bot) = \bigsqcup_i f^i(\bot).$$

□

Order theory 2

Proof.

Notice that f^i is monotone since it is a composite of monotone maps. Applied to $\bot \sqsubseteq f(\bot)$, we get $f^i(\bot) \sqsubseteq f^{i+1}(\bot)$, so $f^i(\bot)$ does form an ω-chain!

Next, our computation does give a fixed point, since

$$f\left(\bigsqcup_i f^i(\bot)\right) = \bigsqcup_i f^{i+1}(\bot) = \bigsqcup_i f^i(\bot).$$

Finally, if x is another fixed-point of f, then applying monotonicity to $\bot \sqsubseteq x$ we get $f^i(\bot) \sqsubseteq f^i(x) = x$, so $\sqsubseteq_i f^i(\bot) \sqsubseteq x$. $\square$

While loops

And now we can define while loop semantics!

While loops

And now we can define while loop semantics!

$$\hat{\mathbb{S}}[\![\textbf{while } c \textbf{ do } s \textbf{ end while}]\!](S) = \mathbb{C}[\![\neg c]\!](\mathrm{lfp}(\lambda X.X \cup \hat{\mathbb{S}}[\![s]\!](\mathbb{C}[\![c]\!](X))))$$

We've finally finished defining the language ...

While loops

And now we can define while loop semantics!

$$\hat{\mathbb{S}}[\![\textbf{while } c \textbf{ do } s \textbf{ end while}]\!](S) = \mathbb{C}[\![\neg c]\!](\mathsf{lfp}(\lambda X.X \cup \hat{\mathbb{S}}[\![s]\!](\mathbb{C}[\![c]\!](X))))$$

We've finally finished defining the language ...
(There are questions about how we can know the inner expression is continuous if we haven't fully defined it but shhh this talk isn't about induction)

Abstract interpretation

The semantics we just described is very non-computable! Abstract interpretation is about approximating our "concrete" semantics so that it becomes computable.

Abstract interpretation

The semantics we just described is very non-computable! Abstract interpretation is about approximating our "concrete" semantics so that it becomes computable.
That is, we want a poset $(A, \sqsubseteq)$ with elements of A easy to represent on a computer, and some computable semantics operator $\mathbb{S}^\sharp[\![s]\!] : A \to A$ for each statement s, that's an approximation of our semantics by a map $\gamma : A \to \hat{\mathcal{D}}$. There are some order theory tricks to help us with this!

Order theory 3

In order to compute least fixed-points, we need a notion of finite joins.

Order theory 3

In order to compute least fixed-points, we need a notion of finite joins.

Definition (Non-binary double feature AND lattice double feature?!)

A poset $(P, \sqsubseteq)$ is a join semi-lattice if every pair of elements x, y has a least upper bound (join) written $x \sqcup y$.

Order theory 3

In order to compute least fixed-points, we need a notion of finite joins.

Definition (Non-binary double feature AND lattice double feature?!)

A poset $(P, \sqsubseteq)$ is a join semi-lattice if every pair of elements x, y has a least upper bound (join) written $x \sqcup y$.

Example

As usual $(\mathcal{P}(X), \sqsubseteq)$ is a join semi-lattice, where joins are unions!

Order theory 3

Definition

If $(C, \sqsubseteq)$ and $(A, \sqsubseteq)$ are posets, and $\alpha : C \rightleftarrows A : \gamma$ are monotone maps, then they form a Galois connection if $\alpha(c) \sqsubseteq a$ iff $c \sqsubseteq \gamma(a)$. We call α the left adjoint and γ the right adjoint. If γ is injective, then we call the pair of maps a Galois embedding.

Order theory 3

Definition

If $(C, \sqsubseteq)$ and $(A, \sqsubseteq)$ are posets, and $\alpha : C \rightleftarrows A : \gamma$ are monotone maps, then they form a Galois connection if $\alpha(c) \sqsubseteq a$ iff $c \sqsubseteq \gamma(a)$. We call α the left adjoint and γ the right adjoint. If γ is injective, then we call the pair of maps a Galois embedding.

Proposition

In a Galois embedding $\alpha : C \rightleftarrows A : \gamma$, $\alpha(\gamma(a)) = a$ for all $a \in A$.

Proof.

Firstly since $\gamma(a) \sqsubseteq \gamma(a)$, $\alpha(\gamma(a)) \sqsubseteq a$ so $\gamma(\alpha(\gamma(a))) \sqsubseteq \gamma(a)$. Next, since $\alpha(\gamma(a)) \sqsubseteq \alpha(\gamma(a))$, $\gamma(a) \sqsubseteq \gamma(\alpha(\gamma(a)))$. Hence $\gamma(\alpha(\gamma(a))) = \gamma(a)$ so by injectivity $\alpha(\gamma(a)) = a$. □

Order theory 3

Galois embeddings let us optimally approximate concrete structure in the abstract structure.

Order theory 3

Galois embeddings let us optimally approximate concrete structure in the abstract structure.

Proposition

In a Galois embedding $\alpha : C \rightleftarrows A : \gamma$, if C is a join semi-lattice, then A is a join semi-lattice with join $a \sqcup b = \alpha(\gamma(a) \sqcup \gamma(b))$.

Proposition

Any operator $f : C \to C$ has its "best abstraction" on A (won't be defined sorry) by $\alpha \circ f \circ \gamma$.

Order theory 3

Galois embeddings let us optimally approximate concrete structure in the abstract structure.

Proposition

In a Galois embedding $\alpha : C \rightleftarrows A : \gamma$, if C is a join semi-lattice, then A is a join semi-lattice with join $a \sqcup b = \alpha(\gamma(a) \sqcup \gamma(b))$.

Proposition

Any operator $f : C \to C$ has its "best abstraction" on A (won't be defined sorry) by $\alpha \circ f \circ \gamma$.


This gives us approximation semantics for free yay

Value domains

Instead of approximating $\hat{\mathcal{D}}$ directly, we can approximate $\mathcal{P}(\mathbb{Z})$.

Value domains

Instead of approximating $\hat{\mathcal{D}}$ directly, we can approximate $\mathcal{P}(\mathbb{Z})$.


- $A =$ 

.

  $\gamma(+) = \{n \in \mathbb{Z} \mid n > 0\}$ and $\alpha(S) = +$ if S is all positive etc.

Value domains

Instead of approximating $\hat{\mathcal{D}}$ directly, we can approximate $\mathcal{P}(\mathbb{Z})$.


- $A =$ 

.

  $\gamma(+) = \{n \in \mathbb{Z} \mid n > 0\}$ and $\alpha(S) = +$ if S is all positive etc.
- $A = \{[a, b] \mid a, b \in \mathbb{Z} \cup \{-\infty, \infty\}; a \leq b\}$ ordered by subsets.
  $\gamma([a, b]) = [a, b]$ and $\alpha(S) = [\min(S), \max(S)]$.

Value domains

Instead of approximating $\hat{\mathcal{D}}$ directly, we can approximate $\mathcal{P}(\mathbb{Z})$.

- $A =$ 

.

  $\gamma(+) = \{n \in \mathbb{Z} \mid n > 0\}$ and $\alpha(S) = +$ if S is all positive etc.
- $A = \{[a, b] \mid a, b \in \mathbb{Z} \cup \{-\infty, \infty\}; a \leq b\}$ ordered by subsets.
  $\gamma([a, b]) = [a, b]$ and $\alpha(S) = [\min(S), \max(S)]$.

We'll focus on intervals for the rest of this talk.

Example again

$F \leftarrow \underbrace{[0, \ldots, 0]}_{\text{100 of them}}$

if $\neg(0 \leq 0 \leq 99 \wedge 0 \leq 1 \leq 99)$ **then**

  explode (out of bounds)

end if

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

$i \leftarrow 2$

while $i < 100$ **do**

  if $\neg(0 \leq i - 2 \leq 99 \wedge 0 \leq i - 1 \leq 99 \wedge 0 \leq i \leq 99)$ **then**

    explode (out of bounds)

  end if

  $F[i] \leftarrow F[i - 1] + F[i - 2]$

  $i \leftarrow i + 1$

end while

return F

At the second bounds check, $i \in [2, 99]$!!

Computing Interval semantics

We have best approximations of the interval domain, is it computable though?!