



# Digital signatures

GIANLUCA DINI  
Dept. of Ingegneria dell'Informazione  
University of Pisa  
email: [gianluca.dini@unipi.it](mailto:gianluca.dini@unipi.it)  
Version: 2022-05-01



1

Digital Signatures

# OVERVIEW


May-22

Digital signatures

2

2

# The problem



UNIVERSITÀ DI PISA

- Alice and Bob share a secret key  $k$
- Alice receives and decrypts a message which makes semantic sense
- Alice concludes that the message comes from Bob
  - Message origin authentication → message integrity
    - Beware, we know that ciphers are malleable!
    - MDC / MAC do not change the reasoning


May-22

Digital signatures

3

3

# The problem



UNIVERSITÀ DI PISA

- The reasoning above works under the assumption of mutual trust
  - If a dispute arise, Alice cannot prove to a third party that Bob generated the message
- There are practical cases in which Alice and Bob wish to securely communicate but they don't trust each other
  - E.g.: e-commerce: customer and merchant have conflicting interests


May-22

Digital signatures

4

4

# The problem



UNIVERSITÀ DI PISA

- Provability/verifiability requirement
  - If a dispute arises an unbiased third party must be able to solve the dispute equitably, without requiring access to the signer's secret
- Symmetric cryptography is of little help
  - Alice and Bob have the same knowledge and capabilities
- Public-key cryptography is the solution
  - Make it possible to distinguish the actions performed by who knows the private key


May-22

Digital signatures

5

5

# Digital signature scheme



UNIVERSITÀ DI PISA


- A signature scheme is defined by three algorithms
- Key generation algorithm  $G$ 
  - takes as input  $1^n$  and outputs  $(\text{pubk}, \text{privk})$
- Signature generation algorithm  $S$ 
  - takes as input a private key  $\text{privk}$  and a message  $x$  and outputs a signature  $\sigma = S(\text{privk}, x)$
- Signature verification algorithm  $V$ 
  - takes as input a public key  $\text{pubk}$ , a signature  $\sigma$  and (optionally) a message  $x$  and outputs True o False

May-22

Digital signatures

6

6



7

# Security model

- Threat model
  - Adaptive chosen-message attack
    - Assume the attacker can induce the sender to sign *messages of the attacker's choice*
    - The attacker knows the public key
  - Security goal: existential unforgeability
    - Attacker should be *unable* to forge valid signature on *any* message not signed by the sender


May-22

Digital signatures

8

8

## Properties




UNIVERSITÀ DI PISA

- Consistency Property
  - For all  $x$  and  $(\text{pubk}, \text{privk})$ ,  $V(\text{pubk}, [x] S(\text{privk}, x)) = \text{TRUE}$
- Security property (informal)
  - Even after observing signatures on multiple messages, an attacker should be unable to forge a valid signature on a new message

May-22 Digital signatures 9

9

## Comments




UNIVERSITÀ DI PISA

- Security property implies
  - Integrity
  - Verifiability
  - Non-repudiation
  - No confidentiality
    - Use a cipher (AES, 3DES,...) if confidentiality is a requirement

May-22 Digital signatures 10

10

# Algorithm families



- Integer factorization
  - RSA
- Discrete logarithm
  - ElGamal, DSA
- Elliptic curves
  - ECDSA

May-22

Digital signatures

11

11

Digital signatures

# NON-REPUDIATION VS AUTHENTICATION

May-22

Digital signatures

12

12

## Non-repudiation



UNIVERSITÀ DI PISA

- Non-repudiation prevents a signer from signing a document and subsequently being able to successfully deny having done so.

May-22

Digital signatures

13

13

## Non-repudiation vs authentication



UNIVERSITÀ DI PISA


- Authentication
  - Based on symmetric cryptography
  - Allows a party to convince itself or a mutually trusted party of the integrity/authenticity of a given message at a given time  $t_0$
- Non-repudiation
  - based on public-key cryptography
  - allows a party to convince others at any time  $t_1 \geq t_0$  of the integrity/authenticity of a given message at time  $t_0$

May-22

Digital signatures

14

14

  
UNIVERSITÀ DI PISA

## Dig sig vs non-repudiation


- Data origin authentication as provided by a digital signature is valid only while the secrecy of the signer’s private key is maintained
- A threat that must be addressed is a signer who intentionally discloses his private key, and thereafter claims that a previously valid signature was forged
- This threat may be addressed by
  - Prevent direct access to the key
  - Use of a trusted timestamp agent
  - Use of a trusted notary agent

May-22


Digital signatures

15

15

  
UNIVERSITÀ DI PISA

## Trusted Timestamping Service



Bob sends  $X, s$  to Alice. Alice sends  $s$  to Trent. Trent responds with  $S_T(\text{priv}K_T, s || t_0)$ .

- Trent certifies that digital signature  $s$  exists at time  $t_0$
- If Bob’s  $\text{priv}K_B$  is compromised at  $t_1 > t_0$ , then  $s$  is valid

May-22


Digital signatures

16

16



# Trusted Notary Service



UNIVERSITÀ DI PISA

- TNS generalize the TTS
- Trent certifies that a certain statement on the digital signature  $s$  is true at a certain time  $t_0$
- Examples of statements
  - Signature  $s$  exists at time  $t_0$
  - Signature  $s$  is valid at time  $t_0$
- Trent may certify the existence of a certain document
  - $s = S(\text{privKT}, H(\text{documents}) || \text{timestamp})$
  - Document remains secret
- Trent is trusted to verify the statement before issuing it

May-22

Digital signatures

17

17

Digital Signatures

# COMPARISON TO MAC

May-22


Digital signatures

18

18

## Digital signatures

- Provide *integrity* in the public-key setting
- Analogous to message authentication codes (MACs) but some key differences...



UNIVERSITÀ DI PISA


May-22

Digital signatures

19

19

## Prototypical application



Patch distribution (Microsoft, Adobe)

$(pk, sk)$   
 $\sigma = S(sk, \text{patch})$


patch,  $\sigma$

pk

pk

pk

pk



UNIVERSITÀ DI PISA

May-22

Digital signatures

20

20

# Comparison to MACs

Patch distribution (Microsoft, Adobe)

$t' = \text{MAC}(k, \text{patch}')$

$\text{patch}', t'$

$\text{patch}, t$

$k$

$t = \text{MAC}(k, \text{patch})$

May-22

Digital signatures

21

21

# Comparison to MACs

Patch distribution (Microsoft, Adobe)

$k_1$

$k_2$

$k_3$

$\text{patch}, t_1, t_2, t_3, \dots$

$k$

$t_i = \text{MAC}(k_i, \text{patch})$


May-22

Digital signatures

22

22

## Comparison to MACs



- Single shared key  $k$ 
  - A client may forge the tag
  - Unfeasible if clients are not trusted
- Point-to-point key  $k_i$ 
  - Computing and network overhead
  - Prohibitive key management overhead
  - Unmanageable!


May-22

Digital signatures

23

23

## Comparison to MACs



- Public verifiability
  - Dig Sig: anyone can verify the signature
  - MAC: Only a holder of the key can verify a MAC tag
- Transferability
  - Dig Sig can forward a signature to someone else
  - MAC cannot


May-22

Digital signatures

24

24

# Comparison to MACs



UNIVERSITÀ DI PISA

- **Nonrepudiability**
  - Signer cannot (easily) deny issuing a signature
    - Crucial for legal application
    - Judge can verify signature using a copy of pK
  - MACs cannot provide this functionality
    - Without access to the key, no way to verify a tag
    - Even if receiver leaks key to judge, how can the judge verify the key is correct?
    - Even if the key is correct, receiver could have generated the tag!

May-22

Digital signatures

25

25

Digital signatures

# THE RSA SIGNATURE SCHEME


May-22

Digital signatures

26

26

## Plain RSA




UNIVERSITÀ DI PISA

- Key generation
  - $(e, n)$  public key;  $(d, n)$  private key
- Signing operation
  - $\sigma = x^d \bmod n$
- Verification operation
  - Return  $(x == \sigma^e \bmod n)$

May-22 Digital signatures 27

27

## Properties




UNIVERSITÀ DI PISA

- Computational aspects
  - *The same considerations as PKE*
- Security
  - Algorithmic attacks
    - Factoring
  - Existential forgery
  - Malleability

May-22 Digital signatures 28

28



UNIVERSITÀ DI PISA

## Existential forgery


- Given public key  $(n, e)$ , generate a valid signature for a random message  $x$ 
  - Choose a signature  $\sigma$
  - Compute  $x = \sigma^e \bmod n$
  - Output  $x, \sigma$
  - Message  $x$  is random and may have no application meaning.
  - However, this property is highly undesirable

May-22

Digital signatures

29

29



UNIVERSITÀ DI PISA

## Malleability

- Combine two signatures to obtain a third (existential forgery)
  - Exploit the homomorphic property of RSA
- The attack
  - Given  $\sigma_1 = x_1^d \bmod n$
  - Given  $\sigma_2 = x_2^d \bmod n$
  - Output  $\sigma_3 \equiv (\sigma_1 \cdot \sigma_2) \bmod n$  that is a valid signature of  $x_3 \equiv (x_1 \cdot x_2) \bmod n$ 
    - PROOF.  
$$x_3 = \sigma_3^e \equiv (\sigma_1 \cdot \sigma_2)^e \equiv \sigma_1^e \cdot \sigma_2^e \equiv x_1^{de} \cdot x_2^{de} \equiv x_1 \cdot x_2 \bmod n$$


May-22

Digital signatures

30

30

# RSA Padding



UNIVERSITÀ DI PISA

- Plain RSA is never used
  - Because of existential forgery and malleability,
- Padding
  - Padding allows only certain message formats
    - It must be difficult to choose a signature whose corresponding message has that format
  - Probabilistic Signature Scheme in PKCS#1
    - Encoding Method for Signature with Appendix (EMSA)


May-22

Digital signatures

31


31

# PSS



UNIVERSITÀ DI PISA

- The message is encoded before signing
  - $s = EM^d \bmod n$  where
    - $M$  = message
    - $EM$  = encoded message
    - salt : random value
      - Makes  $s$  probabilistic
    - MGF: mask generation function
    - fixed values:
      - $bc$ , padding1, padding2



```
graph TD
    M[M] --> H1((Hash))
    H1 --> M_prime["M' = [padding1 | mHash | salt]"]
    M_prime --> H2((Hash))
    H2 --> DB["DB = [padding2 | salt]"]
    DB --> XOR((⊕))
    H2 --> MGF((MGF))
    MGF --> XOR
    XOR --> EM["EM = [maskedDB | H | bc]"]
```

May-22

Digital signatures

32

32



Digital Signatures


DIGITAL SIGNATURES VS HASH  
FUNCTIONS

May-22

Digital signatures

33

33



UNIVERSITÀ DI PISA

Signing long messages

- Consider RSA digsig
  - Message  $0 \leq x < n$ 
    - E.g.,  $n = 1024\text{--}3072$  bits (128–384 bytes)
  - What if  $x > n$ ?
  - An ECB-like approach is not recommended
    1. High-computational load (performance)
    2. Message overhead (performance)
    3. Block reordering and substitution (security)
- We would like to have a short signature for messages on any length
- The solution of this problem is hash functions

May-22

Digital signatures

34

34

## Dig sig vs hash properties

- Hash functions properties
  - Pre-image resistance
  - Second pre-image resistance
  - Collision resistance
- These properties are crucial for digital signatures security



UNIVERSITÀ DI PISA

May-22


Digital signatures

35

35

## Dig sig vs hash properties

- Pre-image Resistance
  - Digital signature scheme based on (school-book) RSA
    - $(n, d)$  is Alice's private key;
    - $(n, e)$  is Alice's public key
    - $s = (H(x))^d \pmod n$
  - If  $H$  is not pre-image resistant, then existential forgery is possible
    - Select  $z < n$
    - Compute  $y = z^e \pmod n$
    - Find  $x'$  such that  $H(x') = y$  (⚡)
    - Claim that  $z$  is the digital signature of  $m'$  Q.E.D



UNIVERSITÀ DI PISA


May-22

Digital signatures

36

36

## Dig sig vs hash properties



UNIVERSITÀ DI PISA

- 2<sup>nd</sup> preimage resistance
  - The protocol
    - Bob → Alice:  $x$
    - Alice → Bob:  $x, s = S(\text{priv}K_A, H(x))$
  - If  $H$  is not 2nd-preimage resistant, the following attack is possible
    - An adversary (e.g., Alice herself) can determine a 2nd-preimage  $x'$  of  $x$  and then (⚡) and then
    - claim that Alice has signed  $x'$  instead of  $x$  Q.E.D


May-22

Digital signatures

37

37

## Dig sig vs hash properties



UNIVERSITÀ DI PISA

- Collision-resistance
  - If  $H$  is not collision resistant, the following attack is possible
    - Alice chooses  $x$  and  $x'$  s.t.  $H(x) = H(x')$  (⚡)
    - computes  $s = S(\text{priv}K_A, H(x))$
    - Sends  $(x, s)$  to Bob
    - later claims that she actually sent  $(x', s)$  Q.E.D


May-22

Digital signatures

38

38

# Hash-and-Sign paradigm




UNIVERSITÀ DI PISA

- Given a signature scheme  $\Sigma = (G, S, V)$  for “short” messages of length  $n$
- Given a Hash function  $H: \{0, 1\}^* \rightarrow \{0, 1\}^n$
- Construct a signature scheme  $\Sigma' = (G, S', V')$  for messages of any length
  - $\sigma = S'(\text{privK}, m) = S(\text{privK}, H(m))$
  - $V'(m, \text{pubK}, \sigma) = V(H(m), \text{pubK}, \sigma)$

May-22      Digital signatures      39

39

# Hash-and-sign paradigm



UNIVERSITÀ DI PISA

- THM. If  $\Sigma$  is secure and  $H$  is collision-resistant, then  $\Sigma'$  is secure
  - PROOF (by contradiction)
  - Assume that the sender authenticates  $m_1, m_2, \dots$  and manages to forge  $(m', \sigma')$ ,  $m' \neq m_i$ , for all  $i$
  - Let  $h_i = H(m_i)$ . Then, we have two cases
    - If  $H(m') = h_i$  for some  $i$ , then collision in  $H$  (contradiction)
    - If  $H(m') \neq h_i$ , for all  $i$ , then forgery in  $\Sigma$  (contradiction)

May-22      Digital signatures      40

40

Digital signatures

RSA-BASED BLIND SIGNATURES


May-22

Digital signatures

41

41

Blind signatures



UNIVERSITÀ DI PISA

• Intuition

– In a blind signature scheme, the signer can’t see what it is signig

• Unlinkabiliy

– The signer is not able to link the signature to the act of signing

May-22

Digital signatures

42

42

# The metaphor

Document to be signed

Carbon paper

John Smith

John Smith

John Smith

John Smith

John Smith

May-22

Digital signatures

43

43

# Blind signatures

→

UNIVERSITÀ DI PISA

- The protocol
  - Alice
    - Randomly chooses  $b$  s.t.  $\gcd(b, n) = 1$
    - Computes  $x' \equiv x \cdot b^e \pmod n$
    - Sends  $x'$  to Bob (signer)
    - Inviare  $x'$  al signer
  - Bob
    - Receive  $x'$
    - Compute  $s' \equiv (x')^d \pmod n$
    - Returns  $s'$  Alice


May-22

Digital signatures

44

44

# Blind signatures



UNIVERSITÀ DI PISA

→

- The protocol
  - Alice
    - Receive  $s'$
    - Compute  $s \equiv s' \cdot b^{-1} \pmod n$ 
      - $s$  is digital signature of  $s$
  - Proof
    - $s' \cdot b^{-1} \equiv (x')^d \cdot b^{-1} \equiv (x \cdot b^e)^d \cdot b^{-1} \equiv x^d \cdot b^{ed} \cdot b^{-1} \equiv x^d \cdot b \cdot b^{-1} \equiv x^d \equiv s \pmod n$

QED


May-22

Digital signatures

45

45

# Applications



UNIVERSITÀ DI PISA

- Privacy related applications
  - Digital cash (David Chaum, 1983)
  - Electronic voting

May-22

Digital signatures

46

46

### Digital cash

The diagram illustrates a digital cash transaction flow with the following steps:

- Issuer** sends **cash equivalent** to **Acquirer** (Step 7).
- Acquirer** sends **certified coin** to **Issuer** (Step 6).
- Issuer** sends **certified coin** to **Customer** (Step 2).
- Customer** sends **Goods/service** to **Merchant** (Step 3).
- Merchant** sends **certified coin** to **Acquirer** (Step 5).
- Acquirer** sends **certified coin** to **Merchant** (Step 4).

Additional labels in the diagram include:

- untraceable** (circled around steps 1 and 2)
- certified coin** (multiple instances)

- coin: a random number
- coin- $b^e$ : blinded coin
- coin, coin $^d$ : certified coin
- $d_{10€}$ : a 10€ worth bank's private key

May-22

Digital signatures

47

47

### Digital cash

The diagram illustrates a digital cash transaction flow with the following steps:

- Issuer** sends **coin, coin $^d$**  to **Acquirer**.
- Acquirer** sends **coin, coin $^d$**  to **Merchant**.
- Merchant** sends **coin, coin $^d$**  to **Customer**.
- Customer** sends **coin $^d$ .b** to **Issuer**.
- Issuer** sends **coin.b $^e$**  to **Acquirer**.

Additional labels in the diagram include:

- untraceable** (circled around steps 3 and 4)
- coin, coin $^d$**  (multiple instances)
- coin.b $^e$**
- coin $^d$ .b**

- coin: a random number
- coin- $b^e$ : blinded coin
- coin, coin $^d$ : certified coin
- $d_{10€}$ : a 10€ worth bank's private key

May-22


Digital signatures

48

48



## Double spending



→

- The protocol does not prevent
  - the customer from spending the digital coin multiple times
  - The merchant from depositing the digital coin multiple times
- Partial countermeasure
  - The issuer maintains the list of spent digital coins
    - Protect the bank from frauds
    - Don't allow issuer to identify the fraudster


May-22

Digital signatures

49

49

## Double spending



↓

- Purely cryptographic solution based on
  - Secret splitting
  - Bit commitment
  - Cut-and-choose
- Inefficient but great impulse to cryptography

May-22

Digital signatures

50

50

Digital signatures

THE ELGAMAL SIGNATURE SCHEME


May-22

Digital signatures

51

51

Elgamal in a nutshell



UNIVERSITÀ DI PISA

- Invented in 1985
- Based on difficulty of discrete logarithm
- Digital signature operations are different from the cipher operations

May-22

Digital signatures

52

52

## Key generation



UNIVERSITÀ DI PISA

- Choose a large prime  $p$
- Choose a primitive element  $\alpha$  of (a subgroup of)  $\mathbb{Z}_p^*$
- Choose a random number  $d \in \{2, 3, \dots, p-2\}$
- Compute  $\beta = \alpha^d \bmod p$
- $\text{pubK} = (p, \alpha, \beta)$  is the public key and
- $\text{privK} = d$  is the private key

May-22

Digital signatures

53

53

## Signature generation



UNIVERSITÀ DI PISA

- Message  $x$
- Choose an ephemeral key  $k_E$  in  $\{0, 1, 2, p-2\}$  such that  $\gcd(k_E, p-1) = 1$
- Compute the signature parameters
  - $r \equiv \alpha^{k_E} \bmod p$
  - $s \equiv (x - d \cdot r) k_E^{-1} \bmod p-1$
  - $(r, s)$  is the digital signature
- Send  $\langle x, (r, s) \rangle$

May-22

Digital signatures

54

54

## Signature verification



UNIVERSITÀ DI PISA

- Verification of  $\langle x, (r, s) \rangle$
- Compute  $t \equiv \beta^r \cdot r^s \pmod{p}$
- If  $(t \equiv \alpha^x \pmod{p}) \rightarrow$  valid signature;  
otherwise  $\rightarrow$  invalid signature

May-22

Digital signatures

55

55

## Proof



UNIVERSITÀ DI PISA

1. Let  $t \equiv \beta^r \cdot r^s \equiv (\alpha^d)^r (\alpha^{k_E})^s \equiv \alpha^{d \cdot r + k_E \cdot s} \pmod{p}$
2. If  $\beta^r \cdot r^s \equiv \alpha^x \pmod{p}$  then  $\alpha^x \equiv \alpha^{d \cdot r + k_E \cdot s} \pmod{p}$  [a]
3. According to Fermat's Little Theorem Eq.[a] holds if  
 $x \equiv d \cdot r + k_E \cdot s \pmod{p-1}$
4. from which the construction of parameter  
 $s = (x - d \cdot r) k_E^{-1} \pmod{p-1}$

May-22

Digital signatures

56

56

## Computational aspects



UNIVERSITÀ DI PISA

- Key generation
  - Generation of a large prime (1024 bits)
  - True random generator for the private key
  - Exponentiation by square-and-multiply
- Signature generation
  - $|s| = |r| = |p|$  thus  $|x, (r, s)| = 3 |x|$  (*msg expansion*)
  - One exponentiation by square-and-multiply
  - One inverse  $k_E^{-1} \bmod p$  by EEA (pre-computation)
- Signature verification
  - Two exponentiations by square-and-multiply
  - One multiplication

May-22

Digital signatures

57

57

## Security aspects



UNIVERSITÀ DI PISA

- The verifier must have the correct public key
- The DLP must be intractable
- Ephemeral key cannot be reused
  - If  $k_E$  is reused the adversary can compute the private key  $d$  and impersonate the signer
- Existential forgery for a random message  $x$  unless it is hashed

May-22


Digital signatures

58

58

## Reuse of ephemeral key

- If the ephemeral key  $k_E$  is reused, an attacker can easily compute the private key  $d$ 
  - Proof
    - Message  $x_1$  and  $x_2$  and the reused ephemeral key  $k_E$  reused
    - $(x_1, (s_1, r))$  and  $(x_2, (s_2, r))$  where
      - $r \equiv \alpha^{k_E} \bmod p$
      - $s_1 \equiv (x_1 - d \cdot r) \cdot k_E^{-1} \bmod p - 1$  [a]
      - $s_2 \equiv (x_2 - d \cdot r) \cdot k_E^{-1} \bmod p - 1$  [b]
      - » [a], [b] is a system in two unknowns and two equations
      - $s_1 - s_2 \equiv (x_1 - x_2) \cdot k_E^{-1} \bmod p - 1$
      - $k_E \equiv (x_1 - x_2) \cdot (s_1 - s_2)^{-1} \bmod p - 1$
      - $d \equiv (x_1 - s_1 \cdot k_E) \cdot r^{-1} \bmod p - 1$



UNIVERSITÀ DI PISA

May-22


Digital signatures

59

59

## Existential Forgery Attack

- The attack



UNIVERSITÀ DI PISA

**Alice**

**Adversary**

**Bob**

privK = d, pubK = (p,  $\alpha$ ,  $\beta$ )

< -----( $p$ ,  $\alpha$ ,  $\beta$ )-----

1. select  $i, j$ , s.t.  $\gcd(j, p - 1) = 1$

2. compute the signature

$r \equiv \alpha^i \cdot \beta^j \bmod p$

$s \equiv -r \cdot j^{-1} \bmod p - 1$

3. compute the message

$x \equiv s \cdot i \bmod p - 1$

< -----( $x$ , ( $r$ ,  $s$ ))-----

verification

$t \equiv \beta^r \cdot r^s \bmod p$  since

$t \equiv \alpha x \bmod p \rightarrow$  valid signature!


May-22

Digital signatures

60

60

# Existential forgery



- Proof
$$\begin{aligned}t &\equiv \beta^r \cdot r^s \equiv (\alpha^d)^r \cdot (\alpha^i \cdot \beta^j)^s \equiv (\alpha^d)^r \cdot (\alpha^i \cdot \alpha^{d \cdot j})^s \equiv \alpha^{d \cdot r} \cdot (\alpha^{i+d \cdot j})^s \\&\equiv \alpha^{d \cdot r} \cdot (\alpha^{i+d \cdot j})^s \equiv \alpha^{d \cdot r} \cdot \alpha^{(i+d \cdot j) \cdot (-r \cdot j^{-1})} \equiv \\&\equiv \alpha^{d \cdot r} \cdot \alpha^{-d \cdot r} \cdot \alpha^{-r \cdot i \cdot j^{-1}} \equiv \alpha^{s \cdot i} \bmod p \text{ [a]}\end{aligned}$$
  - As the message was constructed as  $x \equiv s \cdot i \bmod p$  then equation [a]  $\alpha^{s \cdot i} \equiv \alpha^x \bmod p$  which is the condition to accept the signature as valid
  - The adversary computes in step 3 the message  $x$  whose semantics ( $s$ ) cannot control
  - The attack is not feasible if the message is hashed
    - $s \equiv (H(x) - d \cdot r)k_E^{-1} \bmod p - 1$

May-22

Digital signatures

61

61

# Digital Signatures


## DIGITAL SIGNATURE ALGORITHM (DSA)

May-22

Digital signatures

62

62




UNIVERSITÀ DI PISA

## Introduction

- The Elgamal scheme is rarely used in practice
- DSA is a more popular variant
  - It's a federal US government standard for digital signatures (DSS)
  - It was proposed by NIST
- Advantages of DSA w.r.t. Elgamal
  - Signature is only 320 bits
  - Some attacks against to Elgamal are not applicable to DSA

May-22 Digital signatures 63

63



UNIVERSITÀ DI PISA

## Key Generation


1. Generate a prime  $p$  with  $2^{1023} < p < 2^{1024}$ .
2. Find a prime divisor  $q$  of  $p-1$  with  $2^{159} < q < 2^{160}$ .
3. Find an element  $\alpha$  with  $\text{ord}(\alpha) = q$ , i.e.,  $\alpha$  generates the subgroup with  $q$  elements.
4. Choose a random integer  $d$  with  $0 < d < q$ .
5. Compute  $\beta \equiv \alpha^d \pmod{p}$ .
6. The keys are now:
  1.  $\text{pubK} = (p, q, \alpha, \beta)$
  2.  $\text{privK} = (d)$

May-22 Digital signatures 64

64



## Central idea



- DSA uses two cyclic groups
  - $Z_p^*$ , the order of which has bit length 2014 bit
  - 160-bit subgroup of  $Z_p^*$
  - This setup yields shorter signatures
- Other combinations are possible

$p$	$q$	signature
1024	160	320
2048	224	448
3072	256	512


May-22

Digital signatures

65

65

## Signature Generation



1. Choose an integer as random ephemeral key  $k_E$  with  $0 < k_E < q$ .
2. Compute  $r \equiv (\alpha^{k_E} \bmod p) \bmod q$ .
3. Compute  $s \equiv (\text{SHA}(x) + d \cdot r)k_E^{-1} \bmod q$ .
  - SHA-1( $\cdot$ ) produces a 160-bit value
4. Digital signature is the pair  $(r, s)$ 
  - $160 + 160 = 320$  bit long


May-22

Digital signatures

66

66

# Signature Verification



UNIVERSITÀ DI PISA

1. Compute auxiliary value  $w \equiv s^{-1} \bmod q$ .
2. Compute auxiliary value  $u_1 \equiv w \cdot \text{SHA}(x) \bmod q$ .
3. Compute auxiliary value  $u_2 \equiv w \cdot r \bmod q$ .
4. Compute  $v \equiv (\alpha^{u_1} \cdot \beta^{u_2} \bmod p) \bmod q$ .
5. The verification follows from:
  1. If  $v \equiv r \bmod q \rightarrow$  valid signature
  2. Otherwise  $\rightarrow$  invalid signature


May-22

Digital signatures

67

67

# Proof



UNIVERSITÀ DI PISA

%

- We show that a signature  $(r, s)$  satisfies the verification condition  $v \equiv r \bmod q$ .
  - $s \equiv (\text{SHA}(x) + d \cdot r) k_E^{-1} \bmod q$  which is equivalent to  $k_E \equiv s^{-1} \cdot \text{SHA}(x) + d \cdot s^{-1} \cdot r \bmod q$ .
  - The right-hand side can be expressed in terms of the auxiliary values  $u_1$  and  $u_2$ :  $k_E \equiv u_1 + d \cdot u_2 \bmod q$ .
  - We can raise  $\alpha$  to either side of the equation if we reduce modulo  $p$ :  $\alpha^{k_E} \bmod p \equiv \alpha^{u_1 + d \cdot u_2} \bmod p$ .


May-22

Digital signatures

68

68

# Proof




UNIVERSITÀ DI PISA

- Since the public key value  $\beta$  was computed as  $\beta \equiv \alpha^d \pmod p$ , we can write:  $\alpha^{kE} \equiv \alpha^{u1} \beta^{u2} \pmod p$ .
- We now reduce both sides of the equation modulo  $q$ :  $(\alpha^{kE} \pmod p) \pmod q \equiv (\alpha^{u1} \beta^{u2} \pmod p) \pmod q$ .
- Since  $r$  was constructed as  $r \equiv (\alpha^{kE} \pmod p) \pmod q$  and  $v \equiv (\alpha^{u1} \beta^{u2} \pmod p) \pmod q$ ,
- this expression is identical to the condition for verifying a signature as valid:
  - $r \equiv v \pmod q$ .

May-22      Digital signatures      69

# Computational aspects




UNIVERSITÀ DI PISA

- Key Generation
  - The most challenging phase
    - Find a  $Z_p^*$  with 1024-bit prime  $p$  and a subgroup in the range of  $2^{160}$ 
      - This condition is fulfilled if  $|Z_p^*| = |p - 1|$  has a prime factor  $q$  of 160 bit
  - General approach:
    - To find  $q$  first and then  $p$

May-22      Digital signatures      70

# Computational aspects



UNIVERSITÀ DI PISA

%

- Signing
  - Computing  $r$  requires exponentiation
    - Operands are on 1024 bit
    - Exponent  $q$  is on 160 bit
      - On average  $160 + 80 = 240$  SQs and MULTs
    - Result is reduced mod  $q$
    - Does not depend on  $x$  so can be precomputed
  - Computing  $s$ 
    - Involve 160-bit operands
    - The most costly operation is inverse


May-22

Digital signatures

71

71

# Computational aspects



UNIVERSITÀ DI PISA

- Verification
  - Computing the auxiliary parameters  $w$ ,  $u_1$  and  $u_2$  involves 160-bit operands
  - This is relatively fast


May-22

Digital signatures

72

72

# Security



UNIVERSITÀ DI PISA

- We have to protect from two different DLPs
  1.  $d = \log_{\alpha} \beta \bmod p$ .
    - Index calculus attack
      - Prime  $p$  must be on 1024 bits for 80-bit security level
  2.  $\alpha$  generates a subgroup of order  $q$ 
    - Index calculus attack cannot be applied
    - Only generic DLP attacks can be used
      - Square-root attacks: Baby-step giant-step, Pollard’s rho
      - Running time:  $\sqrt{q} = \sqrt{2^{160}} = 80$
- Vulnerable to  $k_E$  reuse
  - Analogue to ElGamal

May-22

Digital signatures

73

73

May-22

Digital signatures

74

74