

# Diffie-Hellman Key Exchange

Gianluca Dini

Dept. of Ingegneria dell'Informazione

University of Pisa

Email: [gianluca.dini@unipi.it](mailto:gianluca.dini@unipi.it)

Version: 2022-04-27

1

## Preliminaries



UNIVERSITÀ DI PISA

- Whitfield Diffie and Martin Hellman, [New directions in cryptography](#), IEEE Transactions of Information Theory, 22(6), pp. 644-654, Nov. 1976
- Cryptosystem for key establishment
- One-way function
  - $f(x)$ : discrete exponentiation is computationally “easy”
  - $f^{-1}(x)$ : discrete logarithm it is computationally “difficult”

2

## Preliminaries



UNIVERSITÀ DI PISA

- Mathematical foundation
  - Abstract algebra: groups, sub-groups, finite groups and cyclic groups
- We operate in the *multiplicative group*  $\mathbb{Z}_p^*$  with addition and multiplication modulo  $p$ , with  $p$  prime
  - $\mathbb{Z}_p^*$  is the set of integers  $i$  belonging to  $[0, \dots, p-1]$ , s.t.  $\gcd(i, p) = 1$
  - Ex.  $\mathbb{Z}_{11}^* = \{1, 2, 3, 4, 5, 6, 7, 8, 9, 10\}$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

3

3

## Facts on modular arithmetic



UNIVERSITÀ DI PISA

- Multiplication is commutative
  - $(a \times b) \equiv (b \times a) \pmod{n}$
- Exponentiation is commutative
  - $(a^x)^y \equiv (a^y)^x \pmod{n}$
- Power of power is commutative
  - $(a^b)^c \equiv a^{bc} \equiv a^{cb} \equiv (a^c)^b \pmod{n}$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

4

4

## Facts on modular arithmetic



UNIVERSITÀ DI PISA

- Parameters
  - Let  $p$  be prime and  $g \in \mathbb{Z}_p^*$  be a *primitive element* (or *generator*), i.e., for each  $y = 1, 2, \dots, p-1$ , there is  $x$  s.t.  $y \equiv g^x \pmod{p}$
- Discrete Exponentiation
  - Given  $x \in \mathbb{Z}_p^*$ , compute  $y \in \mathbb{Z}_p^*$  s.t.  $y = g^x \pmod{p}$
- Discrete Logarithm Problem (DLP)
  - Given  $y \in \mathbb{Z}_p^*$ , determine  $x \in \mathbb{Z}_p^*$  s.t.  $y = g^x \pmod{p}$ 
    - Notation  $x = \log_g y \pmod{p}$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

5

5

## Properties of discrete log



UNIVERSITÀ DI PISA

- $\log_g(\beta\gamma) \equiv (\log_g\beta + \log_g\gamma) \pmod{p}$
- $\log_g(\beta)^s \equiv s(\log_g\beta) \pmod{p}$


Foundations of Cybersecurity


Diffie-Hellman Key Exchange

6

6

# The Diffie-Hellman Protocol





UNIVERSITÀ DI PISA

## SETUP

- Let  $p$  be a large prime (600 digits, 2000 bits)
- Let  $1 < g < p$  a generator
- Let  $p$  and  $g$  be publicly known

- THE DIFFIE-HELLMAN KEY EXCHANGE (DHKE)
  - Alice chooses a random secret number  $a$  (private key)
  - Bob chooses a random secret number  $b$  (public key)
  - M1: Alice  $\rightarrow$  Bob:  $A, Y_A \equiv g^a \bmod p$  (public key)
  - M2: Bob  $\rightarrow$  Alice:  $B, Y_B \equiv g^b \bmod p$  (public key)
  - Alice computes  $K_{AB} \equiv (Y_B)^a \equiv g^{ab} \bmod p$
  - Bob computes  $K_{AB} \equiv (Y_A)^b \equiv g^{ab} \bmod p$


Foundations of Cybersecurity


Diffie-Hellman Key Exchange

7

7

# DHKE with small numbers





UNIVERSITÀ DI PISA

Let  $p = 11, g = 7$

Alice chooses  $a = 3$  and computes  $Y_A \equiv g^a \equiv 7^3 \equiv 343 \equiv 2 \bmod 11$

Bob chooses  $b = 6$  and computes  $Y_B \equiv g^b \equiv 7^6 \equiv 117649 \equiv 4 \bmod 11$

A  $\rightarrow$  B: 2  
B  $\rightarrow$  A: 4

Alice receives 4 and computes  $K_{AB} = (Y_B)^a \equiv 4^3 \equiv 9 \bmod 11$   
Bob receives 2 and computes  $K_{AB} = (Y_A)^b \equiv 2^6 \equiv 9 \bmod 11$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

8

8

## DHKE computational aspects



UNIVERSITÀ DI PISA

- Large prime  $p$  can be computed as for RSA
- Exponentiation can be computed by square-and-multiply
  - The trick of using small exponents is non applicable here
- $\mathbb{Z}_p^*$  is cyclic
  - $g$  is a generator,  $g^i \bmod p$  defines a permutation
    - $p = 11, g = 2$ 
      - $2^1 \equiv 2 \bmod 11$      $2^5 \equiv 10 \bmod 11$      $2^9 \equiv 6 \bmod 11$
      - $2^2 \equiv 4 \bmod 11$      $2^6 \equiv 9 \bmod 11$      $2^{10} \equiv 1 \bmod 11$
      - $2^3 \equiv 8 \bmod 11$      $2^7 \equiv 7 \bmod 11$     *repeat cyclically*
      - $2^4 \equiv 5 \bmod 11$      $2^8 \equiv 3 \bmod 11$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

9

9

## Security of DHKE



UNIVERSITÀ DI PISA

- Intuition
  - Eavesdropper sees  $p, g, Y_A$  and  $Y_B$  and wants to compute  $K_{AB}$
- Diffie-Hellman Problem (DHP)
  - Given  $p, g, Y_A \equiv g^a \bmod p$  and  $Y_B \equiv g^b \bmod p$ , compute  $K_{AB} = g^{ab} \bmod p$
- How hard is this problem?

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

10

10

## Security of DHKE



UNIVERSITÀ DI PISA

- $\text{DHP} \leq_p \text{DLP}$ 
  - If DLP can be easily solved, then DHP can be easily solved
  - There is no proof of the converse, i.e., if DLP is difficult then DHP is difficult
  - At the moment, we don't see any way to compute  $K_{AB}$  from  $Y_A$  and  $Y_B$  without first obtaining either  $a$  or  $b$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

11

11

Diffie-Hellman Key Exchange

## NOT-INTERACTIVITY

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

12

12

Facebook

$g^a$

$g^b$

$g^c$

$g^d$

Alice

Bob

Charlie

David

a

b

c

d

$K_{AC}=g^{ac}$

$K_{AC}=g^{ac}$

Not-interactive protocol - In order to obtain a shared key with Bob, Alice does not need to receive any message from Bob

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

13

13

Facebook

$g^a$

$g^b$

$g^c$

$g^d$

Alice

Bob

Charlie

David

a

b

c

d

$K_{ABCD}$

$K_{ABCD}$

$K_{ABCD}$

$K_{ABCD}$

n = 2 (DH)

n = 3 (Joux)

n ≥ 4: open

Non-interactive group DH for groups larger than 3 members is still an open problem

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

14

14

Diffie-Hellman Key Exchange

THE MAN-IN-THE-MIDDLE ATTACK


Foundations of Cybersecurity

Diffie-Hellman Key Exchange

15

15

Man-in-the-Middle Attack



$K_{AM} = g^{ac} \bmod p$

$K_{AM} = g^{ac} \bmod p, e$   
 $K_{BM} = g^{bc} \bmod p$

$K_{BM} = g^{bc} \bmod p$

Foundations of Cybersecurity


Diffie-Hellman Key Exchange

16

16



## Man-in-the-Middle Attack



- Beliefs
  - Alice believes to communicate with Bob by means of  $K_{AM}$
  - Bob believes to communicate with Alice by means of  $K_{BM}$
- The adversary can
  - read messages between Alice and Bob
  - impersonate Alice or Bob
- DHKE is insecure against MIM (active) attack

UNIVERSITÀ DI PISA

Foundations of Cybersecurity      Diffie-Hellman Key Exchange      17

17

Diffie-Hellman Key Exchange

## THE GENERALIZED DLP AND ATTACKS AGAINST DLP

Foundations of Cybersecurity      Diffie-Hellman Key Exchange      18

18

## The Generalized DLP



UNIVERSITÀ DI PISA

- DLP can be defined on any cyclic group
- GDLP (def)
  - Given a finite cyclic group  $G$  with group operation  $\bullet$  and cardinality  $n$ , i.e.,  $|G| = n$ . We consider a primitive element  $\alpha \in G$  and another element  $\beta \in G$ . The discrete logarithm problem is finding the integer  $x$ , where  $1 \leq x \leq n$ , such that

$$\beta = \underbrace{\alpha \bullet \alpha \bullet \alpha \bullet \dots \bullet \alpha}_{x \text{ times}} = \alpha^x$$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

19

19

## DLP for cryptography



UNIVERSITÀ DI PISA

- Multiplicative prime group  $\mathbb{Z}_p^*$ 
  - DHKE, ElGamal encryption, Digital Signature Algorithm (DSA)
- Cyclic group formed by Elliptic curves
- Galois field  $\text{GF}(2^m)$ 
  - Equivalent to  $\mathbb{Z}_p^*$
  - Attacks against  $\text{GF}(2^m)$  are more powerful than DLP in  $\mathbb{Z}_p^*$  so we need “higher” bit lengths than  $\mathbb{Z}_p^*$
- Hyperelliptic curves or algebraic varieties

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

20

20

## Algorithms for DLP



UNIVERSITÀ DI PISA

- Generic Algorithms work in any cyclic group:
  - Brute-force Search
  - Shank's Baby-Step Giant-Step Method
  - Pollard's Rho Method
  - Pohlig-Hellman Algorithm
- Nongeneric algorithms exploit inherent structure of certain groups
- FACT – Difficulty of DLP is independent of the generator

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

21

21

## Algorithms for DLP



UNIVERSITÀ DI PISA

- Generic algorithms
  - Brute-force Search
    - Running time:  $O(|G|)$  multiplications
  - Shank's Baby-Step Giant-Step Method
    - Running time:  $O(\sqrt{|G|})$  multiplications
    - Storage:  $O(\sqrt{|G|})$

%

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

22

22

## Algorithms for DLP



UNIVERSITÀ DI PISA

- Generic Algorithms
  - Pollard's Rho Method
    - Based on the Birthday Paradox
    - Running time:  $O(\sqrt{|G|})$  multiplications
    - Storage: negligible

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

23

23

## Algorithms for DLP



UNIVERSITÀ DI PISA

- Generic Algorithms
  - Pohlig-Hellman Algorithm
    - Based on CRT, exploits factorization of  $|G| = \prod_{i=1}^r (p_i)^{e_i}$ 
      - Reduces DLP to DLP in (smaller) groups of order  $p_i^{e_i}$
      - In the EC, computing  $|G|$  is not easy
    - Running time:  $O(\sum_{i=1}^r e_i \cdot (\lg |G| + \sqrt{p_i}))$  multiplications
      - Efficient if each  $p_i$  is «small»
      - To prevent the attack the *smallest factor* of  $|G|$  must be in the range  $2^{160}$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

24

24

## Algorithms for DLP



UNIVERSITÀ DI PISA

- Nongeneric algorithms
  - Exploit inherent structure of certain groups
  - The Index-Calculus Method
    - Very efficient algorithm to compute DLP in  $\mathbb{Z}_p^*$  and  $\text{GF}(2^m)$
    - Sub-exponential running time
      - In  $\mathbb{Z}_p^*$ , in order to achieve 80-bit security, the prime  $p$  must be at list 1024 bit long
      - It is even more efficient in  $\text{GF}(2^m)$  → For this reason, DLP in  $\text{GF}(2^m)$  are not used in practice

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

25

25

## DLP – rule of thumb



UNIVERSITÀ DI PISA

- Let  $p$  be a prime on  $k$  bits ( $p < 2^k$ )
- Exponentiation takes at most  $2 \cdot \log_2 p < 2k$  long integer multiplications (mod  $p$ )
  - Linear in the exponent size ( $k$ )
- Discrete logs require  $p^{1/2} = 2^{k/2}$  multiplication
- Example  $n = 512$ 
  - Exponentiation: #multiplications  $\leq 1024$
  - Discrete log: #multiplications  $\approx 2^{256} = 10^{77}$ 
    - $10^{17}$  seconds since Big Bang

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

26

26

Diffie-Hellman Key Exchange

## DLP IN SUBGROUPS

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

27

27

## Cyclic groups



UNIVERSITÀ DI PISA

- Theorem 8.2.2. For every prime  $p$ ,  $(\mathbb{Z}_p^*, \times)$  is an abelian finite cyclic group
  - **Finite**: contains a finite number of elements
  - **Group**: closed, associative, identity element, inverse, commutative
  - **Cyclic**: contain an element  $\alpha$  with maximum order  $\text{ord}(\alpha) = |\mathbb{Z}_p^*| = p - 1$ , where *order of*  $a \in \mathbb{Z}_p^*$ ,  $\text{ord}(a) = k$ , is the smallest positive integer  $k$  such that  $a^k \equiv 1 \pmod{p}$ 
    - $\alpha$  is called *generator* or *primitive element*
- The notion of finite cyclic group is generalizable to  $(G, \bullet)$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

28

28

## Cyclic groups – order



UNIVERSITÀ DI PISA

- Example: consider  $\mathbb{Z}_{11}^*$  and  $a = 3$ 
  - $a^1 = 3$
  - $a^2 = a \cdot a = 3 \cdot 3 = 9$
  - $a^3 = a^2 \cdot a = 9 \cdot 3 = 27 \equiv 5 \pmod{11}$
  - $a^4 = a^3 \cdot a = 5 \cdot 3 = 15 \equiv 4 \pmod{11}$
  - $a^5 = a^4 \cdot a = 4 \cdot 3 = 12 \equiv 1 \pmod{11} \leftarrow \text{ord}(3) = 5$
  - $a^6 = a^5 \cdot a \equiv 1 \cdot a \equiv 3 \pmod{11}$
  - $a^7 = a^5 \cdot a^2 \equiv 1 \cdot a^2 \equiv 9 \pmod{11}$
  - $a^8 = a^5 \cdot a^3 \equiv 1 \cdot a^3 \equiv 5 \pmod{11}$
  - $a^9 = a^5 \cdot a^4 \equiv 1 \cdot a^4 \equiv 4 \pmod{11}$
  - $a^{10} = a^5 \cdot a^5 \equiv 1 \cdot 1 \equiv 1 \pmod{11} \leftarrow \text{periodic}$
  - $a^{11} = a^{10} \cdot a \equiv 1 \cdot a \equiv 3 \pmod{11}$
  - $3^i$  generates the periodic sequence  $\{3, 9, 5, 4, 1\}$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

29

29

## Cyclic groups – primitive element



UNIVERSITÀ DI PISA

- Example: consider  $\mathbb{Z}_{11}^*$  and  $a = 2$ 
  - $a = 2$   $a^6 \equiv 9 \pmod{11}$
  - $a^2 = 4$   $a^7 \equiv 7 \pmod{11}$
  - $a^3 = 8$   $a^8 \equiv 3 \pmod{11}$
  - $a^4 \equiv 5 \pmod{11}$   $a^9 \equiv 6 \pmod{11}$
  - $a^5 \equiv 10 \pmod{11}$   $a^{10} \equiv 1 \pmod{11} \leftarrow \text{ord}(2)$
  - $\text{ord}(2) = 10 = |\mathbb{Z}_{11}^*| \rightarrow 2$  is a primitive element


Foundations of Cybersecurity

Diffie-Hellman Key Exchange

30

30

# Cyclic groups – permutation



UNIVERSITÀ DI PISA


Powers of a primitive element define a permutation of the elements of  $\mathbb{Z}_p^*$

$i$	1	2	3	4	5	6	7	8	9	10
$2^i$	2	4	8	5	10	9	7	3	6	1

Foundations of Cybersecurity      Diffie-Hellman Key Exchange      31

31

# Cyclic groups – order and generators



UNIVERSITÀ DI PISA

- Order of elements of  $\mathbb{Z}_{11}^*$ 
  - ord(1) = 1      ord(6) = 10
  - ord(2) = 10      ord(7) = 10
  - ord(3) = 5      ord(8) = 10
  - ord(4) = 5      ord(9) = 5
  - ord(5) = 5      ord(10) = 2
- Any order is a divisor of  $|\mathbb{Z}_{11}^*| = 10$
- #(primitive elements) is  $\Phi(10) = \Phi(|\mathbb{Z}_{11}^*|) = 4$
- Set of primitive elements = {2, 6, 7, 8}

Foundations of Cybersecurity      Diffie-Hellman Key Exchange      32

32



## Cyclic groups



UNIVERSITÀ DI PISA

- Theorem 8.2.3
  - Let  $G$  be a finite group. Then for every  $a \in G$  it holds that:
    - 1.  $a^{|G|} = 1$  (Generalization of Fermat's Little Theorem)
    - 2.  $\text{ord}(a)$  divides  $|G|$
- Theorem 8.2.4
  - Let  $G$  be a finite cyclic group. Then it holds that
    - 1. The number of primitive elements of  $G$  is  $\Phi(|G|)$ .
    - 2. If  $|G|$  is prime, then all elements  $a \neq 1 \in G$  are primitive.

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

33

33

## Subgroups



UNIVERSITÀ DI PISA

- Theorem 8.2.5 Cyclic Subgroup Theorem
  - Let  $G$  be a cyclic group. Then every element  $a \in G$  with  $\text{ord}(a) = s$  is the primitive element of a cyclic subgroup with  $s$  elements.
  - Example:  $\mathbb{Z}_{11}^*$ ,  $a = 3$ ,  $s = \text{ord}(3) = 5$ ,  $H = \{1, 3, 4, 5, 9\}$ 
    - $H$  is a finite, cyclic subgroup of order 5


Foundations of Cybersecurity

Diffie-Hellman Key Exchange

34

34

## Subgroups



UNIVERSITÀ DI PISA

- Theorem 8.2.6 (Lagrange’s theorem)
  - Let  $H$  be a subgroup of  $G$ . Then  $|H|$  divides  $|G|$ .
- Example:  $\mathbb{Z}_{11}^*$ 
  - $|\mathbb{Z}_{11}^*| = 10$  whose divisors are 1, 2, 5
  - Subgroup                      elements                      primitive element
  - $H_1$                                $\{1\}$                                $\alpha = 1$
  - $H_2$                                $\{1, 10\}$                                $\alpha = 10$
  - $H_5$                                $\{1, 3, 4, 5, 9\}$                                $\alpha = 3, 4, 5, 9$


Foundations of Cybersecurity

Diffie-Hellman Key Exchange

35

35

## Subgroups



UNIVERSITÀ DI PISA

- Theorem 8.2.7
  - Let  $G$  be a finite cyclic group of order  $n$  and let  $\alpha$  be a generator of  $G$ . Then for every integer  $k$  that divides  $n$  there exists exactly one cyclic subgroup  $H$  of  $G$  of order  $k$ . This subgroup is generated by  $\alpha^{n/k}$ .  $H$  consists exactly of the elements  $a \in G$  which satisfy the condition  $a^k = 1$ . There are no other subgroups.
- Example.
  - Given  $\mathbb{Z}_{11}^*$  and the  $\alpha = 8$  generator, the  $\beta = 8^{10/2} = 10 \bmod 11$  that is a generator for  $H$  of order  $k = 2$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

36

36

## Relevance of subgroups to DLP



UNIVERSITÀ DI PISA

- ON SOLVING DLP
- Pohlig-Hellman Algorithm
  - Exploit factorization of  $|G| = p_1^{e_1} \cdot p_2^{e_2} \cdot \dots \cdot p_\ell^{e_\ell}$
  - Run time depends on the size of prime factors
    - The smallest prime factor must be in the range  $2^{160}$
- $|\mathbb{Z}_p^*| = p - 1$  is even  $\rightarrow 2$  (small) is one of the divisors!
- It is advisable to work in a prime subgroup  $H$ 
  - If  $|H|$  is prime,  $\forall a \in H$ ,  $a$  is a generator (Theorem 8.2.4)

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

37

37

## Safe primes



UNIVERSITÀ DI PISA

- Definition: given a prime  $p = 2 \cdot q + 1$ , where  $q$  is a prime then  $p$  is a safe prime and  $q$  is a Sophie Germain prime
- It follows that  $\mathbb{Z}_p^*$  has a subgroup  $H_q$  of (large) prime order  $q$

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

38

38


## Relevance of subgroups to DLP



UNIVERSITÀ DI PISA

- SMALL SUBGROUP CONFINEMENT ATTACK

- Consider prime  $p$ ,  $\mathbb{Z}_p^*$ , and generator  $\alpha$



Foundations of Cybersecurity

Diffie-Hellman Key Exchange

39

39

## Relevance of subgroups to DLP



UNIVERSITÀ DI PISA

- SMALL SUBGROUP CONFINEMENT ATTACK

- Given THEOREM 8.2.7

- Consider  $k$  that divides  $|\mathbb{Z}_p^*| = p - 1$  then
- $A' \equiv A^{n/k} \equiv (\alpha^a)^{n/k} \equiv (\alpha^{n/k})^a \pmod{p}$
- $B' \equiv B^{n/k} \equiv (\alpha^b)^{n/k} \equiv (\alpha^{n/k})^b \pmod{p}$
- Session key  $K = \beta^{ab} \pmod{p}$ , with  $\beta = \alpha^{n/k}$
- $\beta = \alpha^{n/k}$  is a generator of subgroup  $H$  of order  $k \rightarrow$
- DHKE gets confined in  $H_k$  and brute force becomes easier

Foundations of Cybersecurity

Diffie-Hellman Key Exchange

40

40