

# Lecture 3: Static Analysis Principles – Abstract Syntax Trees (AST)

Passive Testing Techniques for Communication Protocols

Dr. Jorge López, PhD.  
jorgelopezcoronado[at]gmail.com



National Research  
**Tomsk  
State  
University**

February 15, 2016

# ACKNOWLEDGMENTS

Some content was taken from: Saman Amarasinghe, and Martin Rinard. 6.035 Computer Language Engineering, Spring 2010. (Massachusetts Institute of Technology: MIT OpenCourseWare), <http://ocw.mit.edu>. License: Creative Commons BY-NC-SA

# OUTLINE

FROM CFG TO “TREES”

GRAMMAR AMBIGUITIES

ABSTRACT SYNTAX TREES

# REMEMBER THE CFG DERIVATION?

# REMEMBER THE CFG DERIVATION?

## Grammar

- ▶  $op = + | - | / | *$
- ▶  $int = [0 - 9]^+$
- ▶  $opar = ($
- ▶  $cpar = )$

1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \ op \ Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \ Expr \ cpar$

## Example derivation

- ▶ *Start*
- ▶ *Expr* (1)
- ▶ *Expr op Expr* (2)
- ▶ *int op Expr* (3)
- ▶ *int op opar Expr cpar* (4)
- ▶ *int op opar Expr op Expr cpar* (2)
- ▶ *int op opar int op Expr cpar* (3)
- ▶ *int op opar int op int cpar* (3)
- ▶  $10 / ( 7 - 5 )$

# REMEMBER THE CFG DERIVATION?

## Grammar

- ▶  $op = + | - | / | *$
- ▶  $int = [0 - 9]^+$
- ▶  $opar = ($
- ▶  $cpar = )$

1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \ op \ Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \ Expr \ cpar$

## Example derivation

- ▶ *Start*
- ▶ *Expr* (1)
- ▶ *Expr op Expr* (2)
- ▶ *int op Expr* (3)
- ▶ *int op opar Expr cpar* (4)
- ▶ *int op opar Expr op Expr cpar* (2)
- ▶ *int op opar int op Expr cpar* (3)
- ▶ *int op opar int op int cpar* (3)
- ▶  $10 / ( 7 - 5 )$

It has a natural tree-like structure!

# PARSE TREES

## Definition

# PARSE TREES

## Definition

- Formally, a directed graph  $T = \langle V, A \rangle$ , where  $V$  is a set of vertices (nodes),  $A$  is a set of ordered arcs formed by a pairs  $(v_1, v_2) \in V \times V$ , in which each two vertices are connected by a unique simple path (tree-like structure).



# PARSE TREES

## Definition

- ▶ Formally, a directed graph  $T = \langle V, A \rangle$ , where  $V$  is a set of vertices (nodes),  $A$  is a set of ordered arcs formed by a pairs  $(v_1, v_2) \in V \times V$ , in which each two vertices are connected by a unique simple path (tree-like structure).

## Structure

- ▶ Terminal symbols are leafs
- ▶ Non-terminal symbols are intermediate vertices in the tree
- ▶ Initial symbol is the tree root (therefore a rooted tree)
- ▶ Production rules define arcs.

# PARSE TREES

## Definition

- ▶ Formally, a directed graph  $T = \langle V, A \rangle$ , where  $V$  is a set of vertices (nodes),  $A$  is a set of ordered arcs formed by a pairs  $(v_1, v_2) \in V \times V$ , in which each two vertices are connected by a unique simple path (tree-like structure).

## Structure

- ▶ Terminal symbols are leafs
- ▶ Non-terminal symbols are intermediate vertices in the tree
- ▶ Initial symbol is the tree root (therefore a rooted tree)
- ▶ Production rules define arcs.


Let's take a look at one...

# PARSE TREES (CONT.)

10/(7 − 5) parse tree


# PARSE TREES (CONT.)

10/(7 - 5) parse tree



# PARSE TREES (CONT.)


10/(7 - 5) parse tree



1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \text{ op } Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \text{ Expr } cpar$

## PARSE TREES (CONT.)

10/(7 - 5) parse tree




1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \text{ op } Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \ Expr \ cpar$

Please, derive the parse tree for  $2 + 3 * 4$


# PARSE TREES (CONT. CONT.)

$2 + 3 * 4$  parse tree




# PARSE TREES (CONT. CONT.)

$2 + 3 * 4$  parse tree



$2 + 3 * 4$  parse tree!





# Grammar Ambiguities

(and parse trees)

## Grammar Ambiguity...

# GRAMMAR AMBIGUITIES

## Grammar Ambiguity...

- Occurs when multiple derivations (and therefore parse trees) exist for a single string

# GRAMMAR AMBIGUITIES

## Grammar Ambiguity...

- ▶ Occurs when multiple derivations (and therefore parse trees) exist for a single string
- ▶ Ambiguity in the grammar reflects ambiguity in the language semantics

# GRAMMAR AMBIGUITIES

## Grammar Ambiguity...

- ▶ Occurs when multiple derivations (and therefore parse trees) exist for a single string
- ▶ Ambiguity in the grammar reflects ambiguity in the language semantics
  - ▶ For computer languages this is highly undesirable!

# GRAMMAR AMBIGUITIES

## Grammar Ambiguity...

- ▶ Occurs when multiple derivations (and therefore parse trees) exist for a single string
- ▶ Ambiguity in the grammar reflects ambiguity in the language semantics
  - ▶ For computer languages this is highly undesirable!
  - ▶ Non-determinism in computer code is something that humanity is not ready for...

# GRAMMAR AMBIGUITIES

## Grammar Ambiguity...

- ▶ Occurs when multiple derivations (and therefore parse trees) exist for a single string
- ▶ Ambiguity in the grammar reflects ambiguity in the language semantics
  - ▶ For computer languages this is highly undesirable!
  - ▶ Non-determinism in computer code is something that humanity is not ready for...

Solution?

# GRAMMAR MODIFICATIONS (HACKING)

Recursiveness...



# GRAMMAR MODIFICATIONS (HACKING)

Recursiveness...

- ▶ Left recursive production  $P \mapsto P \alpha$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$

# GRAMMAR MODIFICATIONS (HACKING)

## Recursiveness...

- ▶ Left recursive production  $P \mapsto P \alpha$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Left recursive production  $\mapsto$  Left recursive grammar

# GRAMMAR MODIFICATIONS (HACKING)

## Recursiveness...

- ▶ Left recursive production  $P \mapsto P \alpha$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Left recursive production  $\mapsto$  Left recursive grammar
- ▶ Right recursive production  $P \mapsto \alpha P$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$

# GRAMMAR MODIFICATIONS (HACKING)

## Recursiveness...

- ▶ Left recursive production  $P \mapsto P \alpha$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Left recursive production  $\mapsto$  Left recursive grammar
- ▶ Right recursive production  $P \mapsto \alpha P$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Right recursive production  $\mapsto$  Right recursive grammar

# GRAMMAR MODIFICATIONS (HACKING)

## Recursiveness...

- ▶ Left recursive production  $P \mapsto P \alpha$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Left recursive production  $\mapsto$  Left recursive grammar
- ▶ Right recursive production  $P \mapsto \alpha P$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Right recursive production  $\mapsto$  Right recursive grammar

## Associativity

# GRAMMAR MODIFICATIONS (HACKING)

## Recursiveness...

- ▶ Left recursive production  $P \mapsto P \alpha$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Left recursive production  $\mapsto$  Left recursive grammar
- ▶ Right recursive production  $P \mapsto \alpha P$ , where  $P \in T \wedge \alpha \in (T \cap U)^*$
- ▶ Right recursive production  $\mapsto$  Right recursive grammar

## Associativity

- ▶ Try to avoid left and right recursion for the same production rules, leave only one, for instance, only right recursiveness  $\mapsto$  **right associativity**

# GRAMMAR MODIFICATIONS (HACKING) (CONT.)

# GRAMMAR MODIFICATIONS (HACKING) (CONT.)

## Original Grammar

1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \text{ op } Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \text{ Expr } cpar$



# GRAMMAR MODIFICATIONS (HACKING) (CONT.)

## Original Grammar

1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \text{ op } Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \text{ Expr } cpar$

## Hacked Grammar (associativity)

1.  $Start \mapsto Expr$
2.  $Expr \mapsto int \text{ op } Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \text{ Expr } cpar$

# GRAMMAR MODIFICATIONS (HACKING) (CONT.)

## Original Grammar

**Unique**  $2 + 3 * 4$  parse tree

1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \text{ op } Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \ Expr \ cpar$

## Hacked Grammar (associativity)

1.  $Start \mapsto Expr$
2.  $Expr \mapsto int \text{ op } Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar \ Expr \ cpar$

# GRAMMAR MODIFICATIONS (HACKING) (CONT.)


## Original Grammar

1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr\ op\ Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar\ Expr\ cpar$

## Hacked Grammar (associativity)

1.  $Start \mapsto Expr$
2.  $Expr \mapsto \textcolor{blue}{int}\ op\ Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar\ Expr\ cpar$

**Unique**  $2 + 3 * 4$  parse tree



# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful

# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

- ▶ For the previous grammar,  $2 * 3 + 4$  will give an incorrect parse tree given the naturally established **precedence**

# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

- ▶ For the previous grammar,  $2 * 3 + 4$  will give an incorrect parse tree given the naturally established **precedence**
- ▶ If we hack the grammar to make it left associative, then we'd have problems with  $2 + 3 * 4$ , for instance...

# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

- ▶ For the previous grammar,  $2 * 3 + 4$  will give an incorrect parse tree given the naturally established **precedence**
- ▶ If we hack the grammar to make it left associative, then we'd have problems with  $2 + 3 * 4$ , for instance...

## Precedence



# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

- ▶ For the previous grammar,  $2 * 3 + 4$  will give an incorrect parse tree given the naturally established **precedence**
- ▶ If we hack the grammar to make it left associative, then we'd have problems with  $2 + 3 * 4$ , for instance...

## Precedence

- ▶ Group operators rules into precedence levels

# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

- ▶ For the previous grammar,  $2 * 3 + 4$  will give an incorrect parse tree given the naturally established **precedence**
- ▶ If we hack the grammar to make it left associative, then we'd have problems with  $2 + 3 * 4$ , for instance...

## Precedence

- ▶ Group operators rules into precedence levels
- ▶ Non-terminal symbols generated separately for each precedence level

# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

- ▶ For the previous grammar,  $2 * 3 + 4$  will give an incorrect parse tree given the naturally established **precedence**
- ▶ If we hack the grammar to make it left associative, then we'd have problems with  $2 + 3 * 4$ , for instance...

## Precedence

- ▶ Group operators rules into precedence levels
- ▶ Non-terminal symbols generated separately for each precedence level
- ▶ Within each non-terminal symbol associativity is possible

# GRAMMAR MODIFICATIONS (HACKING) (III)

Associativity can be useful, sometimes...

- ▶ For the previous grammar,  $2 * 3 + 4$  will give an incorrect parse tree given the naturally established **precedence**
- ▶ If we hack the grammar to make it left associative, then we'd have problems with  $2 + 3 * 4$ , for instance...

## Precedence

- ▶ Group operators rules into precedence levels
- ▶ Non-terminal symbols generated separately for each precedence level
- ▶ Within each non-terminal symbol associativity is possible
- ▶ Higher precedence  $\rightarrow$  inner production rule (bind first)

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ↺ 🔍 ↻ 13/20

# GRAMMAR MODIFICATIONS (HACKING) (IV)

## Original Grammar

▶  $op = + | - | / | *$

▶  $int = [0 - 9]^+$

▶  $opar = ($

▶  $cpar = )$

1.  $Start \mapsto Expr$

2.  $Expr \mapsto int\ op\ Expr$

3.  $Expr \mapsto int$

4.  $Expr \mapsto opar\ Expr\ cpar$

# GRAMMAR MODIFICATIONS (HACKING) (IV)

## Original Grammar

- ▶  $op = + | - | / | *$
- ▶  $int = [0 - 9]^+$
- ▶  $opar = ($
- ▶  $cpar = )$

1.  $Start \mapsto Expr$
2.  $Expr \mapsto int\ op\ Expr$
3.  $Expr \mapsto int$
4.  $Expr \mapsto opar\ Expr\ cpar$

## Hacked Grammar (precedence)

- ▶  $mop = / | *$
- ▶  $aop = + | -$
- ▶  $int, opar, cpar$  same

1.  $Start \mapsto Expr$

# GRAMMAR MODIFICATIONS (HACKING) (IV)

## Original Grammar

- ▶  $op = + | - | / | *$
  - ▶  $int = [0 - 9]^+$
  - ▶  $opar = ($
  - ▶  $cpar = )$
1.  $Start \mapsto Expr$
  2.  $Expr \mapsto int \ op \ Expr$
  3.  $Expr \mapsto int$
  4.  $Expr \mapsto opar \ Expr \ cpar$

## Hacked Grammar (precedence)

- ▶  $mop = / | *$
- ▶  $aop = + | -$
- ▶  $int, opar, cpar$  same

1.  $Start \mapsto Expr$
2.  $Expr \mapsto Expr \ aop \ Term$
3.  $Expr \mapsto Term$



# GRAMMAR MODIFICATIONS (HACKING) (IV)

## Original Grammar

- ▶  $op = + | - | / | *$
  - ▶  $int = [0 - 9]^+$
  - ▶  $opar = ($
  - ▶  $cpar = )$
1.  $Start \mapsto Expr$
  2.  $Expr \mapsto int \ op \ Expr$
  3.  $Expr \mapsto int$
  4.  $Expr \mapsto opar \ Expr \ cpar$

## Hacked Grammar (precedence)

- ▶  $mop = / | *$
  - ▶  $aop = + | -$
  - ▶  $int, opar, cpar$  same
1.  $Start \mapsto Expr$
  2.  $Expr \mapsto Expr \ aop \ Term$
  3.  $Expr \mapsto Term$
  4.  $Term \mapsto Term \ mop \ Num$
  5.  $Term \mapsto Num$

# GRAMMAR MODIFICATIONS (HACKING) (IV)

## Original Grammar

- ▶  $op = + | - | / | *$
  - ▶  $int = [0 - 9]^+$
  - ▶  $opar = ($
  - ▶  $cpar = )$
1.  $Start \mapsto Expr$
  2.  $Expr \mapsto int\ op\ Expr$
  3.  $Expr \mapsto int$
  4.  $Expr \mapsto opar\ Expr\ cpar$

## Hacked Grammar (precedence)

- ▶  $mop = / | *$
  - ▶  $aop = + | -$
  - ▶  $int, opar, cpar$  same
1.  $Start \mapsto Expr$
  2.  $Expr \mapsto Expr\ aop\ Term$
  3.  $Expr \mapsto Term$
  4.  $Term \mapsto Term\ mop\ Num$
  5.  $Term \mapsto Num$
  6.  $Num \mapsto int$
  7.  $Num \mapsto opar\ Expr\ cpar$

# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

$$\blacktriangleright S \mapsto SS|a|b$$

# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

- ▶  $S \mapsto SS|a|b$ 
  - ▶ One way:

# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

- ▶  $S \mapsto SS|a|b$ 
  - ▶ One way:
    - ▶  $S \mapsto S2 S|a|b$
    - ▶  $S2 \mapsto a|b$

# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

- ▶  $S \mapsto SS|a|b$ 
  - ▶ One way:
    - ▶  $S \mapsto S2 S|a|b$
    - ▶  $S2 \mapsto a|b$
  - ▶ Another

# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

- ▶  $S \mapsto SS|a|b$ 
  - ▶ One way:
    - ▶  $S \mapsto S2 S|a|b$
    - ▶  $S2 \mapsto a|b$
  - ▶ Another
    - ▶  $S \mapsto aS|a|b|bS$



# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

- ▶  $S \mapsto SS|a|b$ 
  - ▶ One way:
    - ▶  $S \mapsto S2 S|a|b$
    - ▶  $S2 \mapsto a|b$
  - ▶ Another
    - ▶  $S \mapsto aS|a|b|bS$
- ▶  $S \mapsto SS|a|c$ ;  $ca$  has priority over  $ac$


# EXERCISES – AMBIGUOUS GRAMMARS

Remove ambiguity from:

- ▶  $S \mapsto SS|a|b$ 
  - ▶ One way:
    - ▶  $S \mapsto S2 S|a|b$
    - ▶  $S2 \mapsto a|b$
  - ▶ Another
    - ▶  $S \mapsto aS|a|b|bS$
- ▶  $S \mapsto SS|a|c$ ;  $ca$  has priority over  $ac$ 
  - ▶ **Homework**


# CONCRETE PARSE TREES...

Old  $2 + 3 * 4$  parse tree




# CONCRETE PARSE TREES...

Old  $2 + 3 * 4$  parse tree



New  $2 + 3 * 4$  parse tree!



# Abstract Syntax Trees (AST)

## The desired structure

# PARSING...

## A Parser (PDA)

# PARSING...

## A Parser (PDA)

- ▶ Can be generated automatically by a parser generator  
(takes as input a CFG and produces a parser)

# PARSING...

## A Parser (PDA)

- ▶ Can be generated automatically by a parser generator (takes as input a CFG and produces a parser)
- ▶ Takes a CFG derivation (a sentence / source code) and produces a “parse tree”



# PARSING...

## A Parser (PDA)

- ▶ Can be generated automatically by a parser generator (takes as input a CFG and produces a parser)
- ▶ Takes a CFG derivation (a sentence / source code) and produces a “parse tree”
- ▶ Its goal is to produce an AST, not a concrete parse tree

# PARSING...

## A Parser (PDA)

- ▶ Can be generated automatically by a parser generator (takes as input a CFG and produces a parser)
- ▶ Takes a CFG derivation (a sentence / source code) and produces a “parse tree”
- ▶ Its goal is to produce an AST, not a concrete parse tree

## AST vs Concrete Parse Tree

- ▶ Concrete used to parse unambiguously

# PARSING...

## A Parser (PDA)

- ▶ Can be generated automatically by a parser generator (takes as input a CFG and produces a parser)
- ▶ Takes a CFG derivation (a sentence / source code) and produces a “parse tree”
- ▶ Its goal is to produce an AST, not a concrete parse tree

## AST vs Concrete Parse Tree

- ▶ Concrete used to parse unambiguously
- ▶ Concrete too complex, we need simpler, we need an AST

# ABSTRACT SYNTAX TREES

What it is

# ABSTRACT SYNTAX TREES

## What it is

- ▶ A concrete parse tree omits unnecessary terminal and non-terminal symbols

# ABSTRACT SYNTAX TREES

## What it is

- ▶ A concrete parse tree omits unnecessary terminal and non-terminal symbols
  - ▶ For example: () or intermediate  $\langle Term \rangle$  symbols

# ABSTRACT SYNTAX TREES

## What it is

- ▶ A concrete parse tree omits unnecessary terminal and non-terminal symbols
  - ▶ For example: () or intermediate  $\langle Term \rangle$  symbols

## How to obtain it?

# ABSTRACT SYNTAX TREES

## What it is

- ▶ A concrete parse tree omits unnecessary terminal and non-terminal symbols
  - ▶ For example: () or intermediate  $\langle Term \rangle$  symbols

## How to obtain it?

- ▶ Start with ambiguous grammar (probably)



# ABSTRACT SYNTAX TREES

## What it is

- ▶ A concrete parse tree omits unnecessary terminal and non-terminal symbols
  - ▶ For example: () or intermediate  $\langle Term \rangle$  symbols

## How to obtain it?

- ▶ Start with ambiguous grammar (probably)
- ▶ Hack the grammar to obtain concrete parse tree

# ABSTRACT SYNTAX TREES

## What it is

- ▶ A concrete parse tree omits unnecessary terminal and non-terminal symbols
  - ▶ For example: () or intermediate  $\langle Term \rangle$  symbols

## How to obtain it?


- ▶ Start with ambiguous grammar (probably)
- ▶ Hack the grammar to obtain concrete parse tree
- ▶ Remove undesired symbols and obtain the AST

## CONCRETE PARSE TREE $\mapsto$ AST

# CONCRETE PARSE TREE $\mapsto$ AST


Concrete parse tree for

$2 + 3 * 4$




# CONCRETE PARSE TREE $\mapsto$ AST

Concrete parse tree for  
 $2 + 3 * 4$



AST for  $2 + 3 * 4$



# ASTs – FINAL REMARKS

# ASTs – FINAL REMARKS

- ▶ Commonly, people show the AST of the generic CFG, representing a somehow ambiguous grammar

# ASTs – FINAL REMARKS

- ▶ Commonly, people show the AST of the generic CFG, representing a somehow ambiguous grammar
- ▶ Many known parser generators, based on this approach, YACC, Bison, ANTLR, etc...



# ASTs – FINAL REMARKS

- ▶ Commonly, people show the AST of the generic CFG, representing a somehow ambiguous grammar
- ▶ Many known parser generators, based on this approach, YACC, Bison, ANTLR, etc...
- ▶ Recently (~2011...) some attention to regular expression derivatives to parse was introduced thanks to YACC is dead [Might and Darais, 2010], and all follow-up from it

# ASTs – FINAL REMARKS

- ▶ Commonly, people show the AST of the generic CFG, representing a somehow ambiguous grammar
- ▶ Many known parser generators, based on this approach, YACC, Bison, ANTLR, etc...
- ▶ Recently (~2011...) some attention to regular expression derivatives to parse was introduced thanks to YACC is dead [Might and Darais, 2010], and all follow-up from it
- ▶ Until today, YACC is very alive...

# ASTs – FINAL REMARKS

- ▶ Commonly, people show the AST of the generic CFG, representing a somehow ambiguous grammar
- ▶ Many known parser generators, based on this approach, YACC, Bison, ANTLR, etc...
- ▶ Recently (~2011...) some attention to regular expression derivatives to parse was introduced thanks to YACC is dead [Might and Darais, 2010], and all follow-up from it
- ▶ Until today, YACC is very alive...
- ▶ See you on Wednesday, we'll talk about some Static Analysis now that we know on which structure to perform it (please note that: this theory applies to much more than just Static Analysis)