

Contents

1	Basic	1
1.1	.vimrc	1
1.2	IncStack	1
1.3	IncStack windows	1
1.4	random	1
1.5	time	1
2	Math	1
2.1	basic	1
2.2	basic	2
2.3	Chinese Remainder Theorem	3
2.4	Discrete Log	3
2.5	Discrete Kth root	3
2.6	FFT	4
2.7	FWT	4
2.8	Gauss Lagrange Eisenstein reduced form	4
2.9	Lagrange Polynomial	4
2.10	Lucas	5
2.11	Meissel-Lehmer PI	5
2.12	Miller Rabin with Pollard rho	5
2.13	Mod Mul Group Order	5
2.14	NTT	5
2.15	Number Theory Functions	6
2.16	Polynomial root	6
2.17	Subset Zeta Transform	7
3	Data Structure	7
3.1	Disjoint Set	7
3.2	Heavy Light Decomposition	7
3.3	KD Tree	7
3.4	Lowest Common Ancestor	8
3.5	Link Cut Tree	8
3.6	PST	9
3.7	Rbst	9
4	Flow	10
4.1	CostFlow	10
4.2	MaxFlow	10
4.3	KM matching	11
4.4	Matching	11
5	Geometry	12
5.1	2D Geometry	12
5.2	3D ConvexHull	13
5.3	Half plane intersection	14
6	Graph	14
6.1	2-SAT	14
6.2	BCC	14
6.3	Bridge	15
6.4	General Matching	15
6.5	CentroidDecomposition	16
6.6	Diameter	16
6.7	DirectedGraphMinCycle	16
6.8	General Weighted Matching	17
6.9	Graph Sequence Test	19
6.10	maximal cliques	19
6.11	MinMeanCycle	19
6.12	Prufer code	19
6.13	SPFA	20
6.14	Virtual Tree	20
7	String	21
7.1	AC automaton	21
7.2	KMP	21
7.3	Manacher	22
7.4	Suffix Array	22
7.5	Suffix Automaton	23
8	Formulas	24
8.1	Pick's theorem	24
8.2	Graph Properties	24
8.3	Number Theory	24
8.4	Combinatorics	24
8.5	Sum of Powers	24
8.6	Burnside's lemma	24
8.7	Count on a tree	24
9	Team Comments	24
9.1	The Who-have-read Table	24

1 Basic

1.1 .vimrc

```
syntax on
set nu ai bs=2 sw=2 ts=2 et ve=all cb=unnamed mouse=a
ruler incsearch hlsearch
```

1.2 IncStack

```
//stack resize (linux)
#include <sys/resource.h>
void increase_stack_size() {
    const rlim_t ks = 64*1024*1024;
    struct rlimit rl;
    int res=getrlimit(RLIMIT_STACK, &rl);
    if(res==0){
        if(rl.rlim_cur<ks){
            rl.rlim_cur=ks;
            res=setrlimit(RLIMIT_STACK, &rl);
        }
    }
}
```

1.3 IncStack windows

```
//stack resize
asm( "mov %0,%esp\n" ::"g"(mem+10000000) );
//change esp to rsp if 64-bit system
```

1.4 random

```
#include <random>
mt19937 rng(0x5EED);
int randint(int lb, int ub)
{ return uniform_int_distribution<int>(lb, ub)(rng); }
```

1.5 time

```
cout << 1.0 * clock() / CLOCKS_PER_SEC;
```

2 Math

2.1 basic

```
PLL exd_gcd(LL a, LL b) {
    if (a % b == 0) return {0, 1};
    PLL T = exd_gcd(b, a % b);
    return {T.second, T.first - a / b * T.second};
}
LL powmod(LL x, LL p, LL mod) {
    LL s = 1, m = x % mod;
    for (; p; p = m * m % mod, p >= 1)
        if (p&1) s = s * m % mod; // or consider int128
    return s;
}
LL LLMul(LL x, LL y, LL mod) {
    LL m = x, s = 0;
    for (; y; y >= 1, m <= 1, m = m >= mod? m - mod: m)
        if (y&1) s += m, s = s >= mod? s - mod: s;
    return s;
}
LL dangerous_mul(LL a, LL b, LL mod){ // 10 times
    faster than the above in average, but could be
    prone to wrong answer (extreme low prob?)
    return (a * b - (LL)((long double)a * b / mod) * mod)
        % mod;
}
vector<LL> linear_inv(LL p, int k) { // take k
```

```
vector<LL> inv(min(p, 1ll + k));
inv[1] = 1;
for (int i = 2; i < inv.size(); ++i)
    inv[i] = (p - p / i) * inv[p % i] % p;
return inv;
}
```

2.2 basic

```
#include <bits/stdc++.h>
using namespace std;

struct BigNum {
    typedef long long ll;

    int sign;
    ll B; // TODO: assert(N * B * B < LL_LIMIT) if mul is
        used
    int BW; // base width
    vector<ll> cells;

    BigNum(string s = "0", ll b = 10000) : sign(1), B(b),
        BW(ceil(log10(b))) {
        if (s[0] == '-') sign = -1, s = s.substr(1);
        cells.resize((s.size() + BW - 1) / BW);
        for (int i = 0; i < cells.size(); ++i) {
            int lb = max(0, int(s.size()) - (i + 1) * BW);
            int len = min(BW, int(s.size()) - i * BW);
            cells[i] = stoi(s.substr(lb, len));
        }
    }
    BigNum(const vector<ll> &v, ll b = 10000) : sign(1),
        B(b), BW(ceil(log10(b))), cells(v) {}

    friend bool operator<(const BigNum &a, const BigNum &
        b) {
        if (a.sign != b.sign) return a.sign < b.sign;
        if (a.cells.size() != b.cells.size()) return a.
            cells.size() < b.cells.size();
        for (int i = a.cells.size() - 1; ~i; --i)
            if (a.cells[i] != b.cells[i]) return a.cells[i] <
                b.cells[i];
        return false;
    }
    friend bool operator==(const BigNum &a, const BigNum
        &b) { return a.sign == b.sign && a.cells == b.
            cells; }
    friend bool operator!=(const BigNum &a, const BigNum
        &b) { return !(a == b); }
    friend bool operator<=(const BigNum &a, const BigNum
        &b) { return !(b < a); }
    friend bool operator>(const BigNum &a, const BigNum &
        b) { return b < a; }
    friend bool operator>=(const BigNum &a, const BigNum
        &b) { return !(a < b); }

    BigNum& normal(int result_sign = 1) {
        ll c = 0;
        for (int i = 0; i < cells.size(); ++i) {
            if (cells[i] < 0) {
                if (i + 1 == cells.size()) cells.emplace_back
                    (0);
                ll u = (abs(cells[i]) + B - 1) / B;
                cells[i + 1] -= u;
                cells[i] += u * B;
            }
            ll u = cells[i] + c;
            cells[i] = u % B;
            c = u / B;
        }
        for (; c; c /= B) cells.emplace_back(c % B);
        while (cells.size() > 1 && cells.back() == 0) cells.
            pop_back();
        sign = result_sign;
        return *this;
    }

    static vector<ll> add(const vector<ll> &a, const
        vector<ll> &b, int al = -1, int ar = -1, int bl =
        -1, int br = -1) {
```

```
    if (al == -1) al = 0, ar = a.size(), bl = 0, br = b
        .size();
    vector<ll> c(max(ar - al, br - bl));
    for (int i = 0; i < c.size(); ++i)
        c[i] = (al + i < a.size() ? a[al + i] : 0) + (bl
            + i < b.size() ? b[bl + i] : 0);
    return c;
}
static vector<ll> sub(const vector<ll> &a, const
    vector<ll> &b, int al = -1, int ar = -1, int bl =
    -1, int br = -1) {
    if (al == -1) al = 0, ar = a.size(), bl = 0, br = b
        .size();
    vector<ll> c(max(ar - al, br - bl));
    for (int i = 0; i < c.size(); ++i)
        c[i] = (al + i < a.size() ? a[al + i] : 0) - (bl
            + i < b.size() ? b[bl + i] : 0);
    return c;
}
static vector<ll> cat_zero(const vector<ll> &a, int k
    ) {
    vector<ll> b(a.size() + k);
    for (int i = 0; i < a.size(); ++i) b[k + i] = a[i];
    return b;
}

friend BigNum operator+(BigNum x, BigNum y) {
    if (x.sign == y.sign) return BigNum(add(x.cells, y.
        cells)).normal();
    if (x.sign == -1) swap(x, y);
    y.sign = 1;
    if (x >= y) return BigNum(sub(x.cells, y.cells)).
        normal();
    return BigNum(sub(y.cells, x.cells)).normal(-1);
}
friend BigNum operator-(BigNum x, BigNum y) {
    y.sign *= -1;
    return x + y;
}

friend BigNum operator*(BigNum x, BigNum y) {
    if (x.cells.size() < y.cells.size()) swap(x, y);
    int nn = 31 - __builtin_clz(int(x.cells.size())) +
        (__builtin_popcount(int(x.cells.size())) > 1);
    function<vector<ll>(const vector<ll> &, const
        vector<ll> &, int, int, int, int)>
        karatsuba = [&](const vector<ll> &a, const
            vector<ll> &b, int al, int ar, int bl, int
            br) {
        if (al + 256 >= ar) {
            vector<ll> r(ar - al << 1);
            for (int i = 0; i < ar - al; ++i)
                for (int j = 0; j < br - bl; ++j)
                    r[i + j] += a[al + i] * b[bl + j];
            return r;
        }
        vector<ll> z1 = karatsuba(a, b, al + ar >> 1,
            ar, bl + br >> 1, br);
        vector<ll> z2 = karatsuba(a, b, al, al + ar
            >> 1, bl, bl + br >> 1);
        vector<ll> p = cat_zero(z1, ar - al);
        vector<ll> a12 = add(a, a, al, al + ar >> 1,
            al + ar >> 1, ar);
        vector<ll> b12 = add(b, b, bl, bl + br >> 1,
            bl + br >> 1, br);
        vector<ll> ab12 = karatsuba(a12, b12, 0, a12.
            size(), 0, b12.size());
        vector<ll> q1 = sub(ab12, z1);
        vector<ll> q2 = sub(q1, z2);
        vector<ll> q = cat_zero(q2, ar - al >> 1);
        vector<ll> r1 = add(p, q);
        vector<ll> r = add(r1, z2);
        return r;
    };
    x.cells.resize(1 << nn);
    y.cells.resize(1 << nn);
    vector<ll> k = karatsuba(x.cells, y.cells, 0, 1 <<
        nn, 0, 1 << nn);
    return BigNum(k).normal(x.sign * y.sign);
}

friend ostream& operator<<(ostream &os, BigNum x) {
    if (x.sign == -1) os << '-';
```

```

    for (auto it = x.cells.rbegin(); it != x.cells.rend()
         (); ++it) {
        if (it == x.cells.rbegin()) os << *it;
        else os << setw(x.BW) << setfill('0') << *it;
    }
    return os;
}

friend istream& operator>>(istream &is, BigNum &x) {
    string s;
    is >> s;
    x = BigNum(s);
    return is;
}

};

signed main() {
    BigNum a, b;
    cin >> a >> b;

    BigNum ab("1");
    for (BigNum i; i < b; i = i + BigNum("1")) ab = ab *
        a;

    BigNum ba("1");
    for (BigNum i; i < a; i = i + BigNum("1")) ba = ba *
        b;

    cout << ab - ba << endl;

    return 0;
}

```

2.3 Chinese Remainder Theorem

```

PLL CRT(PLL eq1, PLL eq2) {
    LL m1, m2, x1, x2;
    tie(x1, m1) = eq1, tie(x2, m2) = eq2;
    LL g = __gcd(m1, m2);
    if ((x1 - x2) % g) return {-1, 0}; // NO SOLUTION
    m1 /= g, m2 /= g;
    auto p = exd_gcd(m1, m2);
    LL lcm = m1 * m2 * g, res = mul(mul(p.first, (x2 - x1
        ), lcm), m1, lcm) + x1;
    return {(res % lcm + lcm) % lcm, lcm};
}

```

2.4 Discrete Log

```

LL discrete_log(LL b, LL p, LL n) {
    map<LL, LL> att;
    LL m = sqrt((double)p) + 1, M = powmod(b, m * (p - 2)
        , p);
    for (LL cur = 1, i = 0; i < m; ++i, cur = cur * b % p
        )
        if (not att.count(cur)) att[cur] = i;
    for (LL cur = 1, i = 0; i * m < p - 1; ++i, cur = cur
        * M % p)
        if (att.count(n * cur % p))
            return (att[cur * n % p] + i * m) % (p - 1);
    return -1;
}

// find x s.t. b**x % p == n with complexity O(sqrt(N))
// return the smallest
// return -1 if ans doesn't exist

```

2.5 Discrete Kth root

```

/*
 * Solve x for x^P = A mod Q
 * https://arxiv.org/pdf/1111.4877.pdf
 * in  $O((\lg Q)^2 + Q^{0.25} (\lg Q)^3)$ 
 * Idea:
 *  $(P, Q-1) = 1 \rightarrow P^{-1} \bmod (Q-1)$  exists
 * x has solution iff  $A^{((Q-1)/P)} = 1 \bmod Q$ 

```

```

 * PP  $\mid (Q-1) \rightarrow P < \sqrt{Q}$ , solve  $\lg Q$  rounds of
   discrete log
 * else  $\rightarrow$  find a s.t.  $s \mid (P a - 1) \rightarrow \text{ans} = A^a$ 
 */

void gcd(LL a, LL b, LL& x, LL& y, LL& g) {
    if (b == 0) {
        x = 1, y = 0, g = a;
        return;
    }
    LL tx, ty;
    gcd(b, a % b, tx, ty, g);
    x = ty;
    y = tx - ty * (a / b);
    return;
}

LL P, A, Q, g;
//  $x^P = A \bmod Q$ 

const int X = 1e5;

LL base;
LL ae[X], aXe[X], iaXe[X];
unordered_map<LL, LL> ht;

void build(LL a) { // ord(a) = P < sqrt(Q)
    base = a;
    ht.clear();
    ae[0] = 1;
    ae[1] = a;
    aXe[0] = 1;
    aXe[1] = pw(a, X, Q);
    iaXe[0] = 1;
    iaXe[1] = pw(aXe[1], Q - 2, Q);
    REP(i, 2, X - 1) {
        ae[i] = mul(ae[i - 1], ae[1], Q);
        aXe[i] = mul(aXe[i - 1], aXe[1], Q);
        iaXe[i] = mul(iaXe[i - 1], iaXe[1], Q);
    }
    FOR(i, X)
        ht[ae[i]] = i;
}

LL dis_log(LL x) {
    FOR(i, X) {
        LL iaXi = iaXe[i];
        LL rst = mul(x, iaXi, Q);
        if (ht.count(rst)) {
            LL res = i * X + ht[rst];
            return res;
        }
    }
}

LL main2() {
    LL t = 0, s = Q - 1;
    while (s % P == 0) {
        ++t;
        s /= P;
    }
    if (A == 0) return 0;

    if (t == 0) {
        //  $a^{P^{-1} \bmod \phi(Q)}$ 
        LL x, y, _;
        gcd(P, Q - 1, x, y, _);
        if (x < 0) {
            x = (x % (Q - 1) + Q - 1) % (Q - 1);
        }
        LL ans = pw(A, x, Q);
        if (pw(ans, P, Q) != A)
            while (1)
                ;
        return ans;
    }

    // A is not P-residue
    if (pw(A, (Q - 1) / P, Q) != 1) return -1;

    for (g = 2; g < Q; ++g) {
        if (pw(g, (Q - 1) / P, Q) != 1) break;
    }
    LL alpha = 0;

```

```

{
    LL y, _;
    gcd(P, s, alpha, y, _);
    if (alpha < 0) alpha = (alpha % (Q - 1) + Q - 1) %
        (Q - 1);
}

if (t == 1) {
    LL ans = pw(A, alpha, Q);
    return ans;
}

LL a = pw(g, (Q - 1) / P, Q);
build(a);
LL b = pw(A, add(mul(P % (Q - 1), alpha, Q - 1), Q -
    2, Q - 1), Q);
LL c = pw(g, s, Q);
LL h = 1;

LL e = (Q - 1) / s / P; // r^{t-1}
REP(i, 1, t - 1) {
    e /= P;
    LL d = pw(b, e, Q);
    LL j = 0;
    if (d != 1) {
        j = -dis_log(d);
        if (j < 0) j = (j % (Q - 1) + Q - 1) % (Q - 1);
    }
    b = mul(b, pw(c, mul(P % (Q - 1), j, Q - 1), Q), Q);
    ;
    h = mul(h, pw(c, j, Q), Q);
    c = pw(c, P, Q);
}

LL ans = mul(pw(A, alpha, Q), h, Q);

return ans;
}

```

2.6 FFT

```

typedef complex<double> cpx;
const double PI = acos(-1);
vector<cpx> FFT(vector<cpx> &P, bool inv = 0) {
    assert(__builtin_popcount(P.size()) == 1);
    int lg = 31 - __builtin_clz(P.size()), n = 1 << lg;
    // == P.size();
    for (int j = 1, i = 0; j < n - 1; ++j) {
        for (int k = n >> 1; k > (i ^ k); k >>= 1);
        if (j < i) swap(P[i], P[j]);
    } //bit reverse
    auto w1 = exp((2 - 4 * inv) * PI / n * cpx(0, 1)); //
    order is 1<<lg
    for (int i = 1; i <= lg; ++i) {
        auto wn = pow(w1, 1<<(lg - i)); // order is 1<<i
        for (int k = 0; k < (1<<lg); k += 1 << i) {
            cpx base = 1;
            for (int j = 0; j < (1 << i - 1); ++j, base =
                base * wn) {
                auto t = base * P[k + j + (1 << i - 1)];
                auto u = P[k + j];
                P[k + j] = u + t;
                P[k + j + (1 << i - 1)] = u - t;
            }
        }
    }
    if (inv)
        for (int i = 0; i < n; ++i) P[i] /= n;
    return P;
} //faster performance with calling by reference

```

2.7 FWT

```

vector<LL> fast_OR_transform(vector<LL> f, bool inverse
) {
    for (int i = 0; (2 << i) <= f.size(); ++i)
        for (int j = 0; j < f.size(); j += 2 << i)
            for (int k = 0; k < (1 << i); ++k)

```

```

                f[j + k + (1 << i)] += f[j + k] * (inverse? -1
                    : 1);
    return f;
}
vector<LL> rev(vector<LL> A) {
    for (int i = 0; i < A.size(); i += 2) swap(A[i], A[i
        ^ (A.size() - 1)]);
    return A;
}
vector<LL> fast_AND_transform(vector<LL> f, bool
    inverse) {
    return rev(fast_OR_transform(rev(f), inverse));
}
vector<LL> fast_XOR_transform(vector<LL> f, bool
    inverse) {
    for (int i = 0; (2 << i) <= f.size(); ++i)
        for (int j = 0; j < f.size(); j += 2 << i)
            for (int k = 0; k < (1 << i); ++k) {
                int u = f[j + k], v = f[j + k + (1 << i)];
                f[j + k + (1 << i)] = u - v, f[j + k] = u + v;
            }
    if (inverse) for (auto &a : f) a /= f.size();
    return f;
}

```

2.8 Gauss Lagrange Eisenstein reduced form

```

// To find min f(x, y) = a * x * x + b * x * y + c * y
    * y
// (x, y) <- Z^2 nonzero
// return (x, y)
PLL form(LL a, LL b, LL c) {
    assert(b * b < 4 * a * c and a > 0);
    LL x, y;
    if (a > c) return tie(x, y) = form(c, b, a), {y, x};
    if (a == c and b < 0) return tie(x, y) = form(a, -b,
        c), {-x, y};
    if (b > a or b <= -a) {
        LL n = (a - b) / (2 * a);
        // -a < 2 * a * n + b <= a
        if (2 * a * n > a - b) --n;
        tie(x, y) = form(a, 2 * a * n + b, a * n * n + b *
            n + c);
        return {x - n * y, y};
    }
    // 1 <= a <= c and -a < b <= a and (a == c implies b
        >= 0)
    return {1, 0};
}

```

2.9 Lagrange Polynomial

```

struct Lagrange_poly {
    vector<LL> fac, p;
    int n;
    Lagrange_poly(vector<LL> p) : p(p) {
        n = p.size();
        fac.resize(n), fac[0] = 1;
        for (int i = 1; i < n; ++i) fac[i] = fac[i - 1] * i
            % MOD;
    }
    LL solve(LL x) {
        if (x < n) return p[x];
        LL ans = 0, to_mul = 1;
        for (int j = 0; j < n; ++j) (to_mul *= MOD - x + j)
            %= MOD;
        for (int j = 0; j < n; ++j) {
            (ans += p[j] * to_mul % MOD *
                powmod(MOD - x + j, MOD - 2, MOD) % MOD *
                powmod(fac[n - 1 - j], MOD - 2, MOD) % MOD *
                powmod(j&1? MOD - fac[j]: fac[j], MOD - 2, MOD))
                %= MOD;
        }
        return ans;
    }
};

```

2.10 Lucas

```
LL fac[1000000] = {1};
LL C(LL a, LL b, LL p) {
    for (int i = 1; i <= p; ++i) fac[i] = fac[i - 1] * i % p;
    LL ans = 1;
    for (; a; a /= p, b /= p) {
        LL A = a % p, B = b % p;
        if (A < B) return 0;
        (ans *= fac[A] * powmod(fac[B] * fac[A - B] % p, p - 2, p) % p) %= p;
    }
    return ans;
}
```

2.11 Meissel-Lehmer PI

```
LL PI(LL m);
const int MAXM = 1000, MAXN = 650, UPBD = 1000000;
// 650 ~ PI(cbrt(1e11))
LL pi[UPBD] = {0}, phi[MAXM][MAXN];
vector<LL> primes;
void init() {
    fill(pi + 2, pi + UPBD, 1);
    for (LL p = 2; p < UPBD; ++p)
        if (pi[p]) {
            for (LL N = p * p; N < UPBD; N += p)
                pi[N] = 0;
            primes.push_back(p);
        }
    for (int i = 1; i < UPBD; ++i) pi[i] += pi[i - 1];
    for (int i = 0; i < MAXM; ++i)
        phi[i][0] = i;
    for (int i = 1; i < MAXM; ++i)
        for (int j = 1; j < MAXN; ++j)
            phi[i][j] = phi[i][j - 1] - phi[i / primes[j - 1]][j - 1];
}
LL P_2(LL m, LL n) {
    LL ans = 0;
    for (LL i = n; primes[i] * primes[i] <= m and i < primes.size(); ++i)
        ans += PI(m / primes[i]) - i;
    return ans;
}
LL PHI(LL m, LL n) {
    if (m < MAXM and n < MAXN) return phi[m][n];
    if (n == 0) return m;
    LL p = primes[n - 1];
    if (m < UPBD) {
        if (m <= p) return 1;
        if (m <= p * p * p) return pi[m] - n + 1 + P_2(m, n);
    }
    return PHI(m, n - 1) - PHI(m / p, n - 1);
}
LL PI(LL m) {
    if (m < UPBD) return pi[m];
    LL y = cbrt(m) + 10, n = pi[y];
    return PHI(m, n) + n - 1 - P_2(m, n);
}
```

2.12 Miller Rabin with Pollard rho

```
bool miller_rabin(LL n, int s = 7) {
    const LL wits[7] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022};
    auto witness = [=](LL a, LL n, LL u, int t) {
        LL x = powmod(a, u, n), nx; // use Llmul, remember
        for (int i = 0; i < t; ++i, x = nx) {
            nx = Llmul(x, x, n);
            if (nx == 1 and x != 1 and x != n - 1) return true;
        }
        return x != 1;
    };
}
```

```
if (n < 2) return 0;
if (n & 1 ^ 1) return n == 2;
LL u = n - 1, t = 0, a; // n == (u << t) + 1
while (u & 1 ^ 1) u >>= 1, ++t;
while (s--)
    if ((a = wits[s] % n) and witness(a, n, u, t))
        return 0;
return 1;
}
// Pollard_rho
LL pollard_rho(LL n) {
    auto f = [=](LL x, LL n) { return Llmul(x, x, n) + 1; };
    if (n & 1 ^ 1) return 2;
    while (true) {
        LL x = rand() % (n - 1) + 1, y = 2, d = 1;
        for (int sz = 2; d == 1; y = x, sz <= 1)
            for (int i = 0; i < sz and d <= 1; ++i)
                x = f(x, n), d = __gcd(abs(x - y), n);
        if (d and n - d) return d;
    }
}
vector<pair<LL, int>> factor(LL m) {
    vector<pair<LL, int>> ans;
    while (m != 1) {
        LL cur = m;
        while (not miller_rabin(cur)) cur = pollard_rho(cur);
        ans.emplace_back(cur, 0);
        while (m % cur == 0) ++ans.back().second, m /= cur;
    }
    sort(ans.begin(), ans.end());
    return ans;
}
```

2.13 Mod Mul Group Order

```
#include "Miller_Rabin_with_Pollard_rho.cpp"
LL phi(LL m) {
    auto fac = factor(m);
    return accumulate(fac.begin(), fac.end(), m, [](LL a, pair<LL, int> p_r) {
        return a / p_r.first * (p_r.first - 1);
    });
}
LL order(LL x, LL m) {
    // assert(__gcd(x, m) == 1);
    LL ans = phi(m);
    for (auto P: factor(ans)) {
        LL p = P.first, t = P.second;
        for (int i = 0; i < t; ++i) {
            if (powmod(x, ans / p, m) == 1) ans /= p;
            else break;
        }
    }
    return ans;
}
LL cycles(LL a, LL m) {
    if (m == 1) return 1;
    return phi(m) / order(a, m);
}
```

2.14 NTT

```
/* p == (a << n) + 1
n 1 << n p a root
5 32 97 3 5
6 64 193 3 5
7 128 257 2 3
8 256 257 1 3
9 512 7681 15 17
10 1024 12289 12 11
11 2048 12289 6 11
12 4096 12289 3 11
13 8192 40961 5 3
14 16384 65537 4 3
15 32768 65537 2 3
16 65536 65537 1 3
```

```

17 131072      786433      6      10
18 262144      786433      3      10 (605028353,
   2308, 3)
19 524288      5767169     11      3
20 1048576     7340033      7      3
21 2097152     23068673     11      3
22 4194304     104857601    25      3
23 8388608     167772161    20      3
24 16777216     167772161    10      3
25 33554432     167772161     5      3 (1107296257, 33,
   10)
26 67108864     469762049     7      3
27 134217728    2013265921    15     31 */
LL root = 10, p = 786433, a = 3;
LL powM(LL x, LL b) {
    LL s = 1, m = x % p;
    for (; b; m = m * m % p, b >= 1)
        if (b&1) s = s * m % p;
    return s;
}
vector<LL> NTT(vector<LL> P, bool inv = 0) {
    assert(__builtin_popcount(P.size()) == 1);
    int lg = 31 - __builtin_clz(P.size()), n = 1 << lg;
    // == P.size();
    for (int j = 1, i = 0; j < n - 1; ++j) {
        for (int k = n >> 1; k > (i ^ k); k >= 1);
        if (j < i) swap(P[i], P[j]);
    } //bit reverse
    LL w1 = powM(root, a * (inv ? p - 2 : 1)); // order is
    1<<lg
    for (LL i = 1; i <= lg; ++i) {
        LL wn = powM(w1, 1<<(lg - i)); // order is 1<<i
        for (int k = 0; k < (1<<lg); k += 1 << i) {
            LL base = 1;
            for (int j = 0; j < (1 << i - 1); ++j, base =
                base * wn % p) {
                LL t = base * P[k + j + (1 << i - 1)] % p;
                LL u = P[k + j] % p;
                P[k + j] = (u + t) % p;
                P[k + j + (1 << i - 1)] = (u - t + p) % p;
            }
        }
    }
    if (inv) {
        LL invN = powM(n, p - 2);
        transform(P.begin(), P.end(), P.begin(), [&](LL a)
            {return a * invN % p;});
    }
    return P;
} //faster performance with calling by reference

```

2.15 Number Theory Functions

```

vector<bool> Atkin_sieve(int limit) {
    assert(limit > 10 and limit <= 1e9);
    vector<bool> sieve(limit, false);
    sieve[2] = sieve[3] = true;
    for (int x = 1; x * x < limit; ++x)
        for (int y = 1; y * y < limit; ++y) {
            int n = (4 * x * x) + (y * y);
            if (n <= limit && (n % 12 == 1 || n % 12 == 5))
                sieve[n] = sieve[n] ^ true;
            n = (3 * x * x) + (y * y);
            if (n <= limit && n % 12 == 7)
                sieve[n] = sieve[n] ^ true;
            n = (3 * x * x) - (y * y);
            if (x > y && n <= limit && n % 12 == 11)
                sieve[n] = sieve[n] ^ true;
        }
    for (int r = 5; r * r < limit; ++r) if (sieve[r])
        for (int i = r * r; i < limit; i += r * r)
            sieve[i] = false;
    return sieve;
}
vector<bool> Eratosthenes_sieve(int limit) {
    assert(limit >= 10 and limit <= 1e9);
    vector<bool> sieve(limit, true);
    sieve[0] = sieve[1] = false;
    for (int p = 2; p * p < limit; ++p) if (sieve[p]) {

```

```

        for (int n = p * p; n < limit; n += p) sieve[n] =
            false;
    }
    return sieve;
}
template<typename T> vector<T> make_mobius(T limit) {
    auto is_prime = Eratosthenes_sieve(limit);
    vector<T> mobius(limit, 1);
    mobius[0] = 0;
    for (LL p = 2; p < limit; ++p) if (is_prime[p]) {
        for (LL n = p; n < limit; n += p)
            mobius[n] = -mobius[n];
        for (LL n = p * p; n < limit; n += p * p)
            mobius[n] = 0;
    }
    return mobius;
}

```

2.16 Polynomail root

```

const double eps = 1e-12;
const double inf = 1e+12;
double a[10], x[10];
int n;
int sign(double x) { return (x < -eps) ? (-1) : (x >
    eps); }
double f(double a[], int n, double x) {
    double tmp = 1, sum = 0;
    for (int i = 0; i <= n; i++) {
        sum = sum + a[i] * tmp;
        tmp = tmp * x;
    }
    return sum;
}
double binary(double l, double r, double a[], int n) {
    int sl = sign(f(a, n, l)), sr = sign(f(a, n, r));
    if (sl == 0) return l;
    if (sr == 0) return r;
    if (sl * sr > 0) return inf;
    while (r - l > eps) {
        double mid = (l + r) / 2;
        int ss = sign(f(a, n, mid));
        if (ss == 0) return mid;
        if (ss * sl > 0)
            l = mid;
        else
            r = mid;
    }
    return l;
}
void solve(int n, double a[], double x[], int &nx) {
    if (n == 1) {
        x[1] = -a[0] / a[1];
        nx = 1;
        return;
    }
    double da[10], dx[10];
    int ndx;
    for (int i = n; i >= 1; i--) da[i - 1] = a[i] * i;
    solve(n - 1, da, dx, ndx);
    nx = 0;
    if (ndx == 0) {
        double tmp = binary(-inf, inf, a, n);
        if (tmp < inf) x[++nx] = tmp;
        return;
    }
    double tmp;
    tmp = binary(-inf, dx[1], a, n);
    if (tmp < inf) x[++nx] = tmp;
    for (int i = 1; i <= ndx - 1; i++) {
        tmp = binary(dx[i], dx[i + 1], a, n);
        if (tmp < inf) x[++nx] = tmp;
    }
    tmp = binary(dx[ndx], inf, a, n);
    if (tmp < inf) x[++nx] = tmp;
}
int main() {
    scanf("%d", &n);
    for (int i = n; i >= 0; i--) scanf("%lf", &a[i]);
    int nx;

```



```

solve(n, a, x, nx);
for (int i = 1; i <= nx; i++) printf("%.6f\n", x[i]);
}

```

2.17 Subset Zeta Transform

```

// if f is add function:
// low2high = true -> zeta(a)[s] = sum(a[t] for t in s)
// low2high = false -> zeta(a)[t] = sum(a[s] for t in s)
// else if f is sub function, you get inverse zeta function
template<typename T>
vector<T> subset_zeta_transform(int n, vector<T> a,
    function<T(T, T)> f, bool low2high = true) {
    assert(a.size() == 1 << n);
    if (low2high) {
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < 1 << n; ++j)
                if (j >> i & 1)
                    a[j] = f(a[j], a[j ^ 1 << i]);
    } else {
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < 1 << n; ++j)
                if (~j >> i & 1)
                    a[j] = f(a[j], a[j | 1 << i]);
    }
    return a;
}

```

3 Data Structure

3.1 Disjoint Set

```

struct DisjointSet {
    // save() is like recursive
    // undo() is like return
    int n, compo;
    vector<int> fa, sz;
    vector<pair<int*, int>> h;
    vector<int> sp;
    void init(int tn) {
        compo = n = tn, sz.assign(n, 1), fa.resize(n);
        for (int i = 0; i < n; ++i)
            fa[i] = i, sz[i] = 1;
        sp.clear(); h.clear();
    }
    void assign(int *k, int v) {
        h.push_back({k, *k});
        *k = v;
    }
    void save() { sp.push_back(h.size()); }
    void undo() {
        assert(!sp.empty());
        int last = sp.back(); sp.pop_back();
        while (h.size() != last) {
            auto x = h.back(); h.pop_back();
            *x.first = x.second;
        }
    }
    int f(int x) {
        while (fa[x] != x) x = fa[x];
        return x;
    }
    bool uni(int x, int y) {
        x = f(x), y = f(y);
        if (x == y) return false;
        if (sz[x] < sz[y]) swap(x, y);
        assign(&sz[x], sz[x] + sz[y]);
        assign(&fa[y], x);
        --compo;
        return true;
    }
} djs;

```

3.2 Heavy Light Decomposition

```

struct HLD {
    using Tree = vector<vector<int>>;
    vector<int> par, head, vid, len, inv;

    HLD(const Tree &g) : par(g.size()), head(g.size()),
        vid(g.size()), len(g.size()), inv(g.size()) {
        int k = 0;
        vector<int> size(g.size(), 1);
        function<void(int, int)> dfs_size = [&](int u, int
            p) {
            for (int v : g[u]) {
                if (v != p) {
                    dfs_size(v, u);
                    size[u] += size[v];
                }
            }
        };
        function<void(int, int, int)> dfs_dcmp = [&](int u,
            int p, int h) {
            par[u] = p;
            head[u] = h;
            vid[u] = k++;
            inv[vid[u]] = u;
            for (int v : g[u]) {
                if (v != p && size[u] < size[v] * 2) {
                    dfs_dcmp(v, u, h);
                }
            }
            for (int v : g[u]) {
                if (v != p && size[u] >= size[v] * 2) {
                    dfs_dcmp(v, u, v);
                }
            }
        };
        dfs_size(0, -1);
        dfs_dcmp(0, -1, 0);
        for (int i = 0; i < g.size(); ++i) {
            ++len[head[i]];
        }
    }

    template<typename T>
    void foreach(int u, int v, T f) {
        while (true) {
            if (vid[u] > vid[v]) {
                if (head[u] == head[v]) {
                    f(vid[v] + 1, vid[u], 0);
                    break;
                } else {
                    f(vid[head[u]], vid[u], 1);
                    u = par[head[u]];
                }
            } else {
                if (head[u] == head[v]) {
                    f(vid[u] + 1, vid[v], 0);
                    break;
                } else {
                    f(vid[head[v]], vid[v], 0);
                    v = par[head[v]];
                }
            }
        }
    }
};

```

3.3 KD Tree

```

#include <bits/stdc++.h>
using namespace std;

struct KNode {
    vector<int> v;
    KNode *lc, *rc;
    KNode(const vector<int> &_v) : v(_v), lc(nullptr),
        rc(nullptr) {}
    static KNode *buildKDTree(vector<vector<int>> &pnts,
        int lb, int rb, int dpt) {

```

```

    if (rb - lb < 1) return nullptr;
    int axis = dpt % pnts[0].size();
    int mb = lb + rb >> 1;
    nth_element(pnts.begin() + lb, pnts.begin() + mb,
        pnts.begin() + rb, [&](const vector<int> &a,
            const vector<int> &b) {
            return a[axis] < b[axis];
        });
    KDNode *t = new KDNode(pnts[mb]);
    t->lc = buildKDTree(pnts, lb, mb, dpt + 1);
    t->rc = buildKDTree(pnts, mb + 1, rb, dpt + 1);
    return t;
}
static void release(KDNode *t) {
    if (t->lc) release(t->lc);
    if (t->rc) release(t->rc);
    delete t;
}
static void searchNearestNode(KDNode *t, KDNode *q,
    KDNode *&c, int dpt) {
    int axis = dpt % t->v.size();
    if (t->v != q->v && (c == nullptr || dis(q, t) <
        dis(q, c))) c = t;
    if (t->lc && (!t->rc || q->v[axis] < t->v[axis])) {
        searchNearestNode(t->lc, q, c, dpt + 1);
        if (t->rc && (c == nullptr || 1LL * (t->v[axis] -
            q->v[axis]) * (t->v[axis] - q->v[axis]) <
                dis(q, c))) {
            searchNearestNode(t->rc, q, c, dpt + 1);
        }
    } else if (t->rc) {
        searchNearestNode(t->rc, q, c, dpt + 1);
        if (t->lc && (c == nullptr || 1LL * (t->v[axis] -
            q->v[axis]) * (t->v[axis] - q->v[axis]) <
                dis(q, c))) {
            searchNearestNode(t->lc, q, c, dpt + 1);
        }
    }
}
static int64_t dis(KDNode *a, KDNode *b) {
    int64_t r = 0;
    for (int i = 0; i < a->v.size(); ++i) {
        r += 1LL * (a->v[i] - b->v[i]) * (a->v[i] - b->v[i]);
    }
    return r;
}
}
signed main() {
    ios::sync_with_stdio(false);
    int T;
    cin >> T;
    for (int ti = 0; ti < T; ++ti) {
        int N;
        cin >> N;
        vector<vector<int>> pnts(N, vector<int>(2));
        for (int i = 0; i < N; ++i) {
            for (int j = 0; j < 2; ++j) {
                cin >> pnts[i][j];
            }
        }
        vector<vector<int>> _pnts = pnts;
        KDNode *root = KDNode::buildKDTree(_pnts, 0, pnts.
            size(), 0);
        for (int i = 0; i < N; ++i) {
            KDNode *q = new KDNode(pnts[i]);
            KDNode *c = nullptr;
            KDNode::searchNearestNode(root, q, c, 0);
            cout << KDNode::dis(c, q) << endl;
            delete q;
        }
        KDNode::release(root);
    }
    return 0;
}

```

3.4 Lowest Common Ancestor

```
const int LOG = 20, N = 200000;
```

```

vector<int> g[N];
int par[N][LOG], tin[N], tout[N];
bool anc(int u, int p) {
    return tin[p] <= tin[u] and tout[u] <= tout[p];
}
void dfs(int v, int p) { // root's parent is root
    par[v][0] = p;
    for (int j = 1; j < LOG; ++j)
        par[v][j] = par[par[v][j - 1]][j - 1];
    static int timer = 0;
    tin[v] = timer++;
    for (int u: g[v]) {
        if (u == p) continue;
        dfs(u, v);
    }
    tout[v] = timer++;
}
int lca(int x, int y) {
    if (anc(x, y)) return y;
    for (int j = LOG - 1; j >= 0; --j)
        if (not anc(x, par[y][j])) y = par[y][j];
    return par[y][0];
}

```

3.5 Link Cut Tree

```

const int MXN = 100005;
const int MEM = 100005;
struct Splay {
    static Splay nil, mem[MEM], *pmem;
    Splay *ch[2], *f;
    int val, rev, size;
    Splay(int _val=-1) : val(_val), rev(0), size(1) {
        f = ch[0] = ch[1] = &nil;
    }
    bool isr() {
        return f->ch[0] != this && f->ch[1] != this;
    }
    int dir() {
        return f->ch[0] == this ? 0 : 1;
    }
    void setCh(Splay *c, int d) {
        ch[d] = c;
        if (c != &nil) c->f = this;
        pull();
    }
    void push() {
        if (!rev) return;
        swap(ch[0], ch[1]);
        if (ch[0] != &nil) ch[0]->rev ^= 1;
        if (ch[1] != &nil) ch[1]->rev ^= 1;
        rev = 0;
    }
    void pull() {
        size = ch[0]->size + ch[1]->size + 1;
        if (ch[0] != &nil) ch[0]->f = this;
        if (ch[1] != &nil) ch[1]->f = this;
    }
} Splay::nil, Splay::mem[MEM], *Splay::pmem = Splay::
    mem;
Splay *nil = &Splay::nil;
void rotate(Splay *x) {
    Splay *p = x->f;
    int d = x->dir();
    if (!p->isr()) p->f->setCh(x, p->dir());
    else x->f = p->f;
    p->setCh(x->ch[!d], d);
    x->setCh(p, !d);
    p->pull(); x->pull();
}
vector<Splay*> splayVec;
void splay(Splay *x) {
    splayVec.clear();
    for (Splay *q=x; q=q->f) {
        splayVec.push_back(q);
        if (q->isr()) break;
    }
    reverse(begin(splayVec), end(splayVec));
    for (auto it : splayVec) it->push();
    while (!x->isr()) {
        if (x->f->isr()) rotate(x);
        else if (x->dir() == x->f->dir())
            rotate(x->f), rotate(x);
    }
}

```



```

    else rotate(x), rotate(x);
}
}
int id(Splay *x) { return x - Splay::mem + 1; }
Splay* access(Splay *x){
    Splay *q = nil;
    for (; x != nil; x = x->f){
        splay(x);
        x->setCh(q, 1);
        q = x;
    }
    return q;
}
void chroot(Splay *x){
    access(x);
    splay(x);
    x->rev ^= 1;
    x->push(); x->pull();
}
void link(Splay *x, Splay *y){
    access(x);
    splay(x);
    chroot(y);
    x->setCh(y, 1);
}
void cut_p(Splay *y) {
    access(y);
    splay(y);
    y->push();
    y->ch[0] = y->ch[0]->f = nil;
}
void cut(Splay *x, Splay *y){
    chroot(x);
    cut_p(y);
}
Splay* get_root(Splay *x) {
    access(x);
    splay(x);
    for (; x->ch[0] != nil; x = x->ch[0])
        x->push();
    splay(x);
    return x;
}
bool conn(Splay *x, Splay *y) {
    x = get_root(x);
    y = get_root(y);
    return x == y;
}
Splay* lca(Splay *x, Splay *y) {
    access(x);
    access(y);
    splay(x);
    if (x->f == nil) return x;
    else return x->f;
}
}

```

3.6 PST

```

constexpr int PST_MAX_NODES = 1 << 22; // recommended:
// prepare at least 4nlg n, n to power of 2
struct Pst {
    int maxv;
    Pst *lc, *rc;
    Pst() : lc(nullptr), rc(nullptr), maxv(0) {}
    Pst(const Pst *rhs) : lc(rhs->lc), rc(rhs->rc), maxv(
        rhs->maxv) {}
    static Pst *build(int lb, int rb) {
        Pst *t = new(mem_ptr++) Pst;
        if (rb - lb == 1) return t;
        t->lc = build(lb, lb + rb >> 1);
        t->rc = build(lb + rb >> 1, rb);
        return t;
    }
    static int query(Pst *t, int lb, int rb, int ql, int
        qr) {
        if (qr <= lb || rb <= ql) return 0;
        if (ql <= lb && rb <= qr) return t->maxv;
        int mb = lb + rb >> 1;
        return max(query(t->lc, lb, mb, ql, qr), query(t->
            rc, mb, rb, ql, qr));
    }
}

```

```

}
static Pst *modify(Pst *t, int lb, int rb, int k, int
    v) {
    Pst *n = new(mem_ptr++) Pst(t);
    if (rb - lb == 1) return n->maxv = v, n;
    int mb = lb + rb >> 1;
    if (k < mb) n->lc = modify(t->lc, lb, mb, k, v);
    else n->rc = modify(t->rc, mb, rb, k, v);
    n->maxv = max(n->lc->maxv, n->rc->maxv);
    return n;
}
static Pst mem_pool[PST_MAX_NODES];
static Pst *mem_ptr;
static void clear() {
    while (mem_ptr != mem_pool) (--mem_ptr)->~Pst();
}
} Pst::mem_pool[PST_MAX_NODES], *Pst::mem_ptr = Pst::
    mem_pool;
/*
Usage:

vector<Pst *> version(N + 1);
version[0] = Pst::build(0, C); // [0, C)
for (int i = 0; i < N; ++i) version[i + 1] = modify(
    version[i], ...);
Pst::query(...);
Pst::clear();

*/

```

3.7 Rbst

```

constexpr int RBST_MAX_NODES = 1 << 20;
struct Rbst {
    int size, val;
    // int minv;
    // int add_tag, rev_tag;
    Rbst *lc, *rc;
    Rbst(int v = 0) : size(1), val(v), lc(nullptr), rc(
        nullptr) {
        // minv = v;
        // add_tag = 0;
        // rev_tag = 0;
    }
    void push() {
        /*
        if (add_tag) { // unprocessed subtree has tag on
            root
            val += add_tag;
            minv += add_tag;
            if (lc) lc->add_tag += add_tag;
            if (rc) rc->add_tag += add_tag;
            add_tag = 0;
        }
        if (rev_tag) {
            swap(lc, rc);
            if (lc) lc->rev_tag ^= 1;
            if (rc) rc->rev_tag ^= 1;
            rev_tag = 0;
        }
        */
    }
    void pull() {
        size = 1;
        // minv = val;
        if (lc) {
            lc->push();
            size += lc->size;
            // minv = min(minv, lc->minv);
        }
        if (rc) {
            rc->push();
            size += rc->size;
            // minv = min(minv, rc->minv);
        }
    }
    static int get_size(Rbst *t) { return t ? t->size :
        0; }
    static void split(Rbst *t, int k, Rbst *&a, Rbst *&b)
        {
    }
}

```

```

if (!t) return void(a = b = nullptr);
t->push();
if (get_size(t->lc) >= k) {
    b = t;
    split(t->lc, k, a, b->lc);
    b->pull();
} else {
    a = t;
    split(t->rc, k - get_size(t->lc) - 1, a->rc, b);
    a->pull();
}
} // splits t, left k elements to a, others to b,
  maintaining order
static Rbst *merge(Rbst *a, Rbst *b) {
    if (!a || !b) return a ? a : b;
    if (rand() % (a->size + b->size) < a->size) {
        a->push();
        a->rc = merge(a->rc, b);
        a->pull();
        return a;
    } else {
        b->push();
        b->lc = merge(a, b->lc);
        b->pull();
        return b;
    }
} // merges a and b, maintaing order
static int lower_bound(Rbst *t, const int &key) {
    if (!t) return 0;
    if (t->val >= key) return lower_bound(t->lc, key);
    return get_size(t->lc) + 1 + lower_bound(t->rc, key);
}
static void insert(Rbst *&t, const int &key) {
    int idx = lower_bound(t, key);
    Rbst *tt;
    split(t, idx, tt, t);
    t = merge(merge(tt, new(mem_ptr++) Rbst(key)), t);
}

static Rbst mem_pool[RBST_MAX_NODES]; // CAUTION!!
static Rbst *mem_ptr;
static void clear() {
    while (mem_ptr != mem_pool) (--mem_ptr)->~Rbst();
}
} Rbst::mem_pool[RBST_MAX_NODES], *Rbst::mem_ptr = Rbst::
  mem_pool;

/*
Usage:

Rbst *t = new(Rbst::mem_ptr++) Rbst(val);
t = Rbst::merge(t, new(Rbst::mem_ptr++) Rbst(
  another_val));
Rbst *a, *b;
Rbst::split(t, 2, a, b); // a will have first 2
  elements, b will have the rest, in order
Rbst::clear(); // wipes out all memory; if you know the
  mechanism of clear() you can maintain many trees
*/

```

4 Flow

4.1 CostFlow

```

template <class TF, class TC>
struct CostFlow {
    static const int MAXV = 205;
    static const TC INF = 0x3f3f3f3f;
    struct Edge {
        int v, r;
        TF f;
        TC c;
        Edge(int _v, int _r, TF _f, TC _c) : v(_v), r(_r),
          f(_f), c(_c) {}
    };
    int n, s, t, pre[MAXV], pre_E[MAXV], inq[MAXV];

```

```

    TF fl;
    TC dis[MAXV], cost;
    vector<Edge> E[MAXV];
    CostFlow(int _n, int _s, int _t) : n(_n), s(_s), t(_t)
      , fl(0), cost(0) {}
    void add_edge(int u, int v, TF f, TC c) {
        E[u].emplace_back(v, E[v].size(), f, c);
        E[v].emplace_back(u, E[u].size() - 1, 0, -c);
    }
    pair<TF, TC> flow() {
        while (true) {
            for (int i = 0; i < n; ++i) {
                dis[i] = INF;
                inq[i] = 0;
            }
            dis[s] = 0;
            queue<int> que;
            que.emplace(s);
            while (not que.empty()) {
                int u = que.front();
                que.pop();
                inq[u] = 0;
                for (int i = 0; i < E[u].size(); ++i) {
                    int v = E[u][i].v;
                    TC w = E[u][i].c;
                    if (E[u][i].f > 0 and dis[v] > dis[u] + w) {
                        pre[v] = u;
                        pre_E[v] = i;
                        dis[v] = dis[u] + w;
                        if (not inq[v]) {
                            inq[v] = 1;
                            que.emplace(v);
                        }
                    }
                }
            }
            if (dis[t] == INF) break;
            TF tf = INF;
            for (int v = t, u, l; v != s; v = u) {
                u = pre[v];
                l = pre_E[v];
                tf = min(tf, E[u][l].f);
            }
            for (int v = t, u, l; v != s; v = u) {
                u = pre[v];
                l = pre_E[v];
                E[u][l].f -= tf;
                E[v][E[u][l].r].f += tf;
            }
            cost += tf * dis[t];
            fl += tf;
        }
        return {fl, cost};
    }
};

```

4.2 MaxFlow

```

template <class T>
struct Dinic {
    static const int MAXV = 10000;
    static const T INF = 0x3f3f3f3f;
    struct Edge {
        int v;
        T f;
        int re;
        Edge(int _v, T _f, int _re) : v(_v), f(_f), re(_re)
          {}
    };
    int n, s, t, level[MAXV];
    vector<Edge> E[MAXV];
    int now[MAXV];
    Dinic(int _n, int _s, int _t) : n(_n), s(_s), t(_t)
      {}
    void add_edge(int u, int v, T f, bool bidirectional =
      false) {
        E[u].emplace_back(v, f, E[v].size());
        E[v].emplace_back(u, 0, E[u].size() - 1);
        if (bidirectional) {
            E[v].emplace_back(u, f, E[u].size() - 1);

```

```

    }
}
bool BFS() {
    memset(level, -1, sizeof(level));
    queue<int> que;
    que.emplace(s);
    level[s] = 0;
    while (not que.empty()) {
        int u = que.front();
        que.pop();
        for (auto it : E[u]) {
            if (it.f > 0 and level[it.v] == -1) {
                level[it.v] = level[u] + 1;
                que.emplace(it.v);
            }
        }
    }
    return level[t] != -1;
}
T DFS(int u, T nf) {
    if (u == t) return nf;
    T res = 0;
    while (now[u] < E[u].size()) {
        Edge &it = E[u][now[u]];
        if (it.f > 0 and level[it.v] == level[u] + 1) {
            T tf = DFS(it.v, min(nf, it.f));
            res += tf;
            nf -= tf;
            it.f -= tf;
            E[it.v][it.re].f += tf;
            if (nf == 0) return res;
        } else {
            ++now[u];
        }
    }
    if (not res) level[u] = -1;
    return res;
}
T flow(T res = 0) {
    while (BFS()) {
        T temp;
        memset(now, 0, sizeof(now));
        while (temp = DFS(s, INF)) {
            res += temp;
            res = min(res, INF);
        }
    }
    return res;
}
};

```

4.3 KM matching

```

const int MAXN = 1000;
template <class TC>
struct KM_matching { // if there's no edge, the weight
    is 0
    // complexity: O(n^3), support for negative edge
    int n, matchy[MAXN];
    bool visx[MAXN], visy[MAXN];
    TC adj[MAXN][MAXN], coverx[MAXN], covery[MAXN], slack
        [MAXN];
    KM_matching(int _n) : n(_n) {
        memset(matchy, -1, sizeof(matchy));
        memset(coverx, 0, sizeof(coverx));
        memset(adj, 0, sizeof(adj));
    }
    void add_edge(int x, int y, TC w) { adj[x][y] = w; }
    bool aug(int u) {
        visx[u] = true;
        for (int v = 0; v < n; ++v)
            if (not visy[v]) {
                TC t = coverx[u] + covery[v] - adj[u][v];
                if (t == 0) { // The edge is in Equality
                    subgraph
                    visy[v] = true;
                    if (matchy[v] == -1 or aug(matchy[v]))
                        return matchy[v] = u, true;
                }
                else if (slack[v] > t) slack[v] = t;
            }
        return false;
    }
};

```

```

    return false;
}
TC solve() {
    for (int u = 0; u < n; ++u)
        coverx[u] = *max_element(adj[u], adj[u] + n);
    for (int u = 0; u < n; ++u) {
        fill(slack, slack + n, INT_MAX);
        while (memset(visx, 0, sizeof(visx)),
            memset(visy, 0, sizeof(visy)),
            not aug(u)) {
            TC d = INT_MAX;
            for (int v = 0; v < n; ++v)
                if (not visy[v]) d = min(d, slack[v]);
            for (int v = 0; v < n; ++v) {
                if (visx[v]) coverx[v] -= d;
                if (visy[v]) covery[v] += d;
            }
        }
    }
    return accumulate(coverx, coverx + n, (TC)0) +
        accumulate(covery, covery + n, (TC)0);
}
};

```

4.4 Matching

```

class matching {
public:
    vector< vector<int> > g;
    vector<int> pa, pb, was;
    int n, m, res, iter;

    matching(int _n, int _m) : n(_n), m(_m) {
        assert(0 <= n && 0 <= m);
        pa = vector<int>(n, -1);
        pb = vector<int>(m, -1);
        was = vector<int>(n, 0);
        g.resize(n);
        res = 0, iter = 0;
    }

    void add_edge(int from, int to) {
        assert(0 <= from && from < n && 0 <= to && to < m);
        g[from].push_back(to);
    }

    bool dfs(int v) {
        was[v] = iter;
        for (int u : g[v])
            if (pb[u] == -1)
                return pa[v] = u, pb[u] = v, true;
            for (int u : g[v])
                if (was[pb[u]] != iter && dfs(pb[u]))
                    return pa[v] = u, pb[u] = v, true;
        return false;
    }

    int solve() {
        while (true) {
            iter++;
            int add = 0;
            for (int i = 0; i < n; i++)
                if (pa[i] == -1 && dfs(i))
                    add++;
            if (add == 0) break;
            res += add;
        }
        return res;
    }

    int run_one(int v) {
        if (pa[v] != -1) return 0;
        iter++;
        return (int) dfs(v);
    }

    pair<vector<bool>, vector<bool>> vertex_cover() {
        solve();
        vector<bool> a_cover(n, true), b_cover(m, false);
        function<void(int)> dfs_aug = [&](int v) {
            a_cover[v] = false;

```

```

    for (int u: g[v])
        if (not b_cover[u])
            b_cover[u] = true, dfs_aug(pb[u]);
    };
    for (int v = 0; v < n; ++v)
        if (a_cover[v] and pa[v] == -1)
            dfs_aug(v);
    return {a_cover, b_cover};
}
};

```

5 Geometry

5.1 2D Geometry

```

namespace geo {
    using pt = complex<double>;
    using cir = pair<pt, double>;
    using poly = vector<pt>;
    using line = pair<pt, pt>; // point to point
    using plane = pair<pt, pt>;
    pt get_pt() { static double a, b; cin >> a >> b;
        return geo::pt(a, b); };
    const double EPS = 1e-10;
    const double PI = acos(-1);
    pt cent(cir C) { return C.first; }
    double radi(cir C) { return C.second; }
    pt st(line H) { return H.first; }
    pt ed(line H) { return H.second; }
    pt vec(line H) { return ed(H) - st(H); }
    int dcmp(double x) { return abs(x) < EPS ? 0 : x > 0
        ? 1 : -1; }
    bool less(pt a, pt b) { return real(a) < real(b) ||
        real(a) == real(b) && imag(a) < imag(b); }
    bool more(pt a, pt b) { return real(a) > real(b) ||
        real(a) == real(b) && imag(a) > imag(b); }
    double dot(pt a, pt b) { return real(conj(a) * b); }
    double cross(pt a, pt b) { return imag(conj(a) * b); }
    double sarea(pt a, pt b, pt c) { return cross(b - a,
        c - a); }
    double area(cir c) { return radi(c) * radi(c) * PI; }
    int ori(pt a, pt b, pt c) { return dcmp(sarea(a, b, c)); }
    double angle(pt a, pt b) { return acos(dot(a, b) /
        abs(a) / abs(b)); }
    pt rotate(pt a, double rad) { return a * pt(cos(rad),
        sin(rad)); }
    pt normal(pt a) { return pt(-imag(a), real(a)) / abs(a); }
    pt normalized(pt a) { return a / abs(a); }

    pt get_line_intersection(line A, line B) {
        pt p = st(A), v = vec(A), q = st(B), w = vec(B);
        return p + v * cross(w, p - q) / cross(v, w);
    }
    double distance_to_line(pt p, line B) {
        return abs(cross(vec(B), p - st(B))) / abs(vec(B));
    }
    double distance_to_segment(pt p, line B) {
        pt a = st(B), b = ed(B), v1(vec(B)), v2(p - a), v3(
            p - b);
        // similar to previous function
        if (a == b) return abs(p - a);
        if (dcmp(dot(v1, v2)) < 0) return abs(v2);
        else if (dcmp(dot(v1, v3)) > 0) return abs(v3);
        return abs(cross(v1, v2)) / abs(v1);
    }
    pt get_line_projection(pt p, line(B)) {
        pt v = vec(B);
        return st(B) + dot(v, p - st(B)) / dot(v, v) * v;
    }
    bool is_segment_proper_intersection(line A, line B) {
        pt a1 = st(A), a2 = ed(A), b1 = st(B), b2 = ed(B);
        double det1 = ori(a1, a2, b1) * ori(a1, a2, b2);
        double det2 = ori(b1, b2, a1) * ori(b1, b2, a2);
        return det1 < 0 && det2 < 0;
    }
}

```

```

double area(poly p) {
    if (p.size() < 3) return 0;
    double area = 0;
    for (int i = 1; i < p.size() - 1; ++i)
        area += sarea(p[0], p[i], p[i + 1]);
    return area / 2;
}
bool is_point_on_segment(pt p, line B) {
    pt a = st(B), b = ed(B);
    return dcmp(sarea(p, a, b)) == 0 && dcmp(dot(a - p,
        b - p)) < 0;
}
bool is_point_in_plane(pt p, line H) {
    return ori(st(H), ed(H), p) > 0;
}
bool is_point_in_polygon(pt p, poly gon) {
    int wn = 0;
    int n = gon.size();
    for (int i = 0; i < n; ++i) {
        if (is_point_on_segment(p, {gon[i], gon[(i + 1) %
            n]})) return true;
        if (not is_point_in_plane(p, {gon[i], gon[(i + 1)
            % n]})) return false;
    }
    return true;
}
poly convex_hull(vector<pt> p) {
    sort(p.begin(), p.end(), less);
    p.erase(unique(p.begin(), p.end()), p.end());
    int n = p.size(), m = 0;
    poly ch(n + 1);
    for (int i = 0; i < n; ++i) { // note that border
        is cleared
        while (m > 1 && ori(ch[m - 2], ch[m - 1], p[i])
            <= 0) --m;
        ch[m++] = p[i];
    }
    for (int i = n - 2, k = m; i >= 0; --i) {
        while (m > k && ori(ch[m - 2], ch[m - 1], p[i])
            <= 0) --m;
        ch[m++] = p[i];
    }
    ch.erase(ch.begin() + m - (n > 1), ch.end());
    return ch;
}
cir circumscribed_circle(poly tri) {
    pt B = tri[1] - tri[0];
    pt C = tri[2] - tri[0];
    double det = 2 * cross(B, C);
    pt r = pt(imag(C) * norm(B) - imag(B) * norm(C),
        real(B) * norm(C) - real(C) * norm(B)) /
        det;
    return {r + tri[0], abs(r)};
}
cir inscribed_circle(poly tri) {
    assert(tri.size() == 3);
    pt ans = 0;
    double div = 0;
    for (int i = 0; i < 3; ++i) {
        double l = abs(tri[(i + 1) % 3] - tri[(i + 2) %
            3]);
        ans += l * tri[i], div += l;
    }
    ans /= div;
    return {ans, distance_to_line(ans, {tri[0], tri
        [1]}); }
}
poly tangent_line_through_point(cir c, pt p) {
    if (dcmp(abs(cent(c) - p) - radi(c)) < 0) return
        {};
    else if (dcmp(abs(cent(c) - p) - radi(c)) == 0)
        return {p};
    double theta = acos(radi(c) / abs(cent(c) - p));
    pt norm_v = normalized(p - cent(c));
    return {cent(c) + radi(c) * rotate(norm_v, +theta),
        cent(c) + radi(c) * rotate(norm_v, -theta)};
}
vector<pt> get_line_circle_intersection(cir d, line B
    ) {
    pt v = vec(B), p = st(B) - cent(d);
}

```

```

double r = radi(d), a = norm(v), b = 2 * dot(p, v),
    c = norm(p) - r * r;
double det = b * b - 4 * a * c;
// t^2 * norm(v) + 2 * t * dot(p, v) + norm(p) - r
// * r = 0
auto get_point = [=](double t) { return st(B) + t *
    v; };
if (dcmp(det) < 0) return {};
if (dcmp(det) == 0) return {get_point(-b / 2 / a)};
return {get_point((-b + sqrt(det)) / 2 / a),
    get_point((-b - sqrt(det)) / 2 / a)};
}
vector<pt> get_circle_circle_intersection(cir c, cir
    d) {
    pt a = cent(c), b = cent(d);
    double r = radi(c), s = radi(d), g = abs(a - b);
    if (dcmp(g) == 0) return {}; // may be C == D
    if (dcmp(r + s - g) < 0 or dcmp(abs(r - s) - g) >
        0) return {};
    pt C_to_D = normalized(b - a);
    double theta = acos((r * r + g * g - s * s) / (2 *
        r * g));
    if (dcmp(theta) == 0) return {a + r * C_to_D};
    else return {a + rotate(r * C_to_D, theta), a +
        rotate(r * C_to_D, -theta)};
}
cir min_circle_cover(vector<pt> A) {
    random_shuffle(A.begin(), A.end());
    cir ans = {0, 0};
    auto is_incir = [&](pt a) { return dcmp(abs(cent(
        ans) - a) - radi(ans)) < 0; };
    for (int i = 0; i < A.size(); ++i) if (not is_incir
        (A[i])) {
        ans = {A[i], 0};
        for (int j = 0; j < i; ++j) if (not is_incir(A[j]
            )) {
                ans = {(A[i] + A[j]) / 2., abs(A[i] - A[j]) /
                    2};
                for (int k = 0; k < j; ++k) if (not is_incir(A[
                    k]))
                    ans = circumscribed_circle({A[i], A[j], A[k]
                        });
            }
        }
    return ans;
}
pair<pt, pt> closest_pair(vector<pt> &V, int l, int r
    ) { // l = 0, r = V.size()
    pair<pt, pt> ret = {pt(-1e18), pt(1e18)};
    const auto upd = [&](pair<pt, pt> a) {
        if (abs(a.first - a.second) < abs(ret.first - ret
            .second)) ret = a;
    };
    if (r - l < 40) { // GOD's number! It performs well
        !
        for (int i = l; i < r; ++i) for (int j = l; j < i
            ; ++j)
            upd({V[i], V[j]});
        return ret;
    }
    int m = l + r >> 1;
    const auto cmpy = [](pt a, pt b) { return imag(a) <
        imag(b); };
    const auto cmpx = [](pt a, pt b) { return real(a) <
        real(b); };
    nth_element(V.begin() + l, V.begin() + m, V.begin()
        + r, cmpx);
    pt mid = V[m];
    upd(closest_pair(V, l, m));
    upd(closest_pair(V, m, r));
    double delta = abs(ret.first - ret.second);
    vector<pt> spine;
    for (int k = l; k < r; ++k)
        if (abs(real(V[k]) - real(V[m])) < delta) spine.
            push_back(V[k]);
    sort(spine.begin(), spine.end(), cmpy);
    for (int i = 0; i < spine.size(); ++i)
        for (int j = i + 1; j - i < 8 and j < spine.size
            (); ++j) {
            upd({spine[i], spine[j]});
        }
    return ret;
}

```

5.2 3D ConvexHull

```

#define SIZE(X) (int(X.size()))
#define PI 3.14159265358979323846264338327950288
struct Pt {
    Pt cross(const Pt &p) const {
        return Pt(y * p.z - z * p.y, z * p.x - x * p.z, x *
            p.y - y * p.x);
    }
    info[N];
    int mark[N][N], n, cnt;
    double mix(const Pt &a, const Pt &b, const Pt &c) {
        return a * (b ^ c);
    }
    double area(int a, int b, int c) {
        return norm((info[b] - info[a]) ^ (info[c] - info[a])
            );
    }
    double volume(int a, int b, int c, int d) {
        return mix(info[b] - info[a], info[c] - info[a], info
            [d] - info[a]);
    }
    struct Face {
        int a, b, c; Face() {}
        Face(int a, int b, int c): a(a), b(b), c(c) {}
        int &operator [](int k) {
            if (k == 0) return a; if (k == 1) return b; return
                c;
        }
    };
    vector<Face> face;
    void insert(int a, int b, int c) {
        face.push_back(Face(a, b, c));
    }
    void add(int v) {
        vector<Face> tmp; int a, b, c; cnt++;
        for (int i = 0; i < SIZE(face); i++) {
            a = face[i][0]; b = face[i][1]; c = face[i][2];
            if (Sign(volume(v, a, b, c)) < 0)
                mark[a][b] = mark[b][a] = mark[b][c] = mark[c][b] =
                    mark[c][a] = mark[a][c] = cnt;
            else tmp.push_back(face[i]);
        }
        face = tmp;
        for (int i = 0; i < SIZE(tmp); i++) {
            a = face[i][0]; b = face[i][1]; c = face[i][2];
            if (mark[a][b] == cnt) insert(b, a, v);
            if (mark[b][c] == cnt) insert(c, b, v);
            if (mark[c][a] == cnt) insert(a, c, v);
        }
    }
    int Find() {
        for (int i = 2; i < n; i++) {
            Pt ndir = (info[0] - info[i]) ^ (info[1] - info[i])
                ;
            if (ndir == Pt()) continue; swap(info[i], info[2]);
            for (int j = i + 1; j < n; j++) if (Sign(volume(0,
                1, 2, j)) != 0) {
                swap(info[j], info[3]); insert(0, 1, 2); insert
                    (0, 2, 1); return 1;
            }
        }
        return 0;
    }
    int main() {
        for (; scanf("%d", &n) == 1; ) {
            for (int i = 0; i < n; i++) info[i].Input();
            sort(info, info + n); n = unique(info, info + n) -
                info;
            face.clear(); random_shuffle(info, info + n);
            if (Find()) { memset(mark, 0, sizeof(mark)); cnt =
                0;
                for (int i = 3; i < n; i++) add(i); vector<Pt>
                    Ndir;
                for (int i = 0; i < SIZE(face); ++i) {
                    Pt p = (info[face[i][0]] - info[face[i][1]]) ^
                        (info[face[i][2]] - info[face[i][1]]);
                    p = p / norm(p); Ndir.push_back(p);
                }
                sort(Ndir.begin(), Ndir.end());
                int ans = unique(Ndir.begin(), Ndir.end()) - Ndir
                    .begin();
                printf("%d\n", ans);
            } else printf("1\n");
        }
    }
    double calcDist(const Pt &p, int a, int b, int c) {
        return fabs(mix(info[a] - p, info[b] - p, info[c] - p
            ) / area(a, b, c));
    }
    //compute the minimal distance of center of any faces
}

```



```
double findDist() { //compute center of mass
    double totalWeight = 0; Pt center(.0, .0, .0);
    Pt first = info[face[0][0]];
    for (int i = 0; i < SIZE(face); ++i) {
        Pt p = (info[face[i][0]]+info[face[i][1]]+info[face[i][2]]+first)*.25;
        double weight = mix(info[face[i][0]] - first, info[face[i][1]] - first, info[face[i][2]] - first);
        totalWeight += weight; center = center + p * weight;
    } center = center / totalWeight;
    double res = 1e100; //compute distance
    for (int i = 0; i < SIZE(face); ++i)
        res = min(res, calcDist(center, face[i][0], face[i][1], face[i][2]));
    return res; }

```

5.3 Half plane intersection

```
template<typename T, typename Real = double>
Poly<Real> halfplane_intersection(vector<Line<T, Real>>
    s) {
    sort(s.begin(), s.end());
    const Real eps = 1e-10;
    int n = 1;
    for (int i = 1; i < s.size(); ++i) {
        if ((s[i].vec()&s[n-1].vec()) < eps or abs(s[i].vec()^s[n-1].vec()) > eps)
            s[n++] = s[i];
    }
    s.resize(n);
    assert(n >= 3);
    deque<Line<T, Real>> q;
    deque<Pt<Real>> p;
    q.push_back(s[0]);
    q.push_back(s[1]);
    p.push_back(s[0].get_intersection(s[1]));
    for (int i = 2; i < n; ++i) {
        while (q.size() > 1 and s[i].ori(p.back()) < -eps)
            p.pop_back(), q.pop_back();
        while (q.size() > 1 and s[i].ori(p.front()) < -eps)
            p.pop_front(), q.pop_front();
        p.push_back(q.back().get_intersection(s[i]));
        q.push_back(s[i]);
    }
    while (q.size() > 1 and q.front().ori(p.back()) < -eps)
        q.pop_back(), p.pop_back();
    while (q.size() > 1 and q.back().ori(p.front()) < -eps)
        q.pop_front(), p.pop_front();
    p.push_back(q.front().get_intersection(q.back()));
    return Poly<Real>(vector<Pt<Real>>(p.begin(), p.end()));
}

```

6 Graph

6.1 2-SAT

```
#include <bits/stdc++.h>

using namespace std;

class two_SAT {
public:
    vector< vector<int> > g, rg;
    vector<int> visit, was;
    vector<int> id;
    vector<int> res;
    int n, iter;

    two_SAT(int _n) : n(_n) {
        g.resize(n * 2);
        rg.resize(n * 2);
    }

```

```
    was = vector<int>(n * 2, 0);
    id = vector<int>(n * 2, -1);
    res.resize(n);
    iter = 0;
}

void add_edge(int from, int to) { // add (a -> b)
    assert(from >= 0 && from < 2 * n && to >= 0 && to < 2 * n);
    g[from].emplace_back(to);
    rg[to].emplace_back(from);
}

void add_or(int a, int b) { // add (a V b)
    int nota = (a < n) ? a + n : a - n;
    int notb = (b < n) ? b + n : b - n;
    add_edge(nota, b);
    add_edge(notb, a);
}

void dfs(int v) {
    was[v] = true;
    for (int u : g[v]) {
        if (!was[u]) dfs(u);
    }
    visit.emplace_back(v);
}

void rdfs(int v) {
    id[v] = iter;
    for (int u : rg[v]) {
        if (id[u] == -1) rdfs(u);
    }
}

int scc() {
    for (int i = 0; i < 2 * n; i++) {
        if (!was[i]) dfs(i);
    }
    for (int i = 2 * n - 1; i >= 0; i--) {
        if (id[visit[i]] == -1) {
            rdfs(visit[i]);
            iter++;
        }
    }
    return iter;
}

bool solve() {
    scc();
    for (int i = 0; i < n; i++) {
        if (id[i] == id[i + n]) return false;
        res[i] = (id[i] < id[i + n]);
    }
    return true;
}

};

/*
usage:
    index 0 ~ n - 1 : True
    index n ~ 2n - 1 : False
    add_or(a, b) : add SAT (a or b)
    add_edge(a, b) : add SAT (a -> b)
    if you want to set x = True, you can add (not X -> X)
    solve() return True if it exist at least one solution
    res[i] store one solution
    false -> choose a
    true -> choose a + n
*/

```

6.2 BCC

```
#include <bits/stdc++.h>

using namespace std;

```



```

class biconnected_component {
public:
    vector< vector<int> > g;
    vector< vector<int> > comp;
    vector<int> pre, depth;
    int n;

    biconnected_component(int _n) : n(_n) {
        depth = vector<int>(n, -1);
        g.resize(n);
    }

    void add(int u, int v) {
        assert(0 <= u && u < n && 0 <= v && v < n);
        g[u].push_back(v);
        g[v].push_back(u);
    }

    int dfs(int v, int pa, int d) {
        depth[v] = d;
        pre.push_back(v);
        for (int u : g[v]) {
            if (u == pa) continue;
            if (depth[u] == -1) {
                int child = dfs(u, v, depth[v] + 1);
                if (child >= depth[v]) {
                    comp.push_back(vector<int>(1, v));
                    while (pre.back() != v) {
                        comp.back().push_back(pre.back());
                        pre.pop_back();
                    }
                }
                d = min(d, child);
            }
            else {
                d = min(d, depth[u]);
            }
        }
        return d;
    }

    vector< vector<int> > solve() {
        for (int i = 0; i < n; i++) {
            if (depth[i] == -1) {
                dfs(i, -1, 0);
            }
        }
        return comp;
    }

    vector<int> get_ap() {
        vector<int> res, count(n, 0);
        for (auto c : comp) {
            for (int v : c) {
                count[v]++;
            }
        }
        for (int i = 0; i < n; i++) {
            if (count[i] > 1) {
                res.push_back(i);
            }
        }
        return res;
    }
};

```

6.3 Bridge

```

struct Bridge {
    vector<int> imo;
    set<pair<int, int>> bridges; // all bridges (u, v), u
    < v
    vector<set<int>> bcc; // bcc[i] has all vertices that
    belong to the i'th bcc
    vector<int> at_bcc; // node i belongs to at_bcc[i]
    int bcc_ctr;

    Bridge(const vector<vector<int>> &g) : bcc_ctr(0) {
        imo.resize(g.size());
        bcc.resize(g.size());
    }
};

```

```

    at_bcc.resize(g.size());
    vector<int> vis(g.size());
    vector<int> dpt(g.size());
    function<void(int, int, int)> mark = [&](int u, int
        fa, int d) {
        vis[u] = 1;
        dpt[u] = d;
        for (int v : G[u]) {
            if (v == fa) continue;
            if (vis[v]) {
                if (dpt[v] > dpt[u]) {
                    ++imo[v];
                    --imo[u];
                }
            } else mark(v, u, d + 1);
        }
    };
    mark(0, -1, 0);
    vis.assign(g.size(), 0);
    function<int(int)> expand = [&](int u) {
        vis[u] = 1;
        int s = imo[u];
        for (int v : G[u]) {
            if (vis[v]) continue;
            int e = expand(v);
            if (e == 0) bridges.emplace(make_pair(min(u, v)
                , max(u, v)));
            s += e;
        }
        return s;
    };
    expand(0);
    fill(at_bcc.begin(), at_bcc.end(), -1);
    for (int u = 0; u < N; ++u) {
        if (~at_bcc[u]) continue;
        queue<int> que;
        que.emplace(u);
        at_bcc[u] = bcc_ctr;
        bcc[bcc_ctr].emplace(u);
        while (que.size()) {
            int v = que.front();
            que.pop();
            for (int w : G[v]) {
                if (~at_bcc[w] || bridges.count(make_pair(min
                    (v, w), max(v, w)))) continue;
                que.emplace(w);
                at_bcc[w] = bcc_ctr;
                bcc[bcc_ctr].emplace(w);
            }
        }
        ++bcc_ctr;
    }
};

```

6.4 General Matching

```

#define MAXN 505
struct Blossom {
    vector<int> g[MAXN];
    int pa[MAXN] = {0}, match[MAXN] = {0}, st[MAXN] =
    {0}, S[MAXN] = {0}, v[MAXN] = {0};
    int t, n;
    Blossom(int _n) : n(_n) {}
    void add_edge(int v, int u) { // 1-index
        g[u].push_back(v), g[v].push_back(u);
    }
    inline int lca(int x, int y) {
        ++t;
        while (v[x] != t) {
            v[x] = t;
            x = st[pa[match[x]]];
            swap(x, y);
            if (x == 0) swap(x, y);
        }
        return x;
    }
    inline void flower(int x, int y, int l, queue<int> &q
    ) {
        while (st[x] != l) {

```

```

    pa[x] = y;
    if (S[y = match[x]] == 1) q.push(y), S[y] = 0;
    st[x] = st[y] = 1, x = pa[y];
}
}
inline bool bfs(int x) {
    for (int i = 1; i <= n; ++i) st[i] = i;
    memset(S + 1, -1, sizeof(int) * n);
    queue<int> q;
    q.push(x), S[x] = 0;
    while (q.size()) {
        x = q.front(), q.pop();
        for (size_t i = 0; i < g[x].size(); ++i) {
            int y = g[x][i];
            if (S[y] == -1) {
                pa[y] = x, S[y] = 1;
                if (not match[y]) {
                    for (int lst; x; y = lst, x = pa[y])
                        lst = match[x], match[x] = y, match[y] = x;
                    return 1;
                }
            }
            q.push(match[y]), S[match[y]] = 0;
        }
        else if (not S[y] and st[y] != st[x]) {
            int l = lca(y, x);
            flower(y, x, l, q), flower(x, y, l, q);
        }
    }
    return 0;
}
inline int blossom() {
    int ans = 0;
    for (int i = 1; i <= n; ++i)
        if (not match[i] and bfs(i)) ++ans;
    return ans;
}
};

```

6.5 CentroidDecomposition

```

vector<int> adj[N];
int p[N], vis[N];
int sz[N], M[N]; // subtree size of u and M(u)

inline void maxify(int &x, int y) { x = max(x, y); }
int centroidDecomp(int x) {
    vector<int> q;
    { // bfs
        size_t pt = 0;
        q.push_back(x);
        p[x] = -1;
        while (pt < q.size()) {
            int now = q[pt++];
            sz[now] = 1;
            M[now] = 0;
            for (auto &nxt : adj[now])
                if (!vis[nxt] && nxt != p[now])
                    q.push_back(nxt), p[nxt] = now;
        }
    }

    // calculate subtree size in reverse order
    reverse(q.begin(), q.end());
    for (int &nd : q)
        if (p[nd] != -1) {
            sz[p[nd]] += sz[nd];
            maxify(M[p[nd]], sz[nd]);
        }
    for (int &nd : q)
        maxify(M[nd], (int)q.size() - sz[nd]);

    // find centroid
    int centroid = *min_element(q.begin(), q.end(),
        [&](int x, int y) {
            return M[x] < M[y];
        });

    vis[centroid] = 1;
    for (auto &nxt : adj[centroid]) if (!vis[nxt])

```

```

        centroidDecomp(nxt);
    return centroid;
}

```

6.6 Diameter

```

const int SIZE = 1e6 + 10;
struct Tree_ecc {
    vector<pair<int, LL>> g[SIZE];
    LL dp[SIZE][2] = {0}, ecc[SIZE];
    int n = -1;
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i)
            g[i].clear(), ecc[i] = dp[i][0] = dp[i][1] = 0;
    }
    void add_edge(int v, int u, LL w) { // 0-index
        g[u].emplace_back(v, w);
        g[v].emplace_back(u, w);
    }
    void dfs_length(int v, int p) {
        for (auto T: g[v]) {
            int u; LL w;
            tie(u, w) = T;
            if (u == p) continue;
            dfs_length(u, v);
            LL length_from_u = dp[u][0] + w;
            if (dp[v][0] < length_from_u)
                dp[v][1] = dp[v][0], dp[v][0] = length_from_u;
            else if (dp[v][1] < length_from_u)
                dp[v][1] = length_from_u;
        }
    }
    void dfs_ecc(int v, int p, LL pass_p) {
        ecc[v] = max(dp[v][0], pass_p);
        for (auto T: g[v]) {
            int u; LL w;
            tie(u, w) = T;
            if (u == p) continue;
            if (dp[u][0] + w == dp[v][0])
                dfs_ecc(u, v, max(pass_p, dp[v][1] + w));
            else dfs_ecc(u, v, max(pass_p, dp[v][0] + w));
        }
    }
    LL diameter() {
        assert(~n);
        dfs_length(0, 0);
        dfs_ecc(0, 0, 0);
        return *max_element(ecc, ecc + n);
    }
} solver;

```

6.7 DirectedGraphMinCycle

```

// works in O(N M)
#define INF 100000000000000LL
#define N 5010
#define M 200010
struct edge {
    int to; LL w;
    edge(int a=0, LL b=0): to(a), w(b){}
};
struct node {
    LL d; int u, next;
    node(LL a=0, int b=0, int c=0): d(a), u(b), next(c){}
} b[M];
struct DirectedGraphMinCycle {
    vector<edge> g[N], grev[N];
    LL dp[N][N], p[N], d[N], mu;
    bool inq[N];
    int n, bn, bsz, hd[N];
    void b_insert(LL d, int u) {
        int i = d/mu;
        if (i >= bn) return;
        b[++bsz] = node(d, u, hd[i]);
        hd[i] = bsz;
    }
    void init(int _n) {

```

```

n = _n;
for( int i = 1 ; i <= n ; i ++ )
    g[ i ].clear();
}
void addEdge( int ai , int bi , LL ci )
{ g[ai].push_back(edge(bi,ci)); }
LL solve(){
    fill(dp[0], dp[0]+n+1, 0);
    for(int i=1; i<=n; i++){
        fill(dp[i]+1, dp[i]+n+1, INF);
        for(int j=1; j<=n; j++) if(dp[i-1][j] < INF){
            for(int k=0; k<(int)g[j].size(); k++){
                dp[i][g[j][k].to] = min(dp[i][g[j][k].to],
                    dp[i-1][j]+g[j][k].w);
            }
        }
    }
    mu=INF; LL bunbo=1;
    for(int i=1; i<=n; i++) if(dp[n][i] < INF){
        LL a=-INF, b=1;
        for(int j=0; j<=n-1; j++) if(dp[j][i] < INF){
            if(a*(n-j) < b*(dp[n][i]-dp[j][i])){
                a = dp[n][i]-dp[j][i];
                b = n-j;
            }
        }
        if(mu*b > bunbo*a)
            mu = a, bunbo = b;
    }
    if(mu < 0) return -1; // negative cycle
    if(mu == INF) return INF; // no cycle
    if(mu == 0) return 0;
    for(int i=1; i<=n; i++){
        for(int j=0; j<(int)g[i].size(); j++){
            g[i][j].w *= bunbo;
        }
        memset(p, 0, sizeof(p));
        queue<int> q;
        for(int i=1; i<=n; i++){
            q.push(i);
            inq[i] = true;
        }
        while(!q.empty()){
            int i=q.front(); q.pop(); inq[i]=false;
            for(int j=0; j<(int)g[i].size(); j++){
                if(p[g[i][j].to] > p[i]+g[i][j].w-mu){
                    p[g[i][j].to] = p[i]+g[i][j].w-mu;
                    if(!inq[g[i][j].to]){
                        q.push(g[i][j].to);
                        inq[g[i][j].to] = true;
                    }
                }
            }
        }
    }
    for(int i=1; i<=n; i++) grev[i].clear();
    for(int i=1; i<=n; i++){
        for(int j=0; j<(int)g[i].size(); j++){
            g[i][j].w += p[i]-p[g[i][j].to];
            grev[g[i][j].to].push_back(edge(i, g[i][j].w));
        }
    }
    LL mldc = n*mu;
    for(int i=1; i<=n; i++){
        bn=mldc/mu, bsz=0;
        memset(hd, 0, sizeof(hd));
        fill(d+i+1, d+n+1, INF);
        b_insert(d[i]=0, i);
        for(int j=0; j<=bn-1; j++) for(int k=hd[j]; k; k=
            b[k].next){
            int u = b[k].u;
            LL du = b[k].d;
            if(du > d[u]) continue;
            for(int l=0; l<(int)g[u].size(); l++) if(g[u][l]
                .to > i){
                if(d[g[u][l].to] > du + g[u][l].w){
                    d[g[u][l].to] = du + g[u][l].w;
                    b_insert(d[g[u][l].to], g[u][l].to);
                }
            }
        }
    }
    for(int j=0; j<(int)grev[i].size(); j++) if(grev[
        i][j].to > i)
        mldc=min(mldc,d[grev[i][j].to] + grev[i][j].w);
    }
    return mldc / bunbo;
}

```

```

}
} graph;

```

6.8 General Weighted Matching

```

struct WeightGraph {
    static const int INF = INT_MAX;
    static const int N = 514;
    struct edge {
        int u, v, w;
        edge() {}
        edge(int ui, int vi, int wi) : u(ui), v(vi), w(wi)
        {}
    };
    int n, n_x;
    edge g[N * 2][N * 2];
    int lab[N * 2];
    int match[N * 2], slack[N * 2], st[N * 2], pa[N * 2];
    int flo_from[N * 2][N + 1], S[N * 2], vis[N * 2];
    vector<int> flo[N * 2];
    queue<int> q;
    int e_delta(const edge& e) { return lab[e.u] + lab[e.
        v] - g[e.u][e.v].w * 2; }
    void update_slack(int u, int x) {
        if (not slack[x] or e_delta(g[u][x]) < e_delta(g[
            slack[x]][x]))
            slack[x] = u;
    }
    void set_slack(int x) {
        slack[x] = 0;
        for (int u = 1; u <= n; ++u)
            if (g[u][x].w > 0 and st[u] != x and S[st[u]] ==
                0) update_slack(u, x);
    }
    void q_push(int x) {
        if (x <= n)
            q.push(x);
        else
            for (size_t i = 0; i < flo[x].size(); i++) q_push
                (flo[x][i]);
    }
    void set_st(int x, int b) {
        st[x] = b;
        if (x > n)
            for (size_t i = 0; i < flo[x].size(); ++i) set_st
                (flo[x][i], b);
    }
    int get_pr(int b, int xr) {
        int pr = find(flo[b].begin(), flo[b].end(), xr) -
            flo[b].begin();
        if (pr % 2 == 1) {
            reverse(flo[b].begin() + 1, flo[b].end());
            return (int)flo[b].size() - pr;
        } else
            return pr;
    }
    void set_match(int u, int v) {
        match[u] = g[u][v].v;
        if (u <= n) return;
        edge e = g[u][v];
        int xr = flo_from[u][e.u], pr = get_pr(u, xr);
        for (int i = 0; i < pr; ++i) set_match(flo[u][i],
            flo[u][i ^ 1]);
        set_match(xr, v);
        rotate(flo[u].begin(), flo[u].begin() + pr, flo[u].
            end());
    }
    void augment(int u, int v) {
        for (;;) {
            int xnv = st[match[u]];
            set_match(u, v);
            if (not xnv) return;
            set_match(xnv, st[pa[xnv]]);
            u = st[pa[xnv]], v = xnv;
        }
    }
    int get_lca(int u, int v) {
        static int t = 0;
        for (++t; u or v; swap(u, v)) {
            if (u == 0) continue;

```

```

    if (vis[u] == t) return u;
    vis[u] = t;
    u = st[match[u]];
    if (u) u = st[pa[u]];
}
return 0;
}

void add_blossom(int u, int lca, int v) {
    int b = n + 1;
    while (b <= n_x and st[b]) ++b;
    if (b > n_x) ++n_x;
    lab[b] = 0, S[b] = 0;
    match[b] = match[lca];
    flo[b].clear();
    flo[b].push_back(lca);
    for (int x = u, y; x != lca; x = st[pa[y]])
        flo[b].push_back(x), flo[b].push_back(y = st[
            match[x]]), q_push(y);
    reverse(flo[b].begin() + 1, flo[b].end());
    for (int x = v, y; x != lca; x = st[pa[y]])
        flo[b].push_back(x), flo[b].push_back(y = st[
            match[x]]), q_push(y);
    set_st(b, b);
    for (int x = 1; x <= n_x; ++x) g[b][x].w = g[x][b].
        w = 0;
    for (int x = 1; x <= n; ++x) flo_from[b][x] = 0;
    for (size_t i = 0; i < flo[b].size(); ++i) {
        int xs = flo[b][i];
        for (int x = 1; x <= n_x; ++x)
            if (g[b][x].w == 0 or e_delta(g[xs][x]) <
                e_delta(g[b][x]))
                g[b][x] = g[xs][x], g[x][b] = g[x][xs];
        for (int x = 1; x <= n; ++x)
            if (flo_from[xs][x]) flo_from[b][x] = xs;
    }
    set_slack(b);
}

void expand_blossom(int b) {
    for (size_t i = 0; i < flo[b].size(); ++i) set_st(
        flo[b][i], flo[b][i]);
    int xr = flo_from[b][g[b][pa[b]].u], pr = get_pr(b,
        xr);
    for (int i = 0; i < pr; i += 2) {
        int xs = flo[b][i], xns = flo[b][i + 1];
        pa[xs] = g[xns][xs].u;
        S[xs] = 1, S[xns] = 0;
        slack[xs] = 0, set_slack(xns);
        q_push(xns);
    }
    S[xr] = 1, pa[xr] = pa[b];
    for (size_t i = pr + 1; i < flo[b].size(); ++i) {
        int xs = flo[b][i];
        S[xs] = -1, set_slack(xs);
    }
    st[b] = 0;
}

bool on_found_edge(const edge& e) {
    int u = st[e.u], v = st[e.v];
    if (S[v] == -1) {
        pa[v] = e.u, S[v] = 1;
        int nu = st[match[v]];
        slack[v] = slack[nu] = 0;
        S[nu] = 0, q_push(nu);
    } else if (S[v] == 0) {
        int lca = get_lca(u, v);
        if (not lca)
            return augment(u, v), augment(v, u), true;
        else
            add_blossom(u, lca, v);
    }
    return false;
}

bool matching() {
    memset(S + 1, -1, sizeof(int) * n_x);
    memset(slack + 1, 0, sizeof(int) * n_x);
    q = queue<int>();
    for (int x = 1; x <= n_x; ++x)
        if (st[x] == x and not match[x]) pa[x] = 0, S[x]
            = 0, q_push(x);
    if (q.empty()) return false;
    for (;;) {
        while (q.size()) {

```

```

            int u = q.front();
            q.pop();
            if (S[st[u]] == 1) continue;
            for (int v = 1; v <= n; ++v)
                if (g[u][v].w > 0 and st[u] != st[v]) {
                    if (e_delta(g[u][v]) == 0) {
                        if (on_found_edge(g[u][v])) return true;
                    } else
                        update_slack(u, st[v]);
                }
        }
        int d = INF;
        for (int b = n + 1; b <= n_x; ++b)
            if (st[b] == b and S[b] == 1) d = min(d, lab[b]
                / 2);
        for (int x = 1; x <= n_x; ++x)
            if (st[x] == x and slack[x]) {
                if (S[x] == -1)
                    d = min(d, e_delta(g[slack[x]][x]));
                else if (S[x] == 0)
                    d = min(d, e_delta(g[slack[x]][x]) / 2);
            }
        for (int u = 1; u <= n; ++u) {
            if (S[st[u]] == 0) {
                if (lab[u] <= d) return 0;
                lab[u] -= d;
            } else if (S[st[u]] == 1)
                lab[u] += d;
        }
        for (int b = n + 1; b <= n_x; ++b)
            if (st[b] == b) {
                if (S[st[b]] == 0)
                    lab[b] += d * 2;
                else if (S[st[b]] == 1)
                    lab[b] -= d * 2;
            }
        q = queue<int>();
        for (int x = 1; x <= n_x; ++x)
            if (st[x] == x and slack[x] and st[slack[x]] !=
                x and
                e_delta(g[slack[x]][x]) == 0)
                if (on_found_edge(g[slack[x]][x])) return
                    true;
        for (int b = n + 1; b <= n_x; ++b)
            if (st[b] == b and S[b] == 1 and lab[b] == 0)
                expand_blossom(b);
    }
    return false;
}

pair<long long, int> solve() {
    memset(match + 1, 0, sizeof(int) * n);
    n_x = n;
    int n_matches = 0;
    long long tot_weight = 0;
    for (int u = 0; u <= n; ++u) st[u] = u, flo[u].
        clear();
    int w_max = 0;
    for (int u = 1; u <= n; ++u)
        for (int v = 1; v <= n; ++v) {
            flo_from[u][v] = (u == v ? u : 0);
            w_max = max(w_max, g[u][v].w);
        }
    for (int u = 1; u <= n; ++u) lab[u] = w_max;
    while (matching()) ++n_matches;
    for (int u = 1; u <= n; ++u)
        if (match[u] and match[u] < u) tot_weight += g[u]
            [match[u]].w;
    return {tot_weight, n_matches};
}

void add_edge(int ui, int vi, int wi) { g[ui][vi].w =
    g[vi][ui].w = wi; }
void init(int _n) { // 1-index, zero indicates
    unsaturated
    n = _n;
    for (int u = 1; u <= n; ++u)
        for (int v = 1; v <= n; ++v) g[u][v] = edge(u, v,
            0);
}
} graph;

```

6.9 Graph Sequence Test

```
bool is_degree_sequence(vector<LL> d) {
    if (accumulate(d.begin(), d.end(), 0LL)&1) return
        false;
    sort(d.rbegin(), d.rend());
    const int n = d.size();
    vector<LL> pre(n + 1, 0);
    for (int i = 0; i < n; ++i) pre[i + 1] += pre[i] + d[i];
    for (LL k = 0, j = 0; k < n; ++k) {
        while (j < n and (j <= k or d[j] < k)) ++j;
        if (pre[k + 1] > k * (k + 1) + pre[j] - pre[k + 1]
            + (k + 1) * (n - j))
            return false;
    }
    return true;
}
```

6.10 maximal cliques

```
#include <bits/stdc++.h>
using namespace std;

const int N = 60;
typedef long long LL;

struct Bron_Kerbosch {
    int n, res;
    LL edge[N];
    void init(int _n) {
        n = _n;
        for (int i = 0; i <= n; i++) edge[i] = 0;
    }
    void add_edge(int u, int v) {
        if (u == v) return;
        edge[u] |= 1LL << v;
        edge[v] |= 1LL << u;
    }
    void go(LL R, LL P, LL X) {
        if (P == 0 && X == 0) {
            res = max(res, __builtin_popcountll(R)); //
            notice LL
            return;
        }
        if (__builtin_popcountll(R) + __builtin_popcountll(P) <= res) return;
        for (int i = 0; i <= n; i++) {
            LL v = 1LL << i;
            if (P & v) {
                go(R | v, P & edge[i], X & edge[i]);
                P &= ~v;
                X |= v;
            }
        }
    }
    int solve() {
        res = 0;
        go(0LL, (1LL << (n+1)) - 1, 0LL);
        return res;
    }
}
/* BronKerbosch1(R, P, X):
   if P and X are both empty:
       report R as a maximal clique
   for each vertex v in P:
       BronKerbosch1(R ∪ {v}, P ∩ N(v), X ∩ N(v))
   P := P \ {v}
   X := X ∪ {v}
*/
} MaxClique;
```

```
int main() {
    MaxClique.init(6);
    MaxClique.add_edge(1,2);
    MaxClique.add_edge(1,5);
    MaxClique.add_edge(2,5);
    MaxClique.add_edge(4,5);
    MaxClique.add_edge(3,2);
    MaxClique.add_edge(4,6);
```

```
MaxClique.add_edge(3,4);
cout << MaxClique.solve() << "\n";
return 0;
}
```

6.11 MinMeanCycle

```
/* minimum mean cycle 0(VE) */
struct MMC{
#define E 101010
#define V 1021
#define inf 1e9
#define eps 1e-6
    struct Edge { int v,u; double c; };
    int n, m, prv[V][V], prve[V][V], vst[V];
    Edge e[E];
    vector<int> edgeID, cycle, rho;
    double d[V][V];
    void init( int _n )
    { n = _n; m = 0; }
    // WARNING: TYPE matters
    void addEdge( int vi , int ui , double ci )
    { e[ m ++ ] = { vi , ui , ci }; }
    void bellman_ford() {
        for(int i=0; i<n; i++) d[0][i]=0;
        for(int i=0; i<n; i++) {
            fill(d[i+1], d[i+1]+n, inf);
            for(int j=0; j<m; j++) {
                int v = e[j].v, u = e[j].u;
                if(d[i][v]<inf && d[i+1][u]>d[i][v]+e[j].c) {
                    d[i+1][u] = d[i][v]+e[j].c;
                    prv[i+1][u] = v;
                    prve[i+1][u] = j;
                }
            }
        }
    }
    double solve(){
        // returns inf if no cycle, mmc otherwise
        double mmc=inf;
        int st = -1;
        bellman_ford();
        for(int i=0; i<n; i++) {
            double avg=-inf;
            for(int k=0; k<n; k++) {
                if(d[n][i]<inf-eps) avg=max(avg,(d[n][i]-d[k][i])/(n-k));
                else avg=max(avg,inf);
            }
            if (avg < mmc) tie(mmc, st) = tie(avg, i);
        }
        FZ(vst); edgeID.clear(); cycle.clear(); rho.clear();
        for (int i=n; !vst[st]; st=prv[i--][st]) {
            vst[st]++;
            edgeID.PB(prve[i][st]);
            rho.PB(st);
        }
        while (vst[st] != 2) {
            int v = rho.back(); rho.pop_back();
            cycle.PB(v);
            vst[v]++;
        }
        reverse(ALL(edgeID));
        edgeID.resize(SZ(cycle));
        return mmc;
    }
} mmc;
```

6.12 Prufer code

```
vector<int> Prufer_encode(vector<vector<int>> T) {
    int n = T.size();
    assert(n > 1);
    vector<int> deg(n), code;
    priority_queue<int, vector<int>, greater<int>> pq;
    for (int i = 0; i < n; ++i) {
        deg[i] = T[i].size();
```

```

    if (deg[i] == 1) pq.push(i);
}
while (code.size() < n - 2) {
    int v = pq.top(); pq.pop();
    --deg[v];
    for (int u: T[v]) {
        if (deg[u]) {
            --deg[u];
            code.push_back(u);
            if (deg[u] == 1) pq.push(u);
        }
    }
}
return code;
}
vector<vector<int>> Prufer_decode(vector<int> C) {
    int n = C.size() + 2;
    vector<vector<int>> T(n, vector<int>(0));
    vector<int> deg(n, 1); // outdeg
    for (int c: C) ++deg[c];
    priority_queue<int, vector<int>, greater<int>> q;
    for (int i = 0; i < n; ++i) if (deg[i] == 1) q.push(i);
    for (int c: C) {
        int v = q.top(); q.pop();
        T[v].push_back(c), T[c].push_back(v);
        --deg[c];
        --deg[v];
        if (deg[c] == 1) q.push(c);
    }
    int u = find(deg.begin(), deg.end(), 1) - deg.begin();
    int v = find(deg.begin() + u + 1, deg.end(), 1) - deg.begin();
    T[u].push_back(v), T[v].push_back(u);
    return T;
}

```

6.13 SPFA

```

struct SPFA {
    const LL INF = 1ll<<62;
    vector<vector<pair<int, LL>>> g;
    vector<int> p;
    vector<LL> d;
    int n;
    void init(int _n) {
        n = _n;
        g.assign(n, vector<pair<int, LL>>(0));
        d.assign(n, INF);
        p.assign(n, -1);
    }
    void add_edge(int u, int v, LL w) {
        g[u].push_back({v, w});
    }
    LL shortest_path(int s, int t) {
        for (int i = 0; i < n; ++i)
            sort(g[i].begin(), g[i].end(), [](pair<int, LL> A, pair<int, LL> B) {
                return A.second < B.second;
            });
        vector<bool> inq(n, false);
        vector<int> inq_t(n, 0);
        queue<int> q;
        q.push(s);
        d[s] = 0, inq_t[s] = 1;
        int u, v;
        LL w;
        while (q.size()) {
            inq[v = q.front()] = false; q.pop();
            for (auto P: g[v]) {
                tie(u, w) = P;
                if (d[u] > d[v] + w) {
                    d[u] = d[v] + w, p[u] = v;
                    if (not inq[u]) {
                        q.push(u), inq[u] = true, ++inq_t[u];
                        if (inq_t[u] > n) return -INF;
                    }
                }
            }
        }
    }
}

```

```

    }
    return d[t];
}
} solver;

```

6.14 Virtual Tree

```

struct Oracle {
    int lgn;
    vector<vector<int>> g;
    vector<int> dep;
    vector<vector<int>> par;
    vector<int> dfn;

    Oracle(const vector<vector<int>> &_g) : g(_g), lgn(
        ceil(log2(_g.size()))) {
        dep.resize(g.size());
        par.assign(g.size(), vector<int>(lgn + 1, -1));
        dfn.resize(g.size());

        int t = 0;
        function<void(int, int)> dfs = [&](int u, int fa) {
            // static int t = 0;
            dfn[u] = t++;
            if (~fa) dep[u] = dep[fa] + 1;
            par[u][0] = fa;
            for (int v : g[u]) if (v != fa) dfs(v, u);
        };
        dfs(0, -1);

        for (int i = 0; i < lgn; ++i)
            for (int u = 0; u < g.size(); ++u)
                par[u][i + 1] = ~par[u][i] ? par[par[u][i]][i] : -1;
    }

    int lca(int u, int v) const {
        if (dep[u] < dep[v]) swap(u, v);
        for (int i = lgn; dep[u] != dep[v]; --i) {
            if (dep[u] - dep[v] < 1 << i) continue;
            u = par[u][i];
        }
        if (u == v) return u;
        for (int i = lgn; par[u][0] != par[v][0]; --i) {
            if (par[u][i] == par[v][i]) continue;
            u = par[u][i];
            v = par[v][i];
        }
        return par[u][0];
    }
};

struct VirtualTree { // O(|C|lg|G|), C is the set of
    // critical points, G is nodes in original graph
    vector<int> cp; // index of critical points in
    // original graph
    vector<vector<int>> g; // simplified tree, i.e.
    // virtual tree
    vector<int> nodes; // i'th node in g has index nodes[
    // i] in original graph
    map<int, int> mp; // inverse of nodes

    VirtualTree(const vector<int> &_cp, const Oracle &
        oracle) : cp(_cp) {
        sort(cp.begin(), cp.end(), [&](int u, int v) {
            return oracle.dfn[u] < oracle.dfn[v]; });
        nodes = cp;
        for (int i = 0; i < nodes.size(); ++i) mp[nodes[i]]
            = i;
        g.resize(nodes.size());

        if (!mp.count(0)) {
            mp[0] = nodes.size();
            nodes.emplace_back(0);
            g.emplace_back(vector<int>());
        }

        vector<int> stk;
        stk.emplace_back(0);
    }
}

```



```

for (int u : cp) {
    if (u == stk.back()) continue;
    int p = oracle.lca(u, stk.back());
    if (p == stk.back()) {
        stk.emplace_back(u);
    } else {
        while (stk.size() > 1 && oracle.dep[stk.end()
            [-2]] >= oracle.dep[p]) {
            g[mp[stk.back()]].emplace_back(mp[stk.end()
                [-2]]);
            g[mp[stk.end()[-2]]].emplace_back(mp[stk.back()]);
            stk.pop_back();
        }
        if (stk.back() != p) {
            if (!mp.count(p)) {
                mp[p] = nodes.size();
                nodes.emplace_back(p);
                g.emplace_back(vector<int>());
            }
            g[mp[p]].emplace_back(mp[stk.back()]);
            g[mp[stk.back()]].emplace_back(mp[p]);
            stk.pop_back();
            stk.emplace_back(p);
        }
        stk.emplace_back(u);
    }
}
for (int i = 0; i + 1 < stk.size(); ++i) {
    g[mp[stk[i]]].emplace_back(mp[stk[i + 1]]);
    g[mp[stk[i + 1]]].emplace_back(mp[stk[i]]);
}
};

```

7 String

7.1 AC automaton

```

// SIGMA[0] will not be considered
const string SIGMA = "
0123456789ABCDEFGHIJKLMNQRSTUWXYZabcdefghijklmnopqrstuvwxyz";
vector<int> INV_SIGMA;
const int SGSZ = 63;

struct PMA {
    PMA *next[SGSZ]; // next[0] is for fail
    vector<int> ac;
    PMA *last; // state of longest accepted string that
                // is pre of this
    PMA() : last(nullptr) { fill(next, next + SGSZ,
        nullptr); }
};

template<typename T>
PMA *buildPMA(const vector<T> &p) {
    PMA *root = new PMA;
    for (int i = 0; i < p.size(); ++i) { // make trie
        PMA *t = root;
        for (int j = 0; j < p[i].size(); ++j) {
            int c = INV_SIGMA[p[i][j]];
            if (t->next[c] == nullptr) t->next[c] = new PMA;
            t = t->next[c];
        }
        t->ac.push_back(i);
    }
    queue<PMA*> que; // make failure link using bfs
    for (int c = 1; c < SGSZ; ++c) {
        if (root->next[c]) {
            root->next[c]->next[0] = root;
            que.push(root->next[c]);
        } else root->next[c] = root;
    }
    while (!que.empty()) {
        PMA *t = que.front();
        que.pop();
        for (int c = 1; c < SGSZ; ++c) {

```

```

            if (t->next[c]) {
                que.push(t->next[c]);
                PMA *r = t->next[0];
                while (!r->next[c]) r = r->next[0];
                t->next[c]->next[0] = r->next[c];
                t->next[c]->last = r->next[c]->ac.size() ? r->
                    next[c] : r->next[c]->last;
            }
        }
    }
    return root;
}

void destructPMA(PMA *root) {
    queue<PMA*> que;
    que.emplace(root);
    while (!que.empty()) {
        PMA *t = que.front();
        que.pop();
        for (int c = 1; c < SGSZ; ++c) {
            if (t->next[c] && t->next[c] != root) que.emplace
                (t->next[c]);
        }
        delete t;
    }
}

template<typename T>
map<int, int> match(const T &t, PMA *v) {
    map<int, int> res;
    for (int i = 0; i < t.size(); ++i) {
        int c = INV_SIGMA[t[i]];
        while (!v->next[c]) v = v->next[0];
        v = v->next[c];
        for (int j = 0; j < v->ac.size(); ++j) ++res[v->ac[
            j]];
        for (PMA *q = v->last; q; q = q->last) {
            for (int j = 0; j < q->ac.size(); ++j) ++res[q->
                ac[j]];
        }
    }
    return res;
}

signed main() {
    INV_SIGMA.assign(256, -1);
    for (int i = 0; i < SIGMA.size(); ++i) {
        INV_SIGMA[SIGMA[i]] = i;
    }
}

```

7.2 KMP

```

template<typename T>
vector<int> build_kmp(const T &s) {
    vector<int> f(s.size());
    int fp = f[0] = -1;
    for (int i = 1; i < s.size(); ++i) {
        while (~fp && s[fp + 1] != s[i]) fp = f[fp];
        if (s[fp + 1] == s[i]) ++fp;
        f[i] = fp;
    }
    return f;
}

template<typename S>
vector<int> kmp_match(const vector<int> fail, const S &P,
    const S &T) {
    vector<int> res; // start from these points
    const int n = P.size();
    for (int j = 0, i = -1; j < T.size(); ++j) {
        while (~i and T[j] != P[i + 1]) i = fail[i];
        if (P[i + 1] == T[j]) ++i;
        if (i == n - 1) res.push_back(j - n + 1), i = fail[
            i];
    }
    return res;
}

```

7.3 Manacher

```
template<typename T, int INF>
vector<int> manacher(const T &s) { // p = "INF" + s.
    join("INF") + "INF", returns radius on p
    vector<int> p(s.size() * 2 + 1, INF);
    for (int i = 0; i < s.size(); ++i) {
        p[i << 1 | 1] = s[i];
    }
    vector<int> w(p.size());
    for (int i = 1, j = 0, r = 0; i < p.size(); ++i) {
        int t = min(r >= i ? w[2 * j - i] : 0, r - i + 1);
        for (; i - t >= 0 && i + t < p.size(); ++t) {
            if (p[i - t] != p[i + t]) break;
        }
        w[i] = --t;
        if (i + t > r) r = i + t, j = i;
    }
    return w;
}
```

7.4 Suffix Array

```
// -----O(NlgNlgN)-----
pair<vector<int>, vector<int>> sa_db(const string s) {
    int n = s.size();
    vector<int> sa(n), ra(n), t(n);
    for (int i = 0; i < n; ++i) ra[sa[i] = i] = s[i];
    for (int h = 1; t[n - 1] != n - 1; h *= 2) {
        auto cmp = [&](int i, int j) {
            if (ra[i] != ra[j]) return ra[i] < ra[j];
            return i + h < n && j + h < n ? ra[i + h] < ra[j + h] : i > j;
        };
        sort(sa.begin(), sa.end(), cmp);
        for (int i = 0; i + 1 < n; ++i) t[i + 1] = t[i] + cmp(sa[i], sa[i + 1]);
        for (int i = 0; i < n; ++i) ra[sa[i]] = t[i];
    }
    return {sa, ra};
}

// O(N) -- CF: 1e6-->31ms, 18MB; 1e7-->296ms; 158MB; 3e7-->856ms, 471MB
bool is_lms(const string &t, int i) {
    return i > 0 && t[i - 1] == 'L' && t[i] == 'S';
}

template<typename T>
vector<int> induced_sort(const T &s, const string &t,
    const vector<int> &lmss, int sigma = 256) {
    vector<int> sa(s.size(), -1);

    vector<int> bin(sigma + 1);
    for (auto it = s.begin(); it != s.end(); ++it) {
        ++bin[*it + 1];
    }

    int sum = 0;
    for (int i = 0; i < bin.size(); ++i) {
        sum += bin[i];
        bin[i] = sum;
    }

    vector<int> cnt(sigma);
    for (auto it = lmss.rbegin(); it != lmss.rend(); ++it) {
        int ch = s[*it];
        sa[bin[ch + 1] - 1 - cnt[ch]] = *it;
        ++cnt[ch];
    }

    cnt = vector<int>(sigma);
    for (auto it = sa.begin(); it != sa.end(); ++it) {
        if (*it <= 0 || t[*it - 1] == 'S') continue;
        int ch = s[*it - 1];
        sa[bin[ch] + cnt[ch]] = *it - 1;
        ++cnt[ch];
    }
}
```

```
cnt = vector<int>(sigma);
for (auto it = sa.rbegin(); it != sa.rend(); ++it) {
    if (*it <= 0 || t[*it - 1] == 'L') continue;
    int ch = s[*it - 1];
    sa[bin[ch + 1] - 1 - cnt[ch]] = *it - 1;
    ++cnt[ch];
}

return sa;
}

template<typename T>
vector<int> sa_is(const T &s, int sigma = 256) {
    string t(s.size(), 0);
    t[s.size() - 1] = 'S';
    for (int i = int(s.size()) - 2; i >= 0; --i) {
        if (s[i] < s[i + 1]) t[i] = 'S';
        else if (s[i] > s[i + 1]) t[i] = 'L';
        else t[i] = t[i + 1];
    }

    vector<int> lmss;
    for (int i = 0; i < s.size(); ++i) {
        if (is_lms(t, i)) {
            lmss.emplace_back(i);
        }
    }

    vector<int> sa = induced_sort(s, t, lmss, sigma);
    vector<int> sa_lms;
    for (int i = 0; i < sa.size(); ++i) {
        if (is_lms(t, sa[i])) {
            sa_lms.emplace_back(sa[i]);
        }
    }

    int lmp_ctr = 0;
    vector<int> lmp(s.size(), -1);
    lmp[sa_lms[0]] = lmp_ctr;
    for (int i = 0; i + 1 < sa_lms.size(); ++i) {
        int diff = 0;
        for (int d = 0; d < sa.size(); ++d) {
            if (s[sa_lms[i] + d] != s[sa_lms[i + 1] + d] ||
                is_lms(t, sa_lms[i] + d) != is_lms(t, sa_lms[i + 1] + d)) {
                diff = 1; // something different in range of lms
                break;
            } else if (d > 0 && is_lms(t, sa_lms[i] + d) &&
                is_lms(t, sa_lms[i + 1] + d)) {
                break; // exactly the same
            }
        }
        if (diff) ++lmp_ctr;
        lmp[sa_lms[i + 1]] = lmp_ctr;
    }

    vector<int> lmp_compact;
    for (int i = 0; i < lmp.size(); ++i) {
        if (~lmp[i]) {
            lmp_compact.emplace_back(lmp[i]);
        }
    }

    if (lmp_ctr + 1 < lmp_compact.size()) {
        sa_lms = sa_is(lmp_compact, lmp_ctr + 1);
    } else {
        for (int i = 0; i < lmp_compact.size(); ++i) {
            sa_lms[lmp_compact[i]] = i;
        }
    }

    vector<int> seed;
    for (int i = 0; i < sa_lms.size(); ++i) {
        seed.emplace_back(lmss[sa_lms[i]]);
    }

    return induced_sort(s, t, seed, sigma);
} // s must end in char(0)

// O(N) lcp, note that s must end in '\0'
```

```

vector<int> build_lcp(string &s, vector<int> &sa,
    vector<int> &ra) {
    int n = s.size();
    vector<int> lcp(n);
    for (int i = 0, h = 0; i < n; ++i) {
        if (ra[i] == 0) continue;
        if (h > 0) --h;
        for (int j = sa[ra[i] - 1]; max(j, i) + h < n; ++h) {
            if (s[j + h] != s[i + h]) break;
        }
        lcp[ra[i] - 1] = h;
    }
    return lcp; // lcp[i] := LCP(s[sa[i]], s[sa[i + 1]])
}

// O(N) build segment tree for lcp
vector<int> build_lcp_rmq(const vector<int> &lcp) {
    vector<int> sgt(lcp.size() << 2);
    function<void(int, int, int)> build = [&](int t, int
        lb, int rb) {
        if (rb - lb == 1) return sgt[t] = lcp[lb], void();
        int mb = lb + rb >> 1;
        build(t << 1, lb, mb);
        build(t << 1 | 1, mb, rb);
        sgt[t] = min(sgt[t << 1], sgt[t << 1 | 1]);
    };
    build(1, 0, lcp.size());
    return sgt;
}

// O(|P| + lg |T|) pattern searching, returns last
// index in sa
int match(const string &p, const string &s, const
    vector<int> &sa, const vector<int> &rmq) { // rmq
    is segtree on lcp
    int t = 1, lb = 0, rb = s.size(); // answer in [lb,
        rb)
    int lcplp = 0; // lcp(char(0), p) = 0
    while (rb - lb > 1) {
        int mb = lb + rb >> 1;
        int lcplm = rmq[t << 1];
        if (lcplp < lcplm) t = t << 1 | 1, lb = mb;
        else if (lcplp > lcplm) t = t << 1, rb = mb;
        else {
            int lcpmp = lcplp;
            while (lcpmp < p.size() && p[lcpmp] == s[sa[mb] +
                lcpmp]) ++lcpmp;
            if (lcpmp == p.size() || p[lcpmp] > s[sa[mb] +
                lcpmp]) t = t << 1 | 1, lb = mb, lcplp =
                lcpmp;
            else t = t << 1, rb = mb;
        }
    }
    if (lcplp < p.size()) return -1;
    return sa[lb];
}

int LCA(int i, int j, const vector<int> &ra, const
    vector<int> &lcp_seg) {
    // lca of ith and jth suffix
    if (ra[i] > ra[j]) swap(i, j);
    function<int(int, int, int, int, int)> query = [&](
        int L, int R, int l, int r, int v) {
        if (L <= l and r <= R) return lcp_seg[v];
        int m = l + r >> 1, ans = 1e9;
        if (L < m) ans = min(ans, query(L, R, l, m, v << 1));
        if (m < R) ans = min(ans, query(L, R, m, r, v <<
            1 | 1));
        return ans;
    };
    return query(ra[i], ra[j], 0, ra.size(), 1);
}

vector<vector<int>> build_lcp_sparse_table(const vector
    <int> &lcp) {
    int n = lcp.size(), lg = 31 - __builtin_clz(n);
    vector<vector<int>> st(lg + 1, vector<int>(n));
    for (int i = 0; i < n; ++i) st[0][i] = lcp[i];
    for (int j = 1; (1<<j) <= n; ++j)
        for (int i = 0; i + (1<<j) <= n; ++i)

```

```

        st[j][i] = min(st[j - 1][i], st[j - 1][i + (1<<(j
            - 1))]);
    }
    return st;
}

int sparse_rmq(int i, int j, const vector<int> &ra,
    const vector<vector<int>> &st) {
    int n = st[0].size();
    if (ra[i] > ra[j]) swap(i, j);
    int k = 31 - __builtin_clz(ra[j] - ra[i]);
    return min(st[k][ra[i]], st[k][ra[j] - (1<<k)]);
} // sparse_rmq(sa[i], sa[j], ra, st) is the lcp of sa(i
    ), sa(j)

```

7.5 Suffix Automaton

```

template<typename T>
struct SuffixAutomaton {
    vector<map<int, int>> edges; // edges[i] : the
        labeled edges from node i
    vector<int> link; // link[i] : the parent
        of i
    vector<int> length; // length[i] : the length
        of the longest string in the ith class
    int last; // the index of the
        equivalence class of the whole string
    vector<bool> is_terminal; // is_terminal[i] : some
        suffix ends in node i (unnecessary)
    vector<int> occ; // occ[i] : number of
        matches of maximum string of node i (unnecessary)
    SuffixAutomaton(const T &s) : edges({map<int, int>()
        }, link({-1}), length({0}), last(0), occ({0}) {
        for (int i = 0; i < s.size(); ++i) {
            edges.push_back(map<int, int>());
            length.push_back(i + 1);
            link.push_back(0);
            occ.push_back(1);
            int r = edges.size() - 1;
            int p = last; // add edges to r and find p with
                link to q
            while (p >= 0 && edges[p].find(s[i]) == edges[p].
                end()) {
                edges[p][s[i]] = r;
                p = link[p];
            }
            if (~p) {
                int q = edges[p][s[i]];
                if (length[p] + 1 == length[q]) { // no need to
                    split q
                    link[r] = q;
                } else { // split q, add qq
                    edges.push_back(edges[q]); // copy edges of
                        q
                    length.push_back(length[p] + 1);
                    link.push_back(link[q]); // copy parent of q
                    occ.push_back(0);
                    int qq = edges.size() - 1; // qq is new
                        parent of q and r
                    link[q] = qq;
                    link[r] = qq;
                    while (p >= 0 && edges[p][s[i]] == q) { //
                        what points to q points to qq
                        edges[p][s[i]] = qq;
                        p = link[p];
                    }
                }
            }
            last = r;
        } // below unnecessary
        is_terminal = vector<bool>(edges.size());
        for (int p = last; p > 0; p = link[p]) is_terminal[
            p] = 1; // is_terminal calculated
        vector<int> cnt(link.size(), states(link.size()));
        // sorted states by length
        for (int i = 0; i < link.size(); ++i) ++cnt[length[
            i]];
        for (int i = 0; i < s.size(); ++i) cnt[i + 1] +=
            cnt[i];
        for (int i = link.size() - 1; i >= 0; --i) states
            [--cnt[length[i]]] = i;
    }
}

```

```

for (int i = link.size() - 1; i >= 1; --i) occ[link
[states[i]]] += occ[states[i]]; // occ
calculated
}
};

```

8 Formulas

8.1 Pick's theorem

For a polygon:

A: The area of the polygon

B: Boundary Point: a lattice point on the polygon (including vertices)

I: Interior Point: a lattice point in the polygon's interior region

$$A = I + \frac{B}{2} - 1$$

8.2 Graph Properties

1. Euler's Formula $V - E + F = 2$
2. For a planar graph, $F = E - V + n + 1$, n is the numbers of components
3. For a planar graph, $E \leq 3V - 6$

For a connected graph G : $I(G)$: the size of maximum independent set $M(G)$: the size of maximum matching $Cv(G)$: be the size of minimum vertex cover $Ce(G)$: be the size of minimum edge cover

4. For any connected graph:

$$\begin{aligned} \text{(a)} \quad I(G) + Cv(G) &= |V| \\ \text{(b)} \quad M(G) + Ce(G) &= |V| \end{aligned}$$

5. For any bipartite:

$$\begin{aligned} \text{(a)} \quad I(G) &= Cv(G) \\ \text{(b)} \quad M(G) &= Ce(G) \end{aligned}$$

8.3 Number Theory

1. $g(m) = \sum_{d|m} f(d) \Leftrightarrow f(m) = \sum_{d|m} \mu(d) \times g(m/d)$
2. $\phi(x), \mu(x)$ are Möbius inverse
3. $\sum_{i=1}^n \sum_{j=1}^m [\gcd(i, j) = 1] = \sum \mu(d) \lfloor \frac{n}{d} \rfloor \lfloor \frac{m}{d} \rfloor$
4. $\sum_{i=1}^n \sum_{j=1}^m lcm(i, j) = n \sum_{d|n} d \times \phi(d)$

8.4 Combinatorics

1. Gray Code: $= n \oplus (n >> 1)$
2. Catalan Number:

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{n!(n+1)!} = \prod_{k=2}^n \frac{n+k}{k}$$

3. $\Gamma(n+1) = n!$
4. $n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$
5. Stirling number of second kind: the number of ways to partition a set of n elements into k nonempty subsets.

$$\begin{aligned} \text{(a)} \quad \{0\} &= \{n\} = 1 \\ \text{(b)} \quad \{n\} &= 0 \\ \text{(c)} \quad \{k\} &= k \{n-1\} + \{k-1\} \end{aligned}$$

6. Bell numbers count the possible partitions of a set:

$$\begin{aligned} \text{(a)} \quad B_0 &= 1 \\ \text{(b)} \quad B_n &= \sum_{k=0}^n \binom{n}{k} B_k \\ \text{(c)} \quad B_{n+1} &= \sum_{k=0}^n \binom{n}{k} C_k B_k \\ \text{(d)} \quad B_{p+n} &\equiv B_n + B_{n+1} \pmod{p}, \text{ p prime} \\ \text{(e)} \quad B_{p^m+n} &\equiv m B_n + B_{n+1} \pmod{p}, \text{ p prime} \\ \text{(f)} \quad \text{From } B_0 : &1, 1, 2, 5, 15, 52, \\ &203, 877, 4140, 21147, 115975 \end{aligned}$$

7. Derangement

$$\begin{aligned} \text{(a)} \quad D_n &= n! \left(1 - \frac{1}{1!} + \frac{1}{2!} - \frac{1}{3!} \dots + (-1)^n \frac{1}{n!}\right) \\ \text{(b)} \quad D_n &= (n-1)(D_{n-1} + D_{n-2}) \\ \text{(c)} \quad \text{From } D_0 : &1, 0, 1, 2, 9, 44, \\ &265, 1854, 14833, 133496 \end{aligned}$$

8. Binomial Equality

$$\begin{aligned} \text{(a)} \quad \sum_k \binom{r}{m+k} \binom{s}{n-k} &= \binom{r+s}{m+n} \\ \text{(b)} \quad \sum_k \binom{r}{m+k} \binom{s}{n-k} &= \binom{r+s}{l+m+n} \\ \text{(c)} \quad \sum_k \binom{r}{m+k} \binom{s}{n-k} (-1)^k &= (-1)^{l+m} \binom{s-m}{n-l} \\ \text{(d)} \quad \sum_{k \leq l} \binom{l-k}{m} \binom{s}{n-k} (-1)^k &= (-1)^{l+m} \binom{s-m-1}{l-n-m} \\ \text{(e)} \quad \sum_{0 \leq k \leq l} \binom{l-k}{m} \binom{q+k}{n} &= \binom{l+q+1}{m+n+1} \\ \text{(f)} \quad \binom{r}{k} &= (-1)^k \binom{r-k}{k} \\ \text{(g)} \quad \binom{r}{m} \binom{m}{k} &= \binom{r}{m-k} \binom{m-k}{k} \\ \text{(h)} \quad \sum_{k \leq n} \binom{r+k}{k} &= \binom{r+n+1}{n} \\ \text{(i)} \quad \sum_{0 \leq k \leq n} \binom{k}{m} &= \binom{n+1}{m+1} \\ \text{(j)} \quad \sum_{k \leq m} \binom{m+r}{k} x^k y^{m-k} &= \sum_{k \leq m} \binom{-r}{k} (-x)^k (x+y)^{m-k} \end{aligned}$$

8.5 Sum of Powers

1. $a^b \% P = a^{b \% \varphi(P) + \varphi(P)} \pmod{P}, b \geq \varphi(P)$
2. $1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^4}{4} + \frac{n^3}{2} + \frac{n^2}{4}$
3. $1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n^5}{5} + \frac{n^4}{2} + \frac{n^3}{3} - \frac{n}{30}$
4. $1^5 + 2^5 + 3^5 + \dots + n^5 = \frac{n^6}{6} + \frac{n^5}{2} + \frac{5n^4}{12} - \frac{n^2}{12}$
5. $0^k + 1^k + 2^k + \dots + n^k = P_k, P_k = \frac{(n+1)^{k+1} - \sum_{i=0}^{k-1} C_i^{k+1} P(i)}{k+1}, P_0 = n+1$
6. $\sum_{k=0}^{m-1} k^n = \frac{1}{n+1} \sum_{k=0}^n C_k^{n+1} B_k m^{n+1-k}$
7. $\sum_{j=0}^m C_j^{m+1} B_j = 0, B_0 = 1$
8. 除了 $B_1 = -1/2$, 剩下的奇數項都是 0
9. $B_2 = 1/6, B_4 = -1/30, B_6 = 1/42, B_8 = -1/30, B_{10} = 5/66, B_{12} = -691/2730, B_{14} = 7/6, B_{16} = -3617/510, B_{18} = 43867/798, B_{20} = -174611/330,$

8.6 Burnside's lemma

1. $|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$
2. $X^g = t^{c(g)}$

8.7 Count on a tree

1. Rooted tree: $s_{n+1} = \frac{1}{n} \sum_{i=1}^n (i \times a_i \times \sum_{j=1}^{\lfloor n/i \rfloor} a_{n+1-i \times j})$
2. Unrooted tree:
 - (a) Odd: $a_n - \sum_{i=1}^{n/2} a_i a_{n-i}$
 - (b) Even: $Odd + \frac{1}{2} a_{n/2} (a_{n/2} + 1)$
3. Spanning Tree
 - (a) 完全圖 $n^n - 2$
 - (b) 一般圖 (Kirchhoff's theorem) $M[i][i] = \deg(V_i), M[i][j] = -1, \text{ if have } E(i, j), 0 \text{ if no edge. delete any one row and col in } A, ans = \det(A)$

9 Team Comments

1. 前一個小時把題目看完
2. 一個題目不只要想，還要想解題時間
3. while (有題目) 寫 // 不管多長
4. 盡快 AC 覺得可以快速 AC 的題目
5. rareone0602: 盡量不要讓我碰細節多的題目，盡量讓我想需要想突破口的題目
6. 如果目前沒有可寫的題目，先有希望題目的 IO
7. 讀過的題目可以像 priority queue 一樣，先花一些時間把題目塞進 pq 就說是 k 題好了，當 pq size 少於 k 把新題目塞進 pq
8. 電腦閒置可以生 debug 的測資

9.1 The Who-have-read Table

	rar	jjj	0w1
pA			
pB			
pC			
pD			
pE			
pF			
pG			
pH			
pI			
pJ			
pK			
pL			