

Contents

1 Basic

1.1 .vimrc

```
syntax on
set nu ai bs=2 sw=2 et ve=all cb=unnamed mouse=a ruler
incsearch
```

2 Combinatorics

2.1 FFT

```
typedef complex<double> cpx;
const double PI = acos(-1);
vector<cpx> FFT(vector<cpx> &P, bool inv = 0) {
    assert(__builtin_popcount(P.size()) == 1);
    int lg = 31 - __builtin_clz(P.size()), n = 1 << lg;
    // == P.size();
    for (int j = 1, i = 0; j < n - 1; ++j) {
        for (int k = n >> 1; k > (i ^ k); k >= 1);
        if (j < i) swap(P[i], P[j]);
    } //bit reverse
    auto w1 = exp((2 - 4 * inv) * PI / n * cpx(0, 1)); //
    // order is 1<<lg
    for (int i = 1; i <= lg; ++i) {
        auto wn = pow(w1, 1<<(lg - i)); // order is 1<<i
        for (int k = 0; k < (1<<lg); k += 1 << i) {
            cpx base = 1;
            for (int j = 0; j < (1 << i - 1); ++j, base =
                base * wn) {
                auto t = base * P[k + j + (1 << i - 1)];
                auto u = P[k + j];
                P[k + j] = u + t;
                P[k + j + (1 << i - 1)] = u - t;
            }
        }
    }
    if(inv)
        for (int i = 0; i < n; ++i) P[i] /= n;
    return P;
} //faster performance with calling by reference
```

2.2 FWT

```
vector<int> fast_OR_transform(vector<int> f, bool
    inverse) {
    for (int i = 0; (2 << i) <= f.size(); ++i)
        for (int j = 0; j < f.size(); j += 2 << i)
            for (int k = 0; k < (1 << i); ++k)
                f[j + k + (1 << i)] += f[j + k] * (inverse? -1
                    : 1);
    return f;
}
vector<int> rev(vector<int> A) {
    for (int i = 0; i < A.size(); i += 2) swap(A[i], A[i
        ^ (A.size() - 1)]);
    return A;
}
vector<int> fast_AND_transform(vector<int> f, bool
    inverse) {
    return rev(fast_OR_transform(rev(f), inverse));
}
vector<int> fast_XOR_transform(vector<int> f, bool
    inverse) {
    for (int i = 0; (2 << i) <= f.size(); ++i)
        for (int j = 0; j < f.size(); j += 2 << i)
            for (int k = 0; k < (1 << i); ++k) {
                int u = f[j + k], v = f[j + k + (1 << i)];
                f[j + k + (1 << i)] = u - v, f[j + k] = u + v;
            }
    if (inverse) for (auto &a : f) a /= f.size();
    return f;
}
```

2.3 NTT

```

/* p == (a << n) + 1
n   1 << n   p       a   root
5   32       97       3   5
6   64       193      3   5
7   128      257      2   3
8   256      257      1   3
9   512      7681     15  17
10  1024     12289    12  11
11  2048     12289    6   11
12  4096     12289    3   11
13  8192     40961    5   3
14  16384    65537    4   3
15  32768    65537    2   3
16  65536    65537    1   3
17  131072   786433   6   10
18  262144   786433   3   10 (605028353,
    2308, 3)
19  524288   5767169  11  3
20  1048576  7340033  7   3
21  2097152  23068673 11  3
22  4194304  104857601 25  3
23  8388608  167772161 20  3
24  16777216 167772161 10  3
25  33554432 167772161 5   3 (1107296257, 33,
    10)
26  67108864 469762049 7   3
27  134217728 2013265921 15 31 */
LL root = 10, p = 786433, a = 3;
LL powM(LL x, LL b) {
    LL s = 1, m = x % p;
    for (; b; m = m * m % p, b >>= 1)
        if (b&1) s = s * m % p;
    return s;
}
vector<LL> NTT(vector<LL> P, bool inv = 0) {
    assert(__builtin_popcount(P.size()) == 1);
    int lg = 31 - __builtin_clz(P.size()), n = 1 << lg;
    // == P.size();
    for (int j = 1, i = 0; j < n - 1; ++j) {
        for (int k = n >> 1; k > (i ^ k); k >>= 1);
        if (j < i) swap(P[i], P[j]);
    } //bit reverse
    LL w1 = powM(root, a * (inv ? p - 2 : 1)); // order is
    1<<lg
    for (LL i = 1; i <= lg; ++i) {
        LL wn = powM(w1, 1<<(lg - i)); // order is 1<<i
        for (int k = 0; k < (1<<lg); k += 1 << i) {
            LL base = 1;
            for (int j = 0; j < (1 << i - 1); ++j, base =
                base * wn % p) {
                LL t = base * P[k + j + (1 << i - 1)] % p;
                LL u = P[k + j] % p;
                P[k + j] = (u + t) % p;
                P[k + j + (1 << i - 1)] = (u - t + p) % p;
            }
        }
    }
    if (inv) {
        LL invN = powM(n, p - 2);
        transform(P.begin(), P.end(), P.begin(), [&](LL a)
            {return a * invN % p;});
    }
    return P;
} //faster performance with calling by reference

```

2.4 permanent

```

typedef vector<vector<LL> > mat;
LL permanent(mat A) {
    LL n = A.size(), ans = 0, *tmp = new LL[n], add;
    for (int pgray = 0, s = 1, gray, i; s < 1 << n; ++s)
    {
        gray = s ^ s >> 1, add = 1;
        i = __builtin_ctz(pgray ^ gray);
        for (int j = 0; j < n; ++j)
            add *= tmp[j] += A[i][j] * (gray>>i&1 ? 1 : -1);
        ans += add * (s&1^n&1? -1 : 1), pgray = gray;
    }
}

```

```

}
return ans;
}
// how many ways to put rooks on a matrix with 0,1 as
    constrain
// 1 - ok to put
// 0 - not ok to put

```

3 Data Structure

3.1 Heavy Light Decomposition

```

struct HLD {
    using Tree = vector<vector<int>>;
    vector<int> par, head, vid, len, inv;

    HLD(const Tree &g) : par(g.size()), head(g.size()),
        vid(g.size()), len(g.size()), inv(g.size()) {
        int k = 0;
        vector<int> size(g.size(), 1);
        function<void(int, int)> dfs_size = [&](int u, int
            p) {
            for (int v : g[u]) {
                if (v != p) {
                    dfs_size(v, u);
                    size[u] += size[v];
                }
            }
        };
        function<void(int, int, int)> dfs_dcmp = [&](int u,
            int p, int h) {
            par[u] = p;
            head[u] = h;
            vid[u] = k++;
            inv[vid[u]] = u;
            for (int v : g[u]) {
                if (v != p && size[u] < size[v] * 2) {
                    dfs_dcmp(v, u, h);
                }
            }
            for (int v : g[u]) {
                if (v != p && size[u] >= size[v] * 2) {
                    dfs_dcmp(v, u, v);
                }
            }
        };
        dfs_size(0, -1);
        dfs_dcmp(0, -1, 0);
        for (int i = 0; i < g.size(); ++i) {
            ++len[head[i]];
        }
    }

    template<typename T>
    void foreach(int u, int v, T f) {
        while (true) {
            if (vid[u] > vid[v]) {
                if (head[u] == head[v]) {
                    f(vid[v] + 1, vid[u], 0);
                    break;
                }
                else {
                    f(vid[head[u]], vid[u], 1);
                    u = par[head[u]];
                }
            }
            else {
                if (head[u] == head[v]) {
                    f(vid[u] + 1, vid[v], 0);
                    break;
                }
                else {
                    f(vid[head[v]], vid[v], 0);
                    v = par[head[v]];
                }
            }
        }
    }
}

```

4 Flow

4.1 CostFlow

```
template <class TF, class TC>
struct CostFlow {
    static const int MAXV = 205;
    static const TC INF = 0x3f3f3f3f;
    struct Edge {
        int v, r;
        TF f;
        TC c;
        Edge(int _v, int _r, TF _f, TC _c) : v(_v), r(_r),
            f(_f), c(_c) {}
    };
    int n, s, t, pre[MAXV], pre_E[MAXV], inq[MAXV];
    TF fl;
    TC dis[MAXV], cost;
    vector<Edge> E[MAXV];
    CostFlow(int _n, int _s, int _t) : n(_n), s(_s), t(_t),
        fl(0), cost(0) {}
    void add_edge(int u, int v, TF f, TC c) {
        E[u].emplace_back(v, E[v].size(), f, c);
        E[v].emplace_back(u, E[u].size() - 1, 0, -c);
    }
    pair<TF, TC> flow() {
        while (true) {
            for (int i = 0; i < n; ++i) {
                dis[i] = INF;
                inq[i] = 0;
            }
            dis[s] = 0;
            queue<int> que;
            que.emplace(s);
            while (not que.empty()) {
                int u = que.front();
                que.pop();
                inq[u] = 0;
                for (int i = 0; i < E[u].size(); ++i) {
                    int v = E[u][i].v;
                    TC w = E[u][i].c;
                    if (E[u][i].f > 0 and dis[v] > dis[u] + w) {
                        pre[v] = u;
                        pre_E[v] = i;
                        dis[v] = dis[u] + w;
                        if (not inq[v]) {
                            inq[v] = 1;
                            que.emplace(v);
                        }
                    }
                }
            }
            if (dis[t] == INF) break;
            TF tf = INF;
            for (int v = t, u, l; v != s; v = u) {
                u = pre[v];
                l = pre_E[v];
                tf = min(tf, E[u][l].f);
            }
            for (int v = t, u, l; v != s; v = u) {
                u = pre[v];
                l = pre_E[v];
                E[u][l].f -= tf;
                E[v][E[u][l].r].f += tf;
            }
            cost += tf * dis[t];
            fl += tf;
        }
        return {fl, cost};
    }
};
```

4.2 Dinic

```
template <class T>
struct Dinic {
    static const int MAXV = 10000;
    static const T INF = 0x3f3f3f3f;
```

```
struct Edge {
    int v;
    T f;
    int re;
    Edge(int _v, T _f, int _re) : v(_v), f(_f), re(_re) {}
};
int n, s, t, level[MAXV];
vector<Edge> E[MAXV];
int now[MAXV];
Dinic(int _n, int _s, int _t) : n(_n), s(_s), t(_t) {}
void add_edge(int u, int v, T f, bool bidirectional = false) {
    E[u].emplace_back(v, f, E[v].size());
    E[v].emplace_back(u, 0, E[u].size() - 1);
    if (bidirectional) {
        E[v].emplace_back(u, f, E[u].size() - 1);
    }
}
bool BFS() {
    memset(level, -1, sizeof(level));
    queue<int> que;
    que.emplace(s);
    level[s] = 0;
    while (not que.empty()) {
        int u = que.front();
        que.pop();
        for (auto it : E[u]) {
            if (it.f > 0 and level[it.v] == -1) {
                level[it.v] = level[u] + 1;
                que.emplace(it.v);
            }
        }
    }
    return level[t] != -1;
}
T DFS(int u, T nf) {
    if (u == t) return nf;
    T res = 0;
    while (now[u] < E[u].size()) {
        Edge &it = E[u][now[u]];
        if (it.f > 0 and level[it.v] == level[u] + 1) {
            T tf = DFS(it.v, min(nf, it.f));
            res += tf;
            nf -= tf;
            it.f -= tf;
            E[it.v][it.re].f += tf;
            if (nf == 0) return res;
        } else {
            ++now[u];
        }
    }
    if (not res) level[u] = -1;
    return res;
}
T flow(T res = 0) {
    while (BFS()) {
        T temp;
        memset(now, 0, sizeof(now));
        while (temp = DFS(s, INF)) {
            res += temp;
            res = min(res, INF);
        }
    }
    return res;
};
```

5 Geometry

5.1 Line and points

```
namespace kika {
    using cod = complex<double>;

    const double EPS = 1e-9;
    const double PI = acos(-1);
```

```

int dcmp(double x) {
    if (abs(x) < EPS) return 0;
    return x > 0 ? 1 : -1;
}

bool less(cod a, cod b) {
    return real(a) < real(b) || real(a) == real(b) &&
        imag(a) < imag(b);
}

bool more(cod a, cod b) {
    return real(a) > real(b) || real(a) == real(b) &&
        imag(a) > imag(b);
}

double dot(cod a, cod b) {
    return real(conj(a) * b);
}

double cross(cod a, cod b) {
    return imag(conj(a) * b);
}

int ori(cod b, cod a, cod c) {
    return dcmp(cross(a - b, c - b));
}

double angle(cod a, cod b) {
    return acos(dot(a, b) / abs(a) / abs(b));
}

double sarea(cod a, cod b, cod c) {
    return cross(b - a, c - a);
}

cod rotate(cod a, double rad) {
    return a * cod(cos(rad), sin(rad));
}

cod normal(cod a) {
    return cod(-imag(a) / abs(a), real(a) / abs(a));
}

cod get_line_intersection(cod p, cod v, cod q, cod w)
    { // p and v are two points that decides a line
    cod u(p - q);
    double t = cross(w, u) / cross(v, w);
    return p + v * t;
}

double distance_to_line(cod p, cod a, cod b) {
    return abs(cross(b - a, p - a) / abs(b - a));
}

double distance_to_segment(cod p, cod a, cod b) {
    if (a == b) return abs(p - a);
    cod v1(b - a), v2(p - a), v3(p - b);
    if (dcmp(dot(v1, v2)) < 0) return abs(v2);
    else if (dcmp(dot(v1, v3)) > 0) return abs(v3);
    return abs(cross(v1, v2)) / abs(v1);
}

cod get_line_projection(cod p, cod a, cod b) {
    cod v(b - a);
    return a + dot(v, p - a) / dot(v, v) * v;
}

bool segment_proper_intersection(cod a1, cod a2, cod
    b1, cod b2) {
    double c1 = cross(a2 - a1, b1 - a1), c2 = cross(a2
        - a1, b2 - a1);
    double c3 = cross(b2 - b1, a1 - b1), c4 = cross(b2
        - b1, a2 - b1);
    return dcmp(c1) * dcmp(c2) < 0 && dcmp(c3) * dcmp(
        c4) < 0;
}

double polygon_area(vector<cod> p) {
    double area = 0;
    for (int i = 1; i < int(p.size()) - 1; ++i) {
        area += cross(p[i] - p[0], p[i + 1] - p[0]);
    }
}

```

```

    return area / 2;
}

bool is_point_on_segment(cod p, cod a1, cod a2) {
    return dcmp(cross(a1 - p, a2 - p)) == 0 && dcmp(dot
        (a1 - p, a2 - p)) < 0;
}

int is_point_in_polygon(cod p, vector<cod> gon) {
    int wn = 0;
    int n = gon.size();
    for (int i = 0; i < n; ++i) {
        if (is_point_on_segment(p, gon[i], gon[(i + 1) %
            n])) return -1;
        int k = dcmp(cross(gon[(i + 1) % n] - gon[i], p -
            gon[i]));
        int d1 = dcmp(imag(gon[i]) - imag(p));
        int d2 = dcmp(imag(gon[(i + 1) % n] - imag(p)));
        wn += k > 0 && d1 <= 0 && d2 > 0;
        wn -= k < 0 && d2 <= 0 && d1 > 0;
    }
    return wn != 0;
}

vector<cod> convex_hull(vector<cod> p) {
    sort(p.begin(), p.end(), less);
    p.erase(unique(p.begin(), p.end(), p.end()));
    int n = p.size(), m = 0;
    vector<cod> ch(n + 1);
    for (int i = 0; i < n; ++i) { // note that border
        is cleared
        while (m > 1 && dcmp(cross(ch[m - 1] - ch[m - 2],
            p[i] - ch[m - 2])) <= 0) {
            --m;
        }
        ch[m++] = p[i];
    }
    for (int i = n - 2, k = m; i >= 0; --i) {
        while (m > k && dcmp(cross(ch[m - 1] - ch[m - 2],
            p[i] - ch[m - 2])) <= 0) {
            --m;
        }
        ch[m++] = p[i];
    }
    ch.erase(ch.begin() + m - (n > 1), ch.end());
    return ch;
}
};

```

6 Graph

6.1 2-SAT

```

#include <cstdio>
#include <vector>
#include <stack>
#include <cstring>
using namespace std;

const int N = 2010;
struct two_SAT {
    int n;
    vector<int> G[N], revG[N];
    stack<int> finish;
    bool sol[N], visit[N];
    int cmp[N];
    void init(int _n) {
        n = _n;
        for (int i = 0; i < N; i++) {
            G[i].clear();
            revG[i].clear();
        }
    }
    void add_edge(int u, int v) {
        // 2 * i -> i is True, 2 * i + 1 -> i is False
        G[u].push_back(v);
        G[v^1].push_back(u^1);
        revG[v].push_back(u);
    }
};

```

```

    revG[u^1].push_back(v^1);
}
void dfs(int v) {
    visit[v] = true;
    for (auto i:G[v]) {
        if ( !visit[i] ) dfs(i);
    }
    finish.push(v);
}
void revdfs(int v, int id) {
    visit[v] = true;
    for (auto i:revG[v]) {
        if ( !visit[i] ) revdfs(i,id);
    }
    cmp[v] = id;
}
int scc() {
    memset( visit, 0, sizeof(visit) );
    for (int i = 0; i < 2 * n; i++) {
        if ( !visit[i] ) dfs(i);
    }
    int id = 0;
    memset( visit, 0, sizeof(visit) );
    while ( !finish.empty() ) {
        int v = finish.top(); finish.pop();
        if ( visit[v] ) continue;
        revdfs(v,++id);
    }
    return id;
}
bool solve() {
    scc();
    for (int i = 0; i < n; i++) {
        if ( cmp[2*i] == cmp[2*i+1] ) return 0;
        sol[i] = ( cmp[2*i] > cmp[2*i+1] );
    }
    return 1;
}
} sat;

int main() {
    // ( a or not b ) and ( b or c ) and ( not c or not a )
    sat.init(3);
    sat.add_edge( 2*0+1, 2*1+1 );
    sat.add_edge( 2*1+1, 2*2+0 );
    sat.add_edge( 2*2+0, 2*0+1 );
    printf("%d\n", sat.solve() );
    return 0;
}

```

6.2 maximal cliques

```

#include <bits/stdc++.h>
using namespace std;

const int N = 60;
typedef long long LL;

struct Bron_Kerbosch {
    int n, res;
    LL edge[N];
    void init(int _n) {
        n = _n;
        for (int i = 0; i <= n; i++) edge[i] = 0;
    }
    void add_edge(int u, int v) {
        if ( u == v ) return;
        edge[u] |= 1LL << v;
        edge[v] |= 1LL << u;
    }
    void go(LL R, LL P, LL X) {
        if ( P == 0 && X == 0 ) {
            res = max( res, __builtin_popcountll(R) ); //
            notice LL
            return;
        }
        if ( __builtin_popcountll(R) + __builtin_popcountll
            (P) <= res ) return;
        for (int i = 0; i <= n; i++) {

```

```

            LL v = 1LL << i;
            if ( P & v ) {
                go( R | v, P & edge[i], X & edge[i] );
                P &= ~v;
                X |= v;
            }
        }
    }
    int solve() {
        res = 0;
        go( 0LL, ( 1LL << (n+1) ) - 1, 0LL );
        return res;
    }
    /* BronKerbosch1(R, P, X):
       if P and X are both empty:
           report R as a maximal clique
       for each vertex v in P:
           BronKerbosch1(R ∪ {v}, P ∩ N(v), X ∩ N(v))
           P := P \ {v}
           X := X ∪ {v}
    */
} MaxClique;

int main() {
    MaxClique.init(6);
    MaxClique.add_edge(1,2);
    MaxClique.add_edge(1,5);
    MaxClique.add_edge(2,5);
    MaxClique.add_edge(4,5);
    MaxClique.add_edge(3,2);
    MaxClique.add_edge(4,6);
    MaxClique.add_edge(3,4);
    cout << MaxClique.solve() << "\n";
    return 0;
}

```

6.3 Tarjan SCC

```

#include <cstdio>
#include <vector>
#include <stack>
#include <cstring>
using namespace std;

const int N = 10010;
struct Tarjan {
    int n;
    vector<int> G[N], revG[N];
    stack<int> finish;
    bool visit[N];
    int cmp[N];
    void init(int _n) {
        n = _n;
        for (int i = 0; i <= n; i++) {
            G[i].clear();
            revG[i].clear();
        }
    }
    void add_edge(int u, int v) {
        G[u].push_back(v);
        revG[v].push_back(u);
    }
    void dfs(int v) {
        visit[v] = true;
        for (auto i:G[v]) {
            if ( !visit[i] ) dfs(i);
        }
        finish.push(v);
    }
    void revdfs(int v, int id) {
        visit[v] = true;
        for (auto i:revG[v]) {
            if ( !visit[i] ) revdfs(i,id);
        }
        cmp[v] = id;
    }
    int solve() {
        memset( visit, 0, sizeof(visit) );
        for (int i = 0; i < n; i++) {
            if ( !visit[i] ) dfs(i);

```

```

    }
    int id = 0;
    memset(visit, 0, sizeof(visit));
    while (!finish.empty()) {
        int v = finish.top(); finish.pop();
        if (visit[v]) continue;
        revdfs(v, ++id);
    }
    return id;
}
} scc;

int main() {
    int V, E;
    scanf("%d %d", &V, &E);
    scc.init(V);
    for (int i = 0; i < E; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        scc.add_edge(u-1, v-1);
    }
    printf("%d\n", scc.solve());
    return 0;
}

```

7 Number Theory

7.1 basic

```

PLL exd_gcd(LL a, LL b) {
    if (a % b == 0) return {0, 1};
    PLL T = exd_gcd(b, a % b);
    return {T.second, T.first - a / b * T.second};
}

LL mul(LL x, LL y, LL mod) {
    LL ans = 0, m = x, s = 0, sgn = (x > 0) xor (y > 0)? -1: 1;
    for (x = abs(x), y = abs(y); y; y >>= 1, m <= 1, m = m >= mod? m - mod: m)
        if (y&1) s += m, s = s >= mod? s - mod: s;
    return s * sgn;
}

LL dangerous_mul(LL a, LL b, LL mod) { // 10 times
    // faster than the above in average, but could be
    // prone to wrong answer (extreme low prob?)
    return (a * b - (LL)((long double)a * b / mod) * mod) % mod;
}

LL powmod(LL x, LL p, LL mod) {
    LL s = 1, m = x % mod;
    for (; p; p = mul(m, m, mod), p >>= 1)
        if (p&1) s = mul(s, m, mod);
    return s;
}

```

7.2 Chinese Remainder Theorem

```

typedef long long LL;
typedef pair<LL, LL> PLL;
PLL exd_gcd(LL a, LL b);
LL CRT(vector<PLL> &eqs) {
    LL prod = 1, ans = 0, ni, ns;
    for (auto P: eqs) prod *= P.second;
    for (auto P: eqs) {
        ni = P.second, ns = prod / ni;
        (ans += ns * P.first % prod * exd_gcd(ni, ns).second) %= prod;
    }
    return (ans + prod) % prod;
}

```

7.3 Discrete Log

```

LL discrete_log(LL b, LL p, LL n) {
    map<LL, LL> att;
    LL m = sqrt((double)p) + 1, M = powmod(b, m * (p - 2), p);
    for (LL cur = 1, i = 0; i < m; ++i, cur = cur * b % p)
        if (not att.count(cur)) att[cur] = i;
    for (LL cur = 1, i = 0; i * m < p - 1; ++i, cur = cur * M % p)
        if (att.count(n * cur % p))
            return (att[cur * n % p] + i * m) % (p - 1);
    return -1;
}
// find x s.t. b**x % p == n with complexity O(sqrt(N))
// return the smallest
// return -1 if ans doesn't exist

```

7.4 Lucas

```

LL fac[100000] = {1};
LL C(LL a, LL b, LL p) {
    for (int i = 1; i <= p; ++i) fac[i] = fac[i - 1] * i % p;
    LL ans = 1;
    for (; a; a /= p, b /= p) {
        LL A = a % p, B = b % p;
        if (A < B) return 0;
        (ans += fac[A] * powmod(fac[B] * fac[A - B] % p, p - 2, p) % p) %= p;
    }
    return ans;
}

```

7.5 Meissel-Lehmer PI

```

LL PI(LL m);
const int MAXM = 1000, MAXN = 650, UPBD = 1000000;
// 650 ~ PI(cbrt(1e11))
LL pi[UPBD] = {0}, phi[MAXM][MAXN];
vector<LL> primes;
void init() {
    fill(pi + 2, pi + UPBD, 1);
    for (LL p = 2; p < UPBD; ++p)
        if (pi[p]) {
            for (LL N = p * p; N < UPBD; N += p)
                pi[N] = 0;
            primes.push_back(p);
        }
    for (int i = 1; i < UPBD; ++i) pi[i] += pi[i - 1];
    for (int i = 0; i < MAXM; ++i)
        phi[i][0] = i;
    for (int i = 1; i < MAXM; ++i)
        for (int j = 1; j < MAXN; ++j)
            phi[i][j] = phi[i][j - 1] - phi[i / primes[j] - 1][j - 1];
}

LL P_2(LL m, LL n) {
    LL ans = 0;
    for (LL i = n; primes[i] * primes[i] <= m and i < primes.size(); ++i)
        ans += PI(m / primes[i]) - i;
    return ans;
}

LL PHI(LL m, LL n) {
    if (m < MAXM and n < MAXN) return phi[m][n];
    if (n == 0) return m;
    LL p = primes[n - 1];
    if (m < UPBD) {
        if (m <= p) return 1;
        if (m <= p * p * p) return pi[m] - n + 1 + P_2(m, n);
    }
    return PHI(m, n - 1) - PHI(m / p, n - 1);
}

LL PI(LL m) {
    if (m < UPBD) return pi[m];
    LL y = cbrt(m) + 10, n = pi[y];
    return PHI(m, n) + n - 1 - P_2(m, n);
}

```

```
|}
```

7.6 Miller Rabin with Pollard rho

```
// Miller_Rabin
LL abs(LL a) {return a > 0? a: -a;}
bool witness(LL a, LL n, LL u, int t) {
    LL x = modpow(a, u, n), nx;
    for (int i = 0; i < t; ++i, x = nx){
        nx = mul(x, x, n);
        if (nx == 1 and x != 1 and x != n - 1) return 1;
    }
    return x != 1;
}
const LL wits[7] = {2, 325, 9375, 28178, 450775,
    9780504, 1795265022};
bool miller_rabin(LL n, int s = 7) {
    if (n < 2) return 0;
    if (n & 1 ^ 1) return n == 2;
    LL u = n - 1, t = 0, a; // n == (u << t) + 1
    while (u & 1 ^ 1) u >>= 1, ++t;
    while (s--){
        if (a = wits[s] % n and witness(a, n, u, t)) return
            0;
        return 1;
    }
}
// Pollard_rho
LL f(LL x, LL n) {
    return mul(x, x, n) + 1;
}
LL pollard_rho(LL n) {
    if (n & 1 ^ 1) return 2;
    while (true) {
        LL x = rand() % (n - 1) + 1, y = 2, d = 1;
        for (int sz = 2; d == 1; y = x, sz <= 1)
            for (int i = 0; i < sz and d == 1; ++i)
                x = f(x, n), d = __gcd(abs(x - y), n);
        if (d and n - d) return d;
    }
}
}
```

7.7 Primitive Root

```
vector<LL> factor(LL N) {
    vector<LL> ans;
    for (LL p = 2, n = N; p * p <= n; ++p)
        if (N % p == 0) {
            ans.push_back(p);
            while (N % p == 0) N /= p;
        }
    if (N != 1) ans.push_back(N);
    return ans;
}
LL find_root(LL p) {
    LL ans = 1;
    for (auto q: factor(p - 1)) {
        LL a = rand() % (p - 1) + 1, b = (p - 1) / q;
        while (powmod(a, b, p) == 1) a = rand() % (p - 1) +
            1;
        while (b % q == 0) b /= q;
        ans = mul(ans, powmod(a, b, p), p);
    }
    return ans;
}
bool is_root(LL a, LL p) {
    for (auto q: factor(p - 1))
        if (powmod(a, (p - 1) / q, p) == 1)
            return false;
    return true;
}
}
```

8 String

8.1 AC automaton

```
// SIGMA[0] will not be considered
const string SIGMA = "
    _0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz";
vector<int> INV_SIGMA;
const int SGSZ = 63;

struct PMA {
    PMA *next[SGSZ]; // next[0] is for fail
    vector<int> ac;
    PMA *last; // state of longest accepted string that
                // is pre of this
    PMA() : last(nullptr) { fill(next, next + SGSZ,
        nullptr); }
};

template<typename T>
PMA *buildPMA(const vector<T> &p) {
    PMA *root = new PMA;
    for (int i = 0; i < p.size(); ++i) { // make trie
        PMA *t = root;
        for (int j = 0; j < p[i].size(); ++j) {
            int c = INV_SIGMA[p[i][j]];
            if (t->next[c] == nullptr) t->next[c] = new PMA;
            t = t->next[c];
        }
        t->ac.push_back(i);
    }
    queue<PMA *> que; // make failure link using bfs
    for (int c = 1; c < SGSZ; ++c) {
        if (root->next[c]) {
            root->next[c]->next[0] = root;
            que.push(root->next[c]);
        } else root->next[c] = root;
    }
    while (!que.empty()) {
        PMA *t = que.front();
        que.pop();
        for (int c = 1; c < SGSZ; ++c) {
            if (t->next[c]) {
                que.push(t->next[c]);
                PMA *r = t->next[0];
                while (!r->next[c]) r = r->next[0];
                t->next[c]->next[0] = r->next[c];
                t->next[c]->last = r->next[c]->ac.size() ? r->
                    next[c] : r->next[c]->last;
            }
        }
    }
    return root;
}

void destructPMA(PMA *root) {
    queue<PMA *> que;
    que.emplace(root);
    while (!que.empty()) {
        PMA *t = que.front();
        que.pop();
        for (int c = 1; c < SGSZ; ++c) {
            if (t->next[c] && t->next[c] != root) que.emplace
                (t->next[c]);
        }
        delete t;
    }
}

template<typename T>
map<int, int> match(const T &t, PMA *v) {
    map<int, int> res;
    for (int i = 0; i < t.size(); ++i) {
        int c = INV_SIGMA[t[i]];
        while (!v->next[c]) v = v->next[0];
        v = v->next[c];
        for (int j = 0; j < v->ac.size(); ++j) ++res[v->ac[
            j]];
        for (PMA *q = v->last; q; q = q->last) {
            for (int j = 0; j < q->ac.size(); ++j) ++res[q->
                ac[j]];
        }
    }
    return res;
}
}
```


8.2 Gusfield

```
template<typename T>
vector<int> gusfield(const T &s) {
    vector<int> z(s.size(), s.size()); // z[i] := max k
        for z[0, k) = z[i, i + k)
    for (int i = 1, L = 0, R = 0; i < s.size(); ++i) {
        if (R < i) {
            L = R = i;
            while (R < s.size() && s[R] == s[R - L]) ++R;
            z[i] = R - L;
            --R;
        } else {
            int k = i - L;
            if (z[k] < R - i + 1) {
                z[i] = z[k];
            } else {
                L = i;
                while (R < s.size() && s[R] == s[R - L]) ++R;
                z[i] = R - L;
                --R;
            }
        }
    }
    return z;
}
```

8.3 KMP

```
template<typename T>
vector<int> build_kmp(const T &s) {
    vector<int> f(s.size());
    int fp = f[0] = -1;
    for (int i = 1; i < s.size(); ++i) {
        while (~fp && s[fp + 1] != s[i]) fp = f[fp];
        if (s[fp + 1] == s[i]) ++fp;
        f[i] = fp;
    }
    return f;
}
```

8.4 Manacher

```
template<typename T, int INF>
vector<int> manacher(const T &s) { // p = "INF" + s.
    join("INF") + "INF", returns radius on p
    vector<int> p(s.size() * 2 + 1, INF);
    for (int i = 0; i < s.size(); ++i) {
        p[i << 1 | 1] = s[i];
    }
    vector<int> w(p.size());
    for (int i = 1, j = 0, r = 0; i < p.size(); ++i) {
        int t = min(r >= i ? w[2 * j - i] : 0, r - i + 1);
        for (; i - t >= 0 && i + t < p.size(); ++t) {
            if (p[i - t] != p[i + t]) break;
        }
        w[i] = --t;
        if (i + t > r) r = i + t, j = i;
    }
    return w;
}
```

8.5 Suffix Array

```
// -----O(NlgNlgN)-----
vector<int> sa_db(const string &s) {
    int n = s.size();
    vector<int> sa(n), r(n), t(n);
    for (int i = 0; i < n; ++i) r[sa[i] = i] = s[i];
    for (int h = 1; t[n - 1] != n - 1; h *= 2) {
        auto cmp = [&](int i, int j) {
            if (r[i] != r[j]) return r[i] < r[j];
            return i + h < n && j + h < n ? r[i + h] < r[j + h] : i > j;
        };
    }
};
```

```
sort(sa.begin(), sa.end(), cmp);
for (int i = 0; i + 1 < n; ++i) t[i + 1] = t[i] +
    cmp(sa[i], sa[i + 1]);
for (int i = 0; i < n; ++i) r[sa[i]] = t[i];
}
return sa;
}
```

// O(N) -- CF: 1e6->31ms,18MB;1e7->296ms;158MB;3e7->856ms,471MB

```
bool is_lms(const string &t, int i) {
    return i > 0 && t[i - 1] == 'L' && t[i] == 'S';
}
```

```
template<typename T>
vector<int> induced_sort(const T &s, const string &t,
    const vector<int> &lmss, int sigma = 256) {
    vector<int> sa(s.size(), -1);
```

```
    vector<int> bin(sigma + 1);
    for (auto it = s.begin(); it != s.end(); ++it) {
        ++bin[*it + 1];
    }
```

```
    int sum = 0;
    for (int i = 0; i < bin.size(); ++i) {
        sum += bin[i];
        bin[i] = sum;
    }
```

```
    vector<int> cnt(sigma);
    for (auto it = lmss.rbegin(); it != lmss.rend(); ++it) {
        int ch = s[*it];
        sa[bin[ch + 1] - 1 - cnt[ch]] = *it;
        ++cnt[ch];
    }
```

```
    cnt = vector<int>(sigma);
    for (auto it = sa.begin(); it != sa.end(); ++it) {
        if (*it <= 0 || t[*it - 1] == 'S') continue;
        int ch = s[*it - 1];
        sa[bin[ch] + cnt[ch]] = *it - 1;
        ++cnt[ch];
    }
```

```
    cnt = vector<int>(sigma);
    for (auto it = sa.rbegin(); it != sa.rend(); ++it) {
        if (*it <= 0 || t[*it - 1] == 'L') continue;
        int ch = s[*it - 1];
        sa[bin[ch + 1] - 1 - cnt[ch]] = *it - 1;
        ++cnt[ch];
    }
    return sa;
}
```

```
template<typename T>
vector<int> sa_is(const T &s, int sigma = 256) {
    string t(s.size(), 0);
    t[s.size() - 1] = 'S';
    for (int i = int(s.size()) - 2; i >= 0; --i) {
        if (s[i] < s[i + 1]) t[i] = 'S';
        else if (s[i] > s[i + 1]) t[i] = 'L';
        else t[i] = t[i + 1];
    }
}
```

```
vector<int> lmss;
for (int i = 0; i < s.size(); ++i) {
    if (is_lms(t, i)) {
        lmss.emplace_back(i);
    }
}
```

```
vector<int> sa = induced_sort(s, t, lmss, sigma);
vector<int> sa_lmss;
for (int i = 0; i < sa.size(); ++i) {
    if (is_lms(t, sa[i])) {
        sa_lmss.emplace_back(sa[i]);
    }
}
```



```

int lmp_ctr = 0;
vector<int> lmp(s.size(), -1);
lmp[sa_lms[0]] = lmp_ctr;
for (int i = 0; i + 1 < sa_lms.size(); ++i) {
    int diff = 0;
    for (int d = 0; d < sa.size(); ++d) {
        if (s[sa_lms[i] + d] != s[sa_lms[i + 1] + d] ||
            is_lms(t, sa_lms[i] + d) != is_lms(t, sa_lms[i + 1] + d)) {
            diff = 1; // something different in range of lms
            break;
        } else if (d > 0 && is_lms(t, sa_lms[i] + d) &&
                    is_lms(t, sa_lms[i + 1] + d)) {
            break; // exactly the same
        }
    }
    if (diff) ++lmp_ctr;
    lmp[sa_lms[i + 1]] = lmp_ctr;
}

vector<int> lmp_compact;
for (int i = 0; i < lmp.size(); ++i) {
    if (~lmp[i]) {
        lmp_compact.emplace_back(lmp[i]);
    }
}

if (lmp_ctr + 1 < lmp_compact.size()) {
    sa_lms = sa_is(lmp_compact, lmp_ctr + 1);
} else {
    for (int i = 0; i < lmp_compact.size(); ++i) {
        sa_lms[lmp_compact[i]] = i;
    }
}

vector<int> seed;
for (int i = 0; i < sa_lms.size(); ++i) {
    seed.emplace_back(lmss[sa_lms[i]]);
}

return induced_sort(s, t, seed, sigma);
} // s must end in char(0)

// O(N) lcp, note that s must end in '\0'
vector<int> build_lcp(const string &s, const vector<int>
    &sa, const vector<int> &rank) {
    int n = s.size();
    vector<int> lcp(n);
    for (int i = 0, h = 0; i < n; ++i) {
        if (rank[i] == 0) continue;
        int j = sa[rank[i] - 1];
        if (h > 0) --h;
        for (; j + h < n && i + h < n; ++h) {
            if (s[j + h] != s[i + h]) break;
        }
        lcp[rank[i] - 1] = h;
    }
    return lcp; // lcp[i] := lcp(s[sa[i]...-1], s[sa[i + 1]...-1])
}

// O(N) build segment tree for lcp
vector<int> build_lcp_rmqs(const vector<int> &lcp) {
    vector<int> sgt(lcp.size() << 2);
    function<void(int, int, int)> build = [&](int t, int
        lb, int rb) {
        if (rb - lb == 1) return sgt[t] = lcp[lb], void();
        int mb = lb + rb >> 1;
        build(t << 1, lb, mb);
        build(t << 1 | 1, mb, rb);
        sgt[t] = min(sgt[t << 1], sgt[t << 1 | 1]);
    };
    build(1, 0, lcp.size());
    return sgt;
}

// O(|P| + lg |T|) pattern searching, returns last
index in sa
int match(const string &p, const string &s, const
    vector<int> &sa, const vector<int> &rmq) { // rmq
    is segtree on lcp

```

```

int t = 1, lb = 0, rb = s.size(); // answer in [lb,
    rb)
int lcplp = 0; // lcp(char(0), p) = 0
while (rb - lb > 1) {
    int mb = lb + rb >> 1;
    int lcplm = rmq[t << 1];
    if (lcplp < lcplm) t = t << 1 | 1, lb = mb;
    else if (lcplp > lcplm) t = t << 1, rb = mb;
    else {
        int lcpmp = lcplp;
        while (lcpmp < p.size() && p[lcpmp] == s[sa[mb] +
            lcpmp]) ++lcpmp;
        if (lcpmp == p.size() || p[lcpmp] > s[sa[mb] +
            lcpmp]) t = t << 1 | 1, lb = mb, lcplp =
            lcpmp;
        else t = t << 1, rb = mb;
    }
}
if (lcplp < p.size()) return -1;
return sa[lb];
}

```

8.6 Suffix Automaton

```

template<typename T>
struct SuffixAutomaton {
    vector<map<int, int>> edges; // edges[i] : the
        labeled edges from node i
    vector<int> link; // link[i] : the parent
        of i
    vector<int> length; // length[i] : the length
        of the longest string in the ith class
    int last; // the index of the
        equivalence class of the whole string
    vector<bool> is_terminal; // is_terminal[i] : some
        suffix ends in node i (unnecessary)
    vector<int> occ; // occ[i] : number of
        matches of maximum string of node i (unnecessary)
    SuffixAutomaton(const T &s) : edges({map<int, int>()
        }), link({-1}), length({0}), last(0), occ({0}) {
        for (int i = 0; i < s.size(); ++i) {
            edges.push_back(map<int, int>());
            length.push_back(i + 1);
            link.push_back(0);
            occ.push_back(1);
            int r = edges.size() - 1;
            int p = last; // add edges to r and find p with
                link to q
            while (p >= 0 && edges[p].find(s[i]) == edges[p].
                end()) {
                edges[p][s[i]] = r;
                p = link[p];
            }
            if (~p) {
                int q = edges[p][s[i]];
                if (length[p] + 1 == length[q]) { // no need to
                    split q
                    link[r] = q;
                } else { // split q, add qq
                    edges.push_back(edges[q]); // copy edges of
                        q
                    length.push_back(length[p] + 1);
                    link.push_back(link[q]); // copy parent of q
                    occ.push_back(0);
                    int qq = edges.size() - 1; // qq is new
                        parent of q and r
                    link[q] = qq;
                    link[r] = qq;
                    while (p >= 0 && edges[p][s[i]] == q) { //
                        what points to q points to qq
                        edges[p][s[i]] = qq;
                        p = link[p];
                    }
                }
            }
            last = r;
        }
        // below unnecessary
    }
    is_terminal = vector<bool>(edges.size());
    for (int p = last; p > 0; p = link[p]) is_terminal[
        p] = 1; // is_terminal calculated

```

```

vector<int> cnt(link.size()), states(link.size());
// sorted states by length
for (int i = 0; i < link.size(); ++i) ++cnt[length[i]];
for (int i = 0; i < s.size(); ++i) cnt[i + 1] += cnt[i];
for (int i = link.size() - 1; i >= 0; --i) states[--cnt[length[i]]] = i;
for (int i = link.size() - 1; i >= 1; --i) occ[link[states[i]]] += occ[states[i]]; // occ calculated
}
};

```

9 Formulas

9.0.1 Pick's theorem

Pick's theorem provides a simple formula for calculating the area A of this polygon in terms of the number i of lattice points in the interior located in the polygon and the number b of lattice points on the boundary placed on the polygon's perimeter:

$$A = i + \frac{b}{2} - 1$$

9.0.2 Graph Properties

- Euler's Formula $V - E + F = 2$
- For a planar graph, $F = E - V + n + 1$, n is the numbers of components
- For a planar graph, $E \leq 3V - 6$ For a connected graph G , let $I(G)$ be the size of maximum independent set, $M(G)$ be the size of maximum matching, $Cv(G)$ be the size of minimum vertex cover, $Ce(G)$ be the size of minimum edge cover.
- For any connected graph:

- $I(G) + Cv(G) = |V|$
- $M(G) + Ce(G) = |V|$

- For any bipartite:

- $I(G) = Cv(G)$
- $M(G) = Ce(G)$

```

double l=0, r=m, stop=1.0/n/n;
while(r-l>=stop){
    double mid;
    if((n*m-sol.maxFlow(s,t))/2>eps)l=mid;
    else r=mid;
}
build(l);
sol.maxFlow(s,t);
vector<int> ans;
for(int i=1;i<=n;++i)
    if(sol.vis[i])ans.push_back(i);

```

9.0.3 Number Theory

- $\sum_{d|n} \phi(n) = n$
- $\sum_{d|n} \mu(n) = [n = 1]$
- $g(m) = \sum_{d|m} f(d) \Leftrightarrow f(m) = \sum_{d|m} \mu(d) \times g(m/d)$
- $\phi(x), \mu(x)$ are Möbius inverse
- $\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum \mu(d) \lfloor \frac{n}{d} \rfloor \lfloor \frac{n}{d} \rfloor$
- $\sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = n \sum_{d|n} d \times \phi(d)$

9.0.4 Combinatorics

- Harmonic series $H_n = \ln(n) + \gamma + 1/(2n) - 1/(12n^2) + 1/(120n^4)$
- $\gamma = 0.57721566490153286060651209008240243104215$
- Gray Code: $= n \oplus (n > 1)$
- Catalan Number: $\frac{C_n^{kn}}{n(k-1)+1}, C_m^n = \frac{n!}{m!(n-m)!}$
- $\gamma(n+1) = n!$
- $H(n, m) \cong x_1 + x_2 \dots + x_n = k, num = C_k^{n+k-1}$
- Stirling number of 2^{nd} kind: n 人分 k 組方法數目

- $S(0, 0) = S(n, n) = 1$
- $S(n, 0) = 0$
- $S(n, k) = kS(n-1, k) + S(n-1, k-1)$

- Bell number, n 人分任意多組方法數目

- $B_0 = 1$
- $B_n = \sum_{i=0}^n S(n, i)$

- $B_{n+1} = \sum_{k=0}^n C_k^n B_k$
- $B_{p+n} \equiv B_n + B_{n+1} \pmod{p}$, p is prime
- $B_{p^m+n} \equiv mB_n + B_{n+1} \pmod{p}$, p is prime
- From $B_0 : 1, 1, 2, 5, 15, 52,$
203, 877, 4140, 21147, 115975

- Derangement, 錯排, 國人在自己位置上

- $D_n = n!(1 - \frac{1}{1} + \frac{1}{2!} - \frac{1}{3!} \dots + (-1)^n \frac{1}{n!})$
- $D_n = (n-1)(D_{n-1} + D_{n-2}), D_0 = 1, D_1 = 0$
- From $D_0 : 1, 0, 1, 2, 9, 44,$
265, 1854, 14833, 133496

- Binomial Equality

- $\sum_k \binom{r}{m+k} \binom{s}{n-k} = \binom{r+s}{m+n}$
- $\sum_k \binom{l}{m+k} \binom{s}{n+k} = \binom{l+s}{l-m+n}$
- $\sum_k \binom{l}{m+k} \binom{s+k}{n} (-1)^k = (-1)^{l+m} \binom{s-m}{n-l}$
- $\sum_{k \leq l} \binom{l-k}{m} \binom{s}{n-k} (-1)^k = (-1)^{l+m} \binom{s-m-1}{l-n-m}$
- $\sum_{0 \leq k \leq l} \binom{l-k}{m} \binom{q+k}{n} = \binom{l+q+1}{m+n+1}$
- $\binom{r}{k} = (-1)^k \binom{k-r-1}{k}$
- $\binom{r}{m} \binom{m}{k} = \binom{r}{k} \binom{r-k}{m-k}$
- $\sum_{k \leq n} \binom{r+k}{n} = \binom{r+n+1}{n}$
- $\sum_{0 \leq k \leq n} \binom{k}{m} = \binom{n+1}{m+1}$
- $\sum_{k \leq m} \binom{m+r}{k} x^k y^{m-k} = \sum_{k \leq m} \binom{-r}{k} (-x)^k (x+y)^{m-k}$

9.0.5 國次, 國次和

- $a^b \% P = a^{b \% \varphi(P) + \varphi(P)} \pmod{P}, b \geq \varphi(P)$
- $1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^4}{4} + \frac{n^3}{2} + \frac{n^2}{4}$
- $1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n^5}{5} + \frac{n^4}{2} + \frac{n^3}{3} - \frac{n}{30}$
- $1^5 + 2^5 + 3^5 + \dots + n^5 = \frac{n^6}{6} + \frac{n^5}{2} + \frac{5n^4}{12} - \frac{n^2}{12}$
- $0^k + 1^k + 2^k + \dots + n^k = P(k), P(k) = \frac{(n+1)^{k+1} - \sum_{i=0}^{k-1} C_i^{k+1} P(i)}{k+1}, P(0) = n+1$
- $\sum_{k=0}^{m-1} k^n = \frac{1}{n+1} \sum_{k=0}^n C_k^{n+1} B_k m^{n+1-k}$
- $\sum_{j=0}^m C_j^{m+1} B_j = 0, B_0 = 1$
- 除了 $B_1 = -1/2$, 剩下的奇數項都是 0
- $B_2 = 1/6, B_4 = -1/30, B_6 = 1/42, B_8 = -1/30, B_{10} = 5/66, B_{12} = -691/2730, B_{14} = 7/6, B_{16} = -3617/510, B_{18} = 43867/798, B_{20} = -174611/330,$

9.0.6 Burnside's lemma

- $|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$
- $X^g = t^{c(g)}$
- G 表示有幾種轉法, X^g 表示在那種轉法下, 有幾種是會保持對稱的, t 是國色數, $c(g)$ 是循環節不動的面數。
- 正立方體塗三國色, 轉 0 有 3^6 個元素不變, 轉 90 有 6 種, 每種有 3^3 不變, 180 有 3×3^4 , 120(角) 有 8×3^2 , 180(邊) 有 6×3^3 , 全部 $\frac{1}{24} (3^6 + 6 \times 3^3 + 3 \times 3^4 + 8 \times 3^2 + 6 \times 3^3) = 57$

9.0.7 Count on a tree

- Rooted tree: $s_{n+1} = \frac{1}{n} \sum_{i=1}^n (i \times a_i \times \sum_{j=1}^{\lfloor n/i \rfloor} a_{n+1-i \times j})$
- Unrooted tree:

- Odd: $a_n - \sum_{i=1}^{n/2} a_i a_{n-i}$
- Even: $Odd + \frac{1}{2} a_{n/2} (a_{n/2} + 1)$

- Spanning Tree

- 完全圖 $n^n - 2$
- 一般圖 (Kirchhoff's theorem) $M[i][i] = \text{degree}(V_i), M[i][j] = -1, \text{if have } E(i, j), 0 \text{ if no edge. delete any one row and col in } A, \text{ans} = \det(A)$