

Relational Database Design by ER- and EER-to-Relational Mapping


Part 1

Relational Database Design by ER-to-Relational Mapping

ER-to-Relational Mapping Algorithm

- **Step 1: Mapping of Regular Entity Types.**

- For each regular (strong) entity type E in the ER schema, create a relation R that includes all the simple attributes of E . Include only the simple component attributes of a composite attribute. Choose one of the key attributes of E as the primary key for R . If the chosen key of E is a composite, then the set of simple attributes that form it will together form the primary key of R .
- If multiple keys were identified for E during the conceptual design the information describing the attributes that form each additional key is kept in order to specify secondary (unique) keys of relation R . Knowledge about keys is also kept for indexing purposes and other types of analyses.



EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary
-------	-------	-------	------------	-------	---------	-----	--------

DEPARTMENT


Dname	<u>Dnumber</u>
-------	----------------

PROJECT

Pname	<u>Pnumber</u>	Plocation
-------	----------------	-----------

- **Step 2: Mapping of Weak Entity Types.**

- For each weak entity type W in the ER schema with owner entity type E , create a relation R and include all simple attributes (or simple components of composite attributes) of W as attributes of R . In addition, include as foreign key attributes of R , the primary key attribute(s) of the relation(s) that correspond to the owner entity type(s); this takes care of mapping the identifying relationship type of W . The primary key of R is the combination of the primary key(s) of the owner(s) and the partial key of the weak entity type W , if any.
- If there is a weak entity type E_2 whose owner is also a weak entity type E_1 , then E_1 should be mapped before E_2 to determine its primary key first.



DEPENDENT


<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

- **Step 3: Mapping of Binary 1:1 Relationship Types.**
 - For each binary 1 : 1 relationship type R in the ER schema, identify the relations S and T that correspond to the entity types participating in R . There are three possible approaches: (1) the foreign key approach, (2) the merged relationship approach, and (3) the cross-reference or relationship relation approach. The first approach is the most useful and should be followed unless special conditions exist.

1. **Foreign key approach:** Choose one of the relations— S , say—and include as a foreign key in S the primary key of T . It is better to choose an entity type with *total participation* in R in the role of S . Include all the simple attributes (or simple components of composite attributes) of the $1 : 1$ relationship type R as attributes of S .

2. **Merged relation approach:** An alternative mapping of a 1 : 1 relationship type is to merge the two entity types and the relationship into a single relation. This is possible when *both participations are total*, as this would indicate that the two tables will have the exact same number of tuples at all times.

3. **Cross-reference or relationship relation approach:** The third option is to set up a third relation R for the purpose of cross-referencing the primary keys of the two relations S and T representing the entity types. The relation R is called a **relationship relation** (or sometimes a **lookup table**), because each tuple in R represents a relationship instance that relates one tuple from S with one tuple from T . The relation R will include the primary key attributes of S and T as foreign keys to S and T . The primary key of R will be one of the two foreign keys, and the other foreign key will be a unique key of R . The drawback is having an extra relation, and requiring an extra join operation when combining related tuples from the tables.




DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

- **Step 4: Mapping of Binary 1:N Relationship Types.** For each regular binary $1 : N$ relationship type R , identify the relation S that represents the participating entity type at the *N-side* of the relationship type. Include as foreign key in S the primary key of the relation T that represents the other entity type participating in R ; we do this because each entity instance on the N-side is related to at most one entity instance on the 1-side of the relationship type. Include any simple attributes (or simple components of composite attributes) of the $1 : N$ relationship type as attributes of S .

- An alternative approach is to use the **relationship relation** (cross-reference) option as in the third option for binary $1 : 1$ relationships. We create a separate relation R whose attributes are the primary keys of S and T , which will also be foreign keys to S and T . The primary key of R is the same as the primary key of S . This option can be used if few tuples in S participate in the relationship to avoid excessive NULL values in the foreign key.



EMPLOYEE


Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

- **Step 5: Mapping of Binary M:N Relationship Types.** For each binary $M:N$ relationship type R , create a new relation S to represent R . Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types; their *combination* will form the primary key of S . Also include any simple attributes of the $M:N$ relationship type (or simple components of composite attributes) as attributes of S .

- The propagate (CASCADE) option for the referential triggered action should be specified on the foreign keys in the relation corresponding to the relationship R , since each relationship instance has an existence dependency on each of the entities it relates. This can be used for both ON UPDATE and ON DELETE.




WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

- **Step 6: Mapping of Multivalued Attributes.** For each multivalued attribute A , create a new relation R . This relation R will include an attribute corresponding to A , plus the primary key attribute K —as a foreign key in R —of the relation that represents the entity type or relationship type that has A as a multivalued attribute. The primary key of R is the combination of A and K . If the multivalued attribute is composite, we include its simple components.

- The propagate (CASCADE) option for the referential triggered action should be specified on the foreign key in the relation R corresponding to the multivalued attribute for both ON UPDATE and ON DELETE. We should also note that the key of R when mapping a composite, multivalued attribute requires some analysis of the meaning of the component attributes. In some cases, when a multivalued attribute is composite, only some of the component attributes are required to be part of the key of R ; these attributes are similar to a partial key of a weak entity type that corresponds to the multivalued attribute.



DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

- **Step 7: Mapping of N-ary Relationship Types.** For each n -ary relationship type R , where $n > 2$, create a new relation S to represent R . Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types. Also include any simple attributes of the n -ary relationship type (or simple components of composite attributes) as attributes of S . The primary key of S is usually a combination of all the foreign keys that reference the relations representing the participating entity types. However, if the cardinality constraints on any of the entity types E participating in R is 1, then the primary key of S should not include the foreign key attribute that references the relation E' corresponding to E .

