

Machine Learning







4105931


Assignment 1 – Scene Recognition

Dataset Details

- Goal
 - Classify image data of natural scenes around the world
- Task
 - image classification (6 classes)
- Training / Testing
 - around 14k / 3k
- Reference
 - <https://www.kaggle.com/puneet6060/intel-image-classification>

Intel Image Classification - Image Scene Classification of Multiclass

 buildings	2019/1/29 下午 0...	檔案資料夾
 forest	2019/1/29 下午 0...	檔案資料夾
 glacier	2019/1/29 下午 0...	檔案資料夾
 mountain	2019/1/29 下午 0...	檔案資料夾
 sea	2019/1/29 下午 0...	檔案資料夾
 street	2019/1/29 下午 0...	檔案資料夾



範例程式簡介

- models.py
 - VGG16模型架構
- dataset.py
 - Dataset 讀取方式/方法
- train.py
 - 訓練模型架構之程式
- test.py
 - 測試訓練完模型架構之程式

參數調整- train.py

1. Reproducibility – 初始權重產生

- torch.manual_seed()

```
12  ##REPRODUCIBILITY
13  torch.manual_seed(0)
14  torch.backends.cudnn.deterministic = True
15  torch.backends.cudnn.benchmark = False
```

2. Batch size

- 批次訓練資料量大小
- 1~128 (1, 20, 50...)

```
29  train_set = IMAGE_Dataset(Path(DATASET_ROOT), data_transform)
30  data_loader = DataLoader(dataset=train_set, batch_size=32, shuffle=True,
31  #print(train_set.num_classes)
```

3. Epoch

- 訓練次數 (1, 20, 50...)

4. Optimizer(SGD, Adam,...等等) ref: <https://pytorch.org/docs/stable/optim.html>

5. Learning rate 調整

- 0 ~ 1
- 建議從0.1開始往下試

```
34  best_model_params = copy.deepcopy(model.state_dict())
35  best_acc = 0.0
36  num_epochs = 50
37  criterion = nn.CrossEntropyLoss()
38  optimizer = torch.optim.SGD(params=model.parameters(), lr=0.001, momentum=0.9)
39
```

執行步驟

1. 設定參數
2. 執行 train.py (執行完畢後會有自動儲存最佳model .pth檔)
3. 在test.py 修改model path

```
9  CUDA_DEVICES = 0
10 DATASET_ROOT = './seg_train'
11 PATH_TO_WEIGHTS = './model-0.90-best_train_acc.pth'
```

4. 執行 test.py

實驗結果觀察

- train.py 執行結果

```
Epoch: 1/50
-----
Training loss: 1.2757    accuracy: 0.4823

Epoch: 2/50
-----
Training loss: 0.9526    accuracy: 0.6219

Epoch: 3/50
-----
Training loss: 0.8242    accuracy: 0.6789

Epoch: 4/50
-----
Training loss: 0.7252    accuracy: 0.7258

Epoch: 5/50
-----
□
```

- test.py 執行結果



```
Accuracy on the ALL test images: 90 %
Accuracy of buildings : 82 %
Accuracy of forest : 98 %
Accuracy of glacier : 80 %
Accuracy of mountain : 89 %
Accuracy of sea : 95 %
Accuracy of street : 95 %
```

作業要求

- 訓練過程之 traing loss,acc 曲線圖

- 測試結果之截圖

```
Accuracy on the ALL test images: 90 %  
Accuracy of buildings : 82 %  
Accuracy of forest : 98 %  
Accuracy of glacier : 80 %  
Accuracy of mountain : 89 %  
Accuracy of sea : 95 %  
Accuracy of street : 95 %
```



作業要求

- 架設PyTorch、Python執行環境
- 利用範例程式、Dataset與下面參數設定方式，完成兩次分類結果
 - 使用一組給定參數值：
 - `seed = 123, epochs = 50, batch_size=32, SGD, lr = 0.01`
 - 調整參數設定，使分類結果高於給定參數結果
- 兩次訓練過程，分別產生下列兩張結果圖 (Matlab繪圖)
 - Training Accuracy(每一個epoch的訓練結果) + Testing Accuracy (每十個epoch跑一次測試)
 - Training Loss
- 最終最佳的測試結果準確率與執行截圖

Assignment #1 – Scene Classification

- You need to hand in your source code and report
- The report should cover:
 - Method description – What is your strategy for parameter selection?
 - Experimental results
 - Two figures of accuracy and loss curves
 - Testing accuracy
 - Discussion
 - Problem and difficulties
- Upload assignment #1 **before 3/27 11:59 pm (Wed)**
- File format – zip all your files into a single file:
studentID_hw1_version, ex: 602410143_hw1_v1

Assignment Rules

- **Late policy**

- You will get 20% deduction of your scores per day.
- It means if the assignment is delayed one day for 80%, two days for 60%,..., five days for 0% .

- **No-copy policy**

- Copying is strictly forbidden in our class.
- Once the assignment is confirmed by TA as COPY, the score will be 0%.