



Power Function in C/C++

Given two numbers base and exponent, the C++ or C **pow()** function finds x raised to the power of y i.e. x^y . Basically in C/C++, the exponent value is calculated using the `pow()` function. The **pow()** function is used to calculate the power of a number in C/C++. It takes double as input and returns double as output.

We have to use **#include <math.h>** in C/C++ to use that `pow()` function in our C/C++ program.

Syntax of pow() Function

```
double pow (double x, double y);
```

pow() Function Parameters

This method takes only two arguments:

- **x**: floating point base value
- **y**: floating point power value

pow() Function Return Value

- The power function returns the floating point value of x raised to the power y (x^y).

Example of pow() Function

```
Input: 2.0, 5.0
```

```
Output: 32.00
```

```
Explanation: pow(2.0, 5.0) executes 2.0 raised to the power 5.0, which equals 32
```

```
Input: 5.0, 2.0
```

```
Output: 25.00
```

C

```
// C program to illustrate
// power function
#include <math.h>
#include <stdio.h>

int main()
{
    double x = 6.1, y = 4.8;

    // Storing the answer in result.
```

[C++ Data Types](#) [C++ Input/Output](#) [C++ Arrays](#) [C++ Pointers](#) [C++ OOPs](#) [C++ STL](#) [C++ Interview Questions](#)

```
    return 0;
}
```

C++

```
// C++ program to illustrate
// power function
#include <bits/stdc++.h>
using namespace std;

int main()
{
    double x = 6.1, y = 4.8;

    // Storing the answer in result.
    double result = pow(x, y);

    // printing the result upto 2
    // decimal place
    cout << fixed << setprecision(2) << result << endl;

    return 0;
}
```

Output

5882.79

Time Complexity: $O(\log(n))$

Auxiliary Space: $O(1)$

Working of pow() Function with Integers

The pow() function takes 'double' as the argument and returns a 'double' value. This function does not always work for integers. One such example is pow(5, 2). When assigned to an integer, it outputs 24 on some compilers and works fine for some other compilers. But pow(5, 2) without any assignment to an integer outputs 25.

One another way can be using the **round** function to assign it to some integer type.

- This is because 5^2 (i.e. 25) might be stored as 24.9999999 or 25.0000000001 because the return type is double. When assigned to int, 25.0000000001 becomes 25 but 24.9999999 will give output 24.
- To overcome this and output the accurate answer in integer format, we can add $1e-9$ or 0.000000001 to the result and typecast it to **int** e.g (int)(pow(5, 2)+1e-9) will give the correct answer(25, in the above example), irrespective of the compiler.

Example 1: C/C++ Program to demonstrate the behavior of the pow() function with integers.

C++

```
// C++ program to illustrate
// working with integers in
// power function
#include <bits/stdc++.h>
using namespace std;
int main()
{
    int a, b;
```

```
// Using typecasting for
// integer result
a = (int)(pow(5, 2) + 0.5);
b = round(pow(5,2));
cout << a << endl << b ;

return 0;
}
```

C

```
// C program to illustrate
// working with integers in
// power function
#include <math.h>
#include <stdio.h>

int main()
{
    int a, b;

    // Using typecasting for
    // integer result
    a = (int)(pow(5, 2) + 1e-9);
    b = round(pow(5,2));
    printf("%d \n%d", a, b);

    return 0;
}
```

Output

25

25

Time Complexity: $O(\log(n))$

Auxiliary Space: $O(1)$

Here's a complete roadmap for you to become a developer: **Learn DSA -> Master Frontend/Backend/Full Stack -> Build Projects -> Keep Applying to Jobs** And why go anywhere else when our [DSA to Development: Coding Guide](https://www.geeksforgeeks.org/power-function-c-cpp/)

helps you do this in a single program!

Apply now to our [DSA to Development Program](#) and our counsellors will connect with you for further guidance & support.

Last Updated : 31 Oct, 2023

119

Previous

[isgreater\(\) in C/C++](#)

Next

[std::is_sorted in C++](#)

Share your thoughts in the comments

Add Your Comment

Similar Reads

Compute the maximum power with a given condition

Smallest number greater than n that can be represented as a sum of distinct power of k

C++ Program for Pairs such that one is a power multiple of other

C++ Program To Find Power Without Using Multiplication(*) And Division(/) Operators

C++ Program To Calculate the Power of a Number

error: call of overloaded 'function(x)' is ambiguous | Ambiguity in Function overloading in C++

Difference between Virtual function and Pure virtual function in C++

How to call function within function in C or C++

Difference between virtual function and inline function in C++

Difference Between Friend Function and Virtual Function in C++



GeeksforGeeks