

Introduction to Java Swing

Last Updated : 30 Jul, 2024



Swing is a Java Foundation Classes [JFC] library and an extension of the Abstract Window Toolkit [AWT]. Java Swing offers much-improved functionality over AWT, new components, expanded components features, and excellent event handling with drag-and-drop support.

Introduction of Java Swing

Swing has about four times the number of User Interface [UI] components as AWT and is part of the standard Java distribution. By today's application GUI requirements, AWT is a limited implementation, not quite capable of providing the components required for developing complex GUIs required in modern commercial applications. The AWT component set has quite a few bugs and does take up a lot of system resources when compared to equivalent Swing resources. Netscape introduced its Internet Foundation Classes [IFC] library for use with Java. Its Classes became very popular with programmers creating GUI's for commercial applications.

- Swing is a Set of API (API- Set of Classes and Interfaces)
- Swing is Provided to Design Graphical User Interfaces
- Swing is an Extension library to the AWT (Abstract Window Toolkit)
- Includes New and improved Components that have been enhancing the looks and Functionality of GUIs'
- Swing can be used to build (Develop) The Standalone swing GUI Apps as Servlets and Applets
- It Employs model/view design architecture.
- Swing is more portable and more flexible than AWT, the Swing is built on top of the AWT.
- Swing is Entirely written in Java.
- Java Swing Components are Platform-independent, and The Swing Components are lightweight.

- Swing Supports a Pluggable look and feel and Swing provides more powerful components.
- such as tables, lists, Scrollpanes, Colourchooser, tabbed pane, etc.
- Further Swing Follows MVC.

Difference between Java Swing and Java AWT

There are certain points from which Java Swing is different than Java AWT as mentioned below:

Java AWT	Java Swing
Java AWT is an API to develop GUI applications in Java.	Swing is a part of Java Foundation Classes and is used to create various applications.
Components of AWT are heavy weighted.	The components of Java Swing are lightweight.
Components are platform dependent.	Components are platform independent.
Execution Time is more than Swing.	Execution Time is less than AWT.
AWT components require java.awt package.	Swing components requires javax.swing package.

To know more about the topic, refer to [Java Swing vs Java AWT](#).

What is JFC?


JFC stands for Java Foundation Classes. JFC is the set of GUI components that simplify desktop Applications. Many programmers think that JFC and Swing are one and the same thing, but that is not so. JFC contains Swing [A UI component package] and quite a number of other items:

- Cut and paste: Clipboard support.
- Accessibility features: Aimed at developing GUIs for users with disabilities.
- The Desktop Colors Features were first introduced in Java 1.1
- Java 2D: it has Improved colors, images, and text support.

Features Of Swing Class

- Pluggable look and feel.
- Uses MVC architecture.
- Lightweight Components
- Platform Independent
- Advanced features such as JTable, JTabbedPane, JScrollPane, etc.
- Java is a platform-independent language and runs on any client machine, the GUI look and feel, owned and delivered by a platform-specific O/S, simply does not affect an application's GUI constructed using Swing components.
- **Lightweight Components:** Starting with the JDK 1.1, its AWT-supported lightweight component development. For a component to qualify as lightweight, it must not depend on any non-Java [O/s based) system classes. Swing components have their own view supported by Java's look and feel classes.
- **Pluggable Look and Feel:** This feature enable the user to switch the look and feel of Swing components without restarting an application. The Swing library supports components' look and feels that remain the same across all platforms wherever the program runs. The Swing library provides an API that gives real flexibility in determining the look and feel of the GUI of an application
- **Highly customizable** – Swing controls can be customized in a very easy way as visual appearance is independent of internal representation.
- **Rich controls**– Swing provides a rich set of advanced controls like Tree TabbedPane, slider, colorpicker, and table controls.

Swing Classes Hierarchy



The MVC Connection

- In general, a visual component is a composite of **three distinct aspects**:
 1. The way that the component looks when rendered on the screen.
 2. The way such that the component reacts to the user.
 3. The state information associated with the component.
- Over the years, one component architecture has proven itself to be exceptionally effective: – **Model-View-Controller** or **MVC** for short.
- In MVC terminology, the **model** corresponds to the state information associated with the Component.
- The **view** determines how the component is displayed on the screen, including any aspects of the view that are affected by the current state of the model.
- The **controller** determines how the component reacts to the user.

The simplest Swing components have capabilities far beyond AWT components as follows:

- Swing buttons and labels can be displaying images instead of or in addition to text.
- The borders around most Swing components can be changed easily. For example, it is easy to put a 1-pixel border around the outside of a Swing label.
- Swing components do not have to be rectangular. Buttons, for example, can be round.

- Now The Latest Assertive technologies such as screen readers can easily get information from Swing components. Example: A screen reader tool can easily capture the text that is displayed on a Swing button or label.

Example of Java Swing Programs

Example 1: Develop a program using label (swing) to display the message “GFG WEB Site Click”:

Java



```
1 // Java program using label (swing)
2 // to display the message "GFG WEB Site Click"
3 import java.io.*;
4 import javax.swing.*;
5
6 // Main class
7 class GFG {
8
9     // Main driver method
10    public static void main(String[] args)
11    {
12        // Creating instance of JFrame
13        JFrame frame = new JFrame();
14
15        // Creating instance of JButton
16        JButton button = new JButton(" GFG WebSite
17Click");
18
19        // x axis, y axis, width, height
20        button.setBounds(150, 200, 220, 50);
21
22        // adding button in JFrame
23        frame.add(button);
24
25        // 400 width and 500 height
26        frame.setSize(500, 600);
27
28        // using no layout managers
29        frame.setLayout(null);
```

```

30         // making the frame visible
31         frame.setVisible(true);
32     }
33 }

```

Output:



Example 2: Write a program to create three buttons with caption OK, SUBMIT, CANCEL.

Java



```

1  // Java program to create three buttons
2  // with caption OK, SUBMIT, CANCEL
3  import java.awt.*;
4
5  class button {
6      button()
7      {
8          Frame f = new Frame();
9
10         // Button 1 created
11         // OK button
12         Button b1 = new Button("OK");
13         b1.setBounds(100, 50, 50, 50);
14         f.add(b1);
15
16         // Button 2 created
17         // Submit button
18         Button b2 = new Button("SUBMIT");


```

```

19         b2.setBounds(100, 101, 50, 50);
20         f.add(b2);
21
22         // Button 3 created
23         // Cancel button
24         Button b3 = new Button("CANCEL");
25         b3.setBounds(100, 150, 80, 50);
26         f.add(b3);
27
28         f.setSize(500, 500);
29         f.setLayout(null);
30         f.setVisible(true);
31     }
32
33     public static void main(String a[]) { new button();
34 }

```

Output:



Output of Example 2

Example 3: Program to Add Checkbox in the Frame

Java

```

1 // Java Swing Program to Add Checkbox
2 // in the Frame
3 import java.awt.*;
4


```

```

5 // Driver Class
6 class Lan {
7     // Main Function
8     Lan()
9     {
10         // Frame Created
11         Frame f = new Frame();
12
13         Label l1 = new Label("Select known Languages");
14
15         l1.setBounds(100, 50, 120, 80);
16         f.add(l1);
17
18         // CheckBox created
19         Checkbox c2 = new Checkbox("Hindi");
20         c2.setBounds(100, 150, 50, 50);
21         f.add(c2);
22
23         // CheckBox created
24         Checkbox c3 = new Checkbox("English");
25         c3.setBounds(100, 200, 80, 50);
26         f.add(c3);
27
28         // CheckBox created
29         Checkbox c4 = new Checkbox("marathi");
30         c4.setBounds(100, 250, 80, 50);
31         f.add(c4);
32
33         f.setSize(500, 500);
34         f.setLayout(null);
35         f.setVisible(true);
36     }
37
38     public static void main(String ar[]) { new Lan(); }
39 }

```

Output:



Output of Example 3

Components of Swing Class the task's percentage

Class	Description
Component	A Component is the Abstract base class for about the non-menu user-interface controls of Java SWING. Components are representing an object with a graphical representation.
Container	A Container is a component that can container Java SWING Components
JComponent	A JComponent is a base class for all swing UI Components In order to use a swing component that inherits from JComponent, the component must be in a containment hierarchy whose root is a top-level Java Swing container.
JLabel	A JLabel is an object component for placing text in a container.
JButton	This class creates a labeled button.
JColorChooser	A JColorChooser provides a pane of controls designed to allow the user to manipulate and select a color.

Class	Description
JCheckBox	A JCheckBox is a graphical (GUI) component that can be in either an on-(true) or off-(false) state.
JRadioButton	The JRadioButton class is a graphical (GUI) component that can be in either an on-(true) or off-(false) state. in the group
JList	A JList component represents the user with the scrolling list of text items.
JComboBox	A JComboBox component is Presents the User with a show up Menu of choices.
JTextField	A JTextField object is a text component that will allow for the editing of a single line of text.
JPasswordField	A JPasswordField object it is a text component specialized for password entry.
JTextArea	A JTextArea object is a text component that allows for the editing of multiple lines of text.
ImageIcon	A ImageIcon control is an implementation of the Icon interface that paints Icons from Images
JScrollbar	A JScrollbar control represents a scroll bar component in order to enable users to Select from range values.
JOptionPane	JOptionPane provides set of standard dialog boxes that prompt users for a value or Something.
JFileChooser	A JFileChooser it Controls represents a dialog window from which the user can select a file.

Class	Description
JProgressBar	As the task progresses towards completion, the progress bar displays the tasks percentage on its completion.
JSlider	A JSlider this class is letting the user graphically (GUI) select by using a value by sliding a knob within a bounded interval.
JSpinner	A JSpinner this class is a single line input where the field that lets the user select by using a number or an object value from an ordered sequence.

 Comment

More info 

Next Article 

Introduction to Java

Similar Reads

Introduction to Java Swing

Swing is a Java Foundation Classes [JFC] library and an extension of the Abstract Window Toolkit [AWT]. Java Swing offers much-improved functionality over AWT, new components, expanded components...

 8 min read

Introduction to Java

Java is a class-based, object-oriented programming language that is designed to have as few implementation dependencies as possible. It is intended to let application developers Write Once and...

 10 min read

Introduction to JSP

In Java, JSP stands for Jakarta Server Pages(JSP; formerly JavaServer Pages)). It is a server-side technology that is used for creating web applications. It is used to create dynamic web content. JSP...

 6 min read

Introduction to Java NIO with Examples

Java IO(Input/Output) is used to perform read and write operations. The java.io package contains all the classes required for input and output operation. Whereas, Java NIO (New IO) was introduced from JDK 4...

🕒 5 min read

Introduction to Spring Framework

Prior to the advent of Enterprise Java Beans (EJB), Java developers needed to use JavaBeans to create Web applications. Although JavaBeans helped in the development of user interface (UI) components, th...

🕒 10 min read

How to Use Swing Applet in Java?

In this article, we will be using the swing Applet or JApplet in Java. Here, we will make a simple multiplication application that will multiply the two input numbers. Approach to Using Swing Applet in...

🕒 4 min read

Introduction of BlueJ

BlueJ is a windows based platform for Java Development Kit (JDK). It is a free Java environment started in 1999 by Michael Kolling and John Rosenberg at Monash University, Australia, as a successor to Blue. It...

🕒 3 min read

Setting up the environment in Java

Java is a general-purpose computer programming language that is concurrent, class-based, object-oriented, etc. Java applications are typically compiled to bytecode that can run on any Java virtual machi...

🕒 6 min read

Java Swing | Creating a Toast Message

What are toast messages? And how to create them by using Java Swing? Toast Messages are a quick way of informing the user by short Pop-up messages that last for a short period of time and then...

🕒 3 min read

7 Things You Didn't Know About Java

Undoubtedly, Java has been the most famous and widely used programming language out there. Not 1, or 2 but, today it covers almost every sector in the market. The reason is its adaptive nature and platfor...

🕒 8 min read

Java Swing | GroupLayout Class

GroupLayout is a LayoutManager that hierarchically group the components and arranges them in a Container. Grouping is done by using the instances of the Group class. It is generally used for developin...

🕒 6 min read

Creating Frames using Swings in Java

Swing is a part of JFC (Java Foundation Classes). Building Graphical User Interface in Java requires the use of Swings. Swing Framework contains a large set of components that allow a high level of...

🕒 4 min read

Network Input in Java

In Java, Network Input is all about sending and getting data over a network. It's about making links, getting data from input sources, and dealing with the information we get. Java offers strong tools, like...

🕒 2 min read

Top 5 Java Debugging Tips

Debugging is the process of finding and fixing errors or bugs in the source code of any software. When software does not work as expected, computer programmers study the code to determine why any error...

🕒 4 min read

JRF Event Streaming in Java

Event streaming is a powerful tool for developers that allows them to process and react to data in real-time. This is possible in the Java programming language by utilizing the Java Remote Function (JRF)...

🕒 4 min read

Difference between AWT and Swing in Java

Java is one of the most in-demand programming languages for developing a variety of applications. The popularity of Java can be attributed to its versatility as it can be used to design customized applications...

🕒 2 min read

Java Swing | Look and Feel

Swing is GUI Widget Toolkit for Java. It is an API for providing Graphical User Interface to Java Programs. Unlike AWT, Swing components are written in Java and therefore are platform-independent. Swing...

🕒 5 min read

Java Swing | Simple Calculator

Java Swing is a GUI (graphical user Interface) widget toolkit for Java. Java Swing is a part of Oracle's Java foundation classes . Java Swing is an API for providing graphical user interface elements to Java...

🕒 4 min read

Java Developer to Software Architect

and Transitioning from a Java Developer to a Software Architect is a significant career progression. The road along this route requires a variation of your skills, a detailed knowledge of system design, and the...

🕒 11 min read

Article Tags :

Java

java-swing

Practice Tags :

Java

