University of Information Technology & Sciences (

Faculty of Science and Engineering

Department of Computer Science and Engineering

Program: B.Sc. in CSE

Lab Test 2, Autumn 2026

Course Title: Microprocessors & Microcontrollers Lab

Course Code: CSE0611324

Set A

Marks: 10 **Section: 6A** **Time: 40 mins**

(Answer all questions)

Instructions:

1. Write your codes using standard 8086 Assembly Language (compatible with EMU8086).
2. Add appropriate comments to explain your logic. Marks will be deducted for uncommented code.
3. The output should be according to the sample output. If sample output is not followed then marks will be deducted.

Question

Suppose, A is divided by B and C is quotient while D is the remainder.

1. Take a single digit input for A and B 1
2. Print a right-angled triangle pattern of ($) with exactly *B* rows.The first row should contain 1 ($), the second row should contain 2 ($), and so on, until the *B*-th row, which contains *B* number of ($). 4
3. Find the largest number between C and D. 4
4. Print as per the sample output 1

Sample output

Enter B: 2
Enter A: 9
$
$$
Largest between C and D: 4

04.11.202
6th Se

University of Information Technology & Sciences (UITS)
Faculty of Science and Engineering
Department of Computer Science and Engineering
Program: B.Sc. in CSE
Lab Test 2, Autumn 2026
Course Title: Microprocessors & Microcontrollers Lab
Course Code: CSE0611324

Set B

Marks: 10 | **Section: 6A** | **Time: 40 mins**

(Answer all questions)

Instructions:

4. Write your codes using standard 8086 Assembly Language (compatible with EMU8086).
5. Add appropriate comments to explain your logic. Marks will be deducted for uncommented code.
6. The output should be according to the sample output. If sample output is not followed then marks will be deducted.

Question

Suppose, A is divided by B and C is quotient while D is the remainder.

1. Take a single digit input for A and B — 1
2. Print a right-angled triangle pattern of asterisks (%) with exactly *A* rows.The first row should contain 1 (%), the second row should contain 2 (%), and so on, until the *A*-th row, which contains *A* number of (%). — 4
3. Find the smallest number between C and D. — 4
4. Print as per the sample output — 1

Sample output

```
Enter B: 3
Enter A: 5
%
%%
%%%
%%%%
%%%%%
Smallest between C and D: 1
```

input → Div → Loop → Pattern
↓
compare
↓
small
↓
output

Jump for below

Abrar Mahbub Tanim Sir
Lima Mam

3/8 = 2