

E228TJ Truck Mounted Platform

PRP1481 Issue 1 – 9/1/2013

Operating Features:

Platform style:	Telescopic Jib
Maximum working height:	21.60 m
Maximum horizontal outreach:	17.20 m
Maximum safe working load capacity:	280 Kg
Main Boom Rotation:	365°



Specification to include:

- Three-man Steel basket fitted with safety harness anchorages, non-slip flooring, recessed handrail and sliding entry bar.
- Basket dimensions of 1.8m by 0.8m.
- Basket rotation of + 70° /- 85°.
- 365° Non-Continuous boom rotation in either direction.
- Basket Load sensing (as per EN280)
- Fully proportional hydraulic controls at the basket (duplicated at the base), as well as 110v wiring, vehicle engine stop/start, emergency lowering controls and emergency stop button.
- Four independently controlled hydraulically operated stabilisers, fully interlocked with boom operation.
- Narrow jacking and single side operation.
- Power-take-off pump, driven from vehicle gearbox.
- Stowage warning lights and PTO engaged warning alarm, complete with PTO controls in cab.
- Sub-frame finish painted in black, boom and basket finished in White.
- Fully CE marked and manufactured in accordance with European standard EN280.

E228TJ Truck Mounted Platform

PRP 1481

