

<WA1/>  
<AW1/>  
2021

# Cascading Style Sheets

## Styling the Web

Fulvio Corno  
Luigi De Russis  
Enrico Masala

*Some slides adapted from Laura Farinetti*



POLITECNICO  
DI TORINO

Applicazioni Web 1 - Web Applications 1 - 2019/2020



## Goal

- Styling web content - CSS
- Advanced layout in web pages
- Responsive layouts
- Libraries

Applicazioni Web 1 - Web Applications 1 - 2019/2020

2

Much more complex than html (many corner cases, options, behaviours...)  
We will use bootstrap library to simplify stuff instead of writing css by hand (long and many details browser dependant!)

## Outline

- CSS syntax
- CSS selectors
- CSS cascading
- CSS box model
- Page layout with grid
- CSS Flexbox
- Responsive layout
- The Bootstrap Library



Applicazioni Web 1 - Web Applications 1 - 2019/2020

3

Same rules may be applied to different elements.


## Cascading Style Sheets

- CSS 1: W3C recommendation (17 Dec 1996)
- CSS 2.1: W3C Recommendation (7 June 2011)
- CSS 3: modular approach, different stages (REC, PR, CR, WD) for different parts
  - See <https://www.w3.org/Style/CSS/>
- Resources:

## Cascading Style Sheets

- CSS 1: W3C recommendation (17 Dec 1996)
- CSS 2.1: W3C Recommendation (7 June 2011)
- CSS 3: modular approach, different stages (REC, PR, CR, WD) for different parts
  - See <https://www.w3.org/Style/CSS/>
- Resources:
  - <https://developer.mozilla.org/en-US/docs/Web/CSS>
  - <https://developer.mozilla.org/en-US/docs/Web/CSS/Reference>

## Overview of CSS development approach



<https://developer.mozilla.org/en-US/docs/Web/CSS/CSS3>

New techniques added every year. Simple syntax, the properties are added, with various complex behaviours

### Cascading Style Sheets

## CSS SYNTAX

## CSS Syntax

Only 1 type of instruction: rules

- CSS is based on **rules**
- A rule is a statement about one [stylistic] aspect of one or more HTML element
  - **Selector** + **Declaration(s)**
- A style sheet is a set of one or more rules that apply to an HTML document



Selects 0,1,many elements to apply this rule to.

h1

{color:blue; font-size:12px;}


Selects 0,1,many elements to apply this rule to.  
Different type of selector with different algorithms to  
Select the various elements

Property Value Property Value  
Declaration is applied on the selected elements! Each element has MANY properties, each with a  
different meaning! We can customize them all! (f12, dom ,browser styles)  
Very powerful! But difficult to understand all the properties and how they interact!

7

## General syntax

All elements called header AND all paragraphs which have class intro




Many rules influence also the children of that element! (cascade)  
Some may not, especially if the child has a rule that overwrites the parent rule!

8

## HTML nested structure

```
<html lang="en">
<head>
  <title>Trickier nesting, still</title>
</head>
<body>
  <div>
    <div>
      <table>
        <tr><th>Steps</th><th>Processes</th></tr>
        <tr><td>1</td><td>Figure out the <em>root element</em>.</td></tr>
        <tr><td>2</td><td>Deal with the <span>head</span> first as it's
usually easy.</td></tr>
        <tr><td>3</td><td>Work through the <span>body</span>. Just <em>take
your time</em>.</td></tr>
      </table>
    </div>
    <div>
      This link is <em>not</em> active, but it it were, the answer to this
      <a></a> would be there. But <em>do the exercise
      anyway!</em>
    </div>
  </div>
</body>
</html>
```




9

## Tree structure and inheritance

- HTML documents are trees
- Styles are inherited along trees
- When two rules are in conflict the most specific wins
- Example

– body {color: green}  
– h1 {color: red}




10

Selector Declaration Declaration

h1 {color:blue; font-size:12px;}

Property Value Property Value



Application: Web I - Web Applications I - 2019/2020

11

Too many!

- Left, center, right: strings with certain meanings

Width, height, spacing, borders, margins, expressed in pixels, line length..

[illegible]

Border-right to specify the property of the right border of a block  
Border-right(color, style, width) is more specific than border-right!

<https://developer.mozilla.org/en-US/docs/Web/CSS/Reference>

For each color element contains All possible values of a color  
5 specifications for each property:  
<meaning>: what it does  
<values>: types of values that it contains  
<initial value> : default value  
<applies to> to which element I can apply that property  
<inherited> : if father has that property, also children has it?



- <http://www.w3schools.com/cssref/>
- <https://developer.mozilla.org/en-US/docs/Web/CSS/Reference>
- <https://www.tutorialrepublic.com/css-reference/css3-properties.php>

12

Application: Web I - Web Applications I - 2019/2020

Different between text (paragraph formatting: alignment,..) and font (letters, characters formatting: font size, color, ..)

- Animation Properties
  - Background Properties
  - Border Properties
  - Color Properties
  - Dimension Properties
  - Generated Content Properties
  - Flexible Box Layout
  - Font Properties
  - List Properties
  - Margin Properties
  - Multi-column Layout Properties
  - Outline Properties
  - Padding Properties
  - Print Properties
  - Table Properties
  - Text Properties
  - Transform Properties
  - Transitions Properties
  - Visual formatting Properties
- <https://www.tutorialrepublic.com>

<https://www.tutorialrepublic.com/css-reference/css3-properties.php>

13

Applicazioni Web I - Web Applications I - 2019/2020

## CSS Units: Most Used

- CSS has several different **units** for expressing a length
  - format: a number followed by a unit (e.g., 10px)
  - width, font-size, margin, padding, ...
- Two types of length units
  - absolute (fixed)
  - relative
- The most common fixed unit is pixel (px)
  - they are relative to the viewing device
  - for low-dpi devices, 1px is one device pixel (dot) of the display
  - for printers and high-resolution screens, 1px implies multiple device pixels
  - not well suited for responsive design (later on)

## CSS Units: Most Used

- The most common relative units, instead:

Unit	Description
em	Relative to the font-size of the element. 2em means 2 times the size of the font of the current element
rem	Relative to font-size of the root element of the HTML page (Root EM)
vw	Relative to 1% of the width of the viewport, i.e., the browser window size
vh	Relative to 1% of the height of the viewport
%	Relative to the parent element


Em="m"


- Suggestions:
  - prefer relative units to absolute ones, when possible
  - rem is (nowadays) preferred to em

## CSS SELECTORS

## CSS selectors

- Patterns used to select the element(s) you want to style
- Three main types of selectors plus “pseudo-selectors”





## Element selector

- Used to apply the same style to all instances of a specific element in a document
- Example: apply the color red to all h1 elements that appear in the document

```

h1
{
    color:red;
}
style.css

```

Application Web I - Web Applications I - 2019/2020

18

## Class selector

- Used to apply the same style to all elements belonging to a specific (defined) class
- Applies a specific style to a set of related elements, identified by class

```

<h1 id="titlemessage">Education is must</h1>
<p class="bluetext">Education in its general sense is a
form of learning in which [...>
</p>
<h3 class="bluetext">Try to teach</h3>
doc.html
.bluetext
{
    color:blue;
}
style.css

```

Application Web I - Web Applications I - 2019/2020

19

## Id selector

- Used to apply a style to a specific element in a document
- You can select a specific element by its (declared) id and apply a style to that (and possibly its children)

```

<h1 id="titlemessage">Education is must</h1>
<p class="bluetext">Education in its general sense is a
form of learning in which [...>
</p>
<h3 class="bluetext">Try to teach</h3>
doc.html
#titlemessage
{
    color:gray
}
style.css

```

Application Web I - Web Applications I - 2019/2020

20

## Attribute selectors

Selector	Example	Example description	CSS
[attribute]	[target]	Selects all elements with a target attribute	2
[attribute=value]	[target=_blank]	Selects all elements with target="_blank"	2
[attribute~value]	[title~flower]	Selects all elements with a title attribute containing the word "flower"	2
[attribute =value]	[lang =en]	Selects all elements with a lang attribute value starting with "en"	2
[attribute^=value]	a[href^="https"]	Selects every <a> element whose href attribute value begins with "https"	3
[attribute\$=value]	a[href\$=".pdf"]	Selects every <a> element whose href attribute value ends with ".pdf"	3
[attribute*=value]	a[href*="w3schools"]	Selects every <a> element whose href attribute value contains the substring "w3schools"	3

21

Applicazioni Web I - Web Applications I - 2019/2020

## Pseudo class selector

- Used to style an element based on something other than the structure of the document
  - E.g., the status of a form element or link

```
/* makes all unvisited links blue */
a:link {color:blue;}
/* makes all visited links green */
a:visited {color:green;}
/* makes links red when hovered or activated */
a:hover, a:active {color:red;}
/* makes table rows red when hovered over */
tr:hover {background-color: red;}
/* makes input elements yellow when focus is applied */
input:focus {background-color:yellow;}
```

22

Applicazioni Web I - Web Applications I - 2019/2020

## Combining selectors

- element.class#id[n=v]
  - may be combined
- S1, S2 → S1 union S2
- S1 S2 → S2 nested within S1
- S1 > S2 → S2 if a child of S1 immediately
- S1 + S2 → S2 if it comes after a S1
- S1 ~ S2 → S2 if it comes later than S1

Header h1 [...] (h1 inside an header) : select element by describing its position in the dom tree of the page!

23

Applicazioni Web I - Web Applications I - 2019/2020



## CSS selectors

Selector	Example	Example description	CSS
<code>.class</code>	<code>.intro</code>	Selects all elements with class="intro"	1
<code>#id</code>	<code>#firstname</code>	Selects the element with id="firstname"	1
<code>*</code>	<code>*</code>	Selects all elements	2
<code>element</code>	<code>p</code>	Selects all <p> elements	1
<code>element,element</code>	<code>div, p</code>	Selects all <div> elements and all <p> elements	1
<code>element element</code>	<code>div p</code>	Selects all <p> elements inside <div> elements	1
<code>element&gt;element</code>	<code>div &gt; p</code>	Selects all <p> elements where the parent is a <div> element	2
<code>element+element</code>	<code>div + p</code>	Selects all <p> elements that are placed immediately after <div> elements	2
<code>element1~element2</code>	<code>p ~ ul</code>	Selects every <ul> element that are preceded by a <p> element	3

[http://www.w3schools.com/cssref/css\\_selectors.asp](http://www.w3schools.com/cssref/css_selectors.asp)

24

Applications Web I - Web Applications I - 2019/2020

## Display property

- Allows to control element visualization (block or inline)
- Changing an inline element to a block element, or vice versa, can be useful for making the page look a specific way

```
li {display:inline;}
```

We can change the default behaviour of the elements from block to inline or viceversa

```
span {display:block;}
```

[http://www.w3schools.com/Css/css\\_display\\_visibility.asp](http://www.w3schools.com/Css/css_display_visibility.asp)

25

Applications Web I - Web Applications I - 2019/2020

## Display and visibility properties

- The property display allows to hide an element, too
  - The element will be hidden, and the page will be displayed as if the element is not there

```
h1.hidden {  
  display: none;  
}
```

Easily make parts of the page disappear! (It is still there!)

- The property visibility also can hide an element, but the element will still take up the same space as before
  - The element will be hidden, but still affects the layout

```
h1.hidden {  
  visibility: hidden;  
}
```

We can prepare placeholders to later insert real content when it's ready/needed

26

Applications Web I - Web Applications I - 2019/2020



# CSS pseudo-class selectors

Selector	Example	Example description	CSS
:active	a:active	Selects the active link	1
:after	p::after	Insert something after the content of each <p> element	2
:before	p::before	Insert something before the content of each <p> element	2
:checked	input:checked	Selects every checked <input> element	3
:disabled	input:disabled	Selects every disabled <input> element	3
:empty	p:empty	Selects every <p> element that has no children (including text nodes)	3
:enabled	input:enabled	Selects every enabled <input> element	3
:first-child	p:first-child	Selects every <p> element that is the first child of its parent	2
:first-letter	p::first-letter	Selects the first letter of every <p> element	1
:first-line	p::first-line	Selects the first line of every <p> element	1

Selector	Example	Example description	CSS
:first-of-type	p:first-of-type	Selects every <p> element that is the first <p> element of its parent	3
:focus	input:focus	Selects the input element which has focus	2
:hover	a:hover	Selects links on mouse over	1
:in-range	input:in-range	Selects input elements with a value within a specified range	3
:invalid	input:invalid	Selects all input elements with an invalid value	3
:lang(language)	p:lang(it)	Selects every <p> element with a lang attribute equal to "it" (Italian)	2
:last-child	p:last-child	Selects every <p> element that is the last child of its parent	3
:last-of-type	p:last-of-type	Selects every <p> element that is the last <p> element of its parent	3
:link	a:link	Selects all unvisited links	1

# CSS pseudo-class selectors

Selector	Example	Example description	CSS
:not(selector)	:not(p)	Selects every element that is not a <p> element	3
:nth-child(n)	p:nth-child(2)	Selects every <p> element that is the second child of its parent	3
:nth-last-child(n)	p:nth-last-child(2)	Selects every <p> element that is the second child of its parent, counting from the last child	3
:nth-last-of-type(n)	p:nth-last-of-type(2)	Selects every <p> element that is the second <p> element of its parent, counting from the last child	3
:nth-of-type(n)	p:nth-of-type(2)	Selects every <p> element that is the second <p> element of its parent	3
:only-of-type	p:only-of-type	Selects every <p> element that is the only <p> element of its parent	3
:only-child	p:only-child	Selects every <p> element that is the only child of its parent	3
:optional	input:optional	Selects input elements with no "required" attribute	3
:out-of-range	input:out-of-range	Selects input elements with a value outside a specified range	3

Selector	Example	Example description	CSS
:read-only	input:read-only	Selects input elements with the "readonly" attribute specified	3
:read-write	input:read-write	Selects input elements with the "readonly" attribute NOT specified	3
:required	input:required	Selects input elements with the "required" attribute specified	3
:root	:root	Selects the document's root element	3
::selection	::selection	Selects the portion of an element that is selected by a user	
:target	#news:target	Selects the current active #news element (clicked on a URL containing that anchor name)	3
:valid	input:valid	Selects all input elements with a valid value	3
:visited	a:visited	Selects all visited links	1

# Cascading Style Sheets

Cascading mechanism: insert style into a page.  
Various places to insert rules. Articulated rules.

- The term “cascading” means that a document can include more than one style sheet
- In this case, visualization follows priority rules

- Inline Style (inside HTML tag)
- Internal Style (usually in the HTML head section)
- External Style
- Browser Default Style

Discouraged  
Discouraged



.css file to link to the page

Applicazioni Web I - Web Applications I - 2019/2020

30

## External style

- Link to an external style sheet using the <link> element

```
h1 { font-size:17px;
      font-family:verdana; color:green; }
h2 { font-size:18px;
      font-family:arial; color:red; }
```

style.css

```
<head>
  <link rel=stylesheet type="text/css"
        href="style.css">
</head>
<body>
  <h1>Questo testo e' di colore verde, e utilizza il
      font verdana a 17 pixel</h1>
  <h2>Questo testo e' di colore rosso, e utilizza il
      font arial a 18 pixel</h2>
</body>
```

Connects external file to the webpage and tell browser to take styles from there!  
Link to the relationship of stylesheet of format text/css.

```
.css
Body{
  Background color = ...
}
Applies property background color=... to the elements selected by body
```

Applicazioni Web I - Web Applications I - 2019/2020

31

## Internal style

- <style> element inside the document header
- Not recommended – prefer external styles

```
<head>
  <style type="text/css">
    h1 { font-size:17px; font-family:verdana;
          color:green; }
    h2 { font-size:18px; font-family:arial;
          color:red; }
  </style>
</head>
```

Applicazioni Web I - Web Applications I - 2019/2020

32

## Inline style

- <style> attribute within an HTML element
- Last resort, just for local (very local) changes

```
<h1 style="font-size:17px;
font-family:verdana; color:green;"> Questo
testo e' di colore verde, e utilizza il
font verdana a 17 pixel </h1>
```

## Priority rules

- Rules can be marked as "important"

```
h1 {
  color:red !important
}
```




Customization that the user can do to their browser

Overwrite some behaviours

### The definitive guide to CSS styling order

Includes CSS stylings for SVG




We try to keep it sample!  
Today we have a flavour, but then we'll use a library for the dirty work!

## CSS BOX MODEL

Reason on the space that each object occupies

### The box model

- One of the cornerstones of CSS
- Every element on the page is considered to be a rectangular box



We start from the CONTENT ("a") (image) (table) ... that occupies the Private space of the element  
 BORDER: of 0px or more (visible) (thin, thick) can change color  
 PADDING: space inside the element to avoid it touching the border (same color of the border)  
 MARGIN: space outside the border to avoid it touching other elements (same color of the outside)


Can be changed directly in the inspector, but these modification don't survive in the real css (useful for testing)

H1 has default margin of the browser, if we don't like it we redefine it!

### The box model

**content** Total element width =  
 width + left padding + right padding +  
 left border + right border + left margin  
 + right margin

- Total element height =  
 height + top padding +  
 bottom padding + top border +  
 bottom border + top margin + bottom  
 margin
- You can set any of these  
 properties, independently



## CSS POSITIONING SCHEMES

Long history of layouts of css


Applicazioni Web I - Web Applications I - 2019/2020

39

### Positioning schemes

Very linked to the internal functioning of the algorithm (low level, difficult)

- **Static:** normal flow
- **Relative:** offset relative to the block position in the normal flow
- **Absolute:** the box position is determined by the top, left, right, bottom properties, relative to the containing block
- **Fixed:** fixed with respect to some reference point (the viewport)




Applicazioni Web I - Web Applications I - 2019/2020

40

### z-index

- In case of overlaps the z-index property specifies the stack order of an element (which element should be placed in front of, or behind, the others)



Applicazioni Web I - Web Applications I - 2019/2020

41

## Floating

- The CSS **float** property gives control over the horizontal position of an element



<https://internetingishard.com/html-and-css/floats/>

Applications Web I - Web Applications I - 2019/2020

42

## Floating

- A floated box can either be shifted to the left or the right until its outer edge touches the edge of its containing box, or another floated box
- Often used for images and when working with layouts

```
img
{
  float:right;
}
```

[http://www.w3schools.com/Css/css\\_float.asp](http://www.w3schools.com/Css/css_float.asp)




Applications Web I - Web Applications I - 2019/2020

43


## Clearing floats

- “Clearing” a float: tell a block to ignore any floats that appear before it
  - Instead of flowing around, a cleared element appears after any floats
  - It’s like forcing a box back into the default vertical flow of the page

### CLEARING WITH CHILD ELEMENT



### Second paragraph cleared




Applications Web I - Web Applications I - 2019/2020


44

## Float-based layouts

- Set the width of the elements you want to position, and then float them left or right
  - Two-column floated layout
  - Three-column floated layout




Tricks and templates to create various layout but it was very difficult!



## Two-column floated layout

- Create a virtual gutter by floating one element left and one element right

Complex layouts with blood and tears




## Two-column floated layout



<https://blog.html.it/layoutgala/index.html>

## Three-column floated layout





# References for CSS box model and positioning

- Learn CSS layout
  - <http://learnlayout.com/>
- Floatutorial
  - <http://css.maxdesign.com.au/floatutorial/>
- All about floats
  - <https://css-tricks.com/all-about-floats/>

## Cascading Style Sheets

### PAGE LAYOUT WITH GRIDS

Now way easier!  
We'll use these in the bootstrap library

## Advanced layout: grid



**Maki-zushi**  
The rice and seaweed rolls with fish and/or vegetables. There are also more specific terms for the rolls depending on the style.



**Nigiri-zushi**  
The little fingers of rice topped with wasabi and a flat of raw or cooked fish or shellfish. Generally the most common form of sushi you will see.



**Temaki-zushi**  
Also called a hand-rol. Cones of sushi rice, fish and vegetables wrapped in seaweed. It is very similar to maki.

#### WHAT IS SUSHI?

Beginning as a method of preserving fish centuries ago, sushi has evolved into an artful, unique dining experience. In its earliest form, dried fish was placed between two pieces of vinegared rice as a way of making it last. The rice (seaweed) was added later as a way to keep one's fingers from getting sticky.



**Sashimi**  
Sashimi is raw fish served sliced, but so is. That means no rice bed or roll, but it is often served alongside dakin and/or shiso. This is my favorite style as you really get the flavor of the fish.



**QUICK & EASY SUSHI COOKBOOK**  
This book has great pictures, however it is not as complete as Sushi Made Easy.



**SUSHI FOR PARTIES: MAKI-ZUSHI AND NIGIRI-ZUSHI**  
This book also has great pictures, with advanced maki (but roll making techniques).



**SUSHI MADE EASY**  
A very decent all-around book for the money.

Elements can occupy different amount of cells.  
We do not need to bother about pixels, higher level mechanism to decide what goes where.  
We can have grids with width of the cells equal for each cell or customizable to make room for different types of elements. Easier to manage than floats, especially for problems about different heights or even variable heights!

## Advanced layout: grid

 <p><b>Maki-zushi</b> The rice and seaweed rolls with fish and/or vegetables. There are also more specific terms for the rolls depending on the style.</p>	 <p><b>Nigiri-zushi</b> The little fingers of rice topped with wasabi and a flat of raw or cooked fish or shellfish. Generally the most common form of sushi you will see.</p>	 <p><b>Temaki-zushi</b> Also called a hand-rol. Cones of sushi rice, fish and vegetables wrapped in seaweed. It is very similar to maki.</p>
<h4>WHAT IS SUSHI?</h4> <p>Beginning as a method of preserving fish centuries ago, sushi has evolved into an artful, unique dining experience. In its earliest form, dried fish was placed between two pieces of vinegared rice as a way of making it last. The rice (seaweed) was added later as a way to keep one's fingers from getting sticky.</p>		
<div><p><b>Sashimi</b> Sashimi is raw fish served sliced, but so is. That means no rice bed or roll, but it is often served alongside dakin and/or shiso. This is my favorite style as you really get the flavor of the fish.</p></div>	<div><p><b>QUICK &amp; EASY SUSHI COOKBOOK</b> This book has great pictures, however it is not as complete as Sushi Made Easy.</p></div>	<div><p><b>SUSHI FOR PARTIES: MAKI-ZUSHI AND NIGIRI-ZUSHI</b> This book also has great pictures, with advanced maki (but roll making techniques).</p></div>
	<div><p><b>SUSHI MADE EASY</b> A very decent all-around book for the money.</p></div>	

We do not need to bother about pixels, higher level mechanism to decide what goes where.  
We can have grids with width of the cells equal for each cell or customizable to make room for different types of elements. Easier to manage than floats, especially for problems about different heights or even variable heights!

## Advanced layout: grid



52

Just declare that one div is a grid, giving rows and columns. Elements position themselves automatically depending on the size of the elements!

## Advanced layout: grid

- It is possible to define a grid in which content can flow or be placed, or that remain empty
- There are 3 ways to define a grid
  - Explicit grid: defined with 'grid-columns' and 'grid-rows' properties
  - Natural grid: automatically created by elements with a natural grid structure (multi-column elements and tables)
  - Default grid: all other block elements define a single-cell grid

53

## Example

- Classic three-column layout

```
<section>
  <header>Title</header>
  <nav>Menu</nav>
  <article>Content</article>
  <aside>Notes</aside>
  <footer>Footer</footer>
</section>
```



54

## Example

```

section {
  display: grid;
  grid-columns: 150px 1fr 200px;
  grid-rows: 50px 1fr 50px;
}
section header {
  grid-column: 2;
  grid-row: 1;
}
section nav {
  grid-column: 1;
  grid-row: 2;
}
section article {
  grid-column: 2;
  grid-row: 2;
}
section aside {
  grid-column: 3;
  grid-row: 2;
}
section footer {
  grid-column: 2;
  grid-row: 3;
}

```

Left border      Right border

Header border      Footer border

- fr = fraction values
  - new unit applicable to grid-rows and grid-columns properties


55

Applicazioni Web I - Web Applications I - 2019/2020

## Suggested reference for Grid Layout

- <https://webkit.org/blog/7434/css-grid-layout-a-new-layout-module-for-the-web/>

<https://webkit.org/blog/7434/css-grid-layout-a-new-layout-module-for-the-web/>



56

Applicazioni Web I - Web Applications I - 2019/2020

Cascading Style Sheets

## CSS FLEXBOX


Alternative to grid layout: flex layout: rules to position elements inside automatically

57

Applicazioni Web I - Web Applications I - 2019/2020

# Flexbox


- Alternative to floats/grids for defining the overall appearance of a web page
- Flexbox gives complete control over the alignment, direction, order, and size of boxes



Applications Web 1 - Web Applications 1 - 2019/2020

58

# Flexbox



- <https://internetingshard.com/html-and-css/flexbox/>
- [https://www.w3schools.com/css/css3\\_flexbox.asp](https://www.w3schools.com/css/css3_flexbox.asp)


Applications Web 1 - Web Applications 1 - 2019/2020

59

Rules are not blocks, inline or other, rules are FLEX, children are FLEX (only 1 level deep)

# Flexbox

- Flexbox uses two types of boxes
  - Flex containers: group a set of flex items and define how they're positioned
  - Flex items
- Every HTML element that's a direct child of a flex container is an item



Applications Web 1 - Web Applications 1 - 2019/2020


60

## Horizontal alignment

```
.menu-container {  
  /* ... */  
  display: flex;  
  justify-content: center;  
}
```

Display property change completely the layout algorithm to apply to the elements inside!  
The container does all the work!  
While with grid we needed to position each element!

- To turn one HTML elements into a flex container:  
`{ display: flex ; }`
- “justify-content” property defines the horizontal alignment of its items
  - center, flex-start, flex-end
  - space-around, space-between




Applications Web I - Web Applications I - 2019/2020

61

## Wrapping

- The `flex-wrap` property creates a grid
  - Then, you can change alignment, direction, order, and size of items




```
.photo-grid {  
  width: 900px;  
  display: flex;  
  justify-content: center;  
  flex-wrap: wrap;  
}
```

Applications Web I - Web Applications I - 2019/2020

62

## Vertical alignment

- Flex containers can also define the vertical alignment of their items




```
.header {  
  width: 900px;  
  height: 300px;  
  display: flex;  
  justify-content: space-between;  
  align-items: center;  
}
```

Applications Web I - Web Applications I - 2019/2020

63

## Direction

- Refers to whether a container renders its items horizontally or vertically



Applications/ Web 1 - Web Applications 1 - 2019/2020

64

Size of the element is computed automatically by the algorithm!

## Flexible items

- Flex items are flexible: they can shrink and stretch to match the width of their containers
- The **flex** property defines the width of individual items in a flex container
  - a *weight* that tells the flex container how to distribute extra space to each item
  - E.g., an item with a flex value of 2 will grow twice as fast as items with the default value of 1




Applications/ Web 1 - Web Applications 1 - 2019/2020

65

## Flexible items

- Example



```
<div class='footer'>
  <div class='footer-item footer-one'></div>
  <div class='footer-item footer-two'></div>
  <div class='footer-item footer-three'></div>
</div>
```

```
.footer {
  display: flex;
  justify-content: space-between;
}

.footer-item {
  border: 1px solid #fff;
  background-color: #D6E9FE;
  height: 200px;
  flex: 1; }

.footer-three { flex: 2; }
```


Weight is the only property that we can give to the children

Applications/ Web 1 - Web Applications 1 - 2019/2020

66

## Grouping

- Flex containers only know how to position elements that are one level deep (i.e., their child elements)
  - You can group flex items using `<div>`



Applicazioni Web I - Web Applications I - 2019/2020

67

## Summary of CSS flexbox

Floats, grids, flex layouts possible!

- `display: flex` to create a flex container
- `justify-content` to define the horizontal alignment of items
- `align-items` to define the vertical alignment of items
- `flex-direction` if you need columns instead of rows
- `row-reverse` or `column-reverse` values to flip item order
- `order` to customize the order of individual elements
- `align-self` to vertically align individual items
- `flex` to create flexible boxes that can stretch and shrink

Applicazioni Web I - Web Applications I - 2019/2020

68

## References for CSS flexbox

- Interneting is hard flexbox tutorial
  - <https://internetingishard.com/html-and-css/flexbox/>
- A complete guide to flexbox
  - <https://css-tricks.com/snippets/css/a-guide-to-flexbox/>
- W3schools
  - [https://www.w3schools.com/css/css3\\_flexbox.asp](https://www.w3schools.com/css/css3_flexbox.asp)
- Flexbox, guida pratica
  - <http://www.html.it/guide/flexbox-guida-pratica/>
- Flexbox Froggy (a game-like tutorial)
  - <http://flexboxfroggy.com/>



Applicazioni Web I - Web Applications I - 2019/2020


69



## RESPONSIVE LAYOUT

### Responsive design

- Display well in everything from widescreen monitors to mobile phones
- Approach to web design to eliminate the distinction between the mobile-friendly version of your website and its desktop counterpart




<https://internetingshard.com/html-and-css/responsive-design/>

### Responsive design

- Responsive design is accomplished through CSS “media queries”
  - A way to conditionally apply CSS rules


```
@media(min-width:900px){p{color:red;}}
```

Mechanism media query: different type of selector that will enable some rules ONLY if some property about the media applies (for example they apply only if screen size is higher than 900px)



Conditional rules on the Browser container property (size of screen).  
Different rules! Same html layed out in different ways depending on the size!

## Layout for responsive design



Applications Web I - Web Applications I - 2019/2020

73

## Grid-view

- Many web pages are based on a grid-view, i.e. the page is divided into columns
- A responsive grid-view often has 12 columns, a total width of 100%, and will shrink and expand as you resize the browser window



Applications Web I - Web Applications I - 2019/2020

74



3-4 main css frameworks

Cascading Style Sheets

## THE BOOTSTRAP FRAMEWORK

Flex layout+media queries+many css classes already defined, that we can use and customize avoiding low level manual css settings.

Applications Web I - Web Applications I - 2019/2020

75

# Bootstrap

- Open Source CSS (and Javascript) framework
  - Allows applying “modern” styles
    - Sensible and nice-looking defaults
    - Easy to apply custom themes
  - Takes care of cross-browser issues
  - Simplified layout model
- Applies modern styles (spacing, fonts), grid based layout internally using flexbox, responsive design, all by applying effects on the containers
- Developed by Twitter
    - <http://getbootstrap.com/> -> go to version 4.6, because version 5 is still in beta
    - <https://getbootstrap.com/docs/4.6/getting-started/introduction/>

Applicazioni Web I - Web Applications I - 2019/2020

76

## Bootstrap philosophy

- Based on CCS classes
- Each class applies one “effect”
- Various classes may be combined in the same element
- Wide range of “standard” classes
- Wide range of additional “components”
  - Ready-to use <sup>Automatically</sup> interactive elements or groups of elements
- Mobile-first
  - Responsive

Applicazioni Web I - Web Applications I - 2019/2020

77

## Using Bootstrap

- Use Bootstrap CDN
  - Bootstrap CSS – in <head>
  - Javascript support – end of <body>
    - Used by Bootstrap (bootstrap.min.js)
    - Used by some components (jQuery and Popper.js)
- Or download locally
  - <https://github.com/twbs/bootstrap/releases/download/v4.6.0/bootstrap-4.6.0-dist.zip>
  - npm install bootstrap

React only support version 4.6 for now! (5.0 still beta)

Applicazioni Web I - Web Applications I - 2019/2020

78

## Bootstrap CDN

```
<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@4.6.0/dist/css/bootstrap.min.css"
integrity="sha384-B0vP5xmATw1+K9KRQjQERJvTumQW0nPEzvF6L/Z6nronJ3oUOFUFpCjEUQouq2+1"
crossorigin="anonymous">
```

Just a css file loaded from network. (or saved offline but online is still fast and more updated)  
We also need 2 js modules because it uses them internally!

```
<script src="https://code.jquery.com/jquery-3.5.1.slim.min.js"
integrity="sha384-Dfxdz2htPH01sSSs5nCTpuj/zy4C+OGpamoFVy38MVBnE+IbbVYUew+OrCXaRkfj"
crossorigin="anonymous"></script>
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.6.0/dist/js/bootstrap.bundle.min.js"
integrity="sha384-Piv4xVNRyMGpQkS2by6br4gNJ7DXjqk09RmUpJ8jgGtD7zP9yug3goQfGII0yAns"
crossorigin="anonymous"></script>
```

Already Enter and Scoring is more Modern looking!

```
src="https://cdn.jsdelivr.net/npm/bootstrap@4.6.0/dist/js/bootstrap.bundle.min.js"
integrity="sha384-Piv4xVNRyMGpQkS2by6br4gNJ7DXjqk09RmUpJ8jgGtD7zP9yug3goQfGI0yAns"
crossorigin="anonymous"></script>
```

Already Fonts and Spacing is more Modern looking!

We write classes on html that refers to the classes styled in the bootstrap library.

To give bootstrap full control on the page we need to put all elements into .container (gives fixed width depending on the size of the browser) or .container fluid (always occupy 100% of the width of the page)

Container defines the grid. New grid environment: new container

Responsive breakpoints: 5 different possible size of screen (xs, s, m, l, xl) (we decide the minimum size until we display grid as column instead of as a block)  
Use grid to decide how much space each element will take on the screen (define row and col)  
Depending on how many columns I decide to put, it splits evenly the available space (max 12, 6-6, 4-3, ...) or unevenly space (col-3) (col-9) (col-3/12) (col-9/12)

Study documentation to format what you need (names of classes to use)

Components: user interfaces already coded.

Consistent, clean, modern framework!

If we don't like it use extensions for it (icons, themes,...)

I can have personal css file to add custom rules to overwrite bootstrap BUT I won't need it because I just need to customize bootstrap (use btn btn-success -> semantic button -> to change color we just need to use a new bootstrap theme which changes the color of the btn -success).

N.B. From JS we can change the value of 1 class! 1 line of code to modify the whole page layout!  
Library to avoid css complexity!

## Starter Template

```
<!doctype html>
<html lang="en">
  <head>
    <!-- Required meta tags -->
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-scale=1, shrink-to-fit=no">

    <!-- Bootstrap CSS -->
    <link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.min.css" integrity="sha384-Vkoo8x4CGs034HhXv8T/

    <title>Hello, world!</title>
  </head>
  <body>
    <h1>Hello, world!</h1>

    <!-- Optional JavaScript -->
    <!-- jQuery first, then Popper.js, then Bootstrap JS -->
    <script src="https://code.jquery.com/jquery-3.4.1.slim.min.js" integrity="sha384-T6qg4849bIE2+poT4WYKhv5vZFSSPP901Ejw@vKJ7imGFAY0wJtyVfor853"
    <script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js" integrity="sha384-Q6E9RHvblyZfJof+2m7BhaEldlvi9IDVysn3t"
    <script src="https://stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.min.js" integrity="sha384-wFSDF2ES0Y201u0J903uMB3nj4UD4Th7YwaYc"
  </body>
</html>
```

## Adding your style

- Write your additional CSS rules in a file, and load it in the head section, after the bootstrap CSS

```
<head>
  ...
  <link rel="stylesheet" href="... > // bootstrap css

  <!-- Custom CSS for this document -->
  <link rel="stylesheet" href="mystyle.css">
  ...
</head>
```

## Containers (mandatory top-level element)

- All-in-one: responsive, fixed-width container: its max-width changes at each breakpoint

```
<div class="container">
  <!-- Content here -->
</div>
```

- Fluid: full width container, spanning the entire width of the viewport

```
<div class="container-fluid">
  ...
</div>
```

## Grid system


- Based on flexbox
- Uses a 12-column virtual grid
- The container is divided in `.row` blocks
- Each Row contains columns `.col`
  - By default, all columns have equal width
  - May specify spanning over more columns (`.col-4`)
  - May specify a breakpoint for that column to be visualized (`.col-sm` or `.col-sm-4`)
- 5 Breakpoints

## Breakpoints

	Extra small <576px	Small ≥576px	Medium ≥768px	Large ≥992px	Extra large ≥1200px
Max container width	None (auto)	540px	720px	960px	1140px
Class prefix	<code>.col-</code>	<code>.col-sm-</code>	<code>.col-md-</code>	<code>.col-lg-</code>	<code>.col-xl-</code>
# of columns	12				
Gutter width	30px (15px on each side of a column)				
Nestable	Yes				
Column ordering	Yes				

## Example layouts

<https://getbootstrap.com/docs/4.6/layout/grid/>



86

## Page content

- Reboot – normalize and replace browser defaults
- Typography – heading and text styles
- Images and Figures – alignment and responsiveness
- Tables – rich visual styles, and responsive tables

• See: <https://getbootstrap.com/docs/4.6/content/>

87

## Components

- Ready-to-use classes for creating common UI elements
- See: <https://getbootstrap.com/docs/4.6/components/>



88

# License



- These slides are distributed under a Creative Commons license “**Attribution-NonCommercial-ShareAlike 4.0 International (CC BY-NC-SA 4.0)**”
- **You are free to:**
  - **Share** — copy and redistribute the material in any medium or format
  - **Adapt** — remix, transform, and build upon the material
  - The licensor cannot revoke these freedoms as long as you follow the license terms.
- **Under the following terms:**
  - **Attribution** — You must give [appropriate credit](#), provide a link to the license, and [indicate if changes were made](#). You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
  - **NonCommercial** — You may not use the material for [commercial purposes](#).
  - **ShareAlike** — If you remix, transform, or build upon the material, you must distribute your contributions under the [same license](#) as the original.
  - **No additional restrictions** — You may not apply legal terms or [technological measures](#) that legally restrict others from doing anything the license permits.
- <https://creativecommons.org/licenses/by-nc-sa/4.0/>

