

# Suprdat Documentation

- Lead Rest Endpoint: [https://suprdat.dk/live\\_delivery\\_api/rest](https://suprdat.dk/live_delivery_api/rest)
- Each apikey is linked to unique country. Do not reuse without consent.
- All URL parameter keys are case-sensitive
- All URL parameter values should be url-encoded (UTF-8)

Parameters	Required	Format / Comment
apikey	Yes	Provided by Suprdat. Each apikey is linked to unique country. E.g. apikeys must not be reused without Suprdat consent.
emailId	Yes	Allowed valid format only
phone	No	Numbers only
firstName	No	
lastName	No	
gender	No	Allowed values are "male" and "female" in lowercase
city	No	
address	No	
postCode	No	
birthdateDay	No	Allowed Numbers only (length = 2) (E.g. 01 )
birthdateMonth	No	Allowed Numbers only (length= 2) (E.g. January = 01 )
birthdateYear	No	Allowed Numbers only (length= 4) (E.g. 1999)
age	No	Allowed Numbers only
ip	No	
optinurl		Allowed Valid URL
optindate		Allowed Format (yyyy-mm-dd)

## Example request

Here a request complete with all placeholders to replace with actual values.

`http://suprdat.dk/live_delivery_api/rest?apikey=%apikey%&emailId=%email%&firstName=%firstname%&lastName=%lastname%&phone=%phone%&gender=%gender%&address=%address%&postCode=%postcode%&city=%city%&birthdateDay=%birthdateDay%&birthdateMonth=%birthdateMonth%&birthdateYear=%birthdateYear%&age=%age%&ip=%ip%&optinurl=%optinurl%&optindate=%optindate%`

Here an example of the placeholders replaced with valid values

[http://suprdat.dk/live\\_delivery\\_api/rest?apikey=\[my\\_api\\_key\]&emailId=myname@suprdat.dk&firstName=John&lastName=Doe&phone=9100000000&gender=male&address=Kolding,Danmark&postCode=123456&city=Danmark&birthdateDay=01&birthdateMonth=01&birthdateYear=1999&age=20&ip=127.0.0.1&optinurl=optinurl&optindate=optiondate](http://suprdat.dk/live_delivery_api/rest?apikey=[my_api_key]&emailId=myname@suprdat.dk&firstName=John&lastName=Doe&phone=9100000000&gender=male&address=Kolding,Danmark&postCode=123456&city=Danmark&birthdateDay=01&birthdateMonth=01&birthdateYear=1999&age=20&ip=127.0.0.1&optinurl=optinurl&optindate=optiondate)

## Response

The endpoint always returns json response object with key 'success' for accepted leads (with 'data' key), and json response object with key 'error' for rejected leads.

### Example of lead accepted response

```
{
  "success": "Data Added Successfully",
  "data": {
    "firstName": "John",
    "lastName": "Doe",
    "emailId": "myname@suprdat.dk",
    "phone": "9100000000",
    "gender": "male",
    "address": "Kolding,Danmark",
    "postCode": "123456",
    "city": "Danmark",
    "country": "SE",
    "birthdateDay": "1",
    "birthdateMonth": "1",
    "birthdateYear": "1999",
    "age": "20",
    "ip": "127.0.0.1"
  }
}
```

### Example of lead error or rejected response

- 1) {"error": "Undefined Api key"}
- 2) {"error": "Api key is blank"}
- 3) {"error": "Invalid apikey"}
- 4) {"error": "Api key is not active. Please contact to admin"}
- 5) {"error": "email is required"}
- 6) {"error": "email is blank"}
- 7) {"error": "Invalid Phone"}
- 8) {"error": "Invalid email format"}
- 9) {"error": "User is blacklisted"}
- 10) {"error": "Duplicate record found"}
- 11) {"error": "Gender should be 'male' or 'female' or other"}
- 12) {"error": "Something went wrong. Please try again later"}