JavaScript Practical

EX1.PROGRAM PRINTING ONLY OUTPUT IN CONSOLE:

```
<html>
<head>
<title>my web page</title>
</head>
<body>
<h1> MY FIRST JS CODE </h1>
<script type="text/javascript">
console.log("Hello World!")
</script>
</body>
</html>
```

EX2. PROGRAM PRINTING OUTPUT IN BROWSER:

```
<html>
<head>
<title>my web page</title>
</head>
<body>
<h1> MY FIRST JS CODE </h1>
<script type="text/javascript">
alert("Hello World!")
</script>
</body>
</html>
```

EX3.PROGRAM USING ID

```
<html>

<html>

<body>


<h2>What Can JavaScript Do?</h2>


<p id="demo">JavaScript can change HTML content.</p>


<button type="button" onclick='document.getElementById("demo").innerHTML = "Hello
JavaScript!"'>Click Me!</button>


</body>

</html>
```

EX4.PROGRAM PRINTING VALUES

```
<html>

<head>

<title> my web page</title>

</head>

<body>

<script>

var a =34;

var b =56;

document.write("the sum of a&b is",  a+b,"<br>")

document.write("the difference of a&b is",  a-b,"<br>")

document.write("the product of a&b is",  a*b,"<br>")

document.write("the division of a&b is",  a/b,"<br>")
```

```
</script>

</body>

</html>
```

EX5.PROGRAM TAKING INPUTS FROM THE USER:

```
<html>

<head>

<title> my web page</title>

</head>

<body>

<script>

var a =prompt("num1:");

var b =prompt("num2");

document.write("the sum of a&b is",  a+b,"<br>")

document.write("the difference of a&b is",  a-b,"<br>")

document.write("the product of a&b is",  a*b,"<br>")

document.write("the division of a&b is",  a/b,"<br>")

</script>

</body>

</html>
```

EX6.PROGRAM ON EMPLOYEES:

```
<html>

<head>

<title> my web page</title>

</head>

<body background="1.jpg">
```

```
<font color="white">
<marquee bgcolor="blue">EMPLOYEE DETAILS</marquee>
<script>
var a =prompt("ENTER EMPLOYEE ID:");
var b =prompt("ENTER EMPLOYEE NAME");
var c =prompt("ENTER BASIC SALARY:");
var d =c*0.20;
document.write("THE EMPLOYEE ID IS :",  a,"<br>")
document.write("THE EMPLOYEE NAME IS :",  b,"<br>")
document.write("THE BASIC SALALRY :",  c,"<br>")
document.write("THE DA IS: ",  d,"<br>")
</script>
</font>
</body>
</html>
```

EX7.PROGRAM USING WHILE LOOP

```
<!DOCTYPE html>
<html>
<head>
</head>
<body>
<script language = "javascript" type = "text/javascript">
var number = 1
while (number<=10)
{
document.write("NUMBER = " + number + "<br>")
```

```
number++
}
document.write ("GET OUT OF THE LOOP WHEN NUMBER IS = " + number)
</script>
</body>
</html>
```

EX8.PROGRAM USING IF AND ELSE:

```
<html>
<head>
<title> my web page</title>
</head>
<body background="1.jpg">
<font color="white">
<script>
var a =prompt("ENTER AGE:");
if (a<=18)
{
document.write("You cannot drive","<br>");
}
else
{
document.write("You Can Drive",);
}
</script>
</font>
</body>
```

```
</html>
```

EX9.PROGRAM ON SIMPLE INTEREST:

```
<html>
<head>
<title> my web page</title>
</head>
<body>
<font color="BLUE">
<script>
var a =parseInt(prompt("ENTER PRINCIPAL:"));
var b =prompt("ENTER RATE OF INTEREST");
var c =prompt("ENTER YEAR:");
var d =parseInt(a*b*c)*0.01;
var e=parseInt(a+d);
document.write("THE PRINCIPAL IS :",  a,"<br>")
document.write("THE RATE OF INTEREST IS :",  b,"<br>")
document.write("THE YEAR IS :",  c,"<br>")
document.write("THE SI IS: ",  d,"<br>")
document.write("THE AMOUNT IS: ",  e,"<br>")
</script>
</font>
</body>
</html>
```

EX10.PROGRAM ON IF AND ELSE BY GIVING INPUTS:

```
<html>
```

```
<head>
<title> my web page</title>
</head>
<body background="1.jpg">
<font color="white">
<script>
var a =prompt("ENTER NUMBER 1:");
var b =prompt("ENTER NUMBER 2:");
if (a>b)
{
document.write("a is greater than b","<br>");
}
else
{
document.write("a is less than b",);
}
</script>
</font>
</body>
</html>
```

EX11.PROGRAM SHOWING RESULT:

```
<html>
<head>
<title> my web page</title>
</head>
<body>
```

```
<font color="BLUE">
<script>
var a =parseInt(prompt("ENTER CCA MARKS:"));
var b =parseInt(prompt("ENTER TALLY MARKS:"));
var c =parseInt(prompt("ENETR DIA MARKS:"));
var d =parseInt(a+b+c);
var avg=parseFloat(d/3);
document.write("THE CCA MARKS IS :",  a,"<br>")
document.write("THE TALLY  MARKS IS :",  b,"<br>")
document.write("THE DIA MARKS :",  c,"<br>")
document.write("THE TOTAL MARKS IS: ",  d,"<br>")
document.write("THE AVERAGE MARKS IS: ",  avg,"<br>")
if(avg>95) {
alert("THE GRADE IS A");
}
else if(avg>=85) {
alert("THE GRADE IS B");
}
else if(avg>=70) {
alert("THE GRADE IS C");
}
else if(avg>=60) {
alert("THE GRADE IS D");
}
else if(avg>=50)  {
alert("THE GRADE IS E");
}
```

```
else {
alert("FAIL");
}
</script>
</font>
</body>
</html>
```

EX12.PROGRAM USING FOR LOOP BY TAKING INPUTS:

```
<html>
<head>
<title> my web page</title>
</head>
<body background="1.jpg">
<font color="white">
<script>
var a =prompt("ENTER NAME:");
document.write(a,"<br>");
for (var i=0;i<=100;i++)
{
document.write(a,"<br>")
}
</script>
</font>
</body>
</html>
```

EX13.PROGRAM USING FOR LOOP:

```
<html>
<head>
<title> my web page</title>
</head>
<body background="1.jpg">
<font color="white">
<script>
var i;
document.write("THE FIRST 100 NATURAL NUMBERS","<br>")
for (var i=0;i<=100;i++)
{
document.write(i,"<br>")
}
</script>
</font>
</body>
</html>
```

EX14.PROGRAM ON INFINITE LOOP:

```
<html>
<head>
<title> my web page</title>
</head>
<body background="1.jpg">
<font color="white">
<script>
```

```
var i;
document.write("THE FIRST 100 NATURAL NUMBERS","<br>")
for (var i=1;i>0;i++)
{
document.write(i,"<br>")
}
</script>
</font>
</body>
</html>
```

EX15.PROGRAM ON LEAP YEAR:

```
<html>
<head>
<title> my web page</title>
</head>
<body background="1.jpg">
<font color="white">
<script>
var a =prompt("ENTER year:");
a= (a%4);
if(a==0)
{
document.write("The Year is a leap Year","<br>");
}
else
{
```

```
document.write("The Year is not a leap Year",);

}

</script>

</font>

</body>

</html>
```