

Teamwork — Session 4: Reset activity, across two slices

Context

Work in your team. The class splits into **six teams of four students**.

`selectTotalActivityCount` already composes `savedOpportunities` and `recentlyViewed` into one number. Nothing in the app can clear both slices at once, in one action.

Goal

Add one derived selector on top of the one already built today, and one control that resets both slices from a single click.

What to build

1. **A derived boolean selector**, in `client/src/store/selectors.ts`, next to `selectTotalActivityCount`: `selectHasAnyActivity(state)`, true whenever there is anything to reset. Build it from `selectTotalActivityCount` — do not recompute the sum yourself.
2. **A "Reset activity" control**, in the Opportunities panel header, near the Activity summary:
 - visible only when `selectHasAnyActivity` is true;
 - on click, clears **both** slices — every saved opportunity and every recently-viewed entry;
 - styled as a secondary, cautionary action (not a primary button).
1. **Decide, and be ready to justify**: does clearing both slices need a new reducer that spans both of them, or can the component that has the button do it another way?

Rules

Allowed — everything from today's live coding: `useAppDispatch`, `useAppSelector`, composing one selector from another, dispatching an existing action from a component.

Not yet (do not use these) — `createAsyncThunk`, `extraReducers`, RTK Query, `createSelector`, custom middleware, persistence libraries.

Do not add a new slice. Do not add a reducer that touches more than one slice's state — a slice's reducers only ever change that slice's own state.

Test it

- With nothing saved and nothing recently viewed, the Reset activity button does not appear.
- Save two opportunities and view a couple of detail pages: the button appears.

- Press it: every star resets, the Navbar badge disappears, the Activity line reads `Activity: 0`, the recently-viewed strip disappears, and the button itself disappears (nothing left to reset).
- `npm run build` and `npm run lint` pass with 0 errors.

Done when

- Both items above are implemented.
- `selectHasAnyActivity` is defined once, calls `selectTotalActivityCount`, and is not duplicated anywhere.
- `npm run build` and `npm run lint` pass with 0 errors.
- Your team's attempt is committed and pushed to your own branch.

Working time

About **25 minutes**, then the official solution is demonstrated.

Before the solution is shown

Commit and push your team's attempt to your own `student-<your-github-username>` branch **before** the official solution is demonstrated. Pushing your own attempt first is part of the exercise.

Be ready to answer

- Why does `selectHasAnyActivity` call `selectTotalActivityCount` instead of comparing `state.savedOpportunities.savedIds.length + state.recentlyViewed.entries.length` to zero directly?
- Both slices need to end up empty. Is that one action, or two? Why?
- If a third slice were added to this app tomorrow, what — if anything — would have to change about `selectHasAnyActivity`'s callers to make the Reset button also clear it?