

# zi.zsh(1)

## NAME

zi.zsh - a shell script

## SYNOPSIS

Documentation automatically generated with `zsdoc'

## FUNCTIONS

```

@autoload
pmodload
zi
.zi-add-fpath
.zi-add-report
.zi-any-to-pid
.zi-any-to-user-plugin
zicdclear
zicdreplay
zicompdef
.zi-compdef-clear
.zi-compdef-replay
zicompinit
zicompinit_fast
+zi-deploy-message
.zi-diff
.zi-diff-env
.zi-diff-functions
.zi-diff-options
.zi-diff-parameter
.zi-find-other-matches
.zi-formatter-auto
.zi-formatter-bar
.zi-formatter-bar-util
.zi-formatter-pid
.zi-formatter-th-bar
.zi-formatter-url
.zi-get-mtime-into
.zi-get-object-path
.zi-ice
.zi-load
.zi-load-ices
.zi-load-object
```

```

.zi-load-plugin
.zi-load-snippet
.zi-main-message-formatter
+zi-message
.zi-pack-ice
.zi-parse-opts
+zi-prehelp-usage-message
.zi-prepare-home
@zi-register-annex
@zi-register-hook
.zi-register-plugin
:zi-reload-and-run
.zi-run
.zi-run-task
-zi_scheduler_add_sh
.zi-set-m-func
.zi-setup-params
.zi-submit-turbo
@zi-substitute
:zi-tmp-subst-alias
:zi-tmp-subst-autoload
:zi-tmp-subst-bindkey
:zi-tmp-subst-compdef
.zi-tmp-subst-off
.zi-tmp-subst-on
:zi-tmp-subst-zle
:zi-tmp-subst-zstyle
zi-turbo
.zi-util-shands-path
zpcdclear
zpcdreplay
zpcmpdef
zpcmpinit
@zsh-plugin-run-on-unload
@zsh-plugin-run-on-update
AUTOLOAD add-zsh-hook
AUTOLOAD compinit
AUTOLOAD is-at-least
PRECMD-HOOK @zi-scheduler

```

## DETAILS

### Script Body

Has 279 line(s). Calls functions:

```

Script-Body
|-- add-zsh-hook

```

```
|-- is-at-least
|-- side.zsh/.zi-check-module
`-- @zi-register-hook
```

Uses feature(s): *add-zsh-hook, alias, autoload, is-at-least, setopt, source, zmodload, zstyle*

▣▼▣~

```
]]]
Compatibility functions. [[[
```

Has 1 line(s). Calls functions:

```
[[[
`-- zi
    |-- additional.zsh/.zi-clear-debug-report
    |-- additional.zsh/.zi-debug-start
    |-- additional.zsh/.zi-debug-stop
    |-- additional.zsh/.zi-debug-unload
    |-- autoload.zsh/.zi-analytics-menu
    |-- autoload.zsh/.zi-cdisable
    |-- autoload.zsh/.zi-cenable
    |-- autoload.zsh/.zi-clear-completions
    |-- autoload.zsh/.zi-compiled
    |-- autoload.zsh/.zi-compile-uncompile-all
    |-- autoload.zsh/.zi-help
    |-- autoload.zsh/.zi-list-bindkeys
    |-- autoload.zsh/.zi-list-compdef-replay
    |-- autoload.zsh/.zi-ls
    |-- autoload.zsh/.zi-module
    |-- autoload.zsh/.zi-recently
    |-- autoload.zsh/.zi-registered-ice-mods
    |-- autoload.zsh/.zi-registered-subcommands
    |-- autoload.zsh/.zi-search-completions
    |-- autoload.zsh/.zi-self-update
    |-- autoload.zsh/.zi-show-all-reports
    |-- autoload.zsh/.zi-show-completions
    |-- autoload.zsh/.zi-show-debug-report
    |-- autoload.zsh/.zi-show-registered-plugins
    |-- autoload.zsh/.zi-show-report
    |-- autoload.zsh/.zi-show-times
    |-- autoload.zsh/.zi-show-zstatus
    |-- autoload.zsh/.zi-uncompile-plugin
    |-- autoload.zsh/.zi-uninstall-completions
    |-- autoload.zsh/.zi-unload
    |-- autoload.zsh/.zi-update-or-status
    |-- autoload.zsh/.zi-update-or-status-all
    |-- compinit
```

```
|-- install.zsh/.zi-compile-plugin
|-- install.zsh/.zi-compinit
|-- install.zsh/.zi-forget-completion
|-- install.zsh/.zi-install-completions
|-- +zi-message
`-- +zi-prehelp-usage-message
    `-- +zi-message
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## @autoload

```
]]]
FUNCTION: @autoload. [[[
```

Has 1 line(s). Calls functions:

```
@autoload
`-- :zi-tmp-subst-autoload
    |-- is-at-least
    `-- +zi-message
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## pmodload

```
FUNCTION: pmodload. [[[
Compatibility with Prezto. Calls can be recursive.
```

Has 15 line(s). Calls functions:

```
pmodload
```

Uses feature(s): *zstyle*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## zi

```
FUNCTION: zi. [[[
Main function directly exposed to user, obtains subcommand and its arguments, has
```

completion.

Has 550 line(s). Calls functions:

```
zi
|-- additional.zsh/.zi-clear-debug-report
|-- additional.zsh/.zi-debug-start
|-- additional.zsh/.zi-debug-stop
|-- additional.zsh/.zi-debug-unload
|-- autoload.zsh/.zi-analytics-menu
|-- autoload.zsh/.zi-cdisable
|-- autoload.zsh/.zi-cenable
|-- autoload.zsh/.zi-clear-completions
|-- autoload.zsh/.zi-compiled
|-- autoload.zsh/.zi-compile-uncompile-all
|-- autoload.zsh/.zi-help
|-- autoload.zsh/.zi-list-bindkeys
|-- autoload.zsh/.zi-list-compdef-replay
|-- autoload.zsh/.zi-ls
|-- autoload.zsh/.zi-module
|-- autoload.zsh/.zi-recently
|-- autoload.zsh/.zi-registered-ice-mods
|-- autoload.zsh/.zi-registered-subcommands
|-- autoload.zsh/.zi-search-completions
|-- autoload.zsh/.zi-self-update
|-- autoload.zsh/.zi-show-all-reports
|-- autoload.zsh/.zi-show-completions
|-- autoload.zsh/.zi-show-debug-report
|-- autoload.zsh/.zi-show-registered-plugins
|-- autoload.zsh/.zi-show-report
|-- autoload.zsh/.zi-show-times
|-- autoload.zsh/.zi-show-zstatus
|-- autoload.zsh/.zi-uncompile-plugin
|-- autoload.zsh/.zi-uninstall-completions
|-- autoload.zsh/.zi-unload
|-- autoload.zsh/.zi-update-or-status
|-- autoload.zsh/.zi-update-or-status-all
|-- compinit
|-- install.zsh/.zi-compile-plugin
|-- install.zsh/.zi-compinit
|-- install.zsh/.zi-forget-completion
|-- install.zsh/.zi-install-completions
|-- +zi-message
`-- +zi-prehelp-usage-message
    |-- +zi-message
```

Uses feature(s): *autoload, compinit, eval, setopt, source*

Called by:

□□□

zi-turbo

*zi-add-fpath*

~~~~~

FUNCTION: .zi-add-fpath. [][]

Has 10 line(s). Calls functions:

.zi-add-fpath

Called by:

zi

*zi-add-report*

~~~~~

FUNCTION: .zi-add-report. [][]  
Adds a report line for given plugin.

\$1 - uspl2, i.e. user/plugin  
\$2, ... - the text

Has 3 line(s). Doesn't call other functions.

Called by:

.zi-load-plugin  
.zi-load-snippet  
:zi-tmp-subst-alias  
:zi-tmp-subst-autoload  
:zi-tmp-subst-bindkey  
:zi-tmp-subst-compdef  
:zi-tmp-subst-zle  
:zi-tmp-subst-zstyle

*zi-any-to-pid*

~~~~~

```
FUNCTION: .zi-any-to-pid. [[[
```

Has 21 line(s). Calls functions:

```
.zi-any-to-pid
```

Uses feature(s): *setopt*

Called by:

```
side.zsh/.zi-any-colorify-as-uspl2  
side.zsh/.zi-exists-physically-message  
side.zsh/.zi-first
```

*zi-any-to-user-plugin*

~~~~~

```
FUNCTION: .zi-any-to-user-plugin. [[[  
Allows elastic plugin-spec across the code.
```

```
$1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)  
$2 - plugin (only when $1 - i.e. user - given)
```

```
Returns user and plugin in $reply.
```

Has 25 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Called by:

```
.zi-add-fpath  
.zi-get-object-path  
.zi-load  
.zi-run  
:zi-tmp-subst-autoload  
autoload.zsh/.zi-any-to-uspl2  
autoload.zsh/.zi-changes  
autoload.zsh/.zi-compiled  
autoload.zsh/.zi-compile-uncompile-all  
autoload.zsh/.zi-create  
autoload.zsh/.zi-delete
```

```
autoload.zsh/.zi-find-completions-of-plugin
autoload.zsh/.zi-glance
autoload.zsh/.zi-show-report
autoload.zsh/.zi-stress
autoload.zsh/.zi-uncompile-plugin
autoload.zsh/.zi-unload
autoload.zsh/.zi-unregister-plugin
autoload.zsh/.zi-update-all-parallel
autoload.zsh/.zi-update-or-status-all
autoload.zsh/.zi-update-or-status
install.zsh/.zi-install-completions
side.zsh/.zi-any-colorify-as-uspl2
side.zsh/.zi-compute-ice
side.zsh/.zi-exists-physically-message
side.zsh/.zi-exists-physically
side.zsh/.zi-first
```

## zicdclear

```
]]]
FUNCTION: zicdclear. [[[
A wrapper for 'zi cdclear -q' which can be called from hook ices like the
atinit'', atload'', etc. ices.
```

Has 1 line(s). Calls functions:

```
zicdclear
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## zicdreplay

```
FUNCTION: zicdreplay. [[[
A function that can be invoked from within 'atinit', 'atload', etc. ice-mod.
It works like 'zi cdreplay', which cannot be invoked from such hook ices.
```

Has 1 line(s). Calls functions:

```
zicdreplay
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).



# zicompdef

```
]]]
FUNCTION: zicompdef. [[[
Stores compdef for a replay with 'zicdreplay' (turbo mode) or with 'zi cdreplay'
(normal mode).
An utility function of an undefined use case.
```

Has 1 line(s). Doesn't call other functions.

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-compdef-clear*

~~~~~

```
FUNCTION: .zi-compdef-clear. [[[
Implements user-exposed functionality to clear gathered compdefs.
```

Has 3 line(s). Calls functions:

```
.zi-compdef-clear
`-- +zi-message
```

Called by:

```
zicdclear
zi
zpcdclear
```

*zi-compdef-replay*

~~~~~

```
FUNCTION: .zi-compdef-replay. [[[
Runs gathered compdef calls. This allows to run 'compinit' after loading plugins.
```

Has 16 line(s). Calls functions:

```
.zi-compdef-replay
`-- +zi-message
```

Uses feature(s): *compdef*

Called by:

```
zicdreplay
zi
zpcdreplay
```

## zicompinit

```
]]]
FUNCTION: zicompinit. [[[
A function that can be invoked from within 'atinit', 'atload', etc. ice-mod.
It runs 'autoload compinit; compinit' and respects
ZI[ZCOMP_DUMP_PATH] and ZI[COMPINIT_OPTS].
```

Has 1 line(s). Calls functions:

```
zicompinit
'-- compinit
```

Uses feature(s): *autoload, compinit*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## zicompinit\_fast

```
]]]
FUNCTION: zicompinit_fast. [[[
Checking the cached .zcompdump file to see if it must be regenerated adds a
noticeable delay to zsh startup.
This restricts checking it once a day, determines when to regenerate, as compinit
doesn't always need to
modify the compdump and compiles mapped to share (total mem reduction) run in
background in multiple shells.
A function that can be invoked from within 'atinit', 'atload'
```

Has 13 line(s). Calls functions:

```
zicompinit_fast
'-- compinit
```

Uses feature(s): *autoload, compinit, zcompile*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## +zi-deploy-message

```
FUNCTION: +zi-deploy-message. [[[
Deploys a sub-prompt message to be displayed OR a `zle
.reset-prompt' call to be invoked
```

Has 13 line(s). Doesn't call other functions.

Uses feature(s): *read, zle*

Called by:

```
.zi-load-snippet
.zi-load
autoload.zsh/.zi-recall
```

*zi-diff*

~ ~ ~

```
FUNCTION: .zi-diff. [[[
Performs diff actions of all types
```

Has 4 line(s). Calls functions:

```
.zi-diff
```

Called by:

```
.zi-load-plugin
additional.zsh/.zi-debug-start
additional.zsh/.zi-debug-stop
```

*zi-diff-env*

~ ~ ~ ~

```
FUNCTION: .zi-diff-env. [[[
Implements detection of change in PATH and FPATH.
```

```
$1 - user/plugin (i.e. uspl2 format)
$2 - command, can be "begin" or "end"
```

Has 15 line(s). Doesn't call other functions.

Called by:

```
.zi-diff  
.zi-load-plugin
```

#### *zi-diff-functions*

~~~~~

```
FUNCTION: .zi-diff-functions. [[[  
Implements detection of newly created functions. Performs data gathering,  
computation is done in *-compute().
```

```
$1 - user/plugin (i.e. uspl2 format)  
$2 - command, can be "begin" or "end"
```

Has 3 line(s). Doesn't call other functions.

Called by:

```
.zi-diff
```

#### *zi-diff-options*

~~~~~

```
FUNCTION: .zi-diff-options. [[[  
Implements detection of change in option state. Performs data gathering,  
computation is done in *-compute().
```

```
$1 - user/plugin (i.e. uspl2 format)  
$2 - command, can be "begin" or "end"
```

Has 2 line(s). Doesn't call other functions.

Called by:

```
.zi-diff
```

#### *zi-diff-parameter*

~~~~~

```
FUNCTION: .zi-diff-parameter. [[[
Implements detection of change in any parameter's existence and type.
Performs data gathering, computation is done in *-compute().
```

```
$1 - user/plugin (i.e. uspl2 format)
$2 - command, can be "begin" or "end"
```

Has 6 line(s). Doesn't call other functions.

Called by:

```
.zi-diff
```

*zi-find-other-matches*

~~~~~

```
FUNCTION: .zi-find-other-matches. [[[
Plugin's main source file is in general `name.plugin.zsh'. However,
there can be different conventions, if that file is not found, then
this functions examines other conventions in the most sane order.
```

Has 17 line(s). Doesn't call other functions.

Called by:

```
.zi-load-plugin
.zi-load-snippet
side.zsh/.zi-first
```

*zi-formatter-auto*

~~~~~

```
FUNCTION: .zi-formatter-auto[[[
The automatic message formatting tool automatically detects,
formats, and colorizes the following pieces of text:
[URLs], [plugin IDs (user/repo) if exists on the disk], [numbers], [time],
[single-word id-as plugins],
[single word commands], [single word functions], [zi commands], [ice modifiers
(e.g: mv'a -> b')],
[single-char bits and quoted strings ('...', ',...', "...")].
```

Has 46 line(s). Calls functions:

```
.zi-formatter-auto
```

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-formatter-bar*

~~~~~

```
FUNCTION: .zi-formatter-bar. [[[
```

Has 1 line(s). Calls functions:

```
.zi-formatter-bar
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-formatter-bar-util*

~~~~~

```
FUNCTION: .zi-formatter-bar-util. [[[
```

Has 6 line(s). Doesn't call other functions.

Called by:

```
.zi-formatter-bar  
.zi-formatter-th-bar
```

*zi-formatter-pid*

~~~~~

```
FUNCTION: .zi-formatter-pid. [[[
```

Has 10 line(s). Calls functions:

```
.zi-formatter-pid  
'-- side.zsh/.zi-any-colorify-as-uspl2
```

Uses feature(s): *source*

Called by:

```
.zi-formatter-auto
```

*zi-formatter-th-bar*

~~~~~

```
FUNCTION: .zi-formatter-th-bar. [[
```

Has 1 line(s). Calls functions:

```
.zi-formatter-th-bar
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-formatter-url*

~~~~~

```
FUNCTION: .zi-formatter-url. [[
```

Has 14 line(s). Doesn't call other functions.

Called by:

```
.zi-formatter-auto
```

*zi-get-mtime-into*

~~~~~

```
FUNCTION: .zi-get-mtime-into. [[
```

Has 7 line(s). Doesn't call other functions.

Called by:

```
Script-Body
autoload.zsh/.zi-self-update
autoload.zsh/.zi-update-or-status-all
```

*zi-get-object-path*

~~~~~

```
FUNCTION: .zi-get-object-path. [[[
```

Has 23 line(s). Calls functions:

```
.zi-get-object-path
```

Called by:

```
.zi-load-ices  
.zi-load-snippet  
.zi-run  
zi  
autoload.zsh/.zi-get-path  
install.zsh/.zi-setup-plugin-dir  
install.zsh/.zi-update-snippet  
side.zsh/.zi-first  
side.zsh/.zi-two-paths
```

*zi-ice*

~~~

```
FUNCTION: .zi-ice. [[[  
Parses ICE specification, puts the result into ICE global hash. The ice-spec is  
valid for  
next command only (i.e. it "melts"), but it can then stick to plugin and activate  
e.g. at update.
```

Has 12 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Called by:

```
zi
```

*zi-load*

~~~

```
FUNCTION: .zi-load. [[[  
Implements the exposed-to-user action of loading a plugin.
```

```
$1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)
```



\$2 - plugin name, if the third format is used

Has 78 line(s). Calls functions:

```
.zi-load  
|-- install.zsh/.zi-get-package  
|-- install.zsh/.zi-setup-plugin-dir  
'-- +zi-deploy-message
```

Uses feature(s): *eval, setopt, source, zle*

Called by:

```
.zi-load-object  
.zi-run-task  
additional.zsh/.zi-service
```

*zi-load-ices*

~~~~~

FUNCTION: .zi-load-ices. [[[

Has 22 line(s). Calls functions:

```
.zi-load-ices
```

Called by:

```
zi
```

*zi-load-object*

~~~~~

FUNCTION: .zi-load-object. [[[

Has 10 line(s). Calls functions:

```
.zi-load-object
```

Called by:

zi

### zi-load-plugin

~~~~~

FUNCTION: .zi-load-plugin. [[[  
Lower-level function for loading a plugin.

\$1 - user  
\$2 - plugin  
\$3 - mode (light or load)

Has 107 line(s). Calls functions:

```
.zi-load-plugin  
|-- additional.zsh/.zi-wrap-functions  
'-- :zi-tmp-subst-autoload  
    |-- is-at-least  
    '-- +zi-message
```

Uses feature(s): *eval, setopt, source, unfunction, zle*

Called by:

.zi-load

### zi-load-snippet

~~~~~

FUNCTION: .zi-load-snippet. [[[  
Implements the exposed-to-user action of loading a snippet.

\$1 - url (can be local, absolute path).

Has 173 line(s). Calls functions:

```
.zi-load-snippet  
|-- additional.zsh/.zi-wrap-functions  
|-- install.zsh/.zi-download-snippet  
|-- +zi-deploy-message
```

```
`-- +zi-message
```

Uses feature(s): *autoload, eval, setopt, source, unfunction, zparseopts, zstyle*

Called by:

```
pmodload
.zi-load-object
.zi-load
.zi-run-task
additional.zsh/.zi-service
```

*zi-main-message-formatter*

~~~~~

```
FUNCTION: +zi-message-formatter [[[
```

Has 18 line(s). Doesn't call other functions.

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## +zi-message

```
FUNCTION: +zi-message. [[[
```

Has 13 line(s). Doesn't call other functions.

Called by:

```
.zi-compdef-clear
.zi-compdef-replay
.zi-load-snippet
+zi-prehelp-usage-message
.zi-register-plugin
.zi-run
.zi-set-m-func
:zi-tmp-subst-autoload
zi
additional.zsh/.zi-debug-start
additional.zsh/.zi-debug-unload
additional.zsh/:zi-tmp-subst-source
autoload.zsh/.zi-analytics-menu
autoload.zsh/.zi-build-module
autoload.zsh/.zi-cd
autoload.zsh/.zi-clear-completions
```

```

autoload.zsh/.zi-compiled
autoload.zsh/.zi-glance
autoload.zsh/.zi-help
autoload.zsh/.zi-module
autoload.zsh/.zi-registered-ice-mods
autoload.zsh/.zi-registered-subcommands
autoload.zsh/.zi-self-update
autoload.zsh/.zi-show-report
autoload.zsh/.zi-show-zstatus
autoload.zsh/.zi-uncompile-plugin
autoload.zsh/.zi-uninstall-completions
autoload.zsh/.zi-unload
autoload.zsh/.zi-update-all-parallel
autoload.zsh/.zi-update-or-status-all
autoload.zsh/.zi-update-or-status
autoload.zsh/.zi-wait-for-update-jobs
install.zsh/.zi-compile-plugin
install.zsh/.zi-compinit
install.zsh/.zi-download-file-stdout
install.zsh/.zi-download-snippet
install.zsh/.zi-extract
install.zsh/ziextract
install.zsh/.zi-get-cygwin-package
install.zsh/.zi-get-latest-gh-r-url-part
install.zsh/.zi-get-package
install.zsh/.zi-install-completions
install.zsh/.zi-mirror-using-svn
install.zsh/zi-mv-hook
install.zsh/zi-ps-on-update-hook
install.zsh/zi-reset-hook
install.zsh/.zi-setup-plugin-dir
install.zsh/.zi-update-snippet
side.zsh/.zi-check-module
side.zsh/.zi-countdown
side.zsh/.zi-exists-physically-message

```

### *zi-pack-ice*

```

FUNCTION: .zi-pack-ice. [[
Remembers all ice-mods, assigns them to concrete plugin. Ice spec is in general
forgotten for
second-next command (that's why it's called "ice" - it melts), however they glue
to the object (plugin
or snippet) mentioned in the next command for later use with e.g. `zi update
...'.

```

Has 3 line(s). Doesn't call other functions.

Called by:

```
.zi-load-snippet  
.zi-load  
@zsh-plugin-run-on-unload  
@zsh-plugin-run-on-update  
install.zsh/.zi-update-snippet  
side.zsh/.zi-compute-ice
```

*zi-parse-opts*

~~~~~

```
]]]  
FUNCTION: +zi-parse-opts. [[[
```

Has 2 line(s). Doesn't call other functions.

Called by:

```
zi  
autoload.zsh/.zi-delete
```

## **+zi-prehelp-usage-message**

```
FUNCTION: +zi-prehelp-usage-message. [[[  
Prints the usage message.
```

Has 34 line(s). Calls functions:

```
+zi-prehelp-usage-message  
'-- +zi-message
```

Called by:

```
zi  
autoload.zsh/.zi-delete
```

*zi-prepare-home*

~~~~~

```
FUNCTION: .zi-prepare-home. [[[
```

Establish all required directories.

Has 64 line(s). Calls functions:

```
.zi-prepare-home  
|-- autoloader.zsh/.zi-clear-completions  
'-- install.zsh/.zi-compinit
```

Uses feature(s): *source*

Called by:

Script-Body

## @zi-register-annex

```
FUNCTION: @zi-register-annex. [[  
Registers the z-annex inside Zi □ i.e. an Zi extension
```

Has 10 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## @zi-register-hook

```
FUNCTION: @zi-register-hook. [[  
Registers the z-annex inside Zi.
```

Has 6 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Called by:

Script-Body

*zi-register-plugin*

~~~~~

```
FUNCTION: .zi-register-plugin. [[[
Adds the plugin to ZI_REGISTERED_PLUGINS array and to the
zsh_loaded_plugins array (managed according to the plugin standard:
https://wiki.zshell.dev/community/zsh\_plugin\_standard).
```

Has 20 line(s). Calls functions:

```
.zi-register-plugin
`-- +zi-message
```

Called by:

```
.zi-load
```

## :zi-reload-and-run

```
FUNCTION: :zi-reload-and-run. [[[
Marks given function ($3) for autoloading, and executes it triggering the load.
$1 is the fpath dedicated to the function, $2 are autoload options. This
function replaces "autoload -X",
because using that on older Zsh versions causes problems with traps.
```

So basically one creates function stub that calls :zi-reload-and-run() instead of "autoload -X".

```
$1 - FPATH dedicated to function
$2 - autoload options
$3 - function name (one that needs autoloading)
```

Author: Bart Schaefer

Has 9 line(s). Doesn't call other functions.

Uses feature(s): *autoload*, *unfunction*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-run*

~

```
FUNCTION: .zi-run. [[[
Run code inside plugin's folder
It uses the 'correct' parameter from upper's scope zi().
```

Has 24 line(s). Calls functions:

```
.zi-run
`-- +zi-message
```

Uses feature(s): *eval, setopt*

Called by:

```
zi
```

*zi-run-task*

```
FUNCTION: .zi-run-task. [[[
A backend, worker function of .zi-scheduler. It obtains the tasks
index and a few of its properties (like the type: plugin, snippet,
service plugin, service snippet) and executes it first checking for
additional conditions (like non-numeric wait'' ice).
```

```
$1 - the pass number, either 1st or 2nd pass
$2 - the time assigned to the task
$3 - type: plugin, snippet, service plugin, service snippet
$4 - task's index in the ZI[WAIT_ICE...] fields
$5 - mode: load or light
$6 - the plugin-spec or snippet URL or alias name (from id-as'')
```

Has 45 line(s). Calls functions:

```
.zi-run-task
`-- autoload.zsh/.zi-unload
```

Uses feature(s): *eval, source, zle, zpty*

Called by:

```
@zi-scheduler
```



## @zi-scheduler

FUNCTION: @zi-scheduler. [[[  
Searches for timeout tasks, executes them. There's an array of tasks waiting for execution, this scheduler manages them, detects which ones should be run at current moment, decides to remove (or not) them from the array after execution.

\$1 - if "following", then it is non-first (second and more) invocation of the scheduler; this results in chain of 'sched' invocations that results in repetitive @zi-scheduler activity.

if "burst", then all tasks are marked timeout and executed one by one; this is handy if e.g. a docker image starts up and needs to install all turbo-mode plugins without any hesitation (delay), i.e. "burst" allows to run package installations from script, not from prompt.

Has 72 line(s). **Is a precmd hook.** Calls functions:

```
@zi-scheduler  
'-- add-zsh-hook
```

Uses feature(s): *add-zsh-hook*, *sched*, *zle*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## -zi\_scheduler\_add\_sh

FUNCTION: -zi\_scheduler\_add\_sh. [[[  
Copies task into ZI\_RUN array, called when a task timeouts.  
A small function ran from pattern in /-substitution as a math function.

Has 7 line(s). Doesn't call other functions.

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-set-m-func*

~~~~~

```
FUNCTION:.zi-set-m-func() [[[
```

```
Sets and withdraws the temporary, atclone/atpull time function `m`.
```

Has 17 line(s). Calls functions:

```
.zi-set-m-func  
`-- +zi-message
```

Uses feature(s): *setopt*

Called by:

```
.zi-load-snippet  
.zi-load  
autoload.zsh/.zi-update-or-status
```

*zi-setup-params*

~~~~~

```
FUNCTION: .zi-setup-params. [[
```

Has 3 line(s). Doesn't call other functions.

Called by:

```
.zi-load-snippet  
.zi-load
```

*zi-submit-turbo*

~~~~~

```
FUNCTION: .zi-submit-turbo. [[  
If `zi load`, `zi light` or `zi snippet` will be  
preceded with `wait`, `load`, `unload` or `on-update-of`/`subscribe`  
ice-mods then the plugin or snippet is to be loaded in turbo-mode,  
and this function adds it to internal data structures, so that  
@zi-scheduler can run (load, unload) this as a task.
```

Has 16 line(s). Doesn't call other functions.

Called by:

```
zi
```

## @zi-substitute

```
FUNCTION: @zi-substitute. [[[
```

Has 36 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Called by:

```
autoload.zsh/.zi-at-eval
install.zsh/zi-atclone-hook
install.zsh/.zi-at-eval
install.zsh/zi-cp-hook
install.zsh/zi-extract-hook
install.zsh/.zi-get-package
install.zsh/zi-make-ee-hook
install.zsh/zi-make-e-hook
install.zsh/zi-make-hook
install.zsh/zi-mv-hook
```

## :zi-tmp-subst-alias

```
FUNCTION: :zi-tmp-subst-alias. [[[
Function defined to hijack plugin's calls to the 'alias' builtin.
```

The hijacking is to gather report data (which is used in unload).

Has 30 line(s). Calls functions:

```
:zi-tmp-subst-alias
```

Uses feature(s): *alias*, *setopt*, *zparseopts*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## :zi-tmp-subst-autoload

```
FUNCTION: :zi-tmp-subst-autoload. [[[
Function defined to hijack plugin's calls to the 'autoload' builtin.
```

The hijacking is not only to gather report data, but also to run custom 'autoload' function, that doesn't need FPATH.

Has 105 line(s). Calls functions:

```
:zi-tmp-subst-autoload  
|-- is-at-least  
'-- +zi-message
```

Uses feature(s): *autoload*, *eval*, *is-at-least*, *setopt*, *zparseopts*

Called by:

```
@autoload  
.zi-load-plugin
```

## :zi-tmp-subst-bindkey

FUNCTION: :zi-tmp-subst-bindkey. [[  
Function defined to hijack plugin's calls to the 'bindkey' builtin.

The hijacking is to gather report data (which is used in unload).

Has 106 line(s). Calls functions:

```
:zi-tmp-subst-bindkey  
'-- is-at-least
```

Uses feature(s): *bindkey*, *is-at-least*, *setopt*, *zparseopts*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## :zi-tmp-subst-compdef

FUNCTION: :zi-tmp-subst-compdef. [[  
Function defined to hijack plugin's calls to the 'compdef' function.  
The hijacking is not only for reporting, but also to save compdef calls so that 'compinit' can be called after loading plugins.

Has 5 line(s). Calls functions:

```
:zi-tmp-subst-compdef
```

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-tmp-subst-off*

~~~~~

```
FUNCTION: .zi-tmp-subst-off. [[[
Turn off temporary substituting of functions completely for a given mode ("load",
"light",
"light-b" (i.e. the 'trackbinds' mode) or "compdef").
```

Has 17 line(s). Doesn't call other functions.

Uses feature(s): *setopt*, *unfunction*

Called by:

```
.zi-load-plugin
additional.zsh/.zi-debug-stop
```

*zi-tmp-subst-on*

~~~~~

```
FUNCTION: .zi-tmp-subst-on. [[[
Turn on temporary substituting of functions of builtins and functions according
to passed
mode ("load", "light", "light-b" or "compdef"). The temporary substituting of
functions is
to gather report data, and to hijack 'autoload', 'bindkey' and 'compdef' calls.
```

Has 29 line(s). Doesn't call other functions.

Uses feature(s): *source*

Called by:

```
.zi-load-plugin
additional.zsh/.zi-debug-start
```

## :zi-tmp-subst-zle

FUNCTION: :zi-tmp-subst-zle. [[  
Function defined to hijack plugin's calls to the 'zle' builtin.

The hijacking is to gather report data (which is used in unload).

Has 33 line(s). Calls functions:

:zi-tmp-subst-zle

Uses feature(s): *setopt*, *zle*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## :zi-tmp-subst-zstyle

FUNCTION: :zi-tmp-subst-zstyle. [[  
Function defined to hijack plugin's calls to the 'zstyle' builtin.

The hijacking is to gather report data (which is used in unload).

Has 19 line(s). Calls functions:

:zi-tmp-subst-zstyle

Uses feature(s): *setopt*, *zparseopts*, *zstyle*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## zi-turbo

FUNCTION: zi-turbo. [[  
With zi-turbo first argument is a wait time and suffix, i.e. "0a".  
Anything that doesn't match will be passed as if it were an ice mod.  
Default ices depth'3' and lucid, allowed values [0-9][a-c].

Has 1 line(s). Calls functions:

```

zi-turbo
`-- zi
    |-- additional.zsh/.zi-clear-debug-report
    |-- additional.zsh/.zi-debug-start
    |-- additional.zsh/.zi-debug-stop
    |-- additional.zsh/.zi-debug-unload
    |-- autoload.zsh/.zi-analytics-menu
    |-- autoload.zsh/.zi-cdisable
    |-- autoload.zsh/.zi-cenable
    |-- autoload.zsh/.zi-clear-completions
    |-- autoload.zsh/.zi-compiled
    |-- autoload.zsh/.zi-compile-uncompile-all
    |-- autoload.zsh/.zi-help
    |-- autoload.zsh/.zi-list-bindkeys
    |-- autoload.zsh/.zi-list-compdef-replay
    |-- autoload.zsh/.zi-ls
    |-- autoload.zsh/.zi-module
    |-- autoload.zsh/.zi-recently
    |-- autoload.zsh/.zi-registered-ice-mods
    |-- autoload.zsh/.zi-registered-subcommands
    |-- autoload.zsh/.zi-search-completions
    |-- autoload.zsh/.zi-self-update
    |-- autoload.zsh/.zi-show-all-reports
    |-- autoload.zsh/.zi-show-completions
    |-- autoload.zsh/.zi-show-debug-report
    |-- autoload.zsh/.zi-show-registered-plugins
    |-- autoload.zsh/.zi-show-report
    |-- autoload.zsh/.zi-show-times
    |-- autoload.zsh/.zi-show-zstatus
    |-- autoload.zsh/.zi-uncompile-plugin
    |-- autoload.zsh/.zi-uninstall-completions
    |-- autoload.zsh/.zi-unload
    |-- autoload.zsh/.zi-update-or-status
    |-- autoload.zsh/.zi-update-or-status-all
    |-- compinit
    |-- install.zsh/.zi-compile-plugin
    |-- install.zsh/.zi-compinit
    |-- install.zsh/.zi-forget-completion
    |-- install.zsh/.zi-install-completions
    |-- +zi-message
    `-- +zi-prehelp-usage-message
        `-- +zi-message

```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-util-shands-path*

~~~~~

FUNCTION: .zi-util-shands-path. [[[

Replaces parts of path with %HOME, etc.

Has 8 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Called by:

```
.zi-any-to-pid
```

## zpcdclear

Has 1 line(s). Calls functions:

```
zpcdclear
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## zpcdreplay

Has 1 line(s). Calls functions:

```
zpcdreplay
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## zpcmpdef

Has 1 line(s). Doesn't call other functions.

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## zpcmpinit

Has 1 line(s). Calls functions:

```
zpcmpinit  
'-- compinit
```

Uses feature(s): *autoload*, *compinit*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).



## @zsh-plugin-run-on-unload

```
FUNCTION: @zsh-plugin-run-on-update. [[[
The Plugin Standard required mechanism, see:
https://wiki.zshell.dev/community/zsh\_plugin\_standard
```

Has 2 line(s). Calls functions:

```
@zsh-plugin-run-on-unload
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## @zsh-plugin-run-on-update

```
FUNCTION: @zsh-plugin-run-on-update. [[[
The Plugin Standard required mechanism
```

Has 2 line(s). Calls functions:

```
@zsh-plugin-run-on-update
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

## add-zsh-hook

```
Add to HOOK the given FUNCTION.
HOOK is one of chpwd, precmd, preexec, periodic, zshaddhistory,
zshexit, zsh_directory_name (the _functions subscript is not required).
```

```
With -d, remove the function from the hook instead; delete the hook
variable if it is empty.
```

```
-D behaves like -d, but pattern characters are active in the
function name, so any matching function will be deleted from the hook.
```

Has 93 line(s). Doesn't call other functions.

Uses feature(s): *autoload*, *getopts*

Called by:

```
Script-Body  
@zi-scheduler
```

## compinit

Initialisation for new style completion. This mainly contains some helper functions and setup. Everything else is split into different files that will automatically be made autoloaded (see the end of this file). The names of the files that will be considered for autoloading are those that begin with an underscore (like `_condition`).

The first line of each of these files is read and must indicate what should be done with its contents:

```
`#compdef <names ...>'
```

Has 573 line(s). Doesn't call other functions.

Uses feature(s): *autoload, bindkey, compdef, compdump, eval, read, setopt, unfunction, zle, zstyle*

Called by:

```
zi  
zicompinit  
zicompinit_fast  
zpcompinit
```

## is-at-least

Test whether `$ZSH_VERSION` (or some value of your choice, if a second argument is provided) is greater than or equal to `x.y.z-r` (in argument one). In fact, it'll accept any dot/dash-separated string of numbers as its second argument and compare it to the dot/dash-separated first argument. Leading non-number parts of a segment (such as the "zefram" in 3.1.2-zefram4) are not considered when the comparison is done; only the numbers matter. Any left-out segments in the first argument that are present in the version string compared are considered as zeroes, eg `3 == 3.0 == 3.0.0 == 3.0.0.0` and so on.

Has 56 line(s). Doesn't call other functions.

Called by:

```
Script-Body  
:zi-tmp-subst-autoload  
:zi-tmp-subst-bindkey
```