

additional.zsh(1)

NAME

additional.zsh - a shell script

SYNOPSIS

Documentation automatically generated with `zsdoc'

FUNCTIONS

```
.zi-clear-debug-report  
.zi-debug-start  
.zi-debug-stop  
.zi-debug-unload  
.zi-service  
.zi-wrap-track-functions  
:zi-tmp-subst-source
```

DETAILS

Script Body

Has 1 line(s). No functions are called (may set up e.g. a hook, a Zle widget bound to a key, etc.).

zi-clear-debug-report

~~~~~

```
FUNCTION: .zi-clear-debug-report []  
Forgets dtrace report gathered up to this moment.
```

Has 1 line(s). Calls functions:

```
.zi-clear-debug-report  
'-- autoload.zsh/.zi-clear-report-for
```

Called by:

```
autoload.zsh/.zi-unload
```

zi.zsh/zi

### *zi-debug-start*

~~~~~

FUNCTION: .zi-debug-start []
Starts Dtrace, i.e. session tracking for changes in Zsh state.

Has 9 line(s). Calls functions:

```
.zi-debug-start  
|-- zi.zsh/+zi-message  
|-- zi.zsh/.zi-diff  
'-- zi.zsh/.zi-tmp-subst-on
```

Called by:

zi.zsh/zi

zi-debug-stop

~~~~~

FUNCTION: .zi-debug-stop []  
Stops Dtrace, i.e. session tracking for changes in Zsh state.

Has 3 line(s). Calls functions:

```
.zi-debug-stop  
|-- zi.zsh/.zi-diff  
'-- zi.zsh/.zi-tmp-subst-off
```

Called by:

zi.zsh/zi

### *zi-debug-unload*

~~~~~

FUNCTION: .zi-debug-unload []
Reverts changes detected by dtrace run.

Has 6 line(s). Calls functions:

```
.zi-debug-unload  
|-- autoload.zsh/.zi-unload  
'-- zi.zsh/+zi-message
```

Uses feature(s): *source*

Called by:

```
zi.zsh/zi
```

zi-service

~~~~~

```
]]]  
FUNCTION: .zi-service [[  
Handles given service, i.e. obtains lock, runs it, or waits if no lock
```

```
$1 - type "p" or "s" (plugin or snippet)  
$2 - mode - for plugin (light or load)  
$3 - id - URL or plugin ID or alias name (from id-as'')
```

Has 29 line(s). Calls functions:

```
.zi-service  
|-- zi.zsh/.zi-load  
'-- zi.zsh/.zi-load-snippet
```

Uses feature(s): *kill, read, setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

*zi-wrap-track-functions*

~~~~~

```
FUNCTION: .zi-wrap-track-functions [[
```

Has 19 line(s). Doesn't call other functions.

Uses feature(s): *eval*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

:zi-tmp-subst-source

```
FUNCTION: :zi-tmp-subst-source [[
```

Has 25 line(s). Calls functions:

```
:zi-tmp-subst-source  
'-- zi.zsh/+zi-message
```

Uses feature(s): *eval*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).