

DAFNA – RestFul API for Truth Discovery Algorithms

API DOCUMENTATION

M. Lamine Ba, Hossam. H. Hammady, Laure Berti-Equille

Hamad Bin Khalifa University



Creation date: November 5, 2015

Revision date: December 6, 2015

Contents

1 Introduction	3
2 Authentication	3
3 Request Format	3
3.1 Scheme	3
3.2 Methods	4
3.3 Base URL	4
3.4 Request Content Type	4
4 Response Format	5
4.1 HTTP Status Codes	5
4.2 Response Body Format	5
5 Endpoints	5
5.1 POST Endpoints	5
5.2 GET Endpoints	7
5.3 DELETE Endpoints	8
6 Supported Algorithms	9
6.1 Cosine	9
6.2 2-Estimates	9
6.3 3-Estimates	10
6.4 Depen	10
6.5 Accu	11
6.6 AccuSim	12
6.7 AccuNoDep	13
6.8 TruthFinder	14
6.9 SimpleLCA	14
6.10GuessLCA	15
6.11MLE	15
6.12LTM	15
7 DAFNA API Usage: Use Case	17
8 Job Monitoring using Pusher	17
9 Online Tool: AllegatorTrack	18
10Further Developments	18
11Questions or Feedbacks	19

1 Introduction

Data Forensics with Analytics, or for short DAFNA, is a project initiated by the Data Analytics Group in Qatar Computing Research Institute, Hamad Bin Khalifa University. One of its various facets aims at providing efficient algorithms and tools for verifying the veracity of information provided by multiple conflicting sources. The DAFNA API for truth discovery is a RestFul API that enables end user applications to access and use twelve existing truth discovery algorithms for fact checking and truth discovery when they have to integrate heterogeneous information coming from untrustworthy sources. This documentation details the use of the API for third-party applications.

If you use this API or related achievements such as the online tool AllegatorTrack, please do not forget to acknowledge the authors by citing “Dalia Attia Waguih, Naman Goel, Hossam M. Hammady, Laure Berti-Equille. AllegatorTrack: Combining and Reporting Results of Truth Discovery from Multi-source Data. The 31th International Conference on Data Engineering (ICDE), Seoul, Korea, 2015”.

2 Authentication

Third party developers wanting to test DAFNA API for truth discovery, or integrate it in their own applications, need to first get the necessary access credentials. To obtain credentials, every 3rd party developer must follow the process below.

- Go to AllegatorTrack
- Register using a valid email id and email confirmation
- Contact DAFNA developers for token access.

Upon token access request done, the user will receive from DAFNA developers the following access credentials.

- **Authentication Token:** API user’s access key
- **Encrypted Password:** user’s secret key

3 Request Format

3.1 Scheme

Requests to the API endpoints are done using plain HTTP. HTTPS is planned to be supported in the future development of the API for ensuring a more secure transmission of the Access Token.

3.2 Methods

The current version of DAFNA API supports three HTTP Requests, i.e., **GET**, **POST**, and **DELETE**, with respect to the operations, for instance creation, listing, or removal of datasets, the 3rd party applications would like to perform on the behalf on the client.

3.3 Base URL

The API is accessible through the following base URL.

- <http://dafna.qcri.org/>

Every endpoint of the API must be appended to this given base URL. For instance, to list the set of available datasets, client must use the following URL.

GET <http://dafna.qcri.org/datasets/>

3.4 Request Content Type

Either (1) "application/x-www-form-urlencoded" or (2) "application/json" can be used as the request content type (HTTP request "Content-Type" header value). If (1) is used, all parameters should be encoded in the URL as a query string with proper escapes and separated by &. If (2) is used, the request body should be a well-formed JSON object.

1. url-encoded form

POST http://dafna.qcri.org/runsets?checked_algo=array_of_parameters

2. json encoding

POST <http://dafna.qcri.org/runsets> {checked_algo: array_of_parameters,
general_config: array_numerical_values}

Note that when using some command line tools to issue your requests, the way the body content is passed could be slighted different. For example, when a particular user issues requests through command lines via "Curl", (1) and (2) argument passing techniques are respectively implemented as follows.

```
curl -X DELETE http://dafna.qcri.org/runsets/1/ -d "user_token=some_string_here"
```

and

```
curl -X POST http://dafna.qcri.org/runsets -H "Content-type: application/json" -d  
'{"user_token": "some_string_here", "datasets": {"dataset_id": "1", "gt_id": "1"},  
"checked_algo": {"Accu": ["0.2", "0", "100", "0.5", "false", "true", "true",  
"false"] }, "general_config": ["0.001", "0.8", "1", "0.4"]}'
```

4 Response Format

4.1 HTTP Status Codes

- **200:** Successful Requests (otherwise, an internal error will occur)
- **401:** Unauthorized Access, e.g., missing, invalid, or expired token
- **403:** Forbidden Access to the resource requested by the client
- **404:** Not Found Resource requested by the user
- **422:** Invalid Action on the accessed resource

4.2 Response Body Format

Responses to user queries are returned in JSON format. For now, JSON is the only supported format by the API for query output. Further development might consider other formats such as XML.

5 Endpoints

The current version of the API provides 8 endpoints, 4 among them are accessed via GET, 2 via POST, and 2 via DELETE:

5.1 POST Endpoints

1. **/datasets**

Requests the creation of a Dataset

Parameters

- **user_token:** secret token provided to the client for authentication
- **s3_key:** a file's s3 key if the file is uploaded at Amazon's s3 official. Right access to this bucket is needed.
- **other_url:** URL (other than the s3 key) if the dataset file is located somewhere else, e.g. in a local computer.
- **kind:** either "claims" or "ground" corresponding to the different types of handled datasets
- **original_filename:** name of the uploaded file. It corresponds to any name that you want to give for identification in future

Response

No data.

200 status code when the request succeeds

Notes

- a) One of **s3_key** or **other_url** parameters are mandatory for parsing dataset.
- b) All uploaded files should be encoded in **UTF-8**.
- c) Be sure that your dataset respects the required format, i.e., it is a CSV file having a header consisting of the following column names in order: **ObjectID, PropertyID, PropertyValue, SourceID, TimeStamp**. A sample example of datasets properly formatted for the API is available at: http://daqcri.github.io/dafna/#/dafna/exp_sections/realworldDS/book.html

2. /runsets

Creating a Runset, i.e., a truth discovery job over a given dataset

Parameters

- **user_token**: secret token provided to the client for authentication
- **datasets**: list of dataset identifiers referring to the datasets on which the runset should be applied. An example input is **datasets**:{"203":"1", "204":"1"} denoting the choice of the dataset numbered 203 along with the corresponding ground truth dataset with the number 204.
- **checked_algo**: set of algorithm name(s), each followed by an array of numerical values for its different input parameters, e.g., "checked_algo": {"Accu": ["0.2", "0", "100", "0.5", "false", "true", "true", "false"], "Cosine": ["1", "0.2"]} specifies two algorithms **Accu** and **Cosine**
- **general_config**: an array of numerical values, e.g., ["0.001", "0.8", "1", "0.4"]

Response

No data.

200 status code when request succeeds.

Notes

- a) **checked_algo** allows to specify the set of truth discovery algorithms along with the values of their input arguments to be used for the truth discovery process. At least one algorithm must be provided, and when several algorithms are specified their results are combined by the system for a better accuracy. We detail in Section 6 the set of supported truth discovery algorithms together with their input arguments.
- b) **general_config** allows to specify the values of the general parameters of a runset, i.e., the convergence test threshold and the initial sources' trustworthiness scores.

5.2 GET Endpoints

1. /datasets

Listing Datasets

Parameters

- **user_token**: secret token provided to the client for authentication
- **kind**: either “claims” or “ground” which correspond to the different types of available datasets
- **start**: an integer number specifying the index from which the listing of available datasets must start
- **length**: an integer specifying the maximum number of datasets to be listed

Response

$\{DS_1, DS_2, \dots, DS_n\}$ where every DS_n is formatted as follows.

```
{ draw: <draw>, recordsTotal: <Number of Records>, recordsFiltered: <Number of filtered Records>, data: <data>, s3_direct_post: <date_time>, fields: <date_time>, key: <date_time>, policy: <policy>, signature: <signatur>, success_action_status: <status> }
```

where <data> contains all the information about to the available datasets.

Notes

- a) **start** and **length** parameters are optional.
- b) When the parameter **kind** is not provided, the user will get an empty set of datasets.
- c) When the arguments **start** and **length** are not specified, all the available datasets of the specified kind are returned.

2. /runsets

Listing Runsets

Parameters

- **user_token**: secret token provided to the client for authentication

Response:

$\{RS_1, RS_2, \dots, RS_n\}$ where the format of RS_n is:
{ id: <runset id>, created_at: <Time of creation>, runs:[{ id: <runset id>, algo: <Time of creation>, crated_at: <>, status: <whether finished>, duration: <Duration of run>, } ,{},{ }...] }

3. /runsets/<id>/results

Listing Results of runsets having id=<id>

Parameters

- **user_token**: secret token provided to the client for authentication
- **id**: an existing identifier of the runset whose results should be listed

Response

```
{ draw: <draw>, recordsTotal: <Total Number of Records>, recordsFiltered: <Filtered Records>, data:
  }
```

4. **/runs**

Listing Runs

Parameters

- **user_token**: secret token provided to the client for authentication

Response

```
{ draw: <draw>, recordsTotal: <Total Number of Records>, recordsFiltered: <Filtered Records>, data:[ { id: <run id>, algorithm: <Name of the algorithm>, created_at: <Time of creation>, runset_id: <Runset ID>, display: <Algorithm name and parameters in paranthesis (in order)>, status: <whether finished>, duration: <Duration of run>, } ,{},{ }... ] }
```

5.3 DELETE Endpoints

1. **/datasets/<id>**

Deleting a Dataset having id=<id>

Parameters

- **user_token**: secret token provided to the client for authentication
- **id**: an existing identifier of the dataset to be deleted

Response

No data.

200 status code when the request succeeds.

2. **/runsets/<id>**

Deleting a Runset having id=<id>

Parameters

- **user_token**: secret token provided to the client for authentication
- **id**: an existing identifier of the runset to be deleted

Response

No data.

200 status code when the request succeeds.

6 Supported Algorithms

The main interest of using the API is to create a truth discovery job which is possible with an instantiation of a runset. Such an instantiation requires to specify one or more truth discovery algorithms to use through the argument **checked_algo**. In the following, we detail the twelve truth discovery algorithms and their specific input parameters supported by DAFNA API.

6.1 Cosine

Description: Cosine is a heuristic approach for estimating a value confidence and source trustworthiness, based on the cosine similarity measure proposed by A. Galland, S. Abiteboul, A. Marian, and P. Senellart. Corroborating Information from Disagreeing Views. In WSDM, pp. 131–140, 2010.

Parameters

- **Initial Value Confidence:** Initialization of value confidence for all properties values.
dataType: double, **min-value:** 0, **max-value:** 1.0, **default-value:** 1
- **Prediction constant:** Constant that gives more weight to predictable views (eg, sources with consistently often correct claims or consistently often wrong claims).
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.2

6.2 2-Estimates

Description: 2-Estimates is a probabilistic model built over the heuristic model, Cosine and proposed by A. Galland, S. Abiteboul, A. Marian, and P. Senellart. Corroborating Information from Disagreeing Views. In WSDM, pp. 131–140, 2010.

Parameters

- **Normalization Factor:** The weight used for normalizing sources' trustworthiness and values' confidence.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5

6.3 3-Estimates

Description: 3-Estimates extends 2-Estimates proposed by A. Galland, S. Abiteboul, A. Marian, and P. Senellart. Corroborating Information from Disagreeing Views. In WSDM, pp. 131–140, 2010.

Parameters

- **Initial Error Factor:** Initialization of value’s error factor for all properties values.
dataType: double, **min-value:** 0, **max-value:** 1.0, **default-value:** 0.4
- **Normalization Factor:** The constant used for normalizing source truthworthiness and value confidence.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5

6.4 Depen

Description: First Bayesian truth discovery model that takes into consideration the copying relationship between sources, proposed by X. L. Dong, L. Bertiequille, and D. Srivastava. Integrating conflicting data: The role of source dependence. PVLDB, 2(1):550–561, 2009.

Parameters

- **Dependence priori probability:** The a priori probability that two data sources are dependent.
dataType: double, **min-value:** 0, **max-value:** 0.5, **default-value:** 0.2
- **Copied value probability:** The probability that a value provided by a copier is copied.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0
- **Number of false values:** The number of false values in the underlying domain for each object.
dataType: int, **min-value:** 1, **max-value:** 1, **default-value:** 100
- **Similarity Constant:** The similarity between values is weighted for the value confidence computation.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5, **hidden:** True
- **considerSimilarity:** False for Depen: the model does not take into account value similarity.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

- **considerSourcesAccuracy:** False for Depen: the model does not take into account the accuracy of the sources.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True
- **considerDependence:** True for Depen: the model takes into account the dependence between sources.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** True, **hidden:** True
- **orderSrcByDependence:** If true, Depen model is based on source dependence ordering, otherwise on lexicographic ordering.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

6.5 Accu

Description: Accu extends Depen model and considers the source accuracy in addition to the source dependence, proposed by X. L. Dong, L. Berti-Equille, and D. Srivastava. Integrating conflicting data: The role of source dependence. PVLDB, 2(1):550–561, 2009.

Parameters

- **Dependence a priori probability:** The a priori probability that two data sources are dependent.
dataType: double, **min-value:** 0, **max-value:** 0.5, **default-value:** 0.2
- **Copied value probability:** The probability that a value provided by a copier is copied.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0
- **Number of false values:** The number of false values in the underlying domain for each object.
dataType: int, **min-value:** 1, **max-value:** 1, **default-value:** 100
- **Similarity Constant:** The similarity between values is weighted for the value confidence computation.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5, **hidden:** True
- **considerSimilarity:** False for Accu: the model does not take into account value similarity.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

- **considerSourcesAccuracy:** True for Accu: the model takes into account the accuracy of the sources.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** True, **hidden:** True
- **considerDependency:** True for Accu: the model takes into account the dependence between sources.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** True, **hidden:** True
- **orderSrcByDependence:** If true, Accu model is based on source dependence ordering, otherwise on lexicographic ordering.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

6.6 AccuSim

Description: Accusim extends Accu model and considers the value similarity, proposed by X. L. Dong, L. Berti-Equille, and D. Srivastava. Integrating conflicting data: The role of source dependence. PVLDB, 2(1):550–561, 2009.

Parameters

- **Dependence a priori probability:** The a priori probability that two data sources are dependent.
dataType: double, **min-value:** 0, **max-value:** 0.5, **default-value:** 0.2
- **Copied value probability:** The probability that a value provided by a copier is copied.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0
- **Number of false values:** The number of false values in the underlying domain for each object.
dataType: int, **min-value:** 1, **max-value:** 1, **default-value:** 100
- **Similarity Constant:** The similarity between values is weighted for the value confidence computation.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5
- **considerSimilarity:** True for AccuSim: the model takes into account value similarity.
dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** True, **hidden:** True
- **considerSourcesAccuracy:** True for AccuSim: the model takes into account the accuracy of the sources.

dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** True, **hidden:** True

- **considerDependency:** True for Accusim: the model takes into account the dependence between sources.

dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** True, **hidden:** True

- **orderSrcByDependence:** If true, AccuSim model is based on source dependence ordering, otherwise on lexicographic ordering.

dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

6.7 AccuNoDep

Description: AccuNoDep extends Accu model while assuming all sources are independent, proposed by X. L. Dong, L. Berti-Equille, and D. Srivastava. Integrating conflicting data: The role of source dependence. PVLDB, 2(1):550–561, 2009.

Parameters

- **Dependence a priori probability:** The a priori probability that two data sources are dependent.

dataType: double, **min-value:** 0, **max-value:** 0.5, **default-value:** 0.2

- **Copied value probability:** The probability that a value provided by a copier is copied.

dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0

- **Number of false values:** The number of false values in the underlying domain for each object.

dataType: int, **min-value:** 1, **max-value:** 1, **default-value:** 100

- **Similarity Constant:** The similarity between values is weighted for the value confidence computation.

dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5, **hidden:** True

- **considerSimilarity:** False for AccuNoDep: the model does not take into account value similarity.

dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

- **considerSourcesAccuracy:** True for AccuNoDep: the model takes into account the accuracy of the sources.

dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** True, **hidden:** True

- **considerDependency:** False for AccuNoDep: the model considers that all sources are independent.

dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

- **orderSrcByDependence:** If true, AccuNoDep model is based on source dependence ordering, otherwise on lexicographic ordering.

dataType: boolean, **min-value:** 0, **max-value:** 1, **default-value:** False, **hidden:** True

6.8 TruthFinder

Description: TruthFinder, proposed by X. Yin, J. Han, and P. S. Yu. Truth Discovery with Multiple Conflicting Information Providers on the Web. TKDE, 20(6):796–808, 2008, is a Bayesian model that iteratively computes and updates the trustworthiness of a source as a function of the belief in its claims, and then the belief score of each claim as a function of the trustworthiness of the sources asserting it.

Parameters

- **Similarity Constant:** The similarity between values is weighted for the value confidence computation.

dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5

- **Dampening Factor:** The damping factor compensates the effect when sources with similar values are actually dependent.

dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.1

6.9 SimpleLCA

Description: SimpleLCA (Latent Credibility Analysis) is a probabilistic model proposed by J. Pasternack and D. Roth. Latent Credibility Analysis. In WWW, pp. 1009–1020, 2013. Each source has a probability of being honest, and all sources are considered independent.

Parameters

- **Prior truth probability:** Prior probability of a claim being the true claim.

dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5

6.10 GuessLCA

Description: GuessLCA extends SimpleLCA by adding a probability of a source guessing the true value while being honest.

Parameters

- **Prior truth probability:** Prior probability of a claim being the true claim.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5

6.11 MLE

Description: MLE (Maximum Likelihood Estimation) proposed by D. Wang, L. M. Kaplan, H. K. Le, and T. F. Abdelzaher. On Truth Discovery in Social Sensing: a Maximum Likelihood Estimation Approach. In IPSN, pp. 233–244, 2012, is based on the Expectation Maximization (EM) algorithm to quantify the reliability of sources and the correctness of their observations. It only deals with boolean positive attributes observations.

Parameters

- **Prior truth probability:** Overall prior probability of the claims being the true claims.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5
- **r:** The probability that a source provides a value for all data items.
dataType: double, **min-value:** 0, **max-value:** 1, **default-value:** 0.5

6.12 LTM

Description: LTM (Latent Truth Model) proposed by B. Zhao, B. I. P. Rubinstein, J. Gemmell, and J. Han. A Bayesian Approach to Discovering Truth from Conflicting Sources for Data Integration. PVLDB, 5(6):550–561, 2012, uses Bayesian Networks for estimating the truth. LTM iterates over a fixed number of iterations, and compute the value confidence using Collapsed Gibbs Sampling process.

Parameters

- **Prior truth probability:** Prior probability of how likely each claim is to be true.
dataType: double, **min-value:** 0.0, **max-value:** 1.0, **default-value:** 0.5
- **Prior falsehood probability:** Prior probability of how likely each claim is to be false.

- dataType:** double, **min-value:** 0.0, **max-value:** 1.0, **default-value:** 0.5
- **Prior true negative count:** Prior number of true negatives for the sources.
dataType: double, **min-value:** 0.0, **max-value:** 1.0, **default-value:** 0.1
 - **Prior false positive count:** Prior number of false positives for the sources.
dataType: double, **min-value:** 0.0, **max-value:** 1.0, **default-value:** 0.9
 - **Prior false negative count:** Prior number of false negatives for the sources.
dataType: double, **min-value:** 0.0, **max-value:** 1.0, **default-value:** 0.1
 - **Prior true positive count:** Prior number of true positives for the sources.
dataType: double, **min-value:** 0.0, **max-value:** 1.0, **default-value:** 0.9
 - **Number Of Iterations:** Number of Iterations.
dataType: int, **min-value:** 1, **max-value:** 10000, **default-value:** 500
 - **Burn-in:** Collapsed Gibbs Sampling burn-in period (ie, the number of discarded first set of iterations) must be significantly less than the number of iterations.
dataType: int, **min-value:** 0, **max-value:** 1000, **default-value:** 100
 - **Thinning:** Collapsed Gibbs Sampling thinning parameter (ie, the number of iterations to be skipped every time before considering the result of a selected iteration) must be significantly less than the number of iterations.
dataType: int, **min-value:** 0, **max-value:** 1000, **default-value:** 9

[†]**General Parameters.** Parameters needed for all Truth Discovery Algorithms (specified via the **general_config** parameter)

Parameters

- **Convergence test threshold:** The difference of source truthworthiness cosine similarity between two successive iterations should be less than the user-defined threshold.

dataType: double, **min-value:** 0, **max-value:** 0.1, **default-value:** 0.001, **step:** 0.001

- **Initial sources truthworthiness:** Initialization of all sources truthworthiness.

dataType: double, **min-value:** 0, **max-value:** 1.0, **default-value:** 0.8

- **Initial Value Confidence:** Initialization of value confidence for all properties values.

dataType: double, **min-value:** 0, **max-value:** 1.0, **hidden:** True

- **Initial Error Factor:** Initialization of error factor for all properties values.

dataType: double, **min-value:** 0, **max-value:** 1.0, **default-value:** 0.4, **hidden:** True

[†]**Combiner.** The combiner of selected truth discovery algorithms. It is automatically selected if you select more than 1 algorithm and 1 ground truth dataset. It is based on Bayes combination from P. Domingos and M. Pazzani. On the optimality of the simple Bayesian classifier under zero-one loss. Machine Learning, 29:103–130, 1997.

7 DAFNA API Usage: Use Case

Let us consider a typical scenario where a given user, holding an access token “_XYH128PL04” to the DAFNA API, would like to discover the correct list of authors of a set of books. The user has first extracted the candidate authors of these books from different Web sources and has stored them into a csv file **book.csv** in a local directory named **./datasets/**.

8 Job Monitoring using Pusher

Some of the jobs you submit (e.g. uploading datasets or running algorithm(s)) might take time to complete for various reasons. Instead of letting users periodically ping the server to verify the status of their ongoing jobs, we provide a manner to make things easier for user applications by setting up a channel on Pusher. User applications can subscribe to this channel in order to be automatically notified for the events they have been binded to. When any event like task completion occurs, a user application will be notified of this. Kindly note that the unexpected approach of repeatedly requesting run statuses rather than listening to the push messages will eventually overwhelm our server, and we may choose to suspend your account. So, please go through the documentation of Pusher to

get a sense of how things work. An client can subscribe to the notifications for her application using **app_id = "79143"**. To this end, a client needs to contact us for a key, which will be sent by email, to enable him to subscribe to the channel. Once you have configured your application using the app_id and key, you can bind to particular events (see examples below), you wish to be notified for.

- **channel.bind('run_change', function(run))**: will notify in case of any change in the status of a run.
- **channel.bind('dataset_change', function(dataset))**: will notify you in case of any change in the status of a dataset.

You may find the following pages to be particularly useful:

1. Client Channel
2. Client Public Channels
3. Client Connect
4. Client Events

9 Online Tool: AllegatorTrack

The main goal of DAFNA project is to design a scalable and accurate truth discovery system to score the veracity of information extracted from multiple online sources. We design DAFNA API as the first proposed API that allows users to tests and compares a large class of well-known truth finding algorithms on different scenarios and datasets. AllegatorTrack, whose the interface is depicted in Figure 1, is the first application that uses DAFNA API and provides to users an online plateform for testing the different features of the API. AllegatorTrack application is accessible at: http://dafna.qcri.org/users/sign_in.

10 Further Developments

Currently, the API is still in improvements and many new other aspects of truth finding and endpoints are still under investigation, based on recent proposed development in the field, discussions with early adopter developers, and users' feedbacks. For example, the scheme may support HTTPS in the future, the response body format may support other output formatting like XML. Most importantly, the API must be extended in the future in order to propose broader class of truth finding algorithms, in particular the new ones.

AllegatorTrack
 Truth Discovery from Multi-Source Data
 Signed in as user@example.com, Change password - Sign out

Discover Explain Allegate

Upload Datasets
 Upload Ground Truth Datasets (optional)
 Select and configure algorithm(s)

Cosine
 Initial Value Confidence: 1
 Prediction constant: 0.2

2-Estimates
 Normalization Factor: 0.5

3-Estimates
 Initial Error Factor: 0.4
 Normalization Factor: 0.5

Depen
 Accu
 AccuSim
 AccuNoDep
 TruthFinder
 SimpleLCA

claim_id	object_id	property_id	property_value	source_id	[74] Combiner
54647	0120455994	AuthorsNamesList	allen,david; aiken,peter	a1books	True
54648	0120455994	AuthorsNamesList	allen,david; aiken,peter	blackwell online	True
54649	0120455994	AuthorsNamesList	allen,david; aiken,peter	bob's books	True
54650	0120455994	AuthorsNamesList	allen,david; aiken,peter	books down under	True
54651	0120455994	AuthorsNamesList	allen,david; aiken,peter	books2anywhere...	True
54652	0120455994	AuthorsNamesList	aiken,peter	brown's books	False
54653	0120455994	AuthorsNamesList	allen,david	caiman	False
54654	0120455994	AuthorsNamesList	aiken,peter	free postage l @th...	False
54655	0120455994	AuthorsNamesList	aiken,peter	gunars store	False
54656	0120455994	AuthorsNamesList	aiken,peter	gunter koppon	False
54657	0120455994	AuthorsNamesList	allen,david; aiken,peter	lakeside books	True
54658	0120455994	AuthorsNamesList	aiken,peter	limelight bookshop	False
54659	0120455994	AuthorsNamesList	allen,david; aiken,peter	papamedia.com	True
54660	0120455994	AuthorsNamesList	allen,david; aiken,peter	paperbackshop-us	True
54661	0120455994	AuthorsNamesList	allen,david; aiken,peter	paperbackworld.de	True
54662	0120455994	AuthorsNamesList	allen,david; aiken,peter	quartermelon	True
54663	0120455994	AuthorsNamesList	allen,david; aiken,peter	revolution books	True

Claim confidence results for 1 dataset(s) and 1 ground truth dataset(s) Showing 1 to 17 of 2,005 unique rows

Figure 1: AllegatorTrack System

11 Questions or Feedbacks

For any questions or feedbacks about the API, please feel free to contact us or visit the website of the DAFNA project for more details by following the link below: <http://dafna.qcrl.org>.