Лаб 5

1) Татвар

Кодны бүтэц:

Abstract

<<class>>

- Salary: long
- GATS: long
- NDSH: float
- TNO: float
- NAT:float
- CHT: float
- TZT: float
- + show(): void

Tatvar2020

<<class>>

- Salary: Long
- NDHSProcent:float
- NATProcent:float
- CHTProcent:float

Main

Create object

Tatvar2021

<<class>>

- Salary: Long
- NDHSProcent:float
- NATProcent:float
- CHTProcent:float

iTatvar

<<Interface>>

+ show(): void

Main.java

```
public class Main {
   public static void main(String[] args) {
     int Salary,type;
     Scanner sc = new Scanner(System.in);
     while(1==1) {
        System.out.println("========Start=======");
        System.out.print("Цалингаа оруулна уу: ");
        Salary = sc.nextInt();
```

```
System.out.print("Аль нэгийн сонгоно уу 1) 2020 2) 2021 3) гарах:

");

type = sc.nextInt();
switch (type) {
    case 1: {
        AbsTatvar Tatvar2020 = new Tatvar2020(Salary);
        Tatvar2020.show();
    }break;
    case 2: {
        AbsTatvar Tatvar2021 = new Tatvar2021(Salary);
        Tatvar2021.show();
    }break;
    default: System.exit(0);
}

}
```

iTatvar(interface)

```
public interface iTatvar {
    void show();
}
```

Tatvar2021.java(class)

```
public class Tatvar2021 extends AbsTatvar implements iTatvar
{
    Tatvar2021(int Salary) {
        super(Salary, (float) 0.11, (float) 0.11
, 10000);
    }
}
```

Tatvar2020.java(class)

```
public class Tatvar2020 extends AbsTatvar implements iTatvar{
    Tatvar2020(int Salary) {
        super(Salary, (float) 0.11, (float) 0.1, 9000);
    }
}
```

AbsTatvar.java(abstract)

```
import java.util.Scanner;

public abstract class AbsTatvar{
    /**HДШ => NDSH = 11%,
```