Interface Control Document

API Name: SDG-DDADS-OpenAPI

Source/ Consumer: Data.Dubai Platform

Target/ Native Provider: General Public

Date: 12-02-2026

This document is classified as "**Confidential - Category B**"

Copyright © Smart Dubai Government Establishment. 2023. All rights reserved.

No Part of this work may be reproduced or transmitted in any form or by any means, electronic, manual, photocopying, recording or by any information storage and retrieval system, without prior written permission of Smart Dubai Government Establishment.

1. CONTENTS

1. Introduction 4
2. Functional Requirements 5
   Interface Metadata 5
   Base URL 5
3. AuthorizATION 5
   Basic Auth 5
4. APIs/ Services 6
   HTTP Status Codes (For REST Services) 7
   Supported Query Parameters 8
   Additional functional Information 8
5. Non-Functional Requirements 8
   Standard NFRs 9
   Message confidentiality Index 9
   Logging Strategy 9
   Error Handling Strategy 9
   API Protection policy 10
6. Point of Contacts 10
7. Terms and Conditions 11

Revision History

Version	Date	Change	Change Author
0.1	12/02/2026	Draft	Nikunj Jain
0.2	16/03/2026	Revised	Nikunj Jain
2	15/04/2026	Added additional details related to downstream API query parameters	Nikunj Jain
2.1	16/04/2026	Updated URLs	Nikunj Jain

1. INTRODUCTION

Below is the high-level block diagram which represents the flow of the request and response of the APIs the input will be the get request accepting entity and dataset name as the path parameters and based on the input the corresponding datasets (ingested in new data fabric platform from various integrated entities) response will be returned.

The ingested datasets are classified in three categories open, confidential and sensitive. Open datasets are provisioned via /open endpoint and confidential and sensitive datasets are provisioned via other /shared* endpoints.



2. FUNCTIONAL REQUIREMENTS

API will accept the request http get request with entity name and dataset Name as the input path parameter and returns the data based on the input parameter, the API has the capability of accepting filtering, offset, sorting etc. as the query parameters.

Interface Metadata

	Source	Target
Entity	DDA	Public
Message Type	JSON	JSON
Communication	HTTP	HTTP
Scheme	HTTPS	HTTPS

Base URL

Environment	Base URL
DDA URLs	
STG	https://stg-apis.data.dubai
PROD	https://apis.data.dubai

3. AUTHORIZATION

This section details the security requirements to secure the endpoints of the service. The section should capture the security mechanism to be implemented along with specifics of implementation like endpoints to generate token in case of OAuth should also be captured

Basic Auth

POST	[Base URL]/secure/ssis/dubaiai/gatewaytoken/1.0.0/getAccessToken			
Request				
Header Parameters	**Name**	**Type**	**Cardinality**	**Description**
	Content-Type	Application/json	1	NA
	x-DDA-SecurityApplicationIdentifier			iPaaS consumer Security Identifier key. Shared by DDA team.
	Name	**Type**	**Cardinality**	**Description**

Request Parameters	client_id	body	1	Client Id of the user to fetch the token
	grant_type	body	1	Value = client_credentials
	client_secret	body	1	Client secret of the user to fetch the token
Sample Request	curl --location --request POST {baseURL}/secure/ssis/dubaiai/gatewaytoken/1.0.0/getAccessToken' \ --header 'x-DDA-SecurityApplicationIdentifier: Identifier key\ --header 'Content-Type: application/json' \ --data-raw '{ "grant_type":"client_credentials", "client_id":"client ID value", "client_secret":" client secret " }'			
Responses				
	Name	**Type**	**Cardinality**	**Description**
Response Parameters	NA	NA	NA	NA
Sample Response				
Success Response	{"access_token":"67398833a809439dbd5bb77571223293ef9d0a7cbab44f0995916c7ea7bcd711","token_type":"Bearer","expires_in":3600,"scope":"authz"}			

Failure Response	{
	"error" : "invalid_client",
	"error_description" : "The request includes no client credentials."
	}			

4. APIS/ SERVICES

The endpoint below is responsible for provisioning all the open datasets present with the new Dubai data platform.

SDG-DDADS-OpenAPI/secure/ddads/openapi/1.0.0:

GET	{BaseURL}/secure/ddads/openapi/1.0.0/<Entity Name>/<Dataset Name>			
Request				
Header Parameters	**Name**	**Type**	**Cardinality**	**Description**

	Authorization	Bearer xxxx	1	OAuth token to hit the API
Request Parameters	**Name**	**Type**	**Cardinality**	**Description**
	Entity Name	Path Parameter	1	Name of the entity for which the dataset must be extracted
	Dataset Name	Path Parameter	1	Name of the dataset for which the data must be extracted
Sample Request	**Original: {BaseURL}**/secure/ddads/openapi/1.0.0/<Entity Name>/<Dataset Name> **Alias:** /open/<Entity Name>/<Dataset Name>			
Responses				
Response Parameters	**Name**	**Type**	**Cardinality**	**Description**
	NA	NA	NA	NA
Sample Response				

Success Response	{
	"results": [
	{
	"trade_name_serial": 166,
	"trade_name_ar": "xxx",
	"trade_name_en": "xxx",
	"license_number": 2288623332,
	"issue_date": "1992-13-40",
	"expiry_date": "2025-14-50",
	"cancel_date": null,
	"load_timestamp": "2025-15-60 20:34:05"
	}
	]
	}			

Failure Response	{
	"status": "error",
	"status_code": 404,
	"error_type": "NotFound",
	"message": "Dataset 'mrhe_mrhe_project-open-api' for entity 'mrhe' not found."
	}			

HTTP Status Codes (For REST Services)

HTTP Status Codes	Description
200	Success. Response received
204	No Content

400	Not all required parameters provided.
401	Unauthorized, Invalid or no credentials provided
403	Forbidden. Invalid credentials i.e. Wrong username or password
404	Not Found
405	Method not allowed. Invalid method sent for calling the API.
500	Server Error.
503	Service Under maintenance

Supported Query Parameters

Parameter	Type	Description	Required
column	string	Comma-separated column names expected to be retrieved in response	Optional
filter	string	Filter expression (filter=value) for filtering response based on any column value	Optional
page	integer	Page number (default: 1)	Optional
pageSize	integer	Records per page	Optional
limit	integer	Max records (alternative to pagination)	Optional
order_by	string	Column to sort by	Optional
order_dir	string	Global sort direction (asc / desc)	Optional
offset	integer	Record offset to get records after that offset.	Optional

Additional functional Information

Parameter	Description
Rate Limit	**60 requests per minute**. Exceeding this limit may result in throttling or temporary request rejection.
Timeout	**30 seconds**. If a response is not received within this duration, the request will be terminated.

5. NON-FUNCTIONAL REQUIREMENTS

This section should capture all non-functional requirements related to the interface. The table details the standard NFRs for a service offered by GSB. If additional NFRs need to be added based on the service requirement, please add it to the below table

Standard NFRs

#	Non-Functional Requirements	Sample Value	Service Specifications
NFR001	Nature of the interface	Real-time Synchronous	
NFR002	Volume of transactions/day	200K request/day	
NFR003	Size of request and response message per transaction	Request – 5 KB Response – 8 MB	
NFR004	Peak volume/sec	~30 requests/sec	

Message confidentiality Index

#	Security Requirements	Comments	Action (if Yes)
SEC001	Is there any sensitive or confidential information (Ex: Passwords) as part of the service request?	No	Sensitive information should be encrypted by source and decrypted at the target.
SEC002	Is there any sensitive or confidential information (Ex: Passwords) as part of the service response?	Yes	Sensitive information should be encrypted by source and decrypted at the target
SEC003	Is there any personally identifiable information (PI) as part of the service request?	No	
SEC004	Is there any personal identifiable information (PI) as part of the service response?	Yes	

Note: If the answer to any of the questions under Security Requirements is **Yes**, GSB will not log request /response payloads of the service.

Logging Strategy

<< Standard logging as described in <Confluence Link> >>

Error Handling Strategy

<< Standard error handling as described in <Confluence Link> >>

API Protection policy

<< Standard logging as described in <Confluence Link> >>

6. POINT OF CONTACTS

In case of any further questions, please submit your queries through the "Contact Us" form on the Data Dubai portal → https://data.dubai/en/contact-us

7. TERMS AND CONDITIONS

It is agreed between parties involved in the integration that no part of this work may be reproduced or transmitted in any form or by any means, electronic, manual, photocopying, recording or by any information storage and retrieval system, without prior written permission of Dubai Digital Authority (DDA). It is the responsibility of integrated parties to securely process and store information, with prior approval from the owner of data, exchanged through the integration layer. DDA will not be responsible for the mishandling of information retrieved or pushed through DDA's integration platform by any of the parties involved in the integration. Additionally, Integrated parties are responsible for securing the access credentials issued to individual entities to consume services through DDA's integration platform. Abuse or Mismanagement of credentials would lead to revocation of access to services offered through DDA integration platform. Upon Production roll out, any service degradation or service disruption or unplanned outages from any party involved in the integration which can potentially cause a negative impact on the service offerings of integrated parties need to be addressed promptly. Planned outages or service disruptions at any of the integrated parties need to be formally communicated upfront.